



HCT CO., LTD.

Product Compliance Division

TEL : +82 31 639 8518 FAX : +82 31 639 8535

CERTIFICATE OF COMPLIANCE
FCC Certification

Applicant Name:

Franklin Technology Inc.

Address:

1505 Digital Tower Aston, 505-15 Gasan-dong,
Gumcheon-gu, Seoul, Korea

Date of Issue:

November 02, 2010

Location:

HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon, Icheon-si,
Kyunggi-Do, Korea(Lab)

Test Report No.: HCTR1010FR11-2

HCT FRN: 0005866421

IC Recognition No.: IC 5944A-2

FCC ID : XHG-M600W

APPLICANT : Franklin Technology Inc.

Model(s): M600W

EUT Type: 4G Module

Tx Frequency: 2 498.5 MHz ~ 2 687.5 MHz (5 MHz Bandwidth)
2 501.0 MHz ~ 2 685.0 MHz (10 MHz Bandwidth)

Rx Frequency: 2 498.5 MHz ~ 2 687.5 MHz (5 MHz Bandwidth)
2 501.0 MHz ~ 2 685.0 MHz (10 MHz Bandwidth)

Max. Conducted Power: 0.219 W 5 MHz 16QAM(23.41 dBm) / 0.217 W 5MHz QPSK(23.37 dBm) /
0.204 W 10 MHz 16QAM(23.11 dBm) / 0.200 W 10MHz QPSK(23.03 dBm)

Emission Designator(s): 5 MHz BW : 4M39G7D (QPSK) / 4M45W7D (16QAM)
10 MHz BW : 9M13G7D (QPSK) / 9M05W7D (16QAM)

FCC Classification: Licensed Non-Broadcast Transmitter (TNB)

FCC Rule Part(s): §27, §2

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Hyo Sun Kwak

Report prepared by

: Hyo Sun Kwak

Test engineer of RF Team

Sang Jun Lee

Approved by

: Sang Jun Lee

Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1010FR11	October 19, 2010	First Approval Report
HCTR1010FR11-1	October 29, 2010	Change the test site description
HCTR1010FR11-2	November 02, 2010	Delete EIRP Test

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION	5
2.2. MEASURING INSTRUMENT CALIBRATION	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS	6
3.1 EQUIVALENT ISOTROPIC RADIATED POWER	6
3.2 OCCUPIED BANDWIDTH	7
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	8
3.4 RADIATED SPURIOUS AND HARMONIC EMISSIONS	9
3.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	10
4. LIST OF TEST EQUIPMENT	11
5. SUMMARY OF TEST RESULTS	12
6. SAMPLE CALCULATION	13
7. TEST DATA	14
7.1 CONDUCTED OUTPUT POWER	14
7.2 OCCUPIED BANDWIDTH	16
7.3 CONDUCTED SPURIOUS EMISSIONS	18
7.3.1 CHANNEL EDGE	19
7.4 RADIATED SPURIOUS EMISSIONS	20
7.4.1 RADIATED SPURIOUS EMISSIONS (WiMAX 5 MHz-16QAM)	20
7.4.2 RADIATED SPURIOUS EMISSIONS (WiMAX 10 MHz-16QAM)	21
7.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	22
7.5.1 FREQUENCY STABILITY (WiMAX-5 MHz)	22
7.5.2 FREQUENCY STABILITY (WiMAX-10 MHz)	23
8. TEST PLOTS	24

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: Franklin Technology Inc.

Address: 1505 Digital Tower Aston, 505-15 Gasan-dong, Gumcheon-gu, Seoul, Korea

FCC ID: XHG-M600W

Application Type: Certification

FCC Classification: Licensed Non-Broadcast Transmitter (TNB)

FCC Rule Part(s): §27, §2

EUT Type: 4G Module

Model(s): M600W

Tx Frequency: 2 498.5 MHz ~ 2 687.5 MHz (5 MHz Bandwidth)
2 501.0 MHz ~ 2 685.0 MHz (10 MHz Bandwidth)

Rx Frequency: 2 498.5 MHz ~ 2 687.5 MHz (5 MHz Bandwidth)
2 501.0 MHz ~ 2 685.0 MHz (10 MHz Bandwidth)

Max. Conducted Power: 0.219 W 5 MHz 16QAM(23.41 dBm) / 0.217 W 5MHz QPSK(23.37 dBm) /
0.204 W 10 MHz 16QAM(23.11 dBm) / 0.200 W 10MHz QPSK(23.03 dBm)

Emission Designator(s): 5 MHz BW : 4M39G7D (QPSK) / 4M45W7D (16QAM)
10 MHz BW : 9M13G7D (QPSK) / 9M05W7D (16QAM)

Date(s) of Tests: October 05, 2010 ~ October 15, 2010

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W



2. INTRODUCTION

2.1. EUT DESCRIPTION

The Franklin Technology Inc. M600W 4G Module consists of Cellular CDMA, PCS CDMA, EVDO Rev.A and **wimax**.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri , Majang-Myeon, Icheon-si, 467-811, KOREA.


The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009 (Registration Number: 90661)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W

3. DESCRIPTION OF TESTS

3.1 EQUIVALENT ISOTROPIC RADIATED POWER

Test Set-up



Test Procedure

Radiated emission measurements were performed at an SAC (Semi-Anechoic Chamber)


The equipment under test is placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. A styrofoam turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W

3.2 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the -13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 30 MHz to 26.5 GHz.. A display line was placed at -25 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

- Band Edge Requirement : When measuring conducted band edge, the ACP feature of the signal analyzer was used. For each segment of the band edge, the allowed integration bandwidth was configured to calculate the channel power that is highest within that band edge segemnt.


- Occupied Bandwidth Emission Limits

- On any frequency outside but within 5.5 MHz from the band edge of a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10\log(P)$ dB. At frequencies greater than 5.5 MHz from any in-band channel edge, the transmitter power (P) shall be attenuated by at least $55 + 10\log(P)$ dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W

3.4 RADIATED SPURIOUS AND HARMONIC EMISSIONS

Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The SAC(Semi-Anechoic Chamber) meets requirements in ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable styrofoam platform mounted at three from the antenna mast.

- 1) The unit mounted on a styrofoam turntable 1.5 m x 1.0 m x 0.80 m is 0.8 meter above test site ground level.
- 2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.

Test Procedure


The equipment under test is placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. A styrofoam turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W

3.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



Test Procedure

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30 °C to +50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.000\ 25\% (\pm 2.5\ ppm)$ of the center frequency.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W



4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	ESI40/ Spectrum Analyzer	831564/003	Annual	10/30/2010
Agilent	E4416A/ Power Meter	GB41291412	Annual	01/14/2011
Agilent	E9327A/ Power Sensor	MY4442009	Annual	07/23/2011
Agilent	E4438C / SIGNAL GENERATOR	GB44400269	Annual	02/10/2011
MITEQ	AMF-6D-001180-35-20P/AMP	990893	Annual	05/20/2011
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	06/25/2011
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	06/25/2011
Agilent	775D/ Dual Directional Coupler	12922	Annual	12/24/2010
Agilent	11636B/ Power Divider	11377	Annual	12/24/2010
Digital	EP-3010/ Power Supply	3110117	Annual	01/08/2011
Schwarzbeck	UHAP/ Dipole Antenna	585	Biennial	02/13/2011
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	02/13/2011
Korea Engineering	KR-1005L / Chamber	KRAB07063-2CH	Annual	12/28/2010
Schwarzbeck	BBHA 9120D/ Horn Antenna	296	Biennial	09/23/2011
Agilent	N9020A / Spectrum Analyzer	US45303008	Annual	03/03/2011

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049, 27.53(l)(6)	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(l)(4)(6)	Band Edge	< $43 + 10\log_{10}(P[\text{Watts}])$ within 5.5MHz from the band edge		PASS
2.1046	Conducted Output Power	N/A		
2.1051, 27.53(l)(4)(6)	Conducted Spurious Emissions	< $55 + 10\log_{10}(P[\text{Watts}])$ for all emissions greater than 5.5MHz from the band edge		PASS
2.1055, 27.54	Frequency stability	Fundamental emissions must stay within the allotted band		PASS
27.50(h)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1053, 27.53(l)(4)	Undesirable Emissions	< $55 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



6. SAMPLE CALCULATION

A. ERP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	384	836.52	-10.96	24.81	2.50	1.19	H	0.41	26.12

ERP = SubstituteLEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (**ERP**).

B. Emission Designator

CDMA Emission Designator

Emission Designator = 1M27F9W

CDMA BW = 1.27 MHz (Measured at the 99% power bandwidth)

F = Frequency Modulation

9 = Composite Digital Info


W = Combination (Audio/Data)

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID: XHG-M600W	
HCTR1010FR11-2	November 02, 2010	4G Module		

7. TEST DATA

7.1 CONDUCTED OUTPUT POWER

A base station simulator was used to establish communication with the EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Test Result

5 MHz channel BW		
Frequency(MHz)	Modulation	Average Power (dBm)
2498.5	QPSK 1/2	22.96
	QPSK 3/4	22.91
	16QAM 1/2	22.85
	16QAM 3/4	22.86
2593.0	QPSK 1/2	23.13
	QPSK 3/4	23.17
	16QAM 1/2	23.11
	16QAM 3/4	23.08
2687.5	QPSK 1/2	23.37
	QPSK 3/4	23.25
	16QAM 1/2	23.41
	16QAM 3/4	23.22

(WiMAX Conducted Average Output Powers)

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W

10 MHz channel BW		
Frequency(MHz)	Modulation	Average Power (dBm)
2501.0	QPSK 1/2	22.57
	QPSK 3/4	22.64
	16QAM 1/2	22.64
	16QAM 3/4	22.63
2593.0	QPSK 1/2	23.02
	QPSK 3/4	22.98
	16QAM 1/2	22.94
	16QAM 3/4	22.84
2685.0	QPSK 1/2	23.03
	QPSK 3/4	22.99
	16QAM 1/2	23.11
	16QAM 3/4	22.97

(WiMAX Conducted Average Output Powers)

Note : Detecting mode is average.

- 5 MHz: Plots of the EUT's Conducted Output Power are shown Page 25 ~ 30.

- 10 MHz: Plots of the EUT's Conducted Output Power are shown Page 31 ~ 36.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W



7.2 OCCUPIED BANDWIDTH

5 MHz

Frequency [MHz]	Modulation	Occupied Bandwidth [MHz]
2498.5	QPSK 1/2	4.3860
	QPSK 3/4	4.3943
	16QAM 1/2	4.4475
	16QAM 3/4	4.4229
2593.0	QPSK 1/2	4.3698
	QPSK 3/4	4.3903
	16QAM 1/2	4.4428
	16QAM 3/4	4.4213
2687.5	QPSK 1/2	4.3648
	QPSK 3/4	4.3871
	16QAM 1/2	4.4421
	16QAM 3/4	4.4200

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W

10 MHz

Frequency [MHz]	Modulation	Occupied Bandwidth [MHz]
2501.0	QPSK 1/2	9.1341
	QPSK 3/4	8.9709
	16QAM 1/2	8.9682
	16QAM 3/4	9.0514
2593.0	QPSK 1/2	9.1290
	QPSK 3/4	8.9638
	16QAM 1/2	8.9625
	16QAM 3/4	9.0442
2685.0	QPSK 1/2	9.1276
	QPSK 3/4	8.9620
	16QAM 1/2	8.9602
	16QAM 3/4	9.0397

- 5 MHz: Plots of the EUT's Occupied Bandwidth are shown Page 37 ~ 42.

- 10 MHz: Plots of the EUT's Occupied Bandwidth are shown Page 43 ~ 48.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



7.3 CONDUCTED SPURIOUS EMISSIONS

5 MHz

Frequency(MHz)	Modulation	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
2498.5	QPSK 1/2	25.914	-33.807
	QPSK 3/4	25.098	-34.283
	16QAM 1/2	25.608	-33.786
	16QAM 3/4	25.735	-33.486
2593.0	QPSK 1/2	2.326	-31.796
	QPSK 3/4	2.326	-31.496
	16QAM 1/2	2.326	-31.430
	16QAM 3/4	2.326	-30.816
2687.5	QPSK 1/2	2.428	-29.448
	QPSK 3/4	2.428	-29.631
	16QAM 1/2	2.428	-28.725
	16QAM 3/4	2.428	-28.805

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W



10 MHz

Frequency(MHz)	Modulation	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
2501.0	QPSK 1/2	24.409	-33.710
	QPSK 3/4	24.970	-33.622
	16QAM 1/2	24.996	-33.541
	16QAM 3/4	25.710	-34.521
2593.0	QPSK 1/2	25.608	-33.921
	QPSK 3/4	25.021	-33.544
	16QAM 1/2	2.326	-34.093
	16QAM 3/4	2.326	-35.010
2685.0	QPSK 1/2	2.428	-29.446
	QPSK 3/4	2.428	-29.316
	16QAM 1/2	2.428	-29.025
	16QAM 3/4	2.428	-28.691

- 5 MHz: Plots of the EUT's Conducted Spurious Emissions are shown Page 57 ~ 68.

- 10 MHz: Plots of the EUT's Conducted Spurious Emissions are shown Page 69 ~ 80.

7.3.1 CHANNEL EDGE

- 5 MHz: Plots of the EUT's Band Edge are shown Page 49 ~ 52.

- 10 MHz: Plots of the EUT's Band Edge are shown Page 53 ~ 56.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W



7.4 RADIATED SPURIOUS EMISSIONS

7.4.1 RADIATED SPURIOUS EMISSIONS (WiMAX 5 MHz-16QAM)

MEASURED OUTPUT POWER: 27.90 dBm = 0.617 W

MODULATION SIGNAL: WiMAX 5 MHz

DISTANCE: 3 meters

LIMIT: $-(43 + 10 \log_{10}(W)) =$ - 52.90 dBc

Operating Freq. (MHz)	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
2498.50	4,997.00	-45.20	12.42	-46.47	3.60	H	-37.65	-65.51
	7,495.50	-46.37	11.36	-38.80	3.88	H	-31.32	-59.18
	9,994.00	-	-	-	-	-	-	-
2593.00	5,186.00	-40.85	12.51	-42.22	3.39	H	-33.10	-60.96
	7,779.00	-45.91	11.26	-38.80	3.72	H	-31.26	-59.12
	10,372.00	-	-	-	-	-	-	-
2687.50	5,375.00	-43.39	12.62	-45.95	3.41	H	-36.74	-64.60
	8,062.50	-46.63	11.21	-37.22	4.07	V	-30.08	-57.94
	10,750.00	-	-	-	-	-	-	-

NOTES:

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004;
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.
3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. Worst case is 16QAM 1/2.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:
HCTR1010FR11-2	November 02, 2010	4G Module	XHG-M600W



7.4.2 RADIATED SPURIOUS EMISSIONS (WiMAX 10 MHz-16QAM)

MEASURED OUTPUT POWER: 30.38 dBm = 1.091 W

MODULATION SIGNAL: WiMAX 10 MHz

DISTANCE: 3 meters

LIMIT: - (43 + 10 log₁₀ (W)) = - 55.38 dBc

Operating Freq. (MHz)	Freq.(MHz)	<u>Measured Level</u> [dBm]	Ant. Gain (dBi)	<u>Substitute Level</u> [dBm]	C.L	Pol.	ERP (dBm)	dBc
2501.00	5,002.00	-48.64	12.41	-50.30	3.60	H	-41.49	-71.86
	7,503.00	-51.14	11.33	-43.64	3.88	H	-36.19	-66.56
	10,004.00	-	-	-	-	-	-	-
2593.00	5,186.00	-47.86	12.51	-49.23	3.39	H	-40.11	-70.48
	7,779.00	-51.27	11.26	-44.16	3.72	H	-36.62	-66.99
	10,372.00	-	-	-	-	-	-	-
2685.00	5,370.00	-48.13	12.62	-50.79	3.41	H	-41.58	-71.95
	8,055.00	-49.93	11.21	-40.32	4.07	H	-33.18	-63.55
	10,740.00	-	-	-	-	-	-	-

NOTES:

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.
3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. Worst case is 16QAM 1/2.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID: XHG-M600W	
HCTR1010FR11-2	November 02, 2010	4G Module		

7.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


7.5.1 FREQUENCY STABILITY (WiMAX-5 MHz)

OPERATING FREQUENCY: 2593,000,000 Hz

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	5.0 V	+20(Ref)	2592 999 997	0	0.000 000	0.000
100%		-30	2592 999 981	-19.00	-0.000 001	-0.007
100%		-20	2592 999 993	-6.90	0.000 000	-0.003
100%		-10	2593 000 004	3.70	0.000 000	0.001
100%		0	2593 000 002	1.90	0.000 000	0.001
100%		+10	2592 999 999	-1.30	0.000 000	-0.001
100%		+30	2593 000 006	5.50	0.000 000	0.002
100%		+40	2593 000 011	11.00	0.000 000	0.004
100%		+50	2593 000 015	15.00	0.000 001	0.006
115%	5.75	+20	2593 000 005	4.80	0.000 000	0.002
Batt. Endpoint	4.25	+20	2593 000 003	2.50	0.000 000	0.001



FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W


7.5.2 FREQUENCY STABILITY (WiMAX-10 MHz)

OPERATING FREQUENCY: 2593,000,000 Hz

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	5.0 V	+20(Ref)	2592 999 993	0	0.000 000	0.000
100%		-30	2592 999 977	-23.00	-0.000 001	-0.009
100%		-20	2592 999 997	-3.10	0.000 000	-0.001
100%		-10	2593 000 002	1.50	0.000 000	0.001
100%		0	2593 000 008	8.00	0.000 000	0.003
100%		+10	2593 000 005	5.00	0.000 000	0.002
100%		+30	2593 000 003	2.70	0.000 000	0.001
100%		+40	2593 000 009	9.10	0.000 000	0.004
100%		+50	2593 000 011	11.00	0.000 000	0.004
115%	5.75	+20	2593 000 006	5.60	0.000 000	0.002
Batt. Endpoint	4.25	+20	2593 000 004	4.20	0.000 000	0.002



FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1010FR11-2	Date of Issue: November 02, 2010	EUT Type: 4G Module	FCC ID: XHG-M600W