

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is an Toy RC Motor Battles operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AA batteries). For more details information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -20.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -20.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 75.2dB $\mu$ V/m at 3m in the frequency 2473MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -20.03dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 73.3dB $\mu$ V/m at 3m in the frequency 2410MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -21.93dBm  
which is within the production variation.

The maximum conducted output power specified is -17.0dBm= 0.020mW

The source- based time-averaging conducted output power  
=0.020mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)  
= 3.0 \* 5 / sqrt (2.473) mW  
= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: XHT-6613-03