# **FCC RF ExposureEvaluation**

#### 1. Product Information

FCC ID:	XHWEGQ378			
Product name	Tablet PC			
Model number	EGQ378			
Power supply	DC 3.7V by Rechargeable Li-ion Battery (2000mAh)			
Power supply	Recharge Voltage: 5V , 1.5A			
	GFSK,π/4DQPSK, 8DPSK for Bluetooth 4.0(BT Classics);			
	GFSK for Bluetooth 4.0(BT LE)			
Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)			
Wiodulation Type	IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)			
	IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)			
	IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)			
Hardware version	BND-RK3126-D86-BJ			
Software version	Android 8.0			
Bluetooth Operation frequency	2402MHz-2480MHz			
	IEEE 802.11b:2412 MHz – 2462 MHz			
WLAN FCC Operation	IEEE 802.11g: 2412 MHz – 2462 MHz			
frequency	IEEE 802.11n HT20: 2412 MHz – 2462 MHz			
	IEEE 802.11n HT20: 2422 MHz – 2452 MHz			
GPS Receiver				
Frequency Range	1575.42MHz			
Channel Number	1			
Antenna Type	PIFA antenna			
Antonna Cain	2.0dBi (maximum)			
Antenna Gain	The BT, 2.4GWIFI and GPS shares the same antenna.			
Exposure category	General population/uncontrolled environment			
EUT Type	Production Unit			
Device Type	Portable Device			

#### 2. Evaluation Method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform

requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

[(max. power of channel, including tune-up tolerance, mW)/ (min. test separation distance, mm)]  $\cdot$  [Vf (GHz)]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

  The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- a) The [ $\sum$  of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg] + [ $\sum$  of MPE ratios] is  $\leq$  1.0.
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all  $\leq$  0.04, and the [ $\supset$  of MPE ratios] is  $\leq$  1.0.

According to KDB 616217 D04 SAR for laptop and tablets v01r02Section 4.2Laptop host platform test requirements, When the modular approach is applied, transmitters and modules must be tested initially without using a representative host for incorporation in the display and/or keyboard of qualified laptop computers for standalone use according to the following minimum test separation distance and antenna installation requirements. The separation distance required for incorporation in qualified hosts is described in KDB Publication 447498 D01; item e) of 4.1 and item a) of 5.2.2 etc

- a) ≤ 25 mm between the antenna and user for incorporation in laptop display screens
- b) ≤ 5 mm between the antenna and user; only when incorporation in the keyboard compartment is required by the hosts, for bottom surface and edge exposure conditions
- c) the antennas used by the host must have been tested for equipment approval or qualify for SAR test exclusion
- d) the antenna polarization, physical orientation, rotation and installation configurations used by the host must have been tested for compliance for the required display and/or keyboard installation conditions and test separation distance(s) or qualify for SAR test exclusion
- e) When the SAR Test Exclusion Threshold in KDB Publication 447498 D01 applies, a minimum test separation distance of 25 mm is required to determine test exclusion for the display, and 5 mm for the keyboard compartment.

#### 3. Refer Evaluation Method

<u>ANSI C95.1–1999:</u> IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

<u>FCC KDB publication 447498 D01 General RF Exposure Guidance v06:</u> Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

<u>FCC KDB publication 616217 D04 SAR for laptop and tablets v01r02:</u>SAR Evaluation Considerations for Laptop, Notebook, and Tablet Computers.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1093: Radiofrequency radiation exposure evaluation: portable devices

### 4. Conducted Power Results

# 4.1 Test Setup Block Diagram



# 4.2 Test Equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	R&S	NRVS	100444	2020-06-14
2	Power Sensor	R&S	NRV-Z32	10057	2020-06-14

Remark: all calibration period of equipment list is one year.

### **4.3 Test Procedure**

- **a.** The EUT was directly connected to the power meter and antenna output port as show in the block diagram Test Setup;
- **b.** Setup EUT work at duty cycle more than 98%;
- c. Read power sensor values in RMS detector;

### <BT LE>

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)		
	0	2402	-2.349		
GFSK	19	2441	-0.478		
	39	2480	-1.507		

# <BT Classics>

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)	
GFSK	0	2402	-2.135	
	39	2440	-0.312	
	78	2480	-0.816	
	0	2402	-2.916	
π/4DQPSK	39	2440	-1.446	
	78	2480	-1.679	
8DPSK	0	2402	-3.063	
	39	2440	-1.425	
	78	2480	-1.677	

### <2.4GWLAN>

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)
	1	2412	9.19
IEEE 802.11b	6	2437	9.18
	11	2462	9.23
	1	2412	9.48
IEEE 802.11g	6	2437	9.44
	11	2462	9.43
	1	2412	9.25
IEEE 802.11n HT20	6	2437	9.42
	11	2462	9.33
IEEE 802.11n HT40	3	2422	9.42
	6	2437	9.35
	9	2452	9.09

# 5. Manufacturing Tolerance

### <BT LE>

GFSK (Peak)					
Channel Channel 0 Channel 19 Channel 39					
Target (dBm)	-2.0	0	-1.0		
Tolerance ±(dB)	1.0	1.0	1.0		

### <BT Classics>

2.0.000.00						
GFSK (Peak)						
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	-1.5	0	0			
Tolerance ±(dB)	1.0	1.0	1.0			
	π/4DQPS	SK (Peak)				
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	-2.0	-1.0	-1.0			
Tolerance ±(dB)	Tolerance ±(dB) 1.0		1.0			
8DPSK (Peak)						
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	-2.5	-1.0	-1.0			
Tolerance ±(dB)	1.0	1.0	1.0			

# <2.4GWLAN>

IEEE 802.11b (Peak)						
Charrent						
Channel	Channel 1	Channel 6	Channel 11			
Target (dBm)	8.5	8.5	8.5			
Tolerance ±(dB)	1.0	1.0	1.0			
	IEEE 802.1	.1g (Peak)				
Channel	Channel 1	Channel 6	Channel 11			
Target (dBm)	8.5	8.5	8.5			
Tolerance ±(dB)	1.0	1.0	1.0			
	IEEE 802.11n HT20 (Peak)					
Channel	Channel 1	Channel 6	Channel 11			
Target (dBm)	8.5	8.5	8.5			
Tolerance ±(dB)	1.0	1.0	1.0			
IEEE 802.11n HT40 (Peak)						
Channel	Channel 3	Channel 6	Channel 9			
Target (dBm)	8.5	8.5	8.5			
Tolerance ±(dB)	1.0	1.0	1.0			

# 6. Evaluation Results

#### **6.1 Standalone Evaluation**

	<sub>f</sub> Antenna		RF output power		SAR Test Exclusion	SAR Test
Band/Mode	(GHz)	Distance (mm)	dBm	mW	Threshold	Exclusion
GFSK – BT LE	2.50	5	1.00	1.2589	0.39< 3.0	Yes
GFSK	2.50	5	1.00	1.2589	0.39< 3.0	Yes
π/4DQPSK	2.50	5	0.00	1.0000	0.31< 3.0	Yes
8DPSK	2.50	5	0.00	1.0000	0.31< 3.0	Yes
IEEE 802.11b	2.50	5	9.50	8.9125	2.8< 3.0	Yes
IEEE 802.11g	2.50	5	9.50	8.9125	2.8< 3.0	Yes
IEEE 802.11n HT20	2.50	5	9.50	8.9125	2.8< 3.0	Yes
IEEE 802.11n HT40	2.50	5	9.50	8.9125	2.8< 3.0	Yes

#### Remark:

- 1. Output power including tune up tolerance;
- 2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

#### 6.2 Simultaneous Transmission for SAR Exclusion

The sample support one BT/WLAN modularand share same antenna, BT and WLAN can be active at the same time, but only with interleaving of packages switched on board level. That means that they don't transmit at the same time. No need consider simultaneous transmission;

### 7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.