

RF EXPOSURE REPORT

for

E-matic.

7" Tablet

Model Number: FunTab 3, FTB3DEMO

FCC ID: XHWFUNTAB3

Prepared for : E-matic.
Address : 3435 Ocean Park Blvd # 107 PMB#444 Santa Monica CA 90405 Los Angeles, CA 90405

Prepared by : Shenzhen BCTC Technology Co., Ltd.
Address : No.101, Yousong Road, Longhua New District, Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V05, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}]$

	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Maximum Output Power: mW	Separation distance mm	RF exposure
802.11b	8.5 ±1.0	9.5	8.91	5	2.77
802.11g	7.0 ±1.0	8	6.31	5	1.96
802.11n(HT20)	7.0 ±1.0	8	6.31	5	1.96
802.11n(HT40)	6.0 ±1.0	7	5.01	5	1.56

The Max RF exposure is 2.47.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.