

Full

TEST REPORT

No. I17D00195-SRD05

For

Client: LongSung Technology

Production: eMTC/NB-IoT/EGPRS Cellular Module

Model Name: A9500

FCC ID: XHZA9500

Hardware Version: QB1MX10A3

Software Version: QB10001_2.0.001

Issued date: 2017-07-08

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

Test Laboratory:

ECIT Shanghai, East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: welcome@ecit.org.cn



RF Test Report

Revision Version

Report No.: I17D00195-SRD05

Report Number	Revision	Date	Memo
I17D00195-SRD05	00	2017-07-08	Initial creation of test report
I17D00195-SRD05	01	2017-07-08	Second creation of test report

East China Institute of Telecommunications Page Number : 2 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017



CONTENTS

1.	TEST L	ABORATORY	5
1.1.	TESTIN	G LOCATION	5
1.2.	TESTIN	G ENVIRONMENT	5
1.3.	PROJE	CT DATA	5
1.4.	SIGNAT	TURE	5
2.	CLIENT	INFORMATION	6
2.1.	APPLIC	ANT INFORMATION	6
2.2.	MANUF	ACTURER INFORMATION	6
3.	EQUIPN	MENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1.	ABOUT	EUT	7
3.2.	INTERN	IAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3.	INTERN	IAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4.	STATE	MENTS	7
4.	REFER	ENCE DOCUMENTS	8
4.1.	REFER	ENCE DOCUMENTS FOR TESTING	8
5.	SUMMA	ARY OF TEST RESULTS	9
6.	TEST E	QUIPMENT UTILIZED	10
7.	TEST E	NVIRONMENT	12
ANN	EX A.	MEASUREMENT RESULTS	13
ANN	EX A.1.	OUTPUT POWER	13
ANN	EX A.2.	PEAK-TO-AVERAGE POWER RATIO	14
ANN	EX A.3.	OCCUPIED BANDWIDTH	14
ANN	EX A.4.	-26DB EMISSION BANDWIDTH	19
ANN	EX A.5.	BAND EDGE AT ANTENNA TERMINALS	23
ANN	EX A.6.	FREQUENCY STABILITY	25

Page Number

: 3 of 37



RF Test Report

ANNEX A.7.	CONDUCTED SPURIOUS EMISSION	27
ANNEX A.8.	RADIATED	31
ANNEX B.	DEVIATIONS FROM PRESCRIBED TEST METHODS	37

Report No.: I17D00195-SRD05

Page Number : 4 of 37 Report Issued Date : Jul.08.2017



1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications					
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District,					
	Shanghai, P. R. China					
Postal Code:	200001					
Telephone:	(+86)-021-63843300					
Fax:	(+86)-021-63843301					
FCC Registration NO.:	489729					

1.2. Testing Environment

Normal Temperature:	15-35℃
Extreme Temperature:	-10/+55℃
Relative Humidity:	20-75%

1.3. Project data

Project Leader:	Yu Anlu
Testing Start Date:	2017-06-22
Testing End Date:	2017-07-08

1.4. Signature

Yang Dejun

杨德君

(Prepared this test report)

1 2

Ding Li

(Reviewed this test report)

Zheng Zhongbin

Director of the laboratory (Approved this test report)

East China Institute of Telecommunications TEL: +86 21 63843300 FAX: +86 21 63843301 Page Number : 5 of 37 Report Issued Date : Jul.08.2017





2. Client Information

2.1. Applicant Information

Company Name: LongSung Technology (Shanghai) Co.,Ltd.

Address:

Room 606, Block B, Bldg. 1, No. 3000 Longdong Avenue.,

Zhangjiang Hi-Tech Park, Pudong District, Shanghai, P.R. China

Report No.: I17D00195-SRD05

Telephone: 021-50809688-669

Email: chenjun@longsung.com

2.2. Manufacturer Information

Company Name: LongSung Technology (Shanghai) Co.,Ltd.

Address:

Room 606, Block B, Bldg. 1, No. 3000 Longdong Avenue.,

Zhangjiang Hi-Tech Park, Pudong District, Shanghai, P.R. China

Telephone: 021-50809688-669

Email: chenjun@longsung.com

East China Institute of Telecommunications Pagr TEL: +86 21 63843300 FAX: +86 21 63843301 Rep

Page Number : 6 of 37 Report Issued Date : Jul.08.2017



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description	eMTC/NB-IoT/EGPRS Cellular Module
Model name	A9500
FCC ID	XHZA9500
Frequency	GSM850
Extreme Temperature	-10/+55℃
Nominal Voltage	3.8V
Extreme High Voltage	4.2V
Extreme Low Voltage	3.3V

Note: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT used during the test

E	EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
١	109	N/A	QB1MX10A3	QB10001_2.0.001	2017-06-21

^{*}EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	RF cable	
AE2		

^{*}AE ID: is used to identify the test sample in the lab internally.

3.4. Statements

The product name A9500, supporting EDGE, manufactured by LongSung Technology (Shanghai) Co.,Ltd., is a new product for testing.

ECIT has verified that the compliance of the tested device specified in section 5 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 5 of this test report.

East China Institute of Telecommunications Page Number : 7 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017



: 8 of 37

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	24 PERSONAL COMMUNICATIONS SERVICES	
FCC Part 22	PUBLIC MOBILE SERVICES	2014
ANSI/TIA-603-E	ISI/TIA-603-E Land Mobile FM or PM Communications Equipment	
	Measurement and Performance Standards	
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from	2014
Low-Voltage Electrical and Electronic Equipment in the		
	Range of 9 kHz to 40 GHz	



5. SUMMARY OF TEST RESULTS

Item	Test items	FCC rules	result
1	Output Power	2.1046/22.913(a)/24.232(c)	Pass
2	Peak-to-Average Ratio	24.232(d)	Pass
3	99%Occupied Bandwidth	2.1049(h)(i)/ 22.917(b)	Pass
4	-26dB Emission Bandwidth	22.917(b)/§24.238(b)	Pass
5	Band Edge at antenna terminals	22.917(a)/24.238(a)	Pass
6	Frequency stability	2.1055/24.235	Pass
7	Conducted Spurious mission	2.1053/22.917(a)/24.238(a)	Pass
8	Emission Limit	2.1051/22.917/24.238/22.913/24.232	Pass

Page Number

: 9 of 37

Report Issued Date : Jul.08.2017

Report No.: I17D00195-SRD05



6. Test Equipment Utilized

Climate chamber

No.	Equipment	Model	Serial Number	Manufactur er	Calibration date	Cal.interval
1	Climate chamber	SH-641	92012011	ESPEC	2016-01-06	2 Year

Radiated emission test system

The test equipment and ancillaries used are as follows.

No.	Equipment	Model	Serial Number	Manufactur er	Calibration date	Cal.interval
1	Universal Radio Communicatio n Tester	CMU20 0	123123	R&S	2017-05-11	1 Year
2	EMI Test Receiver	ESU40	100307	R&S	2017-05-11	1 Year
3	TRILOG Broadband Antenna	VULB9 163	VULB9163- 515	Schwarzbec k	2017-02-25	3 Year
4	Double- ridged Waveguide Antenna	ETS-31 17	00135890	ETS	2017-01-11	3 Year
5	2-Line V-Network	ENV21 6	101380	R&S	2017-05-11	1 Year
6	Substitution A ntenna	ETS-31 17	00135890	ETS	2017-01-11	3 Year
7	RF Signal Generator	SMF10 0A	102314	R&S	2017-05-11	1 Year
8	Substitution A ntenna	VUBA9 117	9117-266	Schwarzbec k	2014-08-19	3 Year
9	Amplifier	SCU03	10009	R&S	2017-01-05	1 Year

East China Institute of Telecommunications TEL: +86 21 63843300 FAX: +86 21 63843301 Page Number : 10 of 37 Report Issued Date : Jul.08.2017



RF Test Report

10	Amplifier	NTWPA -008610 F	12023024	Rflight	2017-01-05	1 Year
11	Attenuators	BW-N3 W5+	/	MCL	2017-01-05	1 Year

Report No.: I17D00195-SRD05

Page Number : 11 of 37 Report Issued Date : Jul.08.2017

Conducted test system

No.	Name	Туре	SN	Manufacture	Calibratio n date	Cal.interval
1	Spectrum Analyzer	FSQ26	101096	R&S	2017-05-11	1 Year
2	Universal Radio Communicat	CMU200	123102	R&S	2017-05-11	1 Year
3	DC Power Supply	ZUP60-1 4	LOC-220Z006 -0007	TDL-Lambda	2017-05-11	1 Year



7. Test Environment

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 35 °C	
Relative humidity	Min. = 20 %, Max. = 75 %	
Shielding effectiveness	> 100 dB	
Ground system resistance	< 0.5 Ω	

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.9 meters×10.9 meters×5.4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
VSWR	Between 0 and 6 dB, from 1GHz to 18GHz
Site Attenuation Deviation	Between -4 and 4 dB,30MHz to 1GHz
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Page Number

: 12 of 37



ANNEX A. MEASUREMENT RESULTS

ANNEX A.1. OUTPUT POWER

A.1.1. Summary

During the process of testing, the EUT was controlled Rhode & Schwarz Digital Radio. Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

Report No.: I17D00195-SRD05

A.1.2. Conducted

A.1.2.1. Method of Measurements

Method of measurements please refer to KDB971168 D01 v02r02 clause 5.

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSQ(peak).

These measurements were done at 3 frequencies,

824.2MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

A.1.2.2 Test procedures:

- 1. The transmitter output port was connected to base station.
- 2. Set the EUT at maximum power through base station.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

A.1.2.3 Limit:

22.913(a) Mobile stations are limited to 7watts.

24.232(c) Mobile and portable stations are limited to 2 watts.

A.1.2.4 Test Procedure:

The transmitter output power was connected to calibrated attenuator, the other end of which was connected to signal analyzer. Transmitter output power was read off the power in dBm. The power outputs at the transmitter antenna port was determined by adding the value of attenuator to the signal analyzer reading.

A.1.2.5 GSM Test Condition:

East China Institute of Telecommunications Page Number : 13 of 37
TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017



RF Test Report

RBW	VBW	Sweep time	Span
1MHz	1MHz	300ms	10MHz

Report No.: I17D00195-SRD05

A.1.2.7 Measurement results:

EDGE 850	GMSK 1 Slot	8PSK 1 Slot
Channel/fc(MHz)	Average power (dBm)	Average power (dBm)
Mid 189/836.4	31.24	24.71
Low 128/824.2	31.17	24.74
High 251/848.8	31.44	25.03

Conclusion: PASS

ANNEX A.2. Peak-to-Average Power Ratio

Method of test measurements please refer to KDB971168 D01 v02r02 clause 5.7.

A.2.1 PAPR Limit

The peak-to-average power ratio (PAPR) of the transmission may not exceed 13dB

A.2.2 Test procedures

- 1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 2.
- 1) Select the spectrum analyzer CCDF function.
- 2) Set RBW ≥ signal's occupied bandwidth.
- 3) Set the number of counts to a value that stabilizes the measured CCDF cure;
- 4) Sweep time \geq 1s.
- 3. Record the maximum PAPR level associated with a probability of 0.1%.

A.2.3 Test results:

EDGE850				
Channel	128	189	251	
Frequency (MHz)	824.2	836.4	848.8	
PAPR(dB)	9.64	10.44	10.28	

Conclusion: PASS

ANNEX A.3. Occupied Bandwidth

East China Institute of Telecommunications Page Number : 14 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017



Method of test please refer to KDB971168 D01 v02r02 clause 4.0.

A.3.1. Occupied Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of GSM850

A.3.2 Test Procedure:

- 1. The EUT output RF connector was connected with a short cable to the signal analyzer.
- 2. RBW was set to about 1% of emission BW, VBW >= 3 times RBW,.
- 3. 99% bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

A.3.3 Test result:

EDGE850(GMSK)				
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)		
Mid 189	836.4	245.19		
Low 128	824.2	245.19		
High 251	848.8	246.79		

EDGE850(8PSK)				
Test channel	Frequency (MHz)	99% Occupied Bandwidth(KHz)		
Mid 189	836.4	243.59		
Low 128	824.2	243.59		
High 251	848.8	243.59		


Conclusion: PASS EDGE 850(GMSK)

East China Institute of Telecommunications
TEL: +86 21 63843300 FAX: +86 21 63843301

Page Number : 15 of 37 Report Issued Date : Jul.08.2017








Date: 21.SEP.2017 10:12:11

Channel 189-Occupied Bandwidth (99%)




Date: 21.SEP.2017 10:13:01

Channel 128-Occupied Bandwidth (99%)

Page Number

: 16 of 37






Date: 21.SEP.2017 10:13:42

Channel 251-Occupied Bandwidth (99%)

EDGE 850(8PSK)



Page Number


: 17 of 37

Report Issued Date : Jul.08.2017

Date: 8.AUG.2017 07:14:37




Channel 189-Occupied Bandwidth (99%)



Date: 8.AUG.2017 07:15:24

Channel 128-Occupied Bandwidth (99%)



Date: 8.AUG.2017 07:16:11

Channel 251-Occupied Bandwidth (99%)

Page Number : 18 of 37 Report Issued Date : Jul.08.2017



ANNEX A.4. -26dB Emission Bandwidth

Method of test please refer to KDB971168 D01 v02r02 clause 4.0.

A.4.1. -26dB Emission Bandwidth

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of GSM850.

A.4.2 Test Procedure:

- 1. The EUT output RF connector was connected with a short cable to the signal analyzer.
- RBW was set to about 1% of emission BW, VBW >= 3 times RBW,.
- 3. 26dB bandwidth were measured, the occupied bandwidth is delta frequency between the two points where the display line intersects the signal trace.

A.4.3 Measurement methods:

For GSM: signal analyzer setting as: RBW=3KHz;VBW=10KHz;Span=1MHz.

A.4.4 Test results:


	EDGE 850(GMSK)				
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(KHz)			
Mid 189	836.4	320.51			
Low 128	824.2	315.71			
High 251	848.8	317.31			

EDGE 850(8PSK)						
Test channel	Frequency (MHz)	–26dBc Emission Bandwidth(KHz)				
Mid 189	836.4	307.692				
Low 128	824.2	301.282				
High 251	848.8	307.692				

Conclusion: PASS EDGE 850(GMSK)


East China Institute of Telecommunications Page Number : 19 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017





Date: 21.SEP.2017 10:24:58






Date: 21.SEP.2017 10:23:38

Channel 128- Emission Bandwidth (-26dBc BW)

Page Number


: 20 of 37



Date: 21.SEP.2017 10:18:00

Channel 251- Emission Bandwidth (-26dBc BW)






Date: 8.AUG.2017 07:19:55

Channel 189- Emission Bandwidth (-26dBc BW)


Page Number : 21 of 37 Report Issued Date : Jul.08.2017





Date: 8.AUG.2017 07:20:24

Channel 128- Emission Bandwidth (-26dBc BW)



Date: 8.AUG.2017 07:20:53

Channel 251- Emission Bandwidth (-26dBc BW)

Page Number

: 22 of 37



ANNEX A.5. Band Edge at antenna terminals

Method of test measurements please refer to KDB971168 D01 v02r02 clause 3.5

A.5.1 Limit:

The magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specification in the instruction manual and/or alignment procedure, shall not be less than 43+10log (Mean power in watts) dBc below the mean power output outside a license's frequency block(-13dBm).

Report No.: I17D00195-SRD05


A.5.2 Test procedure:

- 1. The RF output of the transceiver was connected to a signal analyzer through appropriate attenuation.
- 2. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.
- 3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band
- 4. The limit line is derived from 43+10log(P) Db below the transmitter power P(Watts)
 - =P(W)-[43+10log(P)](Db)
 - =[30+10log(P)](dBm)-[43+10log(P)](Db)
 - =-13dBm

East China Institute of Telecommunications Page Number : 23 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017




EDGE 850



Date: 8.AUG.2017 07:23:54

Channel 128- LOW BAND EDGE BLOCK



Date: 8.AUG.2017 07:24:44

Channel 251- HIGH BAND EDGE BLOCK

Page Number : 24 of 37



ANNEX A.6. FREQUENCY STABILITY

Method of test measurements please refer to KDB971168 D01 v02r02 clause 3.8

A.5.1.Method of Measurement and test procedures

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

Report No.: I17D00195-SRD05

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30℃.
- 3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at $+50^{\circ}$ C.
- 7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 C increments from $+50^{\circ}$ C to -30° C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.5.2. Measurement Limit

A.5.2.1. For Hand carried battery powered equipment

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.3VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages was varied from 85% to 115%.

East China Institute of Telecommunications Page Number : 25 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017



A.5.2.2. For equipment powered by primary supply voltage

According to the JTC standard the GSM frequency stability of the carrier shall be accurate to within 0.1ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec.24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.5.3 Test results
GSM850Mid Channel/fc(MHz) 189/836.4
Frequency Error VS Temperature

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
3.8	-30	21	2091
3.8	-20	15	2091
3.8	-10	1	2091
3.8	0	-5	2091
3.8	10	21	2091
3.8	20	2	2091
3.8	30	11	2091
3.8	40	-4	2091
3.8	50	20	2091

Frequency Error VS Voltage

Power Supply (VDc)	Environment Temperature(℃)	Frequency error(Hz)	Limit (Hz)
3.3	25	17	2091
3.8	25	7	2091
4.2	25	21	2091

Conclusion: PASS

East China Institute of Telecommunications Page Number : 26 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017



ANNEX A.7. CONDUCTED SPURIOUS EMISSION

A.7.1. GSM Measurement Method and test procedures

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For GSM850,data taken from 30 MHz to 10 GHz.
- 2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
- 3. The procedure to get the conducted spurious emission is as follows: The trace mode is set to MaxHold to get the highest signal at each frequency; Wait 25 seconds;Get the result.
- 4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM 850 Transmitter

Channel	Frequency(MHz)
128	824.2
189	836.4
251	848.8

A.7.1.1. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A7.1.2. Measurement result


Spurious emission limit -13dBm.


Note: peak above the limit line is the carrier frequency.

A7.1.2.1. EDGE 850

East China Institute of Telecommunications Page Number : 27 of 37
TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017








Date: 8.AUG.2017 07:28:20

Channel 128: 30MHz~1GHz





Date: 8.AUG.2017 07:28:43

Channel 128: 1GHz~10GHz

Page Number : 28 of 37








Date: 8.AUG.2017 07:27:21

Channel 189: 30MHz~1GHz




Date: 8.AUG.2017 07:27:44

Channel 189: 1GHz~10GHz

Page Number : 29 of 37








Date: 8.AUG.2017 07:29:19

Channel 251: 30MHz~1GHz



Date: 8.AUG.2017 07:29:42

Channel 251: 1GHz~10GHz

Page Number : 30 of 37

Report Issued Date : Jul.08.2017

Conclusion: PASS



ANNEX A.8. RADIATED

A.8.1. ERP

A.8.1.1. GSM ERP

A.8.1.1.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power"and 24.232(c) specifies that "Peak transmit power must be measured over any interval ofcontinuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must

not exceed 7 Watts."


A.8.1.1.2. Method of Measurement

The measurements procedures in TIA-603D-2010 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from thereceive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUTfor emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUTthrough 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



East China Institute of Telecommunications TEL: +86 21 63843300 FAX: +86 21 63843301 Page Number : 31 of 37 Report Issued Date : Jul.08.2017



In the chamber, an substitution antenna for the frequency band of interest is placed at thereference point of the chamber. An RF Signal source for the frequency band of interest isconnected to the substitution antenna with a cable that has been constructed to not interferewith the radiation pattern of the antenna. A power (PMea) is applied to the input of thesubstitution antenna, and adjust the level of the signal generator output until the value of thereceiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. Thetest should be performed by rotating the test item and adjusting the receiving antennapolarization.

Report No.: I17D00195-SRD05

4. A amplifier should be connected to the Signal Source output port. And the cable should beconnect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

Power(EIRP)=PMea+ PAg- PcI+ Ga

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

A.8.1.1.3 GSM 850-ERP 22.913(a)

A.8.1.1.3.1 Limits

	Power Step	Burst Peak ERP (dBm)
EDGE	6	≤38.45dBm (7W)

A.8.1.1.3.2 Measurement result

EDGE(GMSK)

Frequency (MHz)	P _{Mea} (dBm)	Pcl(dB)	P _{Ag} (dB)	GaAntenna Gain(dBd)	PeakERP(d Bm)	Polarizati on
824.2	-4.97	3.1	37	3.11	32.04	Н
836.6	-4.85	3.1	37	3.11	32.16	Н
848.8	-4.48	3.1	37	3.11	32.53	Н

EDGE(8PSK)

Frequency (MHz)	P _{Mea} (dBm)	Pcl(dB)	P _{Ag} (dB)	GaAntenna Gain(dBd)	PeakERP(d Bm)	Polarizati on
824.2	-12.58	3.1	37	3.11	24.43	Н

East China Institute of Telecommunications TEL: +86 21 63843300 FAX: +86 21 63843301 Page Number : 32 of 37 Report Issued Date : Jul.08.2017



RF Test Report

836.6	-11.76	3.1	37	3.11	25.25	Н
848.8	-11.47	3.1	37	3.11	25.54	Н

Report No.: I17D00195-SRD05

Frequency: 824.2MHz

Peak ERP(dBm)= PMea(-12.58dBm) - Pcl(3.1dB) +PAg(37dB) + Ga(3.11dBd)

= 24.43dBm

Note: ANALYZER SETTINGS: RBW = VBW = 3MHz

A.8.2 EMISSION LIMIT (§2.1051/§22.917§24.238)


A.8.2.1 GSM Measurement Method

The measurement procedures in TIA-603D-2010are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of GSM850.

A.8.2.2 The procedure of radiated spurious emissions is as follows:


1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10thharmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.

East China Institute of Telecommunications Page Number : 33 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017





In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (Ppl) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (Ga) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (Ppl) is the summation of the cable loss.

The measurement results are obtained as described below:

Power(EIRP)=PMea- Ppl+ Ga

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi

A.8.2.3 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.8.2.4 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the GSM850 band (824.2MHz, 836.6MHz, 848.8MHz). It was decided that measurements at these three carrierfrequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the GSM850 into any of the other blocks.

East China Institute of Telecommunications TEL: +86 21 63843300 FAX: +86 21 63843301 Page Number : 34 of 37 Report Issued Date : Jul.08.2017

Report No.: I17D00195-SRD05



The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.8.2.5 Measurement Results

Measurements results:

Frequency	Channel	Frequency Range	Result
	Low	30MHz~10GHz	Р
GSM850	Middle	30MHz~10GHz	Р
	High	30MHz~10GHz	Р

GSM850

EGPRS Mode Channel 128

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarizatio n
1906.0714 29	-33.58	4.7	2.8	-35.48	-13	Н
3319.6153 85	-43.77	6.2	5	-44.97	-13	Н
5233.8461 54	-48.04	8	8.6	-47.44	-13	V
6643.0769 23	-48.29	9.1	11.9	-45.49	-13	V
7286.1538 46	-49.64	9.6	13.8	-45.44	-13	V
8570.7692 31	-52.12	10.3	18.2	-44.22	-13	Н

Note:

EGPRS 850, CH128

Power(ERP)= Pmea-PcI+Ga=-33.58-4.7+2.8=-35.48dbm

This method Applicable to the following table.

EGPRS Mode Channel 189

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarizatio n
2576.7857 14	-36.05	5.5	3.5	-38.05	-13	Н

East China Institute of Telecommunications TEL: +86 21 63843300 FAX: +86 21 63843301 Page Number : 35 of 37 Report Issued Date : Jul.08.2017





3319.6153 85	-43.21	6.2	5.4	-44.01	-13	Н
4250.7692 31	-49.88	7.1	7.7	-49.28	-13	V
5442.6923 08	-49.07	8.1	9.4	-47.77	-13	V
7578.4615 39	-50.37	9.7	14.7	-45.37	-13	V
9178.4615 38	-51.39	10.5	18.4	-43.49	-13	V

EGPRS Mode Channel 251

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarizatio n
1785	-36.8	4.5	2.8	-38.5	-13	Н
3323.0769 23	-41.59	6.2	5.4	-42.39	-13	Н
4554.2307 69	-47.13	7.4	7.3	-47.23	-13	Н
5830.3846 15	-49.74	8.4	10.4	-47.74	-13	Н
6635.3846 15	-48.84	9.1	11.9	-46.04	-13	V
7980	-50.41	9.9	16.6	-43.71	-13	Н

Conclusion: PASS

Note: the EUT was displayed in several different direction, the worst cases were shown.

Page Number

: 36 of 37





ANNEX B. Deviations from Prescribed Test Methods

Report No.: I17D00195-SRD05

No deviation from Prescribed Test Methods.	
******End The Repo	r t ******

East China Institute of Telecommunications Page Number : 37 of 37 TEL: +86 21 63843300 FAX: +86 21 63843301 Report Issued Date : Jul.08.2017