



RF EXPOSURE EVALUATION REPORT

FCC ID : XIA-NTC225

Equipment : 4G LTE Cat1 Industrial IoT Router

Brand Name :



Model Name : NTC-225

Applicant : NetComm Wireless Pty Ltd
Level 5, 18-20 Orion Road, Lane Cove NSW 2066 Australia

Manufacturer : Casa Systems Inc.
100 Old River Road Andover, MA 01810 USA

Standard : 47 CFR Part 1.1307
47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 1.1307, 47 CFR Part 2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.

Cona Huang

Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. DETERMINATION OF EXEMPTION.....	5
4. RF EXPOSURE EVALUATION.....	6
4.1. Standalone assessment	6



History of this test report



1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	4G LTE Cat1 Industrial IoT Router
Brand Name	 NetCommWireless
Model Name	NTC-225
FCC ID	XIA-NTC225
Wireless Technology and Frequency Range	LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 13: 777 MHz ~ 787 MHz
Mode	LTE: QPSK, 16QAM, 64QAM
EUT Stage	Production Unit

Reviewed by: Jason Wang

Report Producer: Paula Chen

2. Maximum RF average output power among production units

Mode	Maximum Average power(dBm)	
LTE	Band 4	23.47
	Band 13	22.31



3. Determination of exemption

Per 1.1307(b)(3), (i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \text{ERP}_{20\text{cm}} (d / 20)^x \text{ for distance } d \leq 20\text{cm}$$

$$P_{th} \text{ (mW)} = \text{ERP}_{20\text{cm}} \text{ for distance } 20\text{cm} < d \leq 40\text{cm}$$

$$x = -\log_{10} \left(\frac{60}{\text{ERP}_{20\text{cm}} \sqrt{f}} \right)$$

$\text{ERP}_{20\text{cm}} \text{ (mW)}$	$0.3 \text{ GHz} \leq f < 1.5 \text{ GHz}$:	2040
	$1.5 \text{ GHz} \leq f \leq 6 \text{ GHz}$:	3060

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2R^2$.



4. RF Exposure Evaluation

4.1. Standalone assessment

General Note:

1. P_i means the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm.
2. P_{th} means the exemption threshold power (P_{th}), according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i .
3. In this report, Part1.1307(b)(3)(i)(B) is used to perform RF Exposure evaluation.
4. The distance of 20cm is for this device.

Band	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Maximum EIRP (dBm)	Maximum ERP (dBm)	Maximum EIRP (mW)	Maximum ERP (mW)	P_i (dBm)	P_i (mW)	Part1.1307 option(b) Threshold (mW)
LTE Band 4	3.28	23.47	26.8	24.60	473.15	288.40	24.60	288.40	3060.000
LTE Band 13	4.71	22.31	27.0	24.87	503.50	306.90	24.87	306.90	1585.080

Conclusion:

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.