

MPE Calculation

§ 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

Part 1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

1.1 Test Procedure

An MPE evaluation for was performed in order to show that the device was compliant with §2.1091. The maximum power density was calculated for each transmitter at a separation distance of 20cm.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{ConductedPower(dBm)/10}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$



1.2 Results:

The device contains a cellular transmitter which does transmit simultaneously with any other radios in the device. The following calculations show that the total power density from transmitter in each band at 20cm is less than the limit for general population / un-controlled exposure. The MPE calculations are less than the applicable limit.

CDMA Cell Band Transmitter – External Antenna:

Frequency	824	MHz		
Limit	0.5493	mW/cm ²		
Distance	20	cm		
Conducted Power				
TX Ant Gain	24.5	dBm	281.83829	mW
EIRP	9.40	dB _i		
ERP = EIRP - 2.15	33.90	dBm	2454.7089	mW
Power Density	31.75	dBm	1496.2357	mW
	0.1984	mW/cm ² at 20cm		

CDMA PCS Band Transmitter – External Antenna:

Frequency	1880	MHz		
Limit	1.0000	mW/cm ²		
Distance	20	cm		
Conducted Power				
TX Ant Gain	24.5	dBm	281.83829	mW
EIRP	8.4	dB _i		
ERP = EIRP - 2.15	32.9	dBm	1949.8446	mW
Power Density	0.3879	mW/cm ² at 20cm		

CDMA Cell Band Transmitter – Internal Antenna:

Frequency	836.52	MHz		
Limit	0.5577	mW/cm ²		
Distance	20	cm		
Conducted Power				
TX Ant Gain	24.5	dBm	281.83829	mW
EIRP	6.28	dB _i		
ERP = EIRP - 2.15	30.78	dBm	1196.7405	mW
Power Density	28.63	dBm	729.45751	mW
	0.2382	mW/cm ² at 20cm		



CDMA PCS Band Transmitter – Internal Antenna:

Frequency Limit	1851.25	MHz
Distance Conducted Power	1.0000	mW/cm ²
TX Ant Gain	20	cm
EIRP	24.5	dBm
	6.00	dBi
	30.50	dBm
Power Density	281.83829	mW
	1122.0185	mW
	0.2233	mW/cm ² at 20cm

