

No. 1 Workshop, M-10, Middle Section, Science & Technology Park,  
District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: sgs\_internet\_operations@sgs.com

Report No.: SZEMO09060299201

Page: 1 of 38

## **TEST REPORT**

**Application No.:** SZEMO090602992RF

**Applicant:** Chin Fai Electronics Company

**Manufacturer/ Factory:** Chin Fai Electronics Company

**FCC ID:** XJ46110200907001

**Fundamental Carrier Frequency :** 2.402GHz to 2.480GHz

**Equipment Under Test (EUT):**

Name: SILICON BLUETOOTH KEYBOARD

Model: KB6110, KB6111, KB6112, KB6115, KB6116, KB6117, KB6118, KB6119 \*

Trade mark:



\*

Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

**Standards:** FCC PART 15 Subpart C

ANSI C63.4 2003

**Date of Receipt:** 10 June 2009

**Date of Test:** 11 June to 07 September 2009

**Date of Issue:** 08 September 2009

<b>Test Result :</b>	<b>PASS *</b>
----------------------	---------------

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 2 of this report for further detail.

Authorized Signature:

A handwritten signature in blue ink, appearing to read 'Robinson Lo'.

Robinson Lo  
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 2 Test Summary

Test	Test Requirement	Standard Paragraph	Result
<b>Antenna Requirement</b>	FCC PART 15	Section 15.247 (c)	PASS
<b>Occupied Bandwidth</b>	FCC PART 15	Section 15.247 (a1)	PASS
<b>Carrier Frequencies Separated</b>	FCC PART 15	Section 15.247(a)(1)	PASS
<b>Hopping Channel Number</b>	FCC PART 15	Section 15.247(a)(1)(iii)	PASS
<b>Dwell Time</b>	FCC PART 15	Section 15.247(a)(1)(iii)	PASS
<b>Pseudorandom Frequency Hopping Sequence</b>	FCC PART 15	Section 15.247(a)(1)	PASS
<b>Maximum Peak Output Power</b>	FCC PART 15		PASS
<b>RF Exposure Compliance Requirement</b>	FCC PART 15	15.247(b)(4)& TCB Exclusion List (7 July 2002)	PASS
<b>Radiated Emission</b>	FCC PART 15		PASS*

**Remark:**

1. The EUT was tested installing fully charged batteries
2. Item No.: KB6110, KB6111, KB6112, KB6115, KB6116, KB6117, KB6118, KB6119


Only the Item KB6110 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items.

3. The EUT passed the Radiated Emission test after modification as below:

For the PCB of mainboard, cover it with copper sheet; For the power input lines, add a EMI core, round one circle, model no.: K5B RH4X6X2, supplier: Kingcore; please see the detail information as follow:



For the J1 of the PCB, add 100pF capacitances to all the lines, please see the detail information as follow photo:<sup>4</sup>



### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION .....</b>	<b>5</b>
4.1 CLIENT INFORMATION.....	5
4.2 GENERAL DESCRIPTION OF THE E.U.T .....	5
4.3 DESCRIPTION OF SUPPORT UNITS .....	5
4.4 STANDARDS APPLICABLE FOR TESTING .....	5
4.5 TEST LOCATION .....	5
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
4.7 TEST FACILITY .....	6
<b>5 EQUIPMENTS USED DURING TEST.....</b>	<b>7</b>
<b>6 TEST RESULTS .....</b>	<b>8</b>
6.1 E.U.T. TEST CONDITIONS.....	8
6.2 ANTENNA REQUIREMENT.....	8
6.2.1 <i>Standard requirement</i> .....	8
6.2.2 <i>EUT Antenna</i> .....	8
6.3 OCCUPIED BANDWIDTH.....	9
6.4 CARRIER FREQUENCIES SEPARATED .....	12
6.5 HOPPING CHANNEL NUMBER .....	15
6.6 DWELL TIME .....	16
6.7 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	22
6.7.1 <i>Standard requirement</i> .....	22
6.7.2 <i>EUT Pseudorandom Frequency Hopping Sequence</i> .....	22
6.8 MAXIMUM PEAK OUTPUT POWER .....	23
6.9 BAND EDGE .....	26
6.10 RADIATED EMISSIONS .....	30
6.11 TRANSMITTER EMISSION .....	33-38

## 4 General Information

### 4.1 Client Information

Applicant: Chin Fai Electronics Company  
Manufacturer/ Factory: Chin Fai Electronics Company  
Address of Applicant: Building2c 2d, yingfeng industrial park, sanhe economic development zone huiyang district Huizhou city  
Address of Manufacturer/ Factory: Building2c 2d, yingfeng industrial park, sanhe economic development zone huiyang district Huizhou city

### 4.2 General Description of the E.U.T

Product Name: SILICON BLUETOOTH KEYBOARD  
Model: KB6110, KB6111, KB6112, KB6115, KB6116, KB6117, KB6118, KB6119  
Number of Channels: 79 Channels  
Channel Separation: 1 MHz  
Type of Modulation: FHSS (Frequency Hopping Spread Spectrum); Adaptive Frequency Hopping (AFH) is used.  
Technique of Modulation: GFSK  
Dwell time: Per channel is less than 0.4s  
Antenna Type: Integral  
Antenna Gain: 0 dBi  
Power Supply: keyboard: 2\*1.5(AAA)=3.0V

### 4.3 Description of Support Units

The EUT was tested independently

### 4.4 Standards Applicable for Testing

The customer requested FCC tests for the EUT.

The standard used was FCC PART 15 Subpart C: 2008. ANSI C63.4:2003.and DA 00-705.

### 4.5 Test Location

All tests were performed at:

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

### 4.6 Other Information Requested by the Customer

None.

## 4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.

Date of Registration: September 29, 2008. Valid until September 28, 2011.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.

- **Industry Canada (IC)**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

## 5 Equipments Used during Test

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2009	15-06-2010
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2008	11-12-2009
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	18-06-2009	17-06-2010
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2009	11-08-2010
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	18-06-2009	17-06-2010
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	12-08-2009	11-08-2010
8	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	12-08-2009	11-08-2010
9	Pre-amplifier (1-18GHz)	Rohde & Schwarz	AFS42-00101 800-25-S-42	SEL0081	18-06-2009	17-06-2010
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	SEL0080	18-06-2009	17-06-2010
11	Band filter	Amindeon	82346	SEL0094	18-06-2009	17-06-2010
12	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2009	14-06-2010

## 6 Test Results

### 6.1 E.U.T. test conditions

Operating Environment:

Temperature: 24.0 °C

Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

Test frequencies: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Test frequency is the lowest channel: 0 channel(2402MHz), middle channel: 38 channel(2441MHz) and highest channel: 78 channel(2480MHz)

### 6.2 Antenna Requirement

#### 6.2.1 Standard requirement

15.203 requirement:

For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### 6.2.2 EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.

**Test result: The unit does meet the FCC requirements.**

### 6.3 Occupied Bandwidth

Test Requirement:	FCC 15.247(a)
Test Method:	ANSI C63.4 2003& DA 00-705
Test Status:	Test in fixing operating frequency at lowest, Middle, highest channel.
Test Procedure:	
The Transmitter output of EUT was connected to the spectrum analyzer. The 20 dB bandwidth of the fundamental frequency was measured. The setting of spectrum analyzer is as follows:	
Equipment Mode	Spectrum Analyzer
Detector Function	Peak Mode
RBW	30KHz
VBW	100KHz

**Test result:**

Lowest channel 2.402GHz	Middle channel 2.441GHz	Highest channel 2.480GHz
764 KHz	800 KHz	812 KHz

Result plot as follows:

### 1. Lowest Channel:




Date: 15.JUN.2009 13:13:13

### 2. Middle Channel:



Date: 15.JUN.2009 13:30:39

**3. Highest Channel:**

Date: 15.JUN.2009 16:04:40

**Test result: The unit does meet the FCC requirements.**

## 6.4 Carrier Frequencies Separated

Test Requirement: FCC 15.247(a)

Test Method: ANSI C63.4 2003& DA 00-705

Test requirements: Regulation 15.247(a), (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1 Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.

Equipment mode: Spectrum analyzer

Equipment Mode	Spectrum Analyzer
Detector Function	Peak Mode
RBW	100KHz
VBW	300KHz


2. By using the Max-Hold function record the separation of two adjacent channels.

3. Measure the frequency difference of these two adjacent channels by spectrum analyzer Marker function.


4. Repeat above procedures until all frequencies measured were complete.

**Test result:**

Lowest channel 2.402GHz	Middle channel 2.441GHz	Highest channel 2.480GHz
1.004MHz	1.008MHz	1.168MHz


**1. Lowest Channel:**

Date: 15.JUN.2009 13:19:34

**2. Middle Channel:**

Date: 15.JUN.2009 13:34:04

### 3. Highest Channel:



Date: 15.JUN.2009 16:18:44

**Test result: The unit does meet the FCC requirements.**

## 6.5 Hopping Channel Number

Test Requirement: FCC 15.247(a)

Test Method: ANSI C63.4:2003, 15.247 & DA 00-705

Requirements: Regulation 15.247 (a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.

**Test result:** Total channels are 79 channels.

### Hopping channel numbers



Date: 16.JUN.2009 10:57:35

**Test result:** The unit does meet the FCC requirements.

## 6.6 Dwell Time

Test Standards: FCC 15.247(a)

Test Method: ANSI C63.4 2003& DA 00-705

Test Requirements: Regulation 15.247(a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.  
Equipment mode: spectrum analyzer, detector function: Peak  
RBW=1MHz, VBW=1MHz, Span=zero.
2. Adjust the center frequency of spectrum analyzer on any frequency be measured.
3. Measure the Dwell Time by spectrum analyzer Marker function.
4. Repeat above procedures until all frequencies measured were complete.

Test Result:

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as blow

DH1 time slot=0.392(ms)\*(1600/ (2\*79))\*31.6=125.4 ms

DH3 time slot=1.68(ms)\*(1600/ (4\*79))\*31.6=268.8ms

DH5 time slot=2.96(ms)\*(1600/ (6\*79))\*31.6=315.7ms

DH1 time slot=0.392(ms)\*(1600/ (2\*79))\*31.6=125.4 ms

DH3 time slot=1.68(ms)\*(1600/ (4\*79))\*31.6=268.8ms

DH5 time slot=2.96(ms)\*(1600/ (6\*79))\*31.6=315.7ms


DH1 time slot=0.392(ms)\*(1600/ (2\*79))\*31.6=125.4 ms

DH3 time slot=1.68(ms)\*(1600/ (4\*79))\*31.6=268.8ms


DH5 time slot=3.00(ms)\*(1600/ (6\*79))\*31.6=319.9ms

**The unit does meet the FCC requirements.**


Please refer the graph as below:

**Lowest Channel**
**DH1**


Date: 29.OCT.2009 09:38:13


**DH3**


Date: 29.OCT.2009 09:39:08


**DH5**


Date: 29.OCT.2009 09:47:10


### Middle Channel

**DH1**



Date: 29.OCT.2009 09:36:16

**DH3**



Date: 29.OCT.2009 09:35:04

**DH5**



Date: 29.OCT.2009 09:34:12

**Highest Channel**
**DH1**


Date: 29.OCT.2009 09:30:48

**DH3**


Date: 29.OCT.2009 09:31:51

**DH5**

Date: 29.OCT.2009 09:32:44

## 6.7 Pseudorandom Frequency Hopping Sequence

### 6.7.1 Standard requirement


15.247(a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 6.7.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.


## 6.8 Maximum Peak Output Power

Test Requirement: FCC Part 15.247 & DA 00-705

Test Method: ANSI C63.4: 2003 & DA 00-705

Test Limit: Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.  
Refer to the result "Hopping channel number" of this document. The 1 watt (30.0dBm) limit applies.

Test Configuration:



### Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.


### Test Result:

Lowest channel 2.402GHz	Middle channel 2.441GHz	Highest channel 2.480GHz
2.18dBm	2.18 dBm	-0.55 dBm

**Test result: The unit does meet the FCC requirements.**


**Test result plot as follows:**

**1. Lowest Channel:**




Date: 15.JUN.2009 13:07:31

**2. Middle Channel:**






Date: 15.JUN.2009 13:26:16

**3. Highest Channel:**




Date: 15.JUN.2009 15:59:44

## 6.9 Band edge




Test Requirement:	FCC 15.247(d)
Test Method:	ANSI C63.4:2003 & DA 00-705
Test Status:	Test lowest channel, highest channel.
Test site:	The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
Limit:	15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

**Out-OFF-band spurious emissions-conducted measurement:**
**1. The lowest channel**


## 2. Middle channel



### 3. The highest channel



## 6.10 Radiated Emissions

Test Requirement: 15.209

Test Method: ANSI C63.4:2003

Test Status: Bluetooth mode: Keep the EUT connected to Bluetooth and exchange data.

Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)

Test Range 30MHz to 13GHz

30MHz-1000MHz: Quasi-peak detector RBW=120KHz, VBW=300KHz

Above 1GHz: PK detector RBW=1MHz, VBW=3MHz

15.209 Limit: 40.0 dB $\mu$ V/m between 30MHz & 88MHz



43.5 dB $\mu$ V/m between 88MHz & 216MHz

46.0 dB $\mu$ V/m between 216MHz & 960MHz

54.0 dB $\mu$ V/m between 960MHz & 1000MHz

above 1GHz: Average value Limit 54.0 dB $\mu$ V/m

Peak value Limit 74.0 dB $\mu$ V/m.

**Test Configuration:****Figure1: 30MHz to 1GHz radiated emissions test configuration****Figure 2: Above 1GHz radiated emissions test configuration**

**Test Procedure:** The procedure used was ANSI Standard C63.4-2003. The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

**Test in Bluetooth mode.**
**Vertical**

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Quasi-peak Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector
35.820	0.60	12.70	28.13	46.25	31.42	40.00	-8.58	QP
60.070	0.80	7.19	28.05	46.92	26.86	40.00	-13.14	QP
71.710	0.86	7.06	28.00	49.01	28.93	40.00	-11.07	QP
87.230	1.10	8.45	27.96	42.09	23.68	40.00	-16.32	QP
144.460	1.31	8.53	27.49	46.81	29.16	43.50	-14.34	QP
797.270	3.19	22.09	26.95	41.23	39.56	46.00	-6.44	QP
3195.00	7.03	32.16	39.43	41.27	41.03	74.00	-32.97	PK
3195.00	7.03	32.16	39.43	30.6	30.36	54.00	-23.64	AV
4875.00	10.36	34.34	39.89	39.94	44.75	74.00	-29.25	PK
4875.00	10.36	34.34	39.89	29.8	34.61	54.00	-19.39	AV

**Horizontal**

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Quasi-peak Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector
226.910	1.56	11.56	27.02	40.92	27.02	46.00	-18.98	QP
238.550	1.62	11.93	26.96	44.66	31.25	46.00	-14.75	QP
261.830	1.73	12.55	26.87	43.96	31.37	46.00	-14.63	QP
273.470	1.78	12.78	26.82	44.15	31.89	46.00	-14.11	QP
285.110	1.84	13.26	26.77	44.30	32.63	46.00	-13.37	QP
749.740	3.06	21.70	27.11	42.92	40.57	46.00	-5.43	QP
3515.00	7.5	32.56	39.67	39.54	39.93	74.00	-34.07	PK
3515.00	7.5	32.56	39.67	30.2	30.59	54.00	-23.41	AV
5415.00	11.99	35.06	41.49	40.91	46.47	74.00	-27.53	PK
5415.00	11.99	35.06	41.49	28.2	33.76	54.00	-20.24	AV

## 6.11 Transmitter emission

Test Requirement:	15.247(d),15.209 & 15.205
Test Method:	ANSI C63.4:2003 & DA 00-705
Test Status:	Test lowest channel, Middle, highest channel.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Test Range	30MHz to 25GHz
	30MHz-1000MHz: Quasi-peak detector RBW=120KHz, VBW=300KHz
	Above 1GHz: PK detector RBW=1MHz, VBW=3MHz for Peak
	RBW=1MHz, VBW=10Hz for Average
15.209 Limit:	40.0 dB $\mu$ V/m between 30MHz & 88MHz
	43.5 dB $\mu$ V/m between 88MHz & 216MHz
	46.0 dB $\mu$ V/m between 216MHz & 960MHz
	above 960MHz: Average value Limit 54.0 dB $\mu$ V/m
	Peak value Limit 74.0 dB $\mu$ V/m.

**Transmitter emission below 1GHz**
**The lowest channel (2.402GHz):**
**Peak Measurement: Peak detector**

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390	4.97	32.24	44.75	38.49	30.95	74.00	-43.05	Vertical
2400	4.97	32.25	44.75	43.49	35.96	74.00	-38.04	Vertical
4808	6.61	34.04	45.40	45.25	40.50	74.00	-33.50	Vertical
7137	7.67	36.44	44.58	44.94	44.47	74.00	-29.53	Vertical
9619	8.53	36.99	42.20	42.07	45.39	74.00	-28.61	Vertical
12033	10.11	38.82	43.35	41.89	47.47	74.00	-26.53	Vertical
14447	11.23	39.45	45.53	42.02	47.17	74.00	-26.83	Vertical
2390	4.97	32.24	44.75	37.99	30.45	74.00	-43.55	Horizontal
2400	4.97	32.25	44.75	42.99	35.46	74.00	-38.54	Horizontal
4825	6.62	34.03	45.40	45.88	41.13	74.00	-32.87	Horizontal
7222	7.63	36.29	44.49	45.16	44.59	74.00	-29.41	Horizontal
9585	8.50	36.97	42.23	42.54	45.78	74.00	-28.22	Horizontal
12033	10.11	38.82	43.35	42.53	48.11	74.00	-25.89	Horizontal
14447	11.23	39.45	45.53	41.95	47.10	74.00	-26.90	Horizontal

**Average Measurement: Peak detector**

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit	Polarization
2390	4.97	32.24	44.75	24.99	17.45	54.00	-36.55	Vertical
2400	4.97	32.25	44.75	35.99	28.46	54.00	-25.54	Vertical
4808	6.61	34.04	45.40	32.45	27.70	54.00	-26.30	Vertical
7222	7.63	36.29	44.49	31.68	31.11	54.00	-22.89	Vertical
9619	8.53	36.99	42.20	29.26	32.58	54.00	-21.42	Vertical
12067	10.12	38.84	43.40	29.17	34.73	54.00	-19.27	Vertical
14447	11.23	39.45	45.53	28.42	33.57	54.00	-20.43	Vertical
2390	4.97	32.24	44.75	24.99	17.45	54.00	-36.55	Horizontal
2400	4.97	32.25	44.75	34.99	27.46	54.00	-26.54	Horizontal
4808	6.61	34.04	45.40	32.39	27.64	54.00	-26.36	Horizontal
7239	7.62	36.25	44.48	31.64	31.03	54.00	-22.97	Horizontal
9619	8.53	36.99	42.20	29.35	32.67	54.00	-21.33	Horizontal
12033	10.11	38.82	43.35	29.14	34.72	54.00	-19.28	Horizontal
14447	11.23	39.45	45.53	28.36	33.51	54.00	-20.49	Horizontal

**The middle channel (2.441GHz)**

## Peak Measurement: Peak detector

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit	Polarization
4893	6.65	34.02	45.42	46.50	41.75	74.00	-32.25	Vertical
7358	7.57	36.06	44.35	46.55	45.83	74.00	-28.17	Vertical
9772	8.65	37.12	42.06	43.07	46.78	74.00	-27.22	Vertical
12220	10.17	38.93	43.59	42.87	48.38	74.00	-25.62	Vertical
14634	11.34	39.60	45.40	41.74	47.28	74.00	-26.72	Vertical
4893	6.65	34.02	45.42	46.28	41.53	74.00	-32.47	Horizontal
7392	7.55	35.99	44.32	46.46	45.68	74.00	-28.32	Horizontal
9772	8.65	37.12	42.06	41.85	45.56	74.00	-28.44	Horizontal
12220	10.17	38.93	43.59	42.77	48.28	74.00	-25.72	Horizontal
14634	11.34	39.60	45.40	41.84	47.38	74.00	-26.62	Horizontal

## Average Measurement: Peak detector

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit	Polarization
4893	6.65	34.02	45.42	33.01	28.26	54.00	-25.74	Vertical
7324	7.58	36.10	44.39	32.14	31.43	54.00	-22.57	Vertical
9772	8.65	37.12	42.06	29.19	32.90	54.00	-21.10	Vertical
12220	10.17	38.93	43.59	29.18	34.69	54.00	-19.31	Vertical
14634	11.34	39.60	45.40	28.96	34.50	54.00	-19.50	Vertical
4876	6.64	34.02	45.42	33.35	28.59	54.00	-25.41	Horizontal
7324	7.58	36.10	44.39	32.42	31.71	54.00	-22.29	Horizontal
9687	8.58	37.06	42.14	29.37	32.87	54.00	-21.13	Horizontal
12220	10.17	38.93	43.59	29.29	34.80	54.00	-19.20	Horizontal
14685	11.39	39.67	45.36	29.11	34.81	54.00	-19.19	Horizontal

**The highest channel (2.480GHz)**

## Peak Measurement: Peak detector

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit	Polarization
2483.5	5.08	32.29	44.77	39.00	31.60	74.00	-42.40	Vertical
2500	5.10	32.30	44.78	38.00	30.62	74.00	-43.38	Vertical
4961	6.68	34.01	45.44	45.29	40.54	74.00	-33.46	Vertical
7443	7.52	35.91	44.26	44.35	43.52	74.00	-30.48	Vertical
9976	8.82	37.28	41.88	42.01	46.23	74.00	-27.77	Vertical
12424	10.24	39.06	43.85	42.93	48.38	74.00	-25.62	Vertical
14855	11.56	39.80	45.25	41.72	47.83	74.00	-26.17	Vertical
2483.5	5.08	32.29	44.77	39.00	31.60	74.00	-42.40	Horizontal
2500	5.10	32.30	44.78	37.50	30.12	74.00	-43.88	Horizontal
4961	6.68	34.01	45.44	45.41	40.66	74.00	-33.34	Horizontal
7426	7.53	35.91	44.28	45.28	44.44	74.00	-29.56	Horizontal
9925	8.77	37.23	41.92	42.63	46.71	74.00	-27.29	Horizontal
12424	10.24	39.06	43.85	43.97	49.42	74.00	-24.58	Horizontal
14923	11.63	39.83	45.20	42.86	49.12	74.00	-24.88	Horizontal

## Average Measurement: Peak detector

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit	Polarization
2483.5	5.08	32.29	44.77	29.50	22.10	54.00	-31.90	Vertical
2500	5.10	32.30	44.78	25.00	17.62	54.00	-36.38	Vertical
4978	6.68	34.01	45.45	32.59	27.83	54.00	-26.17	Vertical
7443	7.52	35.91	44.26	31.63	30.80	54.00	-23.20	Vertical
9925	8.77	37.23	41.92	29.08	33.16	54.00	-20.84	Vertical
12424	10.24	39.06	43.85	29.24	34.69	54.00	-19.31	Vertical
14855	11.56	39.80	45.25	29.01	35.12	54.00	-18.88	Vertical
2483.5	5.08	32.29	44.77	29.00	21.60	54.00	-32.40	Horizontal
2500	5.10	32.30	44.78	25.50	18.12	54.00	-35.88	Horizontal
4944	6.67	34.01	45.44	32.57	27.81	54.00	-26.19	Horizontal
7443	7.52	35.91	44.26	31.61	30.78	54.00	-23.22	Horizontal
9925	8.77	37.23	41.92	29.07	33.15	54.00	-20.85	Horizontal
12424	10.24	39.06	43.85	29.20	34.65	54.00	-19.35	Horizontal
14855	11.56	39.80	45.25	28.98	35.09	54.00	-18.91	Horizontal

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor.

Remark: No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Remark:

- 1). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.
- 2) Pre-test the Bluetooth normal mode
- 3) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the 7<sup>th</sup> harmonic of this intentional radiator, the disturbance is very low.

**Section 15.205 Restricted bands of operation.**

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

The result: The unit does meet the FCC requirements