

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen,
Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: sgs_internet_operations@sgs.com

Report No.: SZEMO09100574501
Page: 1 of 41

FCC REPORT

Application No:	SZEMO091005745RF
Applicant:	CHIN FAI ELECTRONICS COMPANY
Product Name:	SILICON BLUETOOTH KEYBOARD
Operation Frequency:	2.402GHz to 2.480GHz
FCC ID:	XJ4KB6114
Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247: 2008
Date of Receipt:	10 October 2009
Date of Test:	10 October to 04 November 2009
Date of Issue:	05 November 2009

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Contents

	Page
2 CONTENTS.....	1
3 TEST SUMMARY	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF E.U.T.....	4
4.3 E.U.T OPERATION MODE.....	6
4.4 TEST FACILITY	7
4.5 TEST LOCATION	7
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
4.7 TEST INSTRUMENTS LIST	8
5 TEST RESULTS AND MEASUREMENT DATA	9
5.1 ANTENNA REQUIREMENT:	9
5.2 CONDUCTED PEAK OUTPUT POWER.....	10
5.3 20DB OCCUPY BANDWIDTH.....	13
5.4 CARRIER FREQUENCIES SEPARATION.....	16
5.5 HOPPING CHANNEL NUMBER	20
5.6 DWELL TIME	22
5.7 BAND EDGE (CONDUCTED MEASUREMENT).....	25
5.8 RF ANTENNA CONDUCTED SPURIOUS EMISSIONS.....	27
5.9 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	31
5.10 RADIATED EMISSION.....	32
5.10.1 Radiated emission below 1GHz.....	34
5.10.2 Transmitter emission above 1GHz.....	35
5.10.3 Band Edge (radiated measurement)	38-41

3 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Passed
Conducted Peak Output Power	15.247 (b)(1)	Passed
20dB Occupied Bandwidth	15.247 (a)(1)	Passed
Carrier Frequencies Separation	15.247 (a)(1)	Passed
Hopping Channel Number	15.247 (b)	Passed
Dwell Time	15.247 (a)(1)	Passed
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)&TCB Exclusion List (7 July 2002)	Passed
Radiated Emission	15.205/15.209/15.247	Passed
Band Edge	15.247(d)	Passed
RF Antenna Conducted spurious emissions	15.247(d)	Passed

Remark: Passed: The EUT complies with the essential requirements in the standard.

Failed: The EUT does not comply with the essential requirements in the standard.

4 General Information

4.1 Client Information

Applicant:	CHIN FAI ELECTRONICS COMPANY
Address of Applicant:	Building2c 2d, yingfeng industrial park, sanhe economic development zone huiyang district Huizhou city
Manufacturer/ Factory:	CHIN FAI ELECTRONICS COMPANY
Address of Manufacturer/ Factory:	Building2c 2d, yingfeng industrial park, sanhe economic development zone huiyang district Huizhou city

4.2 General Description of E.U.T.

Product Name:	SILICON BLUETOOTH KEYBOARD
Trade Name:	 ETAU
Item No.:	KB6114, KB6130, KB6131, KB6132, KB6133, KB6134, KB6135, KB6136, KB6137, KB6138, KB6139
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK
Antenna Type:	Integral
Antenna gain:	0dBi
Power supply:	keyboard: 2*1.5(AAA)=3.0V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

4.3 E.U.T Operation mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1008 mbar
Test mode:	
Normal operation mode:	Bluetooth mode (Keep the EUT connected to PC and exchange data.)
Transmitting mode:	Keep the EUT in transmitting mode with modulation.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.

Date of Registration: September 29, 2008. Valid until September 28, 2011.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.

Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab
No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057
Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594
No tests were sub-contracted.

4.6 Other Information Requested by the Customer

None.

4.7 Test Instruments list

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2009	15-06-2010
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2008	11-12-2009
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	18-06-2009	17-06-2010
6	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2009	11-08-2010
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	12-08-2009	11-08-2010
8	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	12-08-2009	11-08-2010
9	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	18-06-2009	17-06-2010
10	Pre-amplifier (1-18GHz)	Rohde & Schwarz	AFS42-00101 800-25-S-42	SEL0081	18-06-2009	17-06-2010
11	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	SEL0080	18-06-2009	17-06-2010
12	Band filter	Amindeon	82346	SEL0094	18-06-2009	17-06-2010


RF conducted						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	Spectrum Analyzer	Rohde & Schwarz	10336/030	EMC0040	16-06-2009	15-06-2010
2	Coaxial cable	SGS	N/A	SEL0029	18-06-2009	17-06-2010

5 Test results and Measurement Data

5.1 Antenna requirement:


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(c) (1)(i) requirement:	(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.
E.U.T Antenna:	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.

5.2 Conducted Peak Output Power


Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.4:2003 and KDB DA00-705
Limit:	30dBm
Test setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark: Offset the High-Frequency cable loss 2.0 dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 4.7 for details
Test state:	Non-hopping transmitting with modulation.
Test results:	Passed

Measurement Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-8.51	30.00	Pass
Middle	-8.25	30.00	Pass
Highest	-8.01	30.00	Pass


Test plot as follows:


Date: 19.OCT.2009 22:08:47




Date: 19.OCT.2009 23:54:27

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



Date: 20.OCT.2009 00:00:34

5.3 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2003 and KDB DA00-705
Limit:	NA
Test setup:	
Test Instruments:	Refer to section 4.7 for details
Test state:	Non-hopping transmitting with modulation.
Test results:	Passed

Measurement Data

20dB Occupy Bandwidth (KHz)		
Lowest	Middle	Highest
964	968	964


Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Date: 19.OCT.2009 22:09:53

Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




Date: 19.OCT.2009 23:55:15



Date: 20.OCT.2009 00:01:08

5.4 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2003 and KDB DA00-705
Test setup:	
Test Instruments:	Refer to section 4.7 for details
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test state:	Hopping transmitting with modulation.
Test results:	Passed

Measurement Data


GFSK mode			
Test channel	Carrier Frequencies Separation (KHz)	Limit (KHz)	Result
Lowest	1004	645	Pass
Middle	1008	645	Pass
Highest	1004	645	Pass

Note: According to section 5.3

Mode	20dB bandwidth (KHz) (worse case)	Limit (KHz) (Carrier Frequencies Separation)
GFSK	968	645


Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Date: 21.OCT.2009 16:17:05

Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




Date: 21.OCT.2009 16:20:17




Date: 21.OCT.2009 16:24:07

5.5 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (b)	
Test Method:	ANSI C63.4:2003 and KDB DA00-705	
Limit:	75channels	
Test setup:		
Test Instruments:	Refer to section 4.7 for details	
Test state:	Hopping transmitting with modulation.	
Test results:	Passed	


Measurement Data

Mode	Hopping channel numbers	Limit
GFSK	79	75

Test plot as follows

Date: 21.OCT.2009 16:12:11

5.6 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2003 and KDB DA00-705
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 4.7 for details
Test state:	Hopping transmitting with modulation.
Test results:	Passed

Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.139	0.4
	DH3	0.275	0.4
	DH5	0.319	0.4

Test Result:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as blow


$$\text{DH1 time slot} = 0.435(\text{ms}) * (1600 / (2 * 79)) * 31.6 = 139 \text{ ms}$$

$$\text{DH3 time slot} = 1.72(\text{ms}) * (1600 / (4 * 79)) * 31.6 = 275 \text{ ms}$$

$$\text{DH5 time slot} = 3.00(\text{ms}) * (1600 / (6 * 79)) * 31.6 = 319 \text{ ms}$$


Test plot as follows

Test mode:	GFSK	Test Packet:	DH1
------------	------	--------------	-----




Date: 28.OCT.2009 16:52:56


Test mode:	GFSK	Test Packet:	DH3
------------	------	--------------	-----



Date: 28.OCT.2009 16:52:08



5.7 Band Edge (conducted measurement)


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.4:2003 and KDB DA00-705
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark: Offset the High-Frequency cable loss 2.0dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 4.7 for details
Test state:	Hopping transmitting with modulation.
Test results:	Passed

Remark:

Band Edge (radiated measurement) is tested and described in 5.10.3 chapter.


Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Date: 21.OCT.2009 16:58:18

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




Date: 21.OCT.2009 16:55:50


5.8 RF Antenna Conducted spurious emissions

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.4:2003 and KDB DA00-705
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark: Offset the High-Frequency cable loss 2.0dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 4.7 for details
Test results:	Passed

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------



Date: 19.OCT.2009 23:48:07




Date: 19.OCT.2009 23:49:19


Test mode:	GFSK	Test channel:	Middle
<p>Ref 0 dBm * Att 20 dB * RBW 100 kHz Delta 2 [T1] * VBW 300 kHz -46.62 dB SWT 2.5 s -799.040000000 MHz</p> <p>0 Offset 2 dB</p> <p>Marker 1 [T1] -10.18 dBm 2 427120000 GHz</p> <p>1 PK VIEW LVL 3DB</p> <p>Start 30 MHz 2.497 GHz / Stop 25 GHz</p>			

Date: 19.OCT.2009 23:56:29

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




Date: 20.OCT.2009 00:02:14




Date: 20.OCT.2009 00:03:15

5.9 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) requirement:																						
	<p>Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</p> <p>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p>																						
EUT Pseudorandom Frequency Hopping Sequence																							
	<p>The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none">• Number of shift register stages: 9• Length of pseudo-random sequence: $2^9 - 1 = 511$ bits• Longest sequence of zeros: 8 (non-inverted signal)  <p>Linear Feedback Shift Register for Generation of the PRBS sequence</p> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p> <table><tr><td>0</td><td>2</td><td>4</td><td>6</td><td>62</td><td>64</td><td>78</td><td>1</td><td>73</td><td>75</td><td>77</td></tr><tr><td> </td><td> </td></tr></table> <p>Each frequency used equally on the average by each transmitter. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</p>	0	2	4	6	62	64	78	1	73	75	77											
0	2	4	6	62	64	78	1	73	75	77													

5.10 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209, 15.205 and 15.247(d)																								
Test Method:	ANSI C63.4: 2003																								
Test Frequency Range:	30MHz to 25GHz																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table border="1"><thead><tr><th>Frequency</th><th>Detector</th><th>RBW</th><th>VBW</th><th>Remark</th></tr></thead><tbody><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average Value</td></tr></tbody></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	Peak	1MHz	10Hz	Average Value																					
Limit:	<table border="1"><thead><tr><th>Frequency</th><th>Limit (dBuV/m @3m)</th><th>Remark</th></tr></thead><tbody><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>74.0</td><td>Peak Value</td></tr></tbody></table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	74.0	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	74.0	Peak Value																							
Test Procedure:	<ol style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.																								
Test Instruments:	Refer to section 4.7 for details																								
Test mode:	Normal operation mode																								
Test results:	Passed																								



Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

5.10.1 Radiated emission below 1GHz

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
36.790	0.60	12.30	28.12	31.01	15.79	40.00	-24.21	Vertical
63.950	0.80	7.07	28.03	37.63	17.47	40.00	-22.53	Vertical
122.150	1.26	7.85	27.67	34.26	15.70	43.50	-27.80	Vertical
525.670	2.63	18.53	27.68	35.11	28.59	46.00	-17.41	Vertical
797.270	3.20	22.09	26.95	37.75	36.09	46.00	-9.91	Vertical
935.980	3.64	23.30	26.43	33.75	34.26	46.00	-11.74	Vertical
118.270	1.25	8.02	27.70	39.27	20.84	43.50	-22.66	Horizontal
272.500	1.78	12.76	26.82	36.43	24.15	46.00	-21.85	Horizontal
478.140	2.52	17.80	27.65	34.78	27.45	46.00	-18.55	Horizontal
710.940	2.94	21.60	27.24	38.62	35.92	46.00	-10.08	Horizontal
749.740	3.06	21.70	27.11	44.20	41.85	46.00	-4.15	Horizontal
797.270	3.20	22.09	26.95	38.06	36.40	46.00	-9.60	Horizontal

Remark: the data above is tested with QP detector.

5.10.2 Transmitter emission above 1GHz

Test mode:	GFSK	Test channel:	Lowest	Remark:	Peak
------------	------	---------------	--------	---------	------

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2377	6.25	29.96	39.11	47.51	44.61	74.00	-29.39	Vertical
2394	6.31	30.01	38.95	47.51	44.88	74.00	-29.12	Vertical
2400	6.34	30.03	38.87	47.02	44.52	74.00	-29.48	Vertical
4842	11.47	34.30	41.59	48.86	53.04	74.00	-20.96	Vertical
6219	14.46	36.09	41.69	50.91	59.77	74.00	-14.23	Vertical
11506	15.53	38.70	38.43	45.64	61.44	74.00	-12.56	Vertical
2360	6.17	29.88	39.35	47.29	43.99	74.00	-30.01	Horizontal
2394	6.31	30.01	38.95	47.58	44.95	74.00	-29.05	Horizontal
2400	6.34	30.03	38.87	47.72	45.22	74.00	-28.78	Horizontal
5726	12.89	35.47	42.00	50.02	56.38	74.00	-17.62	Horizontal
7783	14.18	37.58	39.61	48.10	60.25	74.00	-13.75	Horizontal
12186	18.03	39.21	39.27	44.90	62.87	74.00	-11.13	Horizontal

Test mode:	GFSK	Test channel:	Lowest	Remark:	Average
------------	------	---------------	--------	---------	---------

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)	Polarization
2343	6.11	29.84	39.51	27.60	24.04	54.00	-29.96	Vertical
2394	6.31	30.01	38.95	28.80	26.17	54.00	-27.83	Vertical
2400	6.34	30.03	38.87	29.50	27.00	54.00	-27.00	Vertical
6797	13.47	36.85	40.18	28.30	38.44	54.00	-15.56	Vertical
10401	14.15	38.18	36.61	26.50	42.22	54.00	-11.78	Vertical
13019	16.68	39.77	38.88	24.90	42.47	54.00	-11.53	Vertical
2326	6.02	29.76	39.75	27.61	23.64	54.00	-30.36	Horizontal
2394	6.31	30.01	38.95	28.30	25.67	54.00	-28.33	Horizontal
2400	6.34	30.03	38.87	28.80	26.30	54.00	-27.70	Horizontal
4315	8.79	33.57	39.87	29.30	31.79	54.00	-22.21	Horizontal
7800	14.34	37.60	39.65	26.30	38.59	54.00	-15.41	Horizontal
15620	18.05	40.78	41.81	25.10	42.12	54.00	-11.88	Horizontal

Test mode:	GFSK	Test channel:	Middle	Remark:	Peak
------------	------	---------------	--------	---------	------

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)	Polarization
2377	6.25	29.96	39.11	46.90	44.00	74.00	-30.00	Vertical
3431	7.24	32.46	39.65	48.08	48.13	74.00	-25.87	Vertical
4298	8.74	33.54	39.85	47.85	50.28	74.00	-23.72	Vertical
6746	13.38	36.78	40.42	49.80	59.54	74.00	-14.46	Vertical
7800	14.34	37.60	39.65	47.10	59.39	74.00	-14.61	Vertical
10503	14.58	38.20	36.32	44.91	61.37	74.00	-12.63	Vertical
2343	6.11	29.84	39.51	47.37	43.81	74.00	-30.19	Horizontal
3703	7.40	32.78	39.14	48.38	49.42	74.00	-24.58	Horizontal
4876	10.36	34.34	39.89	48.40	53.21	74.00	-20.79	Horizontal
5947	13.10	35.74	41.93	49.20	56.11	74.00	-17.89	Horizontal
7715	13.68	37.54	39.47	48.14	59.89	74.00	-14.11	Horizontal
10690	14.90	38.24	36.82	45.37	61.69	74.00	-12.31	Horizontal

Test mode:	GFSK	Test channel:	Middle	Remark:	Average
------------	------	---------------	--------	---------	---------

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)	Polarization
2343	6.11	29.84	39.51	26.80	23.24	54.00	-30.76	Vertical
3499	7.27	32.54	39.34	26.30	26.77	54.00	-27.23	Vertical
4842	11.47	34.30	41.59	25.40	29.58	54.00	-24.42	Vertical
6797	13.47	36.85	40.18	26.80	36.94	54.00	-17.06	Vertical
10605	14.91	38.22	36.57	22.80	39.36	54.00	-14.64	Vertical
12169	18.03	39.21	39.27	23.50	41.47	54.00	-12.53	Vertical
2377	6.25	29.96	39.11	28.60	25.70	54.00	-28.30	Horizontal
5250	11.78	34.85	41.18	25.59	31.04	54.00	-22.96	Horizontal
7800	14.34	37.60	39.65	26.30	38.59	54.00	-15.41	Horizontal
10605	14.91	38.22	36.57	22.60	39.16	54.00	-14.84	Horizontal
12169	18.03	39.21	39.27	23.90	41.87	54.00	-12.13	Horizontal

Test mode:	GFSK	Test channel:	Highest	Remark:	Peak
------------	------	---------------	---------	---------	------

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)	Polarization
2360	6.17	29.88	39.35	47.34	44.04	74.00	-29.96	Vertical
2483.5	6.22	30.32	39.53	47.88	44.89	74.00	-29.11	Vertical
2513	5.81	30.42	39.13	47.20	44.30	74.00	-29.70	Vertical
5199	11.71	34.77	41.19	48.21	53.50	74.00	-20.50	Vertical
8429	13.07	37.75	38.31	45.41	57.92	74.00	-16.08	Vertical
13087	16.65	39.92	39.16	41.36	58.77	74.00	-15.23	Vertical
2377	6.25	29.96	39.11	47.48	44.58	74.00	-29.42	Horizontal
2483.5	6.22	30.32	39.53	47.31	44.32	74.00	-29.68	Horizontal
2496	5.99	30.35	39.34	47.15	44.15	74.00	-29.85	Horizontal
6967	13.71	37.08	40.95	49.69	59.53	74.00	-14.47	Horizontal
9194	13.26	37.86	38.35	47.08	59.85	74.00	-14.15	Horizontal
11098	15.12	38.38	37.81	45.44	61.13	74.00	-12.87	Horizontal


Test mode:	GFSK	Test channel:	Highest	Remark:	Average
------------	------	---------------	---------	---------	---------

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit (dB)	Polarization
2326	6.02	29.76	39.75	26.31	22.34	54.00	-31.66	Vertical
2483.5	6.22	30.32	39.53	26.80	23.81	54.00	-30.19	Vertical
2496	5.99	30.35	39.34	27.50	24.50	54.00	-29.50	Vertical
6797	13.47	36.85	40.18	26.80	36.94	54.00	-17.06	Vertical
9500	13.66	37.95	37.26	24.70	39.05	54.00	-14.95	Vertical
12169	18.03	39.21	39.27	22.80	40.77	54.00	-13.23	Vertical
2377	6.25	29.96	39.11	26.80	23.90	54.00	-30.10	Horizontal
2483.5	6.22	30.32	39.53	26.40	23.41	54.00	-30.59	Horizontal
2496	5.99	30.35	39.34	28.50	25.50	54.00	-28.50	Horizontal
6848	13.55	36.93	40.44	27.40	37.44	54.00	-16.56	Horizontal
9687	13.69	38.01	37.79	22.50	36.41	54.00	-17.59	Horizontal
13495	17.19	40.65	40.57	20.30	37.57	54.00	-16.43	Horizontal

Remark: The disturbance above 13GHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.


5.10.3 Band Edge (radiated measurement)

Test mode:	GFSK	Test channel:	Lowest	Polarization:	Vertical
------------	------	---------------	--------	---------------	----------

**Remark:**


From above plot, we can calculate that the radio frequency power that is produced by the intentional radiator is at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, so it is compliance to the limit requirement of band edge.

Test mode:	GFSK	Test channel:	Lowest	Polarization:	Horizontal
------------	------	---------------	--------	---------------	------------

**Remark:**


From above plot, we can calculate that the radio frequency power that is produced by the intentional radiator is at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, so it is compliance to the limit requirement of band edge.

Test mode:	GFSK	Test channel:	Highest	Polarization:	Vertical
------------	------	---------------	---------	---------------	----------

**Remark:**

From above plot, we can calculate that the radio frequency power that is produced by the intentional radiator is at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, so it is compliance to the limit requirement of band edge.

Test mode:	GFSK	Test channel:	Highest	Polarization:	Horizontal
------------	------	---------------	---------	---------------	------------



Remark:

From above plot, we can calculate that the radio frequency power that is produced by the intentional radiator is at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, so it is compliance to the limit requirement of band edge.