

# 1. RF Exposure Requirements

---

## 1.1 General Information

### Client Information

Applicant: UConnect International Co., Ltd.  
Address of applicant: 8F., No.200-3, Jianxing Rd., Zhongli Dist., Taoyuan City ZIP: 32097, Taiwan

Manufacturer: UConnect International Co., Ltd.  
Address of manufacturer: 8F., No.200-3, Jianxing Rd., Zhongli Dist., Taoyuan City ZIP: 32097, Taiwan

### General Description of EUT:

Product Name: WiFi 802.11ah HaLow Module  
Trade Name: /  
Model No.: WAHMV1  
Adding Model(s): WAHMV2, WAHMV3  
Rated Voltage: DC3.3V  
Battery Capacity: /  
FCC ID: XJ8-WAHMV1  
Equipment Type: Mobile device

### Technical Characteristics of EUT:

Frequency Range: Bandwidth:1MHz: 903.5-926.5MHz  
RF Output Power: Bandwidth:2MHz: 903-925MHz  
Modulation: Bandwidth:4MHz: 906-926MHz  
Bandwidth:1MHz: 12.90dBm (Conducted)  
Bandwidth:2MHz: 12.11dBm (Conducted)  
Bandwidth:4MHz: 11.31dBm (Conducted)  
BPSK,QPSK,16QAM,64QAM  
Bandwidth:1MHz:24  
Quantity of Channels: Bandwidth:2MHz:12  
Bandwidth:4MHz:6  
Bandwidth:1MHz: 1MHz  
Channel Separation: Bandwidth:2MHz: 2MHz  
Bandwidth:4MHz: 4MHz  
Type of Antenna: External Antenna  
Antenna Gain: 2.34dBi

## 1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

**Option A:** FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

**Option B:** FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula.  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

**Option C:** FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency.  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

**For Multiple RF sources:** FCC Rule Part 1.1307(b)(3)(ii):

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).

(B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

### 1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
SRD	903.5	12.90	2.34	100	13.00	13.19
SRD	903	12.11	2.34	100	13.00	13.19
SRD	906	11.31	2.34	100	12.00	12.19

Frequency (MHz)	Option	Min. Distance (cm)	Max. Power (dBm)		Exposure Limit (mW)	Ratio	Result
			(dBm)	(mW)			
903.5	C	20.00	13.19	20.84	462.59	0.05	Pass
903	C	20.00	13.19	20.84	462.34	0.05	Pass
906	C	20.00	12.19	16.56	463.87	0.04	Pass

*Note:* 1. Time-Averaged Power=Output Power \* Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB

2. Option A, B and C refers as clause 1.2.
3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;
4. For option B,  $P_{th}$  (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).
5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

#### Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
--	--	--	--	--	--

Result: Pass