



# TEST REPORT

**Report Reference No.**.....: **TRE1408009401** **R/C.....:**19400  
**FCC ID.**.....: **XJN-PX4032**  
**Applicant's name**.....: **SHUOYING INDUSTRIAL (SHENZHEN) CO.,LTD**  
**Address**.....: shuoying Road,Hebei Industry Area,Dalang,Longhua Town,Baoan,Shenzhen,China  
**Manufacturer**.....: **SHUOYING INDUSTRIAL (SHENZHEN) CO.,LTD**  
**Address**.....: shuoying Road,Hebei Industry Area,Dalang,Longhua Town,Baoan,Shenzhen,China  
**Test item description**.....: **Mobile Internet Devices**  
**Trade Mark**.....: /  
**Model/Type reference**.....: **PX4302**  
**Listed Model(s)**.....: /  
**Standard**.....: **FCC CFR Title 47 Part 15 Subpart C Section 15.247**  
**Date of receipt of test sample**.....: Aug 25, 2014  
**Date of testing**.....: Aug 26~ Sept 05, 2014  
**Date of issue**.....: Sept 05, 2014  
**Result**.....: **PASS**

Compiled by  
( position+printed name+signature)..: File administrators Any Yang

Supervised by  
( position+printed name+signature)..: Project Engineer Lion Cai

Approved by  
( position+printed name+signature)..: RF Manager Hans Hu

**Testing Laboratory Name**.....: **Shenzhen Huatongwei International Inspection Co., Ltd**  
**Address**.....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

## Contents

<u>1.</u>	<u>TEST STANDARDS AND TEST DESCRIPTION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Test Description	3
<u>2.</u>	<u>SUMMARY</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	EUT operation mode	5
2.4.	EUT configuration	5
2.5.	Modifications	5
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>6</u>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>9</u>
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	13
4.4.	Power Spectral Density	14
4.5.	6dB bandwidth	19
4.6.	Band Edge	24
4.7.	Spurious Emission (conducted)	33
4.8.	Spurious Emission (radiated)	46
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>52</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>53</u>

## 1. TEST STANDARDS AND TEST DESCRIPTION

### 1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V03R02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

### 1.2. Test Description

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
Line Conducted Emission (AC Main)	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Power Spectral Density	15.247 (e)	Pass
6dB Bandwidth	15.247 (a)(2)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

## 2. SUMMARY

### 2.1. Client Information

Applicant:	SHUOYING INDUSTRIAL (SHENZHEN) CO.,LTD
Address:	shuoying Road,Hebei Industry Area,Dalang,Longhua Town,Baoan,Shenzhen,China
Manufacturer:	SHUOYING INDUSTRIAL (SHENZHEN) CO.,LTD
Address:	shuoying Road,Hebei Industry Area,Dalang,Longhua Town,Baoan,Shenzhen,China

### 2.2. Product Description

Name of EUT	Mobile Internet Devices
Trade Mark:	/
Model No.:	PX4302
Listed Model(s):	/
Power supply:	DC 3.7V From Internal Battery
Adapter information:	Model No.:WLC050150UU Input: AC 100~240V, 50/60Hz, 0.3A Output: DC 5.0V 1.5A
<b>WIFI</b>	
Supported type:	802.11b/802.11g/802.11n(H20)/802.11n(H40)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20)/802.11n(H40):OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11 802.11n(H40): 7
Channel separation:	5MHz
Antenna type:	Internal Antenna
Antenna gain:	2.0 dBi

#### Operation Frequency List:

<b>802.11b/g/n(H20)</b>		<b>802.11n(H40)</b>	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	--
02	2417	02	--
03	2422	03	2422
:	:	:	:
06	2437	06	2442
:	:	:	:
09	2452	09	2452
10	2457	10	--
11	2462	11	--

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

### 2.3. EUT operation mode

The EUT has been tested under test mode condition. The Applicant provides software to control the EUT for staying in continuous transmitting and receiving mode for testing.

And found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Mode	Bit rate (worst mode)
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	13.5Mbps
802.11n(H40)	13.5Mbps

The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

### 2.4. EUT configuration

**The following peripheral devices and interface cables were connected during the measurement:**

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

### 2.5. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

Test Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd  
Address: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China  
Phone: 86-755-26715686 Fax: 86-755-26748089

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: Mar. 01, 2012. Valid time is until February 28, 2015.

##### **A2LA-Lab Cert. No. 2243.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

##### **FCC-Registration No.: 662850**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date Jul. 01, 2012, valid time is until Jun. 01, 2015.

##### **IC-Registration No.: 5377A**

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

##### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

##### **VCCI**

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.:R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

##### **DNV**

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

### 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 1" and TR-100028-02 "Electromagnetic compatibilityand Radio spectrum Matters (ERM);Uncertainties in the measurementof mobile radio equipment characteristics;Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emissio 1~18GHz	5.16 dB	(1)
Radiated Emissio 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

### 3.5. Equipments Used during the Test

AC Power Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2014/10/25
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2014/10/25
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2014/10/25
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2014/10/25
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2014/10/25
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORN ANTENNA	ShwarzBeck	9120D	1011	2014/10/25
8	Amplifier	Sonoma	310N	E009-13	2014/10/25
9	JS amplifier	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2014/10/25
10	High pass filter	Compliance Direction systems	BSU-6	34202	2014/10/25
11	HORN ANTENNA	ShwarzBeck	9120D	1012	2014/10/25
12	Amplifier	Compliance Direction systems	PAP1-4060	120	2014/10/25
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2014/10/25
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2014/10/25
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2014/10/25

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2014/10/25
2	Power Meter	Anritsu	MA2411B	100258	2014/10/25

The Cal.Interval was one year

## 4. TEST CONDITIONS AND RESULTS

### 4.1. Antenna requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### Test Result:

The antenna is integral antenna, the best case gain of the antenna is 2dBi



## 4.2. Conducted Emission (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION




### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10:2009 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

### TEST RESULTS

Test mode:	Tx	Polarization	L
------------	----	--------------	---

**SCAN TABLE: "Voltage (9K-30M)fin"**  
Short Description: 150K-30M Voltage



**MEASUREMENT RESULT: "HTW1126330\_fin"**


8/26/2014 3:11PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB $\mu$ V	dB	dB $\mu$ V	dB			
	0.168000	39.60	10.3	65	25.5	QP	L1	GND
	0.366000	43.70	10.5	59	14.9	QP	L1	GND
	0.375000	44.70	10.5	58	13.7	QP	L1	GND
	0.870000	34.60	10.2	56	21.4	QP	L1	GND
	1.441500	34.30	10.3	56	21.7	QP	L1	GND
	2.098500	32.90	10.3	56	23.1	QP	L1	GND

**MEASUREMENT RESULT: "HTW1126330\_fin2"**

8/26/2014 3:11PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB $\mu$ V	dB	dB $\mu$ V	dB			
	0.375000	34.40	10.5	48	14.0	AV	L1	GND
	0.379500	33.70	10.5	48	14.6	AV	L1	GND
	0.919500	23.60	10.2	46	22.4	AV	L1	GND
	1.455000	25.10	10.3	46	20.9	AV	L1	GND
	2.130000	23.50	10.3	46	22.5	AV	L1	GND
	2.629500	22.80	10.3	46	23.2	AV	L1	GND

Test mode:	Tx	Polarization	N
------------	----	--------------	---

**SCAN TABLE: "Voltage (9K-30M)fin"**  
Short Description: 150K-30M Voltage



**MEASUREMENT RESULT: "HTW1126329\_fin"**

8/26/2014 3:08PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB $\mu$ V	dB	dB $\mu$ V	dB			
	0.361500	50.70	10.5	59	8.0	QP	N	GND
	0.375000	51.20	10.5	58	7.2	QP	N	GND
	0.721500	36.40	10.3	56	19.6	QP	N	GND
	1.410000	39.80	10.3	56	16.2	QP	N	GND
	1.887000	36.90	10.3	56	19.1	QP	N	GND
	2.926500	33.30	10.3	56	22.7	QP	N	GND

**MEASUREMENT RESULT: "HTW1126329\_fin2"**

8/26/2014 3:08PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB $\mu$ V	dB	dB $\mu$ V	dB			
	0.366000	37.00	10.5	49	11.6	AV	N	GND
	0.397500	25.20	10.5	48	22.7	AV	N	GND
	0.753000	27.60	10.2	46	18.4	AV	N	GND
	1.360500	27.00	10.3	46	19.0	AV	N	GND
	1.941000	25.70	10.3	46	20.3	AV	N	GND

### 4.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2009 and KDB 558074 D01 V03R02 for compliance to FCC 47CFR 15.247 requirements.
2. Use the wideband power meter to test peak power and record the result.

#### TEST RESULTS

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11b	01	16.02	30.00	Pass
	06	16.55		
	11	16.94		
802.11g	01	14.30	30.00	Pass
	06	13.67		
	11	13.97		
802.11n(H20)	01	13.51	30.00	Pass
	06	13.89		
	11	13.36		
802.11n(H40)	03	12.02	30.00	Pass
	06	12.60		
	09	12.37		

#### 4.4. Power Spectral Density

##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e): **8dBm/3KHz**

*For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.*

##### TEST CONFIGURATION




##### TEST PROCEDURE


1. According to KDB 558074 D01 V03R02 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.
2. Analyzer set:  
Center frequency =Channel center frequency  
RBW =3 kHz~100 kHz, VBW $\geq$ 3RBW, Detector=Peak, Span=1.5 times the bandwidth
3. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
4. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


##### TEST RESULTS


Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-7.911	8.00	Pass
	06	-7.652		
	11	-7.184		
802.11g	01	-10.57	8.00	Pass
	06	-10.11		
	11	-9.6		
802.11n(H20)	01	-12.14	8.00	Pass
	06	-11.4		
	11	-10.78		
802.11n(H40)	03	-14.18	8.00	Pass
	06	-13.46		
	09	-14.27		

Test plot as follows:









## 4.5. 6dB bandwidth

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2): **at least 500KHz**

*For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.*

### TEST CONFIGURATION




### TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer
2. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.
3. According to KDB 558074 D01 V03R02 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.  
Center frequency =Channel center frequency  
RBW =100 kHz, VBW $\geq$ 3RBW, Detector=Peak,
4. Allow the trace to stabilize.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


### TEST RESULTS


Type	Channel	6dB Bandwidth(MHz)	Limit (KHz)	Result
802.11b	01	10.07	$\geq$ 500	Pass
	06	10.07		
	11	10.08		
802.11g	01	16.51	$\geq$ 500	Pass
	06	16.51		
	11	16.51		
802.11n(H20)	01	17.63	$\geq$ 500	Pass
	06	17.63		
	11	17.63		
802.11n(H40)	03	35.94	$\geq$ 500	Pass
	06	35.79		
	09	35.87		

Test plot as follows:









CH09

## 4.6. Band Edge

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).*

### TEST CONFIGURATION



### TEST PROCEDURE


1. According to KDB 558074 D01 V03R02 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies  $\leq 30$  MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies  $> 1000$  MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:  

$$E = EIRP - 20\log D + 104.8$$


where:

E = electric field strength in  $\text{dB}\mu\text{V}/\text{m}$ ,  
EIRP = equivalent isotropic radiated power in dBm  
D = specified measurement distance in meters.
11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test dures until all measured frequencies were complete.


### TEST RESULTS




Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2413.04	9.678	2.00	0.00	106.938	Peak		Pass
2390.00	-39.44	2.00	0.00	57.82	Peak	74.00	Pass
2411.08	4.215	2.00	0.00	101.475	Average		Pass
2390.00	-47.4	2.00	0.00	49.86	Average	54.00	Pass




Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2483.50	-38.5	2.00	0.00	58.76	Peak	74.00	Pass
2463.04	10.42	2.00	0.00	107.68	Peak		Pass
2483.50	-48.41	2.00	0.00	48.85	Average	54.00	Pass
2461.24	5.113	2.00	0.00	102.373	Average		Pass




Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2415.00	7.13	2.00	0.00	104.39	Peak		Pass
2390.00	-37.06	2.00	0.00	60.2	Peak	74.00	Pass
2415.56	-5.304	2.00	0.00	91.956	Average		Pass
2390.00	-47.17	2.00	0.00	50.09	Average	54.00	Pass




Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2483.50	-35.19	2.00	0.00	62.07	Peak		Pass
2465.20	8.188	2.00	0.00	105.448	Peak	74.00	Pass
2483.50	-47.53	2.00	0.00	49.73	Average		Pass
2465.44	-3.787	2.00	0.00	93.473	Average	54.00	Pass




Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2414.16	5.466	2.00	0.00	102.726	Peak	74.00	Pass
2390.00	-33.73	2.00	0.00	63.53	Peak		Pass
2415.00	-4.689	2.00	0.00	92.571	Average	54.00	Pass
2390.00	-46.32	2.00	0.00	50.94	Average		Pass



Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2483.50	-30.98	2.00	0.00	66.28	Peak	74.00	Pass
2464.32	6.564	2.00	0.00	103.824	Peak		Pass
2483.50	-46.07	2.00	0.00	51.19	Average	54.00	Pass
2465.08	-3.863	2.00	0.00	93.397	Average		Pass



Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2432.52	0.438	2.00	0.00	97.698	Peak		Pass
2390.00	-36.99	2.00	0.00	60.27	Peak	74.00	Pass
2431.22	-8.374	2.00	0.00	88.886	Average		Pass
2390.00	-45.75	2.00	0.00	51.51	Average	54.00	Pass



Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2483.50	-32.7	2.00	0.00	64.56	Peak	74.00	Pass
2459.20	2.834	2.00	0.00	100.094	Peak		Pass
2483.50	-45.15	2.00	0.00	52.11	Average	54.00	Pass
2461.24	-7.718	2.00	0.00	89.542	Average		Pass

#### 4.7. Spurious Emission (conducted)

##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.*

##### TEST CONFIGURATION




##### TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz, scan up through 10th harmonic

##### TEST RESULTS


Test plot as follows:





























## 4.8. Spurious Emission (radiated)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

### TEST CONFIGURATION

- Below 1GHz



- Above 1GHz



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10:2009 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2009 on radiated measurement.
5. The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.
6. The frequency range from 30MHz to 10th harmonic is checked.

### TEST RESULTS

*Noted:*


*Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.*

## Measurement data:

- Below 1GHz

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.1 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163


***MEASUREMENT RESULT: "RE140905011\_red"***

9/5/2014 1:52PM

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det. QP	Height cm	Azimuth deg	Polarization
47.460000	15.30	-15.1	40.0	24.7	QP	100.0	248.00	HORIZONTAL
83.350000	18.10	-17.9	40.0	21.9	QP	300.0	291.00	HORIZONTAL
140.580000	26.30	-18.5	43.5	17.2	QP	300.0	97.00	HORIZONTAL
187.140000	19.50	-15.1	43.5	24.0	QP	300.0	252.00	HORIZONTAL
552.830000	25.40	-5.3	46.0	20.6	QP	100.0	77.00	HORIZONTAL
919.490000	34.70	3.0	46.0	11.3	QP	100.0	162.00	HORIZONTAL

***SWEET TABLE: "test (30M-1G)"***

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.1 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163

***MEASUREMENT RESULT: "RE140905010\_red"***

9/5/2014 1:49PM

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det. QP	Height cm	Azimuth deg	Polarization
30.000000	34.80	-16.4	40.0	5.2	QP	100.0	203.00	VERTICAL
61.040000	27.40	-16.0	40.0	12.6	QP	100.0	0.00	VERTICAL
83.350000	28.60	-17.9	40.0	11.4	QP	100.0	251.00	VERTICAL
98.870000	24.40	-13.8	43.5	19.1	QP	100.0	14.00	VERTICAL
538.280000	25.60	-5.7	46.0	20.4	QP	100.0	229.00	VERTICAL
928.220000	34.10	3.1	46.0	11.9	QP	100.0	65.00	VERTICAL

**Above 1GHz**

Test channel:	01
---------------	----

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization
4824	52.8	31.44	5.87	35.46	54.65	74	-19.35	Vertical
7236	36.71	36.38	7.08	35.32	44.85	74	-29.15	Vertical
9648	38.33	38.01	9.01	35.72	49.63	74	-24.37	Vertical
12060	*					74		Vertical
14472	*					74		Vertical
4824	54.93	31.44	5.87	35.46	56.78	74	-17.22	Horizontal
7236	37.8	36.38	7.08	35.32	45.94	74	-28.06	Horizontal
9648	38.44	38.01	9.01	35.72	49.74	74	-24.26	Horizontal
12060	*					74		Horizontal
14472	*					74		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization
4824	43.89	31.44	5.87	35.46	45.74	54	-8.26	Vertical
7236	29.84	36.38	7.08	35.32	37.98	54	-16.02	Vertical
9648	27.22	38.01	9.01	35.72	38.52	54	-15.48	Vertical
12060	*					54		Vertical
14472	*					54		Vertical
4824	40.7	31.44	5.87	35.46	42.55	54	-11.45	Horizontal
7236	29.44	36.38	7.08	35.32	37.58	54	-16.42	Horizontal
9648	27.64	38.01	9.01	35.72	38.94	54	-15.06	Horizontal
12060	*					54		Horizontal
14472	*					54		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	06
---------------	----

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874	49.94	30.88	5.7	35.27	51.25	74	-22.75	Vertical
7311	37.03	35.82	6.91	35.13	44.63	74	-29.37	Vertical
9748	36.78	37.45	8.84	35.53	47.54	74	-26.46	Vertical
12185	*					74		Vertical
14622	*					74		Vertical
4874	51.37	30.88	5.7	35.27	52.68	74	-21.32	Horizontal
7311	38.04	35.82	6.91	35.13	45.64	74	-28.36	Horizontal
9748	37.8	37.45	8.84	35.53	48.56	74	-25.44	Horizontal
12185	*					74		Horizontal
14622	*					74		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874	38.94	30.88	5.7	35.27	40.25	54	-13.75	Vertical
7311	30.25	35.82	6.91	35.13	37.85	54	-16.15	Vertical
9748	28.19	37.45	8.84	35.53	38.95	54	-15.05	Vertical
12185	*					54		Vertical
14622	*					54		Vertical
4874	40.13	30.88	5.7	35.27	41.44	54	-12.56	Horizontal
7311	30.25	35.82	6.91	35.13	37.85	54	-16.15	Horizontal
9748	27.88	37.45	8.84	35.53	38.64	54	-15.36	Horizontal
12185	*					54		Horizontal
14622	*					54		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	11
---------------	----

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	48.67	30.98	5.73	35.32	50.06	74	-23.94	Vertical
7386	36.68	35.92	6.94	35.18	44.36	74	-29.64	Vertical
9848	37.54	37.55	8.87	35.58	48.38	74	-25.62	Vertical
12310	*					74		Vertical
14772	*					74		Vertical
4924	51.22	30.98	5.73	35.32	52.61	74	-21.39	Horizontal
7386	37.68	35.92	6.94	35.18	45.36	74	-28.64	Horizontal
9848	38.7	37.55	8.87	35.58	49.54	74	-24.46	Horizontal
12310	*					74		Horizontal
14772	*					74		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	40.15	30.98	5.73	35.32	41.54	54	-12.46	Vertical
7386	29.95	35.92	6.94	35.18	37.63	54	-16.37	Vertical
9848	27.7	37.55	8.87	35.58	38.54	54	-15.46	Vertical
12310	*					54		Vertical
14772	*					54		Vertical
4924	40.97	30.98	5.73	35.32	42.36	54	-11.64	Horizontal
7386	29.78	35.92	6.94	35.18	37.46	54	-16.54	Horizontal
9848	28.41	37.55	8.87	35.58	39.25	54	-14.75	Horizontal
12310	*					54		Horizontal
14772	*					54		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 5. Test Setup Photos of the EUT

Radiated Emission (30MHz-1GHz)



Conducted Emission (AC Mains)



## **6. External and Internal Photos of the EUT**



### **External photos of the EUT**







Internal photos of the EUT



.....End of Report.....