

## FCC PART 15B

### TEST REPORT

For

**INGENICO**

9 Avenue de la gare - Rolvatain TGV, Valence Cedex 9, 26958, France

**FCC ID: XKB-APOSA8WULEWF**

|                                        |                                                                                                                                                                                                                                                       |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report | <b>Product Type:</b><br>Smart POS Terminal                                                                                                                                                                                                            |
| <b>Report Number:</b>                  | RXM200310053-00E                                                                                                                                                                                                                                      |
| <b>Report Date:</b>                    | 2020-04-18                                                                                                                                                                                                                                            |
| <b>Reviewed By:</b>                    | Ivan Cao<br>Assistant Manager                                                                                                                                     |
| <b>Test Laboratory:</b>                | Bay Area Compliance Laboratories Corp. (Dongguan)<br>No.69 Pulongcun, Puxinhu Industry Area,<br>Tangxia, Dongguan, Guangdong, China<br>Tel: +86-769-86858888<br>Fax: +86-769-86858891<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |

## **TABLE OF CONTENTS**

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>General Information .....</b>                         | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) ..... | 3         |
| OBJECTIVE .....                                          | 3         |
| RELATED SUBMITTAL(S)/GRANT(S) .....                      | 3         |
| TEST METHODOLOGY .....                                   | 3         |
| MEASUREMENT UNCERTAINTY .....                            | 4         |
| TEST FACILITY .....                                      | 4         |
| DECLARATIONS .....                                       | 4         |
| <b>System Test Configuration .....</b>                   | <b>5</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                  | 5         |
| EQUIPMENT MODIFICATIONS .....                            | 5         |
| EUT EXERCISE SOFTWARE .....                              | 5         |
| LOCAL SUPPORT EQUIPMENT LIST AND DETAILS .....           | 5         |
| SUPPORT CABLE LIST AND DETAILS .....                     | 5         |
| BLOCK DIAGRAM OF TEST SETUP .....                        | 6         |
| TEST EQUIPMENT LIST .....                                | 7         |
| ENVIRONMENTAL CONDITIONS .....                           | 7         |
| <b>Summary of Test Results .....</b>                     | <b>8</b>  |
| <b>Conducted emissions .....</b>                         | <b>9</b>  |
| EUT SETUP .....                                          | 9         |
| EMI TEST RECEIVER SETUP .....                            | 9         |
| TEST PROCEDURE .....                                     | 9         |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....           | 10        |
| TEST DATA .....                                          | 11        |
| <b>Radiated emissions .....</b>                          | <b>13</b> |
| EUT SETUP .....                                          | 13        |
| EMI TEST RECEIVER SETUP .....                            | 14        |
| TEST PROCEDURE .....                                     | 14        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....           | 14        |
| TEST DATA .....                                          | 15        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                     |                |                                            |
|-------------------------------------|----------------|--------------------------------------------|
| <b>EUT Name:</b>                    |                | Smart POS Terminal                         |
| <b>EUT Model:</b>                   |                | APOS A8                                    |
| <b>Highest Operation Frequency:</b> |                | 2690 MHz                                   |
| <b>Rated Input Voltage:</b>         |                | DC 7.2V from battery or DC 5V from Adapter |
| <b>Adapter Information:</b>         | <b>Model:</b>  | P12GUSB050200                              |
|                                     | <b>Input:</b>  | AC 100-240V, 50/60Hz, 0.3A                 |
|                                     | <b>Output:</b> | DC 5.0V, 2.0A                              |
| <b>Serial Number:</b>               |                | RXM200310053-RF-S4                         |
| <b>EUT Received Date:</b>           |                | 2020.03.15                                 |
| <b>EUT Received Status:</b>         |                | Good                                       |

Note: The EUT have two configuration, the information as below, and more please refer to the Product similarity declaration:

| EUT Configuration | Screen Model | Manufacturer                                  | Serial Number      |
|-------------------|--------------|-----------------------------------------------|--------------------|
| #1                | MDT0550B     | SKYWORTH LCD<br>MODULES(SHENZHEN) CO.,<br>LTD | RXM200310053-RF-S4 |
| #2                | MDT0550B     | TIANMA MICRO-ELECTRONICS<br>Corporation       | RXM200310053-RF-S5 |

### Objective

This report is prepared on behalf of *INGENICO* in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective is to determine the compliance of EUT with: FCC Part 15B Class B.

### Related Submittal(s)/Grant(s)

FCC Part 15C DSS,DTS, DXX and Part 22H,24E, 27 submissions with  
FCC ID: XKB-APOSA8WULEWF

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

## Measurement Uncertainty

| Parameter                         | Measurement Uncertainty                                                                                              |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Unwanted Emissions, radiated      | 30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB |
| Temperature                       | ±1℃                                                                                                                  |
| Humidity                          | ±5%                                                                                                                  |
| AC Power Lines Conducted Emission | 3.12 dB (150 kHz to 30 MHz)                                                                                          |

*Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0022.

## Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in typical fashion (as normally used by a typical user)

The test mode configuration as below, and all modes was performed test, and typical worst mode was reported in the report.

| Test Mode | EUT Configuration | Operating Configuration |
|-----------|-------------------|-------------------------|
| 1         | #1                | Printing                |
| 2         |                   | Video Playing           |
| 3         |                   | Camera Recording        |
| 4         |                   | Card Testing            |
| 5         | #2                | Printing                |
| 6         |                   | Video Playing           |
| 7         |                   | Camera Recording        |
| 8         |                   | Card Testing            |

The batteries made by SCUD(Fujian) Electronics Co., Ltd or Xinyu Ganfeng Electronics Co., Ltd, have been pretested and proved that the battery has no effect.

### Equipment Modifications

No modification was made to the EUT.

### EUT Exercise Software

No Software was used in test.


### Local Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| 1MORE        | earphone    | 1m301 | 5521427       |
| Kinston      | SD Card     | 4G    | 0084G         |

### Support Cable List and Details

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To       |
|-------------------|----------------|--------------|------------|-----------|----------|
| Earphone Cable    | No             | No           | 1.2        | EUT       | Earphone |
| USB Cable         | No             | No           | 0.8        | Adapter   | EUT      |

# Block Diagram of Test Setup



**Test Equipment List**

| Manufacturer                         | Description       | Model      | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------------------|-------------------|------------|---------------|------------------|----------------------|
| <b>Conducted emissions</b>           |                   |            |               |                  |                      |
| Unknown                              | Coaxial Cable     | C-NJNJ-50  | C-0200-01     | 2019-09-05       | 2020-09-05           |
| R&S                                  | Test Software     | EMC32      | Version8.53.0 | N/A              | N/A                  |
| R&S                                  | LISN              | ENV 216    | 101614        | 2019-09-12       | 2020-09-12           |
| R&S                                  | EMI Test Receiver | ESCI       | 101121        | 2019-05-09       | 2020-05-09           |
| <b>Radiated emissions Below 1GHz</b> |                   |            |               |                  |                      |
| R&S                                  | EMI Test Receiver | ESR3       | 102453        | 2019-09-12       | 2020-09-12           |
| Farad                                | Test Software     | EZ-EMC     | V1.1.4.2      | N/A              | N/A                  |
| Sunol Sciences                       | Antenna           | JB3        | A060611-1     | 2017-11-10       | 2020-11-10           |
| Unknown                              | Coaxial Cable     | C-NJNJ-50  | C-0400-01     | 2019-09-05       | 2020-09-05           |
| Unknown                              | Coaxial Cable     | C-NJNJ-50  | C-0075-01     | 2019-09-05       | 2020-09-05           |
| Unknown                              | Coaxial Cable     | C-NJNJ-50  | C-1400-01     | 2019-05-06       | 2020-05-06           |
| HP                                   | Amplifier         | 8447D      | 2727A05902    | 2019-09-05       | 2020-09-05           |
| <b>Radiated emissions Above 1GHz</b> |                   |            |               |                  |                      |
| Agilent                              | Spectrum Analyzer | E4440A     | SG43360054    | 2019-05-09       | 2020-05-09           |
| Farad                                | Test Software     | EZ-EMC     | V1.1.4.2      | N/A              | N/A                  |
| ETS-Lindgren                         | Horn Antenna      | 3115       | 000 527 35    | 2018-10-12       | 2021-10-12           |
| Unknown                              | Coaxial Cable     | C-SJSJ-50  | C-0800-01     | 2019-09-05       | 2020-09-05           |
| Mini-Circuit                         | Amplifier         | ZVA-213-S+ | 54201245      | 2019-09-05       | 2020-09-05           |

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Environmental Conditions**

| Test Item:                | Conducted emissions | Radiated emissions (Below 1GHz) | Radiated emissions (Above 1GHz) |
|---------------------------|---------------------|---------------------------------|---------------------------------|
| <b>Temperature:</b>       | 21.3°C              | 24.1°C                          | 24.8°C                          |
| <b>Relative Humidity:</b> | 65%                 | 51%                             | 49%                             |
| <b>ATM Pressure:</b>      | 101.4kPa            | 101.4 kPa                       | 101.1 kPa                       |
| <b>Tester:</b>            | Sem Xiang           | Jackson Zhang                   | Vern Shen                       |
| <b>Test Date:</b>         | 2020-04-01          | 2020-03-30                      | 2020-03-24                      |

---


**SUMMARY OF TEST RESULTS**

---

| Rule and Clause | Description of Test | Test Result |
|-----------------|---------------------|-------------|
| FCC §15.107     | Conducted emissions | Compliance  |
| FCC §15.109     | Radiated emissions  | Compliance  |

## CONDUCTED EMISSIONS

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

**Corrected Amplitude & Margin Calculation**

The basic equation is as follows:

Result (QuasiPeak or Average) = Meter Reading + Corr.

Note:

Corr. = Cable loss + Factor of coupling device


The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## Test Data

Please refer to following table and plots:

Model Number: APOS A8  
Port: L  
Test Mode: M1  
Power Source: AC 120V/60Hz




## Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|
| 0.153015        | 49.3             | 9.000           | L1   | 9.7        | 16.5        | 65.8         |
| 0.261872        | 40.1             | 9.000           | L1   | 9.7        | 21.3        | 61.4         |
| 0.475741        | 41.3             | 9.000           | L1   | 9.7        | 15.1        | 56.4         |
| 0.660657        | 43.4             | 9.000           | L1   | 9.7        | 12.6        | 56.0         |
| 0.759409        | 46.0             | 9.000           | L1   | 9.7        | 10.0        | 56.0         |
| 0.822331        | 41.5             | 9.000           | L1   | 9.7        | 14.5        | 56.0         |

## Final Result 2

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|
| 0.466367        | 25.9           | 9.000           | L1   | 9.7        | 20.7        | 46.6         |
| 0.660657        | 25.0           | 9.000           | L1   | 9.7        | 21.0        | 46.0         |
| 0.767003        | 30.8           | 9.000           | L1   | 9.7        | 15.2        | 46.0         |
| 0.847248        | 32.1           | 9.000           | L1   | 9.7        | 13.9        | 46.0         |
| 1.236582        | 23.6           | 9.000           | L1   | 9.7        | 22.4        | 46.0         |
| 3.278819        | 26.9           | 9.000           | L1   | 9.8        | 19.1        | 46.0         |

Model Number: APOS A8  
Port: N  
Test Mode: M1  
Power Source: AC 120V/60Hz



## Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|
| 0.153015        | 48.7             | 9.000           | N    | 9.7        | 17.2        | 65.8         |
| 0.241834        | 38.2             | 9.000           | N    | 9.7        | 23.8        | 62.0         |
| 0.660657        | 44.0             | 9.000           | N    | 9.6        | 12.0        | 56.0         |
| 0.729777        | 44.2             | 9.000           | N    | 9.6        | 11.8        | 56.0         |
| 0.759409        | 39.2             | 9.000           | N    | 9.6        | 16.8        | 56.0         |
| 0.814189        | 44.6             | 9.000           | N    | 9.6        | 11.4        | 56.0         |


## Final Result 2

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|
| 0.360058        | 33.6           | 9.000           | N    | 9.6        | 15.1        | 48.7         |
| 0.569057        | 32.9           | 9.000           | N    | 9.6        | 13.1        | 46.0         |
| 0.722551        | 34.8           | 9.000           | N    | 9.6        | 11.2        | 46.0         |
| 0.767003        | 33.6           | 9.000           | N    | 9.6        | 12.4        | 46.0         |
| 0.822331        | 36.6           | 9.000           | N    | 9.6        | 9.4         | 46.0         |
| 1.236582        | 29.4           | 9.000           | N    | 9.6        | 16.6        | 46.0         |


## RADIATED EMISSIONS

### EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 13.5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Measurement |
|-------------------|---------|-----------|---------|-------------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz   | 120 kHz | QP          |
| Above 1 GHz       | 1 MHz   | 3 MHz     | /       | Peak        |
|                   | 1 MHz   | 10Hz      | /       | AVG         |

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

During the radiated emissions, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

All emissions under the average limit and under the noise floor have not recorded in the report.

## Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Meter Reading+ Corrected

Note:

Corrected = Antenna Factor + Cable Loss - Amplifier Gain

or

Corrected = Antenna Factor + Cable Loss + Insertion loss of attenuator - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Limit} - \text{Result}$$

**Test Data**

Please refer to following table and plots:

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M1


**Polarization:** Horizontal  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Detector | Corrected<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----|--------------------|-------------------------|----------|---------------------|--------------------------|-------------------------|----------------|
| 1   | 30.0000            | 25.82                   | peak     | 1.72                | 27.54                    | 40.00                   | 12.46          |
| 2   | 241.4600           | 45.00                   | QP       | -5.97               | 39.03                    | 46.00                   | 6.97           |
| 3   | 256.9800           | 45.20                   | QP       | -5.75               | 39.45                    | 46.00                   | 6.55           |
| 4   | 281.2300           | 42.00                   | QP       | -4.12               | 37.88                    | 46.00                   | 8.12           |
| 5   | 302.5700           | 42.04                   | peak     | -3.75               | 38.29                    | 46.00                   | 7.71           |
| 6   | 730.3400           | 27.61                   | peak     | 3.28                | 30.89                    | 46.00                   | 15.11          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M1


**Polarization:** Vertical  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 30.0000            | 28.70             | QP       | 1.72                | 30.42              | 40.00             | 9.58           |
| 2   | 120.2100           | 31.09             | peak     | -4.83               | 26.26              | 43.50             | 17.24          |
| 3   | 261.8300           | 40.47             | peak     | -4.94               | 35.53              | 46.00             | 10.47          |
| 4   | 282.2000           | 43.03             | peak     | -4.09               | 38.94              | 46.00             | 7.06           |
| 5   | 347.1900           | 32.87             | peak     | -3.15               | 29.72              | 46.00             | 16.28          |
| 6   | 902.0300           | 32.95             | peak     | 0.14                | 33.09              | 46.00             | 12.91          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M1


**Polarization:** Horizontal  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Detector | Corrected<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----|--------------------|-------------------------|----------|---------------------|--------------------------|-------------------------|----------------|
| 1   | 2010.000           | 36.68                   | peak     | 3.71                | 40.39                    | 74.00                   | 33.61          |
| 2   | 2010.000           | 24.43                   | AVG      | 3.71                | 28.14                    | 54.00                   | 25.86          |
| 3   | 4687.500           | 36.27                   | peak     | 10.00               | 46.27                    | 74.00                   | 27.73          |
| 4   | 4687.500           | 24.13                   | AVG      | 10.00               | 34.13                    | 54.00                   | 19.87          |
| 5   | 5712.500           | 35.27                   | peak     | 13.04               | 48.31                    | 74.00                   | 25.69          |
| 6   | 5712.500           | 23.16                   | AVG      | 13.04               | 36.20                    | 54.00                   | 17.80          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M1


**Polarization:** Horizontal  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Detector | Corrected<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----|--------------------|-------------------------|----------|---------------------|--------------------------|-------------------------|----------------|
| 1   | 9438.000           | 34.77                   | peak     | 18.09               | 52.86                    | 74.00                   | 21.14          |
| 2   | 9438.000           | 22.56                   | AVG      | 18.09               | 40.65                    | 54.00                   | 13.35          |
| 3   | 17904.000          | 33.79                   | peak     | 31.20               | 64.99                    | 74.00                   | 9.01           |
| 4   | 17904.000          | 21.44                   | AVG      | 31.20               | 52.64                    | 54.00                   | 1.36           |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M1


**Polarization:** Vertical  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 1597.500           | 36.13             | peak     | 1.43                | 37.56              | 74.00             | 36.44          |
| 2   | 1597.500           | 24.05             | AVG      | 1.43                | 25.48              | 54.00             | 28.52          |
| 3   | 3715.000           | 36.58             | peak     | 8.44                | 45.02              | 74.00             | 28.98          |
| 4   | 3715.000           | 24.37             | AVG      | 8.44                | 32.81              | 54.00             | 21.19          |
| 5   | 5550.000           | 35.34             | peak     | 12.44               | 47.78              | 74.00             | 26.22          |
| 6   | 5550.000           | 23.19             | AVG      | 12.44               | 35.63              | 54.00             | 18.37          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M1


**Polarization:** Vertical  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 8814.000           | 34.33             | peak     | 17.04               | 51.37              | 74.00             | 22.63          |
| 2   | 8814.000           | 22.16             | AVG      | 17.04               | 39.20              | 54.00             | 14.80          |
| 3   | 17778.000          | 33.51             | peak     | 30.36               | 63.87              | 74.00             | 10.13          |
| 4   | 17778.000          | 21.26             | AVG      | 30.36               | 51.62              | 54.00             | 2.38           |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M5


**Polarization:** Horizontal  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Detector | Corrected<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----|--------------------|-------------------------|----------|---------------------|--------------------------|-------------------------|----------------|
| 1   | 30.0000            | 28.22                   | peak     | 1.72                | 29.94                    | 40.00                   | 10.06          |
| 2   | 85.2900            | 34.52                   | peak     | -11.41              | 23.11                    | 40.00                   | 16.89          |
| 3   | 202.6600           | 29.81                   | peak     | -6.04               | 23.77                    | 43.50                   | 19.73          |
| 4   | 263.7700           | 45.60                   | QP       | -4.63               | 40.97                    | 46.00                   | 5.03           |
| 5   | 637.2200           | 28.02                   | peak     | 2.20                | 30.22                    | 46.00                   | 15.78          |
| 6   | 778.8400           | 28.53                   | peak     | 4.36                | 32.89                    | 46.00                   | 13.11          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M5


**Polarization:** Vertical  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 31.9400            | 33.44             | peak     | 0.19                | 33.63              | 40.00             | 6.37           |
| 2   | 123.1200           | 30.30             | peak     | -4.57               | 25.73              | 43.50             | 17.77          |
| 3   | 275.4100           | 41.94             | peak     | -4.13               | 37.81              | 46.00             | 8.19           |
| 4   | 364.6500           | 31.18             | peak     | -2.82               | 28.36              | 46.00             | 17.64          |
| 5   | 637.2200           | 28.20             | peak     | 2.20                | 30.40              | 46.00             | 15.60          |
| 6   | 728.4000           | 28.24             | peak     | 3.26                | 31.50              | 46.00             | 14.50          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M5


**Polarization:** Horizontal  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 2005.000           | 37.00             | peak     | 3.70                | 40.70              | 74.00             | 33.30          |
| 2   | 2005.000           | 24.85             | AVG      | 3.70                | 28.55              | 54.00             | 25.45          |
| 3   | 3605.000           | 36.60             | peak     | 7.98                | 44.58              | 74.00             | 29.42          |
| 4   | 3605.000           | 24.43             | AVG      | 7.98                | 32.41              | 54.00             | 21.59          |
| 5   | 5497.500           | 34.57             | peak     | 12.34               | 46.91              | 74.00             | 27.09          |
| 6   | 5497.500           | 22.39             | AVG      | 12.34               | 34.73              | 54.00             | 19.27          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M5


**Polarization:** Horizontal  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Detector | Corrected<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----|--------------------|-------------------------|----------|---------------------|--------------------------|-------------------------|----------------|
| 1   | 8484.000           | 34.76                   | peak     | 16.46               | 51.22                    | 74.00                   | 22.78          |
| 2   | 8484.000           | 22.57                   | AVG      | 16.46               | 39.03                    | 54.00                   | 14.97          |
| 3   | 17502.000          | 35.08                   | peak     | 28.50               | 63.58                    | 74.00                   | 10.42          |
| 4   | 17502.000          | 22.85                   | AVG      | 28.50               | 51.35                    | 54.00                   | 2.65           |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M5


**Polarization:** Vertical  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 1987.500           | 36.81             | peak     | 3.52                | 40.33              | 74.00             | 33.67          |
| 2   | 1987.500           | 24.68             | AVG      | 3.52                | 28.20              | 54.00             | 25.80          |
| 3   | 4487.500           | 36.14             | peak     | 9.57                | 45.71              | 74.00             | 28.29          |
| 4   | 4487.500           | 24.03             | AVG      | 9.57                | 33.60              | 54.00             | 20.40          |
| 5   | 5547.500           | 35.03             | peak     | 12.44               | 47.47              | 74.00             | 26.53          |
| 6   | 5547.500           | 23.01             | AVG      | 12.44               | 35.45              | 54.00             | 18.55          |

**Condition:** FCC Part 15B Class B  
**EUT:** Smart POS Terminal  
**Model:** APOS A8  
**Test mode:** M5

**Polarization:** Vertical  
**Power:** AC 120V/60Hz  
**Distance:** 3m



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Detector | Corrected<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|-----|--------------------|-------------------|----------|---------------------|--------------------|-------------------|----------------|
| 1   | 6918.000           | 35.14             | peak     | 14.77               | 49.91              | 74.00             | 24.09          |
| 2   | 6918.000           | 23.05             | AVG      | 14.77               | 37.82              | 54.00             | 16.18          |
| 3   | 17856.000          | 34.15             | peak     | 30.88               | 65.03              | 74.00             | 8.97           |
| 4   | 17856.000          | 22.01             | AVG      | 30.88               | 52.89              | 54.00             | 1.11           |

\*\*\*\*\*END OF REPORT\*\*\*\*\*