

TEST REPORT CONCERNING THE COMPLIANCE OF A 13.56 MHZ INDUCTIVE PROXIMITY TAG READER, BRAND COLLIS, MODEL SMARTWAVE BOX WITH 47 CFR PART 15 (10-1-09 Edition) AND THE REQUIREMENTS OF INDUSTRY CANADA: RSS-GEN AND RSS-210 (ISSUE 8, DECEMBER 2010.

10100601.fcc01 June 27, 2011

> FCC listed : 90828 Industry Canada : 2932G-1 VCCI Registered : R-1518, C-1598

R&TTE, LVD, EMC Notified Body: 1856

TÜV Rheinland EPS B.V. P.O. Box 15 9822 ZG Niekerk (NL) Smidshornerweg 18 9822 TL Niekerk (NL)

Telephone: +31 594 505005 Telefax: +31 594 504804

E-mail: info@tuv-eps.com Web: www.tuv-eps.com



Test specification(s): FCC Part 15, RSS-GEN, RSS-210

Description of EUT: 13.56MHz Inductive proximity Tag Reader

Manufacturer: Collis B.V. Brand mark: Collis

Model: SmartWave Box

XKD-SMARTWAVEBOX FCC ID: 8417A-SWBOX IC:

# MEASUREMENT/TECHNICAL REPORT

**COLLIS** 

**Model: SmartWave Box** 

FCC ID: XKD-SMARTWAVEBOX **IC: 8417A-SWBOX** 

June 27, 2011

This report concerns: Original grant/certification Class 2 change Verification

Equipment type: 13.56 MHz Inductive proximity tag reader

: Richard van der Meer Report prepared by: Name

Company name : TÜV Rheinland EPS B.V. : Smidshornerweg 18 Address : 9822 TL Niekerk Postal code/city

: P.O. Box 15 Mailing address Postal code/city : 9822 ZG Niekerk Country : The Netherlands Telephone number : + 31 594 505 005 Telefax number : + 31 594 504 804

E-mail : info@tuv-eps.com

The data taken for this test and report herein was done in accordance with 47 CFR Part 15 (10-1-09 Edition), RSS-GEN, RSS-210 and the measurement procedures of ANSI C63.4-2009. TÜV Rheinland EPS B.V. at Niekerk, The Netherlands, certifies that the data is accurate and contains a true representation of the emission profile of the Equipment Under Test (EUT) on the date of the test as noted in the test report. I have reviewed the test report and find it to be an accurate description of the test(s) performed and the EUT so tested.

Date: June 27, 2011 Signature:

O. Hoekstra

Senior Engineer Telecom TÜV Rheinland EPS B.V.

If Weekh

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 2 of 17



Test specification(s): FCC Part 15, RSS-GEN, RSS-210

Description of EUT: 13.56MHz Inductive proximity Tag Reader
Manufacturer: Collis B.V.

Manufacturer: Collis E Brand mark: Collis

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

IC: 8417A-SWBOX

## **Summary**

The device under test does:

• fulfill the general approval requirements as identified in this test report

o not fulfill the general approval requirements as identified in this test report

### **Description of test item**

Test item : Inductive proximity tag reader, operating on 13.56 MHz

Manufacturer : Collis B.V. Brand : Collis

Model(s) : SmartWave Box

Serial number(s) : n.a. Revision : 2.21

# **Applicant information**

Applicant's representative : Mr. R. Jozefzoon

Company : Collis B.V.

Address : De Heyderweg 1

Postal code : 2314 XZ City : Leiden

Country : The Netherlands
Telephone number : +31 71 581 36 36
Telefax number : +31 71 581 36 30
Email : info@collis.nl
Internet : www.collis.nl

# Test(s) performed

Location : Niekerk
Test(s) started : April 01, 2011
Test(s) completed : April 11, 2011

Purpose of test(s) Equipment Authorization (Class 2 Permissive Change)

Test specification(s) : 47 CFR Part 15 (10-1-09 Edition) and

RSS-GEN (ISSUE 3, DECEMBÉR 2010) AND RSS-210 (ISSUE 8, DECEMBER

2010)

Test engineer(s) : R. van der Meer

Report written by : R. van der Meer

Report date : June 27, 2011

This report shall not be reproduced, except in full, without the written permission of TÜV Rheinland EPS B.V.

The test results relate only to the item(s) tested.

Project number : 10100601.SMARTWAVEBOX.fcc01 Page 3 of 17



Test specification(s): Description of EUT: Manufacturer: Brand mark:

FCC Part 15, RSS-GEN, RSS-210 13.56MHz Inductive proximity Tag Reader Collis B.V.

Collis B.

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX IC: 8417A-SWBOX

# Table of contents

1 General information	
1.1 Product description	Ę
1.1.1 Introduction.	Ę
1.2 Related submittal(s) and/or Grant(s)	
1.2.1 General	
1.3 Test Summary	
2 Tested system details	
2.1.1 Description of input and output ports	
2.2 Test methodology	
2.3 Test facility.	
2.4 Test conditions.	
3 System test configuration	10
3.1 Justification	
3.2 EUT mode of operation.	10
3.3 Special accessories	10
3.4 Equipment modifications.	10
3.5 Product Labelling	10
3.6 Block diagram of the EUT	10
3.7 Schematics of the EUT	
3.8 Part list of the EUT.	10
4 Radiated emission data	11
4.1 Radiated field strength measurements (30 MHz – 1 GHz, E-field	)11
4.2 Radiated field strength measurements (frequency range of 0.009	9-30 MHz, H-field)12
5 Conducted emission data	
5.1 Conducted emission data of the EUT	14
6 Plot of the Occupied bandwidth	16
7 List of utilized test equipment	17



Test specification(s): Description of EUT:

FCC Part 15, RSS-GEN, RSS-210 13.56MHz Inductive proximity Tag Reader

Manufacturer: Collis B.V. Brand mark: Collis

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

8417A-SWBOX IC:

1 General information.

#### 1.1 Product description.

#### Introduction.

The Contactless Smartcard reader & simulator, brand Collis, model SmartWave Box, operates on a frequency of 13.56 MHz and is therefore classified as an inductive proximity card reader. The SmartWave Box is a hardware tool that acts as a card simulator, using the SmartWave Box Probe to wave in the terminal's target field for contactless cards. A PC with a software package, the TEST REPORT, is set up by placing Collis SmartWave Box (in the case of contactless cards) in between the card and the terminal/reader. This picks up the communication between the two entities and sends it to the PC where the TEST REPORT software is running.

Some changes have been made to the hardware from the originally certified device for added functionality. The changes require a Class 2 Permissive Change and this testreports.

The content of this report and measurement results have not been changed other than the way of presenting the data.

#### 1.2 Related submittal(s) and/or Grant(s).

#### 1.2.1 General.

This test report supports the Permissive Change 2 in equipment authorization files under FCC ID: XKD-SMARTWAVEBOX and IC: 8417A-SWBOX.

#### **Test Summary** 1.3

The EUT was tested in accordance with the specifications given in the table below.

Test S	tandard				
47 CFR Part 15 (10-1-09 Edition)	,		Page	Pass / Fail	
15.207(a)	RSS-Gen(7.2.4)	Conducted emissions	14 - 15	Pass	
15.209, 15.225	RSS-Gen(4.9 and 7.2.5) and RSS-210(2.5)	Radiated emissions	11 - 13	Pass	

Table: testspecifications

Testmethods: ANSI C63:2009 and RSS-Gen Issue 3, December 2010

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 5 of 17



Test specification(s): FCC Part 15, RSS-GEN, RSS-210

Description of EUT: 13.56MHz Inductive proximity Tag Reader Collis B.V.

Manufacturer: Brand mark: Collis

Model: SmartWave Box

FCC ID: XKD-SMARTWAVEBOX

8417A-SWBOX IC:

#### Tested system details. 2

Details and an overview of the system and all of its components, as it has been tested, may be found below.

**EUT** Contactless Smartcard reader & simulator

Manufacturer Collis B.V. **Brand** Collis

Model SmartWave Box

Serial number n.a. Voltage input rating 18 Vdc Voltage output rating n.a.

Current input rating not provided Antenna Internal Remarks v02.21

AUX1 Probe Manufacturer Collis B.V. **Brand** Collis Model v02.00 Serial number N.a.

Connect to EUT with FireWire cable Remark

AUX2 Cardman Manufacturer Omnikey **Brand** Cardman Models 5321 Serial number Voltage input rating Current input rating

Connect to AUX4 with USB cable Remark



Test specification(s): FCC Part 15, RSS-GEN, RSS-210 Description of EUT:

13.56MHz Inductive proximity Tag Reader

Manufacturer: Collis B.V. Brand mark: Collis

Model: SmartWave Box

FCC ID: XKD-SMARTWAVEBOX

8417A-SWBOX IC:

AUX3 Adapter Manufacturer Friwo **Brand** Friwo

FW75550/18 Models

Serial number

Voltage input rating 100-240Vac 50/60Hz

Current input rating 18Vdc/840mA Remark Connect to EUT


AUX4 Laptop Manufacturer Lenovo **Brand** Lenovo Models IBM ThinkPad Serial number L3-BF847 07/02

Voltage input rating 18Vdc Current input rating 18Vdc/5A

Remark Connect to AUX2 Software Collis Card Spy v1.0

AUX5 Oscilloscoop Inventory Number 15232 (see section 6 for details)

AUX2 and AUX4 are only used to program the EUT and were not part of the testsetup.



Photograph of the system



Test specification(s): Description of EUT:
Manufacturer:

FCC Part 15, RSS-GEN, RSS-210 13.56MHz Inductive proximity Tag Reader

Collis B.V. Brand mark: Collis

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

8417A-SWBOX IC:

#### 2.1.1 Description of input and output ports.

Number	Terminal	From	То	Remarks
1	Mains	Adapter	EUT	Cable 1.5m
2	Probe	AUX1	EUT	Cable 1.8m
3	Link cable	Laptop	EUT	Cable 60cm
4	USB	Laptop	AUX2	Cable 1.5m
5	Trig In	Trig Out front	Trig In rear	Coax
6	Trig Out	Trig Out rear	Oscilloscope CH-1	Coax




Figure 1. Basic set-up normal use

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 8 of 17



Description of EUT: 13.56MHz I Manufacturer: Collis B.V.

Brand mark: Collis

Model: SmartWave Box
FCC ID: XKD-SMARTWAVEBOX

IC: 8417A-SWBOX

### 2.2 Test methodology.

The test methodology used is based on the requirements of 47 CFR Part 15 (10-1-09 Edition), sections 15.31, 15.207,15.209, 15.225 and RSS-GEN (ISSUE 3, DECEMBER 2010) RSS-210 (ISSUE 8, DECEMBER 2010).

The test methods, which have been used, are based on ANSI C63.4: 2009.

Radiated emission tests above 30 MHz were performed at a measurement distance of 3 meters.

Radiated emission tests below 30 MHz were performed at a measurement distance of 3 meters.

To calculate the field strength level from these results to the appropriate distance at which the limit is specified, the appropriate extrapolation factor is used.

The receivers are switching automatically to the right bandwidth in accordance with CISPR 16. This is implemented in the receiver. The antenna factors are programmed in the test receiver. The receiver automatically calculates the appropriate correction factor for the utilized antenna and also the appropriate antenna factor for the cable loss. The total correction is automatically added to the measured value.

#### 2.3 Test facility.

The Federal Communications Commission and Industry Canada has reviewed the technical characteristics of the test facilities at TÜV Rheinland EPS B.V., located in Niekerk, 9822 TL Smidshornerweg 18, The Netherlands, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 23, 2000.

The description of the test facilities has been filed at the Office of the Federal Communications Commission under registration number 90828. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The description of the test facilities has been filed to Industry Canada under registration number 2932G-1. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

## 2.4 Test conditions.

Normal test conditions:

Temperature (\*) : +15°C to +35°C Relative humidity(\*) : 20 % to 75 %

Supply voltage : 120VAC/60Hz to the AC/DC Power Supply

Air pressure : 950 – 1050 hPa

\*When is was impracticable to carry out the tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests are stated separately.



Manufacturer: Collis B.V. Brand mark: Collis

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

IC: 8417A-SWBOX

# 3 System test configuration.

#### 3.1 Justification.

The system was configured for testing in a typical fashion (as a customer would normally use it).

The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.4: 2009.

## 3.2 EUT mode of operation.

The EUT has been tested in active mode, i.e. the EUT is ready to detect a tag. To assess the behavior of the EUT while reading the tag, the EUT is tested with a tag presented such that it continuously reads the tag. The intentional radiator tests have been performed with a complete functioning EUT and interconnections.

#### 3.3 Special accessories.

No special accessories are used and/or needed to achieve compliance.

#### 3.4 Equipment modifications.

No modifications have been made to the equipment in order to achieve compliance.

#### 3.5 Product Labelling

The product labeling information is available in the technical documentation package.

### 3.6 Block diagram of the EUT.

The block diagram is available in the technical documentation package.

# 3.7 Schematics of the EUT.

The schematics are available in the technical documentation package.

## 3.8 Part list of the EUT.

The part list is available in the technical documentation package.

Project number : 10100601.SMARTWAVEBOX.fcc01

Page 10 of 17



Manufacturer: Brand mark:

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

Collis

8417A-SWBOX IC:

#### Radiated emission data. 4

# Radiated field strength measurements (30 MHz - 1 GHz, E-field)

Frequency (MHz)	Measurement results @3m Vertical (dBµV)	Measurement results @3m Horizontal (dBµV)	Correction factor (dB)	Results after correction Vertical (dBµV/m)	Results after correction Horizontal (dBµV/m)	Limits @3m (dBµV/m)	Pass/Fail
54.7	15.7	7.7	8.1	23.8	15.8	40.0	Pass
57.2	10.9	7.1	7.5	18.4	14.6	40.0	Pass
135.6	14.1	12.3	14.1	28.2	26.4	43.5	Pass
149.16	9.1	8.4	13.7	22.8	22.1	43.5	Pass
271.2	8.7	11.6	16.9	25.6	28.5	46.0	Pass
436.2	5.9	5.9	22.4	28.3	28.3	46.0	Pass
975.7	7.1	6.9	34.7	41.8	41.6	46.0	Pass

Table 1: Radiated emissions of the EUT.

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15 section 15.209, 15.225 and RSS-Gen with the EUT operating in on 13.56 MHz are depicted in Table 1. The system is tested without AUX 2 and AUX4 and the associating cables. AUX2 and AUX4 were only used in the situation for programming the EUT for continues transmitting.

# Notes:

- 1. Field strength values of radiated emissions at frequencies not listed in the table above are more than 20 dB below the applicable limit.
- Measurement uncertainty is ±5.0dB
- 3. The reported field strength values are the worst case values at the indicated frequency. The EUT was varied in three positions, the antenna was varied in horizontal and vertical orientations and also in height (between 1m and 4m).
- 4. A Quasi-peak detector was used with a resolution bandwidth of 120 kHz

Used test equipment and ancillaries:

15232	99070	99071	99107	99608	99609	99699	99547	15453
99580								

Test engineer

Signature

Name : Richard van der Meer

Date : April 01, 2011

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 11 of 17



Manufacturer: Collis B.V.
Brand mark: Collis

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

IC: 8417A-SWBOX

# 4.2 Radiated field strength measurements (frequency range of 0.009-30 MHz, H-field).

Frequency (MHz)	Measurement results	Detector	Antenna factor	Cable loss	Extrapolation factor	Measurement results (calculated)	Limits
	dBµV @3m		dB	dB	dB	dBµV/m@30m (unless otherwise stated)	dBµV/m@30m (unless otherwise stated)
0.749	10.0	Qp	20.1	1	40	-8.9	32.0
1.00964	7.0	Qp	20.1	1	40	-11.9	23.8
9.546	4.7	Qp	19.7	1	40	-14.6	29.5
13.56 (fundamental)	49.2	Qp	19.6	1	40	29.8	84
15.67	15.1	Qp	19.7	1	40	-4.2	29.5
27.12	45.0	Qp	20.0	1	40	26.0	29.5

Table 2: Radiated emissions of the EUT

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15 section 15.209, 15.225 and RSS-210 and RSS-Gen with the EUT operating in continuous transmit mode on 13.56 MHz, are depicted in Table 2.

## Notes:

- 1. Calculated measurement results are obtained by using the 40 dB/decade extrapolation factor and the antenna factor and cable loss is included. For instance the corrected value for the 13.56 MHz fundamental is calculated as: Measurement result + Antenna Factor + Cable loss Extrapolation Factor => 49.2 dBuV + 19.6 dB + 1 dB 40 dB = 29.8 dBuV/m.
- 2. Frequency range:
  - except for a. and b. below a Quasi-Peak detector was used during testing.
    - a. 9- 90 kHz Average detector used during measurements
    - b. 110-490 kHz Average detector used during measurements
- 3. A resolution bandwidth of 9kHz was used during testing
- 4. n.i. Indicates that no field strength values could be measured on the listed frequencies or in the listed frequency range.
- 5. Field strength values of radiated emissions at frequencies not listed in Table 2 are more than 20 dB below the applicable limit
- 6. The EUT was varied in three positions, the loop antenna was varied in horizontal and vertical orientations and also around it's axis. The reported value is the worst case found at the reported frequency.
- 7. The EUT was tested in both normal mode (i.e. without a tag in its proximity) and in activated mode (i.e. with a tag in its proximity).
- 8. Measurement uncertainty is ±5.0dB

## Used test equipment and ancillaries:

99580	99070	99107	99120	15453	99608	99609	99699	99547
15232								

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 12 of 17



Test specification(s): Description of EUT: Manufacturer: Brand mark:

FCC Part 15, RSS-GEN, RSS-210 13.56MHz Inductive proximity Tag Reader

Collis B.V. Collis

Model: **SmartWave Box** 

FCC ID: XKD-SMARTWAVEBOX 8417A-SWBOX

# Test engineer

Signature

Name : R. van der Meer

Date : April 01, 2011



Manufacturer: Collis B.V.

Brand mark: Collis

Model: SmartWave Box FCC ID: XKD-SMARTWAVEBOX

IC: 8417A-SWBOX

# 5 Conducted emission data.

# 5.1 Conducted emission data of the EUT

Frequency (MHz)	Measurement results dB(μV) Neutral		dB	nent results (µV) ne 1	Limits dB(μV)		Result
. ,	QP	AV	QP	AV	QP	AV	
0.198	33.2	Note 4	25.7	Note 4	63.6	53.6	PASS
0.794	31.4	٠,	27.3	.,	56.0	46.0	PASS
0.898	17.8	٠,	30.3	.,	56.0	46.0	PASS
2.074	31.5	.,	29.6	د،	56.0	46.0	PASS
2.670	23.7	٤,	31.8	د،	56.0	46.0	PASS
2.786	27.4	67	30.9	.,	56.0	46.0	PASS
2.994	27.9	67	30.9	.,	56.0	46.0	PASS
3.786	22.4	67	31.9	.,	56.0	46.0	PASS
4.554	19.9	67	31.7	.,	56.0	46.0	PASS
5.478	23.8	67	31.2	.,	60.0	50.0	PASS
6.282	23.2	67	30.7	.,	60.0	50.0	PASS
7.950	27.2	67	31.7	"	60.0	50.0	PASS
13.558	35.9	()	34.8	()	60.0	50.0	PASS
27.118	26.8	67	28.0	د،	60.0	50.0	PASS

Table 3: Conducted emission measurements.

The results of the conducted emission tests, carried out in accordance with 47 CFR Part 15 section 15.207 and RSS-Gen section 7.2.4, at the 120 Volts AC mains connection terminals of the AC/DC power supply which was connected to the EUT, are depicted in Table 3. The EUT was tested in both passive and active mode (while detecting a card). Maximum values recorded. The system is tested as in whole, so with all equipment as shown in Figure.1 in place and functioning. Being the worst case situation.

#### Notes:

- 1. Measurement uncertainty is ±3.5dB
- 2. The resolution bandwidth used was 9 kHz.
- 3. Values of conducted emissions at frequencies not listed in Table 3 are more than 20 dB below the applicable limit.
- 4. QP (Quasi Peak) values already within Av (Average) limits, therefore Av not tested.

Used test equipment and ancillaries:

99548	99161	12512	15232???	13313	99699	

Test engineer

Signature

Name : R. van der Meer

Date : April 11, 2011

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 14 of 17



Test specification(s): Description of EUT: 13.56MHz II
Manufacturer: Collis B.V.

Brand mark: Model:


13.56MHz Inductive proximity Tag Reader

FCC Part 15, RSS-GEN, RSS-210


Collis

SmartWave Box

FCC ID: XKD-SMARTWAVEBOX IC: 8417A-SWBOX



Plot 1: Conducted emissions of the EUT on L1



Plot 2: Conducted emissions of the EUT on Neutral

Page 15 of 17



Test specification(s): Description of EUT: Manufacturer: Brand mark:

13.56MHz Inductive proximity Tag Reader Collis B.V.


FCC Part 15, RSS-GEN, RSS-210

d mark: Collis
Model: SmartWave Box

FCC ID: XKD-SMARTWAVEBOX

IC: 8417A-SWBOX

# 6 Plot of the Occupied bandwidth



Plot 3: Occupied bandwidth = 0,910 kHz as measured with a spectrum analyzer (taken from the original filing)

Project number: 10100601.SMARTWAVEBOX.fcc01 Page 16 of 17



Test specification(s): Description of EUT:

Manufacturer:

FCC Part 15, RSS-GEN, RSS-210 13.56MHz Inductive proximity Tag Reader

Collis B.V. Brand mark: Collis

Model: **SmartWave Box** FCC ID: XKD-SMARTWAVEBOX

8417A-SWBOX

#### List of utilized test equipment. 7

Inventory number	Description	Brand	Model	Last cal.	Next cal.
12512	LISN	EMCO	3625/2	01/2010	01/2012
13313	Pulse Limiter	R&S	ESH3-Z2	02/2011	02/2012
15232	Oscilloscope	Teltronix	TDS-220	02/2011	02/2012
15453	Active loopant. 60 cm	Chase	HLA6120	05/2010	05/2011
15633	Biconilog Testantenna	Chase	CBL 6111B	02/2011	02/2012
99070	Coax 15m RG213 OATS	NMi Certin B.V.	KABEL 15M OATS	10/2010	10/2011
99071	Coax OATS ground	NMi Certin B.V.	KABEL GROND OATS	10/2010	10/2011
99107	Controller OATS	Heinrich Deisel	4630-100	NA	NA
99161	Variac 250V 6A	RFT	LTS006	NA	NA
99547	Temperature-Humiditymeter	Europe supplies	WS-7082	10/2010	10/2011
99580	OATS	Comtest	FCC listed: 90828	08/2008	08/2011
99608	Controller (OATS)	EMCS	DOC202	NA	NA
99609	Antenna mast	EMCS	AP-4702C	NA	NA
99699	Measuring receiver	R&S	ESCI	02/2011	02/2012
12476	Antenna mast	EMCO	TR3	NA	NA
12477	Antenna mast 1-4 mtr	Poelstra	NA	NA	NA
99608	Controller (OATS)	EMCS	DOC202	NA	NA
99651	Variac	NA	Vast Activa: 08-9510	NA	NA

NA= Not Applicable