



BUREAU  
VERITAS

Test Report No.: FS140319N033

## RF EXPOSURE REPORT

Applicant	MEDIALINK PRODUCTS LLC
Address	1951 OLD CUTHBERT RD., STE 301 CHERRY HILL, NJ 08034-1411

Manufacturer or Supplier	Tranwo Technology Corp.
Address:	No.236, Sec. 3, Huanbei Rd., Jubei City, Hsinchu County 30265,Taiwan
Product	Travel Wi-Fi Router
Brand Name	MEDIALINK
Model	MWN-TR150N
Additional Model & Model Difference	N/A
Date of tests	May 24, 2013 ~ Jun. 20, 2013

**FCC Part 2 (Section 2.1091)**  
 **FCC OET Bulletin 65, Supplement C (01-01)**  
 **IEEE C95.1**

**CONCLUSION:** The submitted sample was found to COMPLY with the test requirement

Tested by Venless Long Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	

Date: Mar. 24, 2014

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## Table of Contents

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT .....	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION .....	5
5. ANTENNA GAIN.....	5
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



BUREAU  
VERITAS

Test Report No.: FS140319N033

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS130523N031	Original release	Jun. 21, 2013
FS140319N033	Base on the original report RF130523N031 change the applicant, manufacturer, brand name, product name, model and FCC ID.	Mar. 24, 2014



**BUREAU  
VERITAS** Test Report No.: FS140319N033

## 1. CERTIFICATION

**PRODUCT:** Travel Wi-Fi Router

**BRAND NAME:** MEDIALINK

**MODEL NO.:** MWN-TR150N

**TEST SAMPLE:** ENGINEERING SAMPLE

**APPLICANT:** MEDIALINK PRODUCTS LLC

**TESTED DATE:** Jun. 21, 2013

**STANDARDS:** FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1



## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
<b>LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE</b>				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

## 3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

## 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	3.5	PIFA



BUREAU  
VERITAS Test Report No.: FS140319N033

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412-2462	29.65	3.5	20	0.013205	1.00

--- END ---