

RF EXPOSURE REPORT

REPORT NO.: SA990316C02 MODEL NO.: FS-GM102

FCC ID: XLG-FS-GM102

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: Favite Inc.

ADDRESS: No. 176, Taihe Road, Jhubei City, Hsinchu

County 30267, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB LOCATION: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung

1

Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien

307, Taiwan



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in our lab, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)		
(MHz)						
(A)Limits For Occupational / Control Exposures						
300-1500			F/300	6		
1500-100,000			5	6		
(B)Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

Report No.: SA990316C02



3. Friis Formula

Friis transmission formula : Pd = $(Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 0.601 mW/cm2. If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 23cm.

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3

5. Classification

This device is Limits for General Population / Uncontrolled Exposure.

This device is classified as **Mobile Device**.



6. Test Results

6.1 Antenna Gain

The maximum Gain is 5dBi or 3.162278 (numeric)

Antenna Type	Connector Type	Gain (dBi)
Patch	UFL	5

6.2 Output Power Into Antenna & RF Exposure value at distance 23cm:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm²)
0	902.75	955.0	0.454	0.601
25	915.25	977.2	0.465	0.601
49	927.25	955.0	0.454	0.601