PCTEST

PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA Tel. 410.290.6652 / Fax 410.290.6554 http://www.pctestlab.com



RF EXPOSURE EVALUATION (MAXIMUM PERMISSIBLE EXPOSURE)

Applicant Name:

Digital Receiver Technology, Inc 20250 Century Boulevard, Suite 300 Germantown, MD 20874-1114 USA #N/A Date of Testing:
Feb. 24 - March 12, 2009
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0903030373.DRT

FCC ID: TBD

APPLICANT: Digital Receiver Technology, Inc

EUT Type: Portable Base Station

EUT Model: DRT1201B

FCC Rule Part(s): FCC Part 1 (§1.1310) and Part 2 (§2.1091)


FCC Classification: PCS Licensed Transmitter (PCB)

Test Procedure: OET Bulletin 65

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.





FCC ID: TBD	ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	DRT Ogst Reser brings to	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 1 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		rage 1 of 1



TABLE OF CONTENTS

1.0	RF E	EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	3
		INTRODUCTION	
	1.2	EUT DESCRIPTION	3
	1.3	MPE REQUIREMENTS OVERVIEW	4
	1.4	PROCEDURE	ξ
	1.5	SUMMARY OF RESULTS	6
2.0	CON	ICLUSION	7

FCC ID: TBD	PCTEST:		DRT Paper haven having to	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 2 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		rage 2 oi 1



RF EXPOSURE EVALUATION - MAXIMUM PERMISSIBLE 1.0 **EXPOSURE (MPE)**

1.1 Introduction

This document is prepared on behalf of Digital Receiver Technology, Inc to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (Minutes)		
(A	(A) Limits For Occupational / Control Exposures (f = frequency)					
30-300	61.4	0.163	1.0	6		
300-1500			f/300	6		
1500-100,000			5.0	6		
(B) Lim	its For General Pop	ulation / Uncontrolle	ed Exposure (f = freq	uency)		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

1.2 **EUT Description**

The DRT Model: 1201B is a Portable Base Station with operating modes of Cellular/PCS GSM, Cellular/PCS CDMA, and 850 Band. For this MPE evaluation the device is set to transmit from the 1201B for each mode of operation and the RF exposure of each transmitter is evaluated individually. The maximum antenna gains are determined by the actual limit of RF Exposure or EIRP.

EUT:

Model: 1201B

Grantee: Digital Receiver Technology, Inc

FCC ID: **TBD**

Modes: 850 Band

Cellular GSM Cellular CDMA PCS GSM **PCS CDMA**

FCC ID: TBD	PCTEST:	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	DRT Sight Reserve Servestage (n)	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 3 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		raye 3 01 7



1.3 **MPE Requirements Overview**

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- Occupational/Controlled Exposure: In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- General Population/Uncontrolled Exposure: The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The DRT Portable Base Station FCC ID: TBD is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure as no special RF Exposure training is involved for the use of this device.

FCC ID: TBD	ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	DRT Split Reserve Servicing Se	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 4 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		rage 4 or 7
0903030373.DRT	,	Portable Base Station		DE\/ 0.4



1.4 **Procedure**

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a power meter and the powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

The antenna gains of each antenna to be used with the different available transmitters were used to calculate the MPE in all relevant bands of operation.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out}*G) / (4\pi r^2)$

Where,

 P_d = Power Density (mW/cm²) $\pi = 3.1416$

P_{out} = output power to antenna (mW) r = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

There is no co-location between the electric fields of any two transmitters therefore following power densities are calculated for each individual transmitter by frequency at 20cm spacing:

Frequency	869.2 MHz
Limit	0.579 mW/cm^2
Distance (cm), R =	20 cm
Power (dBm), P =	10.4 dBm 10.96 mW
TX Ant Gain (dBi), G =	24.2 dBi
Power Density (S) =	0.574 mW/cm ² (at 20cm)
Minimum Distance =	19.9 cm

Table 1-2. Calculated MPE Data for Cellular Band - GSM

Frequency:	869.7 MHz
Limit:	0.580 mW/cm^2
Distance (cm), R =	20 cm
Power (dBm), P =	8.54 dBm 7.14 mW
TX Ant Gain (dBi), G =	26.1 dBi
Power Density (S) =	0.5791 mW/cm^2 (at 20cm)
Minimum Distance =	20.0 cm

Table 1-3, Calculated MPE Data for Cellular Band - CDMA

FCC ID: TBD	ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	DRT Spiritumer forming to	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 5 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		rage 5 or r



Frequency	1930.2 MHz
Limit	1.000 mW/cm^2
Distance (cm), R =	20 cm
Power (dBm), P =	10.2 dBm 10.47 mW
TX Ant Gain (dB), G =	26.8 dBi
Power Density (S) =	0.997 mW/cm^2 (at 20cm)
Minimum Distance =	20.0 cm

Table 1-4. Calculated MPE Data for PCS Band - GSM

Frequency	1931.25 MHz
Limit	1.000 mW/cm^2
Distance (cm), R =	20 cm
Power (dBm), P =	6.45 dBm 4.42 mW
TX Ant Gain (dB), G =	30.5 dBi
Power Density (S) =	0.986 mW/cm^2 (at 20cm)
Minimum Distance =	19.9 cm

Table 1-5. Calculated MPE Data for PCS Band - CDMA

Frequency	851 MHz
Limit	0.567 mW/cm^2
Distance (cm), R =	20 cm
Power (dBm), P =	8.68 dBm 7.38 mW
TX Ant Gain (dB), G =	25.8 dBi
Power Density (S) =	0.558 mW/cm^2 (at 20cm)
Minimum Distance =	19.8 cm

Table 1-6. Calculated MPE Data for 850 Band

1.5 Summary of Results

Frequency Band [MHz]	Maximum Antenna Gain [dBi]	MPE @ 20cm (mW/cm²)	Test Result
Cellular – GSM	24.2	0.574	PASS
Cellular – CDMA	26.1	0.579	PASS
PCS – GSM	26.8	0.997	PASS
PCS – CDMA	30.5	0.986	PASS
850 Band	25.8	0.558	PASS

Table 1-7. Maximum Permissible Exposure Summary Table

FCC ID: TBD	ENCINERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	DRT Spiritumer forming to	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 6 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		raye o oi 7



2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: TBD	PETEST:	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	DRT Total Name Salang St	Reviewed by: Quality Manager
Test Report S/N:	Test Dates:	EUT Type:		Page 7 of 7
0903030373.DRT	Feb. 24 - March 12, 2009	Portable Base Station		Page 7 of 7