



Report No.: TBR-C-202407-0262-3

Page: 1 of 17

Radio Test Report

FCC ID: XMF-MID1058

Change II

| | | |
|-----------------------------------|---|---|
| Report No. | : | TBR-C-202407-0262-3 |
| Applicant | : | Lightcomm Technology Co., Ltd. |
| Equipment Under Test (EUT) | | |
| EUT Name | : | 10.1" Tablet |
| Model No. | : | DL1050 |
| Series Model No. | : | MID1058-AD |
| Brand Name | : | N/A |
| Sample ID | : | HC-C-202407-0263-01-01&HC-C-202407-0263-01-02 |
| Receipt Date | : | 2024-08-06 |
| Test Date | : | 2024-08-06 to 2024-08-14 |
| Issue Date | : | 2024-08-14 |
| Standards | : | FCC Part 15 Subpart C 15.247 |
| Test Method | : | ANSI C63.10: 2013 KDB 558074 D01 15.247 Meas Guidance v05r02 |
| Conclusions | : | PASS |
| | | In the configuration tested, the EUT complied with the standards specified above. |
| Test By | : | <i>Mike Yan</i> |
| Reviewed By | : | <i>Henry Huang</i> |
| Approved By | : | <i>Ivan Su</i> |



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

TB-RF-074-1.0

Contents

| | |
|---|-----------|
| CONTENTS | 2 |
| 1. GENERAL INFORMATION ABOUT EUT | 4 |
| 1.1 Client Information | 4 |
| 1.2 General Description of EUT (Equipment Under Test) | 4 |
| 1.3 Block Diagram Showing the Configuration of System Tested..... | 5 |
| 1.4 Description of Support Units..... | 6 |
| 1.5 Description of Test Mode | 6 |
| 1.6 Description of Test Software Setting..... | 7 |
| 1.7 Measurement Uncertainty..... | 7 |
| 1.8 Test Facility..... | 8 |
| 2. TEST SUMMARY..... | 9 |
| 3. TEST SOFTWARE | 9 |
| 4. TEST EQUIPMENT AND TEST SITE | 10 |
| 5. RADIATED AND CONDUCTED UNWANTED EMISSIONS..... | 11 |
| 6.1 Test Standard and Limit | 11 |
| 6.2 Test Setup..... | 12 |
| 6.3 Test Procedure | 13 |
| 6.4 Deviation From Test Standard..... | 14 |
| 6.5 EUT Operating Mode | 14 |
| 6.6 Test Data..... | 14 |
| 6. ANTENNA REQUIREMENT | 15 |
| 11.1 Test Standard and Limit | 15 |
| 11.2 Deviation From Test Standard | 15 |
| 11.3 Antenna Connected Construction..... | 15 |
| 11.4 Test Data | 15 |
| ATTACHMENT A--UNWANTED EMISSIONS DATA | 16 |



Revision History



1. General Information about EUT

1.1 Client Information

| | | |
|---------------------|---|---|
| Applicant | : | Lightcomm Technology Co., Ltd. |
| Address | : | UNIT 1306 13/F ARION COMMERCIAL CENTRE,2-12 QUEEN'S ROAD WEST,SHEUNG WAN HK,CHINA |
| Manufacturer | : | Huizhou Hengdu Electronics Co., Ltd |
| Address | : | No.8 Huitai Road, Huinan High-tech Industrial Park, Huiao Avenue, Huizhou, Guangdong.China. |

1.2 General Description of EUT (Equipment Under Test)


| | | |
|--|--------------------------|--|
| EUT Name | : | 10.1" Tablet |
| Models No. | : | DL1050, MID1058-AD |
| Model Different | : | All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name, brand name and product name. |
| Product Description | Operation Frequency: | Bluetooth (BLE): 2402MHz~2480MHz |
| | Number of Channel: | Bluetooth (BLE): 40 channels |
| | Antenna Gain: | 0.23dBi FPC Antenna |
| | Modulation Type: | GFSK |
| | Bit Rate of Transmitter: | 1Mbps&2Mbps |
| Power Rating | : | AC Adapter (Model: TEKA-UCA20US) Input: 100-240V~50/60Hz, 0.35A Output: 5.0V--2.0A DC 3.8V 6000mAh Rechargeable Li-ion battery |
| Software Version | : | Android 14 |
| Hardware Version | : | BND-C30 V1.1 |
| Remark: The adapter provided by the TOBY ,the antenna gain from the manufacturer, the verified for the RF conduction test provided by TOBY test lab.The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible. | | |



(1) Channel List:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 00 | 2402 | 14 | 2430 | 28 | 2458 |
| 01 | 2404 | 15 | 2432 | 29 | 2460 |
| 02 | 2406 | 16 | 2434 | 30 | 2462 |
| 03 | 2408 | 17 | 2436 | 31 | 2464 |
| 04 | 2410 | 18 | 2438 | 32 | 2466 |
| 05 | 2412 | 19 | 2440 | 33 | 2468 |
| 06 | 2414 | 20 | 2442 | 34 | 2470 |
| 07 | 2416 | 21 | 2444 | 35 | 2472 |
| 08 | 2418 | 22 | 2446 | 36 | 2474 |
| 09 | 2420 | 23 | 2448 | 37 | 2476 |
| 10 | 2422 | 24 | 2450 | 38 | 2478 |
| 11 | 2424 | 25 | 2452 | 39 | 2480 |
| 12 | 2426 | 26 | 2454 | | |
| 13 | 2428 | 27 | 2456 | | |

1.3 Block Diagram Showing the Configuration of System Tested



1.4 Description of Support Units

| Equipment Information | | | | |
|-----------------------|-----------|------------------|--------------|----------|
| Name | Model | S/N | Manufacturer | Used “√” |
| Notebook | HYLR-WFQ9 | AAMFPM1418000165 | honour | √ |

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

| For Conducted Test(AC POWER) | |
|------------------------------------|----------------------------------|
| Final Test Mode | Description |
| Mode 1 | TX Mode |
| For Radiated and RF Conducted Test | |
| Final Test Mode | Description |
| Mode 2 | TX Mode |
| Mode 3 | TX 1Mbps Mode (Channel 00/19/39) |
| Mode 4 | TX 2Mbps Mode (Channel 00/19/39) |

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:
BLE Mode: GFSK Modulation Transmitting mode.
- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a Mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.



1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

| Test Software Version | adb command | | |
|-----------------------|-------------|---------|----------|
| Frequency | 2402 MHz | 2440MHz | 2480 MHz |
| BLE 1M | DEF | DEF | DEF |
| BLE 2M | DEF | DEF | DEF |

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| Test Item | Parameters | Expanded Uncertainty (U_{Lab}) |
|--------------------|---|------------------------------------|
| Conducted Emission | Level Accuracy: 9kHz~150kHz 150kHz to 30MHz | ± 3.50 dB ± 3.10 dB |
| Radiated Emission | Level Accuracy: 9kHz to 30 MHz | ± 4.60 dB |
| Radiated Emission | Level Accuracy: 30MHz to 1000 MHz | ± 4.50 dB |
| Radiated Emission | Level Accuracy: Above 1000MHz | ± 4.20 dB |



1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



2. Test Summary

| Standard Section | Test Item | Test Sample(s) | Judgment | Remark |
|------------------------|-------------------------------|------------------------|----------|------------------------|
| FCC 15.207(a) | Conducted Emission | HC-C-202407-0263-01-02 | N/A | N/A _(note2) |
| FCC 15.209 & 15.247(d) | Radiated Unwanted Emissions | HC-C-202407-0263-01-02 | PASS | N/A |
| FCC 15.203 | Antenna Requirement | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| FCC 15.247(a)(2) | 6dB Bandwidth | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| / | 99% Occupied bandwidth | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| FCC 15.247(b)(3) | Peak Output Power and E.I.R.P | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| FCC 15.247(e) | Power Spectral Density | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| FCC 15.247(d) | Band Edge Measurements | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| FCC 15.207(a) | Conducted Unwanted Emissions | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| FCC 15.247(d) | Emissions in Restricted Bands | HC-C-202407-0263-01-01 | N/A | N/A _(note2) |
| / | On Time and Duty Cycle | HC-C-202407-0263-01-01 | / | N/A _(note2) |

Note:

- (1) N/A is an abbreviation for Not Applicable.
- (2) This report is Class II change report for the original equipment have changed, the transmitter module itself has not changed. More information about the test data please refer to the original test report.
- (3) As there is no change regard RF transmitter portion and Antenna assembly, the change will not have effect on Radiated emission below 1GHz by judging for experience, thus testing is performed up to 1GHz only.

3. Test Software

| Test Item | Test Software | Manufacturer | Version No. |
|--------------------------|---------------|--------------|-------------|
| Conducted Emission | EZ-EMC | EZ | CDI-03A2 |
| Radiation Emission | EZ-EMC | EZ | FA-03A2RE |
| Radiation Emission | EZ-EMC | EZ | FA-03A2RE+ |
| RF Conducted Measurement | MTS-8310 | MWRFtest | V2.0.0.0 |
| RF Test System | JS1120 | Tonscend | V3.2.22 |



4. Test Equipment and Test Site

| Test Site | | | | |
|-------------|------------------------|--------------|-------------------|------|
| No. | Test Site | Manufacturer | Specification | Used |
| TB-EMCSR001 | Shielding Chamber #1 | YIHENG | 7.5*4.0*3.0 (m) | X |
| TB-EMCSR002 | Shielding Chamber #2 | YIHENG | 8.0*4.0*3.0 (m) | X |
| TB-EMCCA001 | 3m Anechoic Chamber #A | ETS | 9.0*6.0*6.0 (m) | X |
| TB-EMCCB002 | 3m Anechoic Chamber #B | YIHENG | 9.0*6.0*6.0 (m) | ✓ |

| Conducted Emission Test | | | | | |
|-------------------------|--|-------------|------------|---------------|---------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Due Date |
| EMI Test Receiver | Rohde & Schwarz | ESCI | 100321 | Jun. 17, 2024 | Jun. 16, 2025 |
| RF Switching Unit | Compliance Direction Systems Inc | RSU-A4 | 34403 | Jun. 17, 2024 | Jun. 16, 2025 |
| AMN | SCHWARZBECK | NNBL 8226-2 | 8226-2/164 | Jun. 17, 2024 | Jun. 16, 2025 |
| LISN | Rohde & Schwarz | ENV216 | 101131 | Jun. 17, 2024 | Jun. 16, 2025 |

| Radiation Emission Test(B Site) | | | | | |
|---------------------------------|-----------------|--------------------|-------------|---------------|---------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Due Date |
| Spectrum Analyzer | Agilent | N9020A | MY49100060 | Aug. 30, 2023 | Aug. 29, 2024 |
| Spectrum Analyzer | Rohde & Schwarz | FSV40-N | 102197 | Jun. 17, 2024 | Jun. 16, 2025 |
| EMI Test Receiver | Rohde & Schwarz | ESU-8 | 100472/008 | Feb. 23, 2024 | Feb. 22, 2025 |
| Bilog Antenna | SCHWARZBECK | VULB 9168 | 1225 | Nov. 13, 2023 | Nov. 12, 2025 |
| Horn Antenna | SCHWARZBECK | BBHA 9120 D | 2463 | Jun. 14, 2024 | Jun. 13, 2026 |
| Horn Antenna | SCHWARZBECK | BBHA 9170 | 1118 | Feb. 27, 2024 | Feb. 26, 2026 |
| Loop Antenna | SCHWARZBECK | FMZB 1519 B | 1519B-059 | Jun. 14, 2024 | Jun. 13, 2026 |
| HF Amplifier | Tonscend | TAP9E6343 | AP21C806117 | Aug. 30, 2023 | Aug. 29, 2024 |
| HF Amplifier | Tonscend | TAP051845 | AP21C806141 | Aug. 30, 2023 | Aug. 29, 2024 |
| HF Amplifier | Tonscend | TAP0184050 | AP21C806129 | Aug. 30, 2023 | Aug. 29, 2024 |
| Highpass Filter | CD | HPM-6.4/18G | --- | N/A | N/A |
| Highpass Filter | CD | HPM-2.8/18G | --- | N/A | N/A |
| Highpass Filter | XINBO | XBLBQ-HTA67(8-25G) | 22052702-1 | N/A | N/A |

| Antenna Conducted Emission | | | | | |
|----------------------------------|--------------------|-------------------|---------------|---------------|---------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Due Date |
| Spectrum Analyzer | Rohde & Schwarz | FSV40-N | 102197 | Jun. 17, 2024 | Jun. 16, 2025 |
| MXA Signal Analyzer | KEYSIGHT | N9020B | MY60110172 | Aug. 30, 2023 | Aug. 29, 2024 |
| MXA Signal Analyzer | Agilent | N9020A | MY47380425 | Aug. 30, 2023 | Aug. 29, 2024 |
| RF Power Sensor | DARE!! Instruments | RadiPowerRPR3006W | 17I00015SNO26 | Aug. 30, 2023 | Aug. 29, 2024 |
| | DARE!! Instruments | RadiPowerRPR3006W | 17I00015SNO29 | Aug. 30, 2023 | Aug. 29, 2024 |
| | DARE!! Instruments | RadiPowerRPR3006W | 17I00015SNO31 | Aug. 30, 2023 | Aug. 29, 2024 |
| | DARE!! Instruments | RadiPowerRPR3006W | 17I00015SNO33 | Aug. 30, 2023 | Aug. 29, 2024 |
| Temperature and Humidity Chamber | ZhengHang | ZH-QTH-1500 | ZH2107264 | Jun. 17, 2024 | Jun. 16, 2025 |



5. Radiated and Conducted Unwanted Emissions

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209 & FCC Part 15.247(d)

5.1.2 Test Limit

| General field strength limits at frequencies Below 30MHz | | | |
|--|-------------------------------------|------------------------------------|-------------------------------|
| Frequency (MHz) | Field Strength ($\mu\text{A/m}$)* | Field Strength (microvolt/meter)** | Measurement Distance (meters) |
| 0.009~0.490 | 6.37/F (F in kHz) | 2400/F(KHz) | 300 |
| 0.490~1.705 | 63.7/F (F in kHz) | 24000/F(KHz) | 30 |
| 1.705~30.0 | 0.08 | 30 | 30 |

Note: 1, The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.
 2, *is for RSS Standard, **is for FCC Standard.

| General field strength limits at frequencies above 30 MHz | | |
|---|--|-------------------------------|
| Frequency (MHz) | Field strength ($\mu\text{V/m}$ at 3 m) | Measurement Distance (meters) |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

| General field strength limits at frequencies Above 1000MHz | | |
|--|-------------------------|---------|
| Frequency (MHz) | Distance of 3m (dBuV/m) | |
| | Peak | Average |
| Above 1000 | 74 | 54 |


Note:
 (1) The tighter limit applies at the band edges.
 (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.




5.2 Test Setup


Radiated measurement



Below 30MHz Test Setup




Below 1000MHz Test Setup



Above 1GHz Test Setup



Conducted measurement



5.3 Test Procedure

---Radiated measurement

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- Testing frequency range 30MHz-1GHz the measuring instrument use $VBW=120$ kHz with Quasi-peak detection. Testing frequency range 9KHz-150Hz the measuring instrument use $VBW=200$ Hz with Quasi-peak detection. Testing frequency range 9KHz-30MHz the measuring instrument use $VBW=9$ kHz with Quasi-peak detection.
- Testing frequency range above 1GHz the measuring instrument use $RBW=1$ MHz and $VBW=3$ MHz with Peak Detector for Peak Values, and use $RBW=1$ MHz and $VBW=10$ Hz with Peak Detector for Average Values.
- For the actual test configuration, please see the test setup photo.

--- Conducted measurement

● Reference level measurement

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the $RBW = 100$ kHz.
- d) Set the $VBW \geq [3 * RBW]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

● Emission level measurement

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the $RBW = 100$ kHz.
- c) Set the $VBW \geq [3 * RBW]$.
- d) Detector = peak.



- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

5.4 Deviation From Test Standard

No deviation

5.5 EUT Operating Mode

Please refer to the description of test mode.

5.6 Test Data

Radiated measurement please refer to the Attachment A inside test report.



6. Antenna Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.203

6.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2 Deviation From Test Standard

No deviation

6.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 0.23dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

6.4 Test Data

The EUT antenna is a FPC Antenna. It complies with the standard requirement.

| Antenna Type |
|--|
| <input checked="" type="checkbox"/> Permanent attached antenna |
| <input type="checkbox"/> Unique connector antenna |
| <input type="checkbox"/> Professional installation antenna |



Attachment A--Unwanted Emissions Data


---Radiated Unwanted Emissions

9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB Below the permissible value has no need to be reported.

30MHz~1GHz



| | | | | | | | | |
|--|------------------------------|--------------------------------------|----------------------|--------------------------------------|--------------------------------------|--------------------|-----------------|------------|
| Test Voltage: | AC 120V/60Hz | | | | | | | |
| Ant. Pol. | Vertical | | | | | | | |
| Test Mode: | Mode 1 | | | | | | | |
| Remark: | Only worse case is reported. | | | | | | | |
|  (RF)FCC 15C 3M Radiation Margin -6 dB | | | | | | | | |
| Temperature: 23.8 °C | | | | Humidity: 45 % | | | | |
| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | P/F |
| 1 | 40.7016 | 45.42 | -23.81 | 21.61 | 40.00 | -18.39 | peak | P |
| 2 * | 76.2442 | 53.54 | -26.98 | 26.56 | 40.00 | -13.44 | peak | P |
| 3 | 110.1816 | 48.97 | -24.82 | 24.15 | 43.50 | -19.35 | peak | P |
| 4 | 143.3260 | 48.19 | -21.85 | 26.34 | 43.50 | -17.16 | peak | P |
| 5 | 473.8346 | 45.62 | -16.82 | 28.80 | 46.00 | -17.20 | peak | P |
| 6 | 916.0686 | 38.21 | -7.30 | 30.91 | 46.00 | -15.09 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)
3. Margin (dB) = QuasiPeak (dB μ V/m) - Limit QPK(dB μ V/m)

-----END OF THE REPORT-----

