



FCC TEST REPORT

FCC ID: XMF-MID1110

On Behalf of

Lightcomm Technology Co., Ltd.

Tablet

Model No.: MID1110, MID1109, MID1057, MID1061, MID8601, MID106, M11
PRO, R11, R10 Pro, R10 XS

Prepared for : Lightcomm Technology Co., Ltd.
Address : UNIT 1306 13/F ARION COMMERCIAL CENTRE, 2-12 QUEEN'S
ROAD WEST, SHEUNG WAN HK

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2501041-C01-R02
Date of Receipt : January 7, 2025
Date of Test : January 10, 2025-January 17, 2025
Date of Report : February 5, 2025
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results.....	6
1.1. Description of Standards and Results	6
2. General Information.....	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Software test version and power setting information	9
2.7. Test Conditions	10
2.8. Test Facility.....	10
2.9. Measurement Uncertainty	10
2.10. Test Equipment List	11
3. Maximum Peak Output Power	12
3.1. Limit	12
3.2. Test Procedure	12
3.3. Test Setup.....	12
3.4. Test Result.....	12
4. Bandwidth	18
4.1. Limit	18
4.2. Test Procedure	18
4.3. Test Result.....	18
5. Carrier Frequency Separation	29
5.1. Limit	29
5.2. Test Procedure	29
5.3. Test Result.....	29
6. Number Of Hopping Channel	31
6.1. Limit	31
6.2. Test Procedure	31
6.3. Test Result.....	31
7. Dwell Time	33
7.1. Test limit.....	33
7.2. Test Procedure	33
7.3. Test Result.....	33
8. Out-of-band Emissions	43
8.1. Test Limits.....	43
8.2. Test Procedure	43
8.3. Test Setup.....	43
8.4. Test Results	43
9. Radiated Emissions.....	67
9.1. Limit	67
9.2. Block Diagram of Test setup.....	70

9.3. Test Procedure	71
9.4. Test Results	71
10. Band Edge Test.....	79
10.1. Block Diagram of Test Setup	79
10.2. Test Limit	79
10.3. Test Procedure	79
10.4. Test Results	80
11. Power Line Conducted Emissions.....	83
11.1. Block Diagram of Test Setup	83
11.2. Limit.....	83
11.3. Test Procedure	83
11.4. Test Results	84
12. Frequency stability	87
12.1. Test limit.....	87
12.2. Test Procedure	87
12.3. Test Setup.....	87
12.4. Test Results	87
13. Antenna Requirements	88
13.1. Limit.....	88
13.2. Result	88
14. Photos of test setup	89
15. Photos of EUT	89

TEST REPORT DECLARATION

Applicant : Lightcomm Technology Co., Ltd.
Address : UNIT 1306 13/F ARION COMMERCIAL CENTRE, 2-12 QUEEN'S ROAD WEST,
SHEUNG WAN HK
Manufacturer : Lightcomm Technology Co., Ltd.
Address : UNIT 1306 13/F ARION COMMERCIAL CENTRE, 2-12 QUEEN'S ROAD WEST,
SHEUNG WAN HK
EUT Description : Tablet
(A) Model No. : MID1110, MID1109, MID1057, MID1061, MID8601,
MID106, M11 PRO, R11, R10 Pro, R10 XS
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2013

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....: Felix Pang
Test Engineer 
Approved by (name + signature).....: Simple Guan
Project Manager 
Date of issue.....: February 5, 2025

Revision History

Revision	Issue Date	Revisions	Revised By
V0	February 5, 2025	Initial released Issue	Felix Pang



1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1), RSS-247(5.4 b), ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215, RSS-247(5.1 a), ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1), RSS-247(5.1 b), ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1), RSS-247(5.1 d),ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1), RSS-247(5.1 d),ANSI C63.10 :2013	P
Radiated Spurious Emission	FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-Gen(8.9), RSS-247(5.5), ANSI C63.10 :2013	P
Out-of-band Emissions	FCC Part 15: 15.247(d), RSS-Gen(8.9), RSS-247(5.5), ANSI C63.10 :2013	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), RSS-Gen(6.13), RSS-247(5.5), ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207, RSS-GEN(8.8),ANSI C63.10 :2013	P
Frequency stability	RSS-GEN(6.11)	N/A
Antenna requirement	FCC Part 15: 15.203, RSS-GEN(6.8)	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty. 5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.		

2. General Information

2.1. Description of Device (EUT)

Product Name : Tablet

Model No. : MID1110, MID1109, MID1057, MID1061, MID8601, MID106, M11 PRO, R11, R10 Pro, R10 XS

Diff : There is no difference except the name of the model. All tests are made with the MID1110 model.

Power supply : DC 5V/9V from adapter, DC 3.8V from battery.

Radio Technology : Bluetooth V5.0 EDR

Operation frequency : 2402-2480MHz

Channel No. : 79 channels

Channel Separation : 1MHz

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK

Antenna Type : Internal antenna, maximum gain is -1.89dBi.

PMN : N/A

HVIN : N/A

Software version : N/A

Hardware version/FVIN : N/A

Note : Antenna information is provided by applicant.
Testing lab is not responsible for the accuracy of the information.

2.2. Accessories of Device (EUT)


Accessories 1 : AC ADAPTER
 Manufacturer : GUANGDONG TEKA TECHNOLOGY CO., LTD
 Model : TEKA-SCC20US
 Rating : Input: 100-240V~50/60Hz 0.5A MAX
 Output: DC 5V/3A; 9V/2.22A;12V/1.67A

Accessories 2 : USB Cable
 Manufacturer : N/A
 Model : 1.0m

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	N/A	N/A	N/A	N/A
2	N/A	N/A	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

The test software used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK / Pi/4-DQPSK / 8DPSK Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK / Pi/4-DQPSK / 8DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK / Pi/4-DQPSK / 8DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480

2.6. Software test version and power setting information

Software testing version	Engineering mode.exe		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
GFSK, Pi/4-DQPSK, 8DPSK	CH0	2402	TX level is set as defaults value.
	CH39	2441	TX level is set as defaults value.
	CH78	2480	TX level is set as defaults value.



2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2024.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2024.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2024.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2024.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2024.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2024.12.18	1 Year
12	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.0 2-1111533-F z	/	2024.12.18	1 Year
13	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2024.12.18	1 Year
14	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2024.12.18	1 Year
15	Temp. & Humid Chamber	Auchno	9606	/	/	2024.12.18	1 Year
16	Regulated DC Power Supply	Xinouhua	ADC120V10 A	2022112516 38		2024.12.18	1 Year
For Test Software Information							
Item	Software Name	Manufacturer			Version		
RE	EZ_EMC	Farad			PSI-3A1		
CE	EZ_EMC	Farad			PSI-3A1		
RF	RTS	TACHOY			V1.0.0		

3. Maximum Peak Output Power

3.1. Limit


Please refer FCC part 15.247 & RSS-247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup




3.4. Test Result


Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1-DH1	2402.00	3.08	2.03	1000	Pass
NVNT	ANT1	1-DH1	2441.00	3.95	2.48	1000	Pass
NVNT	ANT1	1-DH1	2480.00	4.07	2.55	1000	Pass
NVNT	ANT1	2-DH1	2402.00	2.13	1.63	125	Pass
NVNT	ANT1	2-DH1	2441.00	2.76	1.89	125	Pass
NVNT	ANT1	2-DH1	2480.00	3.03	2.01	125	Pass
NVNT	ANT1	3-DH1	2402.00	2.12	1.63	125	Pass
NVNT	ANT1	3-DH1	2441.00	3.00	1.99	125	Pass
NVNT	ANT1	3-DH1	2480.00	3.21	2.09	125	Pass

Condition	Antenna	Rate	Frequency (MHz)	Dutycycle(%)	Duty_factor
NVNT	ANT1	1-DH1	2402.00	30.65	5.14
NVNT	ANT1	1-DH1	2441.00	30.65	5.14
NVNT	ANT1	1-DH1	2480.00	31.75	4.98
NVNT	ANT1	2-DH1	2402.00	30.16	5.21
NVNT	ANT1	2-DH1	2441.00	30.65	5.14
NVNT	ANT1	2-DH1	2480.00	31.75	4.98
NVNT	ANT1	3-DH1	2402.00	32.26	4.91
NVNT	ANT1	3-DH1	2441.00	30.65	5.14
NVNT	ANT1	3-DH1	2480.00	31.75	4.98


Duty_Cycle_NVNT_ANT1_1-DH1_2402




Duty_Cycle_NVNT_ANT1_1-DH1_2441




Duty_Cycle_NVNT_ANT1_1-DH1_2480




Duty_Cycle_NVNT_ANT1_2-DH1_2402




Duty_Cycle_NVNT_ANT1_2-DH1_2441




Duty_Cycle_NVNT_ANT1_2-DH1_2480




Duty_Cycle_NVNT_ANT1_3-DH1_2402



Duty_Cycle_NVNT_ANT1_3-DH1_2441



Duty_Cycle_NVNT_ANT1_3-DH1_2480



4. Bandwidth

4.1. Limit


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in RSS-GEN, FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


4.2. Test Procedure


The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	if larger than CFS
NVNT	ANT1	1-DH1	2402.00	0.827	No
NVNT	ANT1	1-DH1	2441.00	0.829	No
NVNT	ANT1	1-DH1	2480.00	0.827	No
NVNT	ANT1	2-DH1	2402.00	1.109	Yes
NVNT	ANT1	2-DH1	2441.00	1.110	Yes
NVNT	ANT1	2-DH1	2480.00	1.109	Yes
NVNT	ANT1	3-DH1	2402.00	1.159	Yes
NVNT	ANT1	3-DH1	2441.00	1.160	Yes
NVNT	ANT1	3-DH1	2480.00	1.158	Yes

-20dB_Bandwidth_NVNT_ANT1_1-DH1_2402_00**-20dB_Bandwidth_NVNT_ANT1_1-DH1_2441_00**

-20dB_Bandwidth_NVNT_ANT1_1-DH1_2480_00**-20dB_Bandwidth_NVNT_ANT1_2-DH1_2402_00**

-20dB_Bandwidth_NVNT_ANT1_2-DH1_2441_00**-20dB_Bandwidth_NVNT_ANT1_2-DH1_2480_00**

-20dB_Bandwidth_NVNT_ANT1_3-DH1_2402_00**-20dB_Bandwidth_NVNT_ANT1_3-DH1_2441_00**


-20dB_Bandwidth_NVNT_ANT1_3-DH1_2480_00

Condition	Antenna	Modulation	Frequency (MHz)	99%BW(MHz)
NVNT	ANT1	1-DH1	2402.00	0.861
NVNT	ANT1	1-DH1	2441.00	0.861
NVNT	ANT1	1-DH1	2480.00	0.862
NVNT	ANT1	2-DH1	2402.00	1.047
NVNT	ANT1	2-DH1	2441.00	1.048
NVNT	ANT1	2-DH1	2480.00	1.048
NVNT	ANT1	3-DH1	2402.00	1.084
NVNT	ANT1	3-DH1	2441.00	1.081
NVNT	ANT1	3-DH1	2480.00	1.080

99%_Occupied_Bandwidth_NVNT_ANT1_1-DH1_2402_00



99%_Occupied_Bandwidth_NVNT_ANT1_1-DH1_2441_00



99%_Occupied_Bandwidth_NVNT_ANT1_1-DH1_2480_00



99%_Occupied_Bandwidth_NVNT_ANT1_2-DH1_2402_00



99%_Occupied_Bandwidth_NVNT_ANT1_2-DH1_2441_00



99%_Occupied_Bandwidth_NVNT_ANT1_2-DH1_2480_00



99%_Occupied_Bandwidth_NVNT_ANT1_3-DH1_2402_00



99%_Occupied_Bandwidth_NVNT_ANT1_3-DH1_2441_00



99%_Occupied_Bandwidth_NVNT_ANT1_3-DH1_2480_00



5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


Please refer FCC part 15.247 & RSS-247.

5.2. Test Procedure


The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW.

5.3. Test Result

Condition	Antenna	Modulation	Frequency(MHz)	Hopping NO.0 (MHz)	Hopping NO.1 (MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	1-DH1	2441.00	2440.849	2441.845	1.00	0.829	Pass
NVNT	ANT1	2-DH1	2441.00	2441.488	2442.496	1.01	0.740	Pass
NVNT	ANT1	3-DH1	2441.00	2440.840	2441.848	1.01	0.773	Pass



Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_2-DH1_Hopping



Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_3-DH1_Hopping



6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Please refer FCC part 15.247 & RSS-247.


6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.


6.3. Test Result

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	1-DH1	79	15	Pass
NVNT	ANT1	2-DH1	79	15	Pass
NVNT	ANT1	3-DH1	79	15	Pass


Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_1-DH1_Hopping



Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_2-DH1_Hopping



Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_3-DH1_Hopping



7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247 & RSS-247.

Frequency hopping systems operating in the 2400MHz-2483.5MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.2.6. The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

7.2.7. Dwell Time=Pulse Time* Hops Number

7.3. Test Result

Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	1-DH1	0.380	320.00	121.600	0.40	Pass
NVNT	ANT1	2-DH1	0.390	320.00	124.800	0.40	Pass
NVNT	ANT1	3-DH1	0.380	320.00	121.600	0.40	Pass
NVNT	ANT1	1-DH3	1.650	166.00	273.900	0.40	Pass
NVNT	ANT1	1-DH5	2.890	114.00	329.460	0.40	Pass
NVNT	ANT1	2-DH3	1.640	159.00	260.760	0.40	Pass
NVNT	ANT1	2-DH5	2.890	107.00	309.230	0.40	Pass
NVNT	ANT1	3-DH3	1.640	164.00	268.960	0.40	Pass
NVNT	ANT1	3-DH5	2.900	111.00	321.900	0.40	Pass

Dwell_Time_(Hopping)_NVNT_ANT1_1-DH1_2441_00_One_Burst_Time

Keysight Spectrum Analyzer - Swept SA

Center Freq 2.441000000 GHz

Trig Delay-500.0 μ s #Avg Type: Log-Pwr

PNO: Fast IFGain:Low Trig: Video Atten: 30 dB

Ref Offset 4.08 dB Ref 23.16 dBm

AMkr1 380.0 μ s -47.80 dBm

Center 2.441000000 GHz Span 0 Hz

Res BW 1.0 MHz #VBW 1.0 MHz Sweep 10.00 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ 2	1	t	(Δ)	380.0 μ s	(Δ)	-47.80 dB	
2	F	1	t		480.0 μ s		3.50 dBm	
3								
4								
5								
6								
7								
8								
9								
10								
11								

Frequency

Auto Tune

Center Freq 2.441000000 GHz

Start Freq 2.441000000 GHz

Stop Freq 2.441000000 GHz

CF Step 1.000000 MHz

Auto

Freq Offset 0 Hz

Scale Type Log Lin

MSG STATUS

KeySight Spectrum Analyzer - Swept SA

Center Freq 2.441000000 GHz

Ref Offset 4.08 dB
Ref 24.08 dBm

10 dB/div
Log

14.1
4.08
-5.92
-15.9
-25.9
-35.9
-45.9
-55.9
-65.9

Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 1.0 MHz
Sweep 31.60 s (30001 pts)

Span 0 Hz

Auto Tune

Center Freq
2.441000000 GHz

Start Freq
2.441000000 GHz

Stop Freq
2.441000000 GHz

CF Step
1.000000 MHz
Man

Auto

Freq Offset
0 Hz

Scale Type
Log

MSG | STATUS

Dwell_Time_(Hopping)_NVNT_ANT1_2-DH1_2441_00_One_Burst_Time

Keysight Spectrum Analyzer - Swept SA

Center Freq 2.441000000 GHz

Trig Delay: 500.0 μ s #Avg Type: Log-Pwr

PNO: Fast IFGain: Low Trig: Video Atten: 24 dB

03:42:35 PM Jan 16, 2025

Ref Offset 4.08 dB Ref 17.16 dBm

Δ Mkr1 390.0 μ s -47.02 dB

Center 2.441000000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 10.00 ms (1001 pts) Span 0 Hz

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ 2	1	t	(Δ)	390.0 μ s	(Δ)	-47.02 dB	
2	F	1	t		480.0 μ s		2.25 dBm	
3								
4								
5								
6								
7								
8								
9								
10								
11								

MSG STATUS

Frequency

Auto Tune

Center Freq 2.441000000 GHz

Start Freq 2.441000000 GHz

Stop Freq 2.441000000 GHz

CF Step 1.000000 MHz

Auto Man

Freq Offset 0 Hz

Scale Type Log Lin

Dwell_Time_(Hopping)_NVNT_ANT1_2-DH1_2441_00_Accumulated

Keysight Spectrum Analyzer - Swept SA

Center Freq 2.441000000 GHz

Trig: Free Run

PNO: Fast IFGain: Low Atten: 30 dB

03:43:15 PM Jan 16, 2025

Ref Offset 4.08 dB Ref 24.08 dBm

Mkr1 2.460 s 2.67 dBm

Center 2.441000000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 31.60 s (30001 pts) Span 0 Hz

MSG STATUS

Frequency

Auto Tune

Center Freq 2.441000000 GHz

Start Freq 2.441000000 GHz

Stop Freq 2.441000000 GHz

CF Step 1.000000 MHz

Auto Man

Freq Offset 0 Hz

Scale Type Log Lin

[illegible]

Keysight Spectrum Analyzer - Swept SA

RL RF 50 Ω AC SENSE:PULSE 04:52:37 PM Jan 16, 2025

Center Freq 2.441000000 GHz #Avg Type: Log-Pwr

PNO: Fast → Trg: Free Run IFGain: Low Atten: 30 dB

TRACE 1 2 3 4 5 6 TYPE W W W W W W W W DET P N N N N N N

Ref Offset 4.08 dB Ref 24.08 dBm

10 dB/div Log

Mkr1 13.10 s 3.97 dBm

Center Freq 2.441000000 GHz Res BW 1.0 MHz Span 0 Hz Sweep 31.60 s (30001 pts)

MSG STATUS

Frequency Auto Tune Center Freq 2.441000000 GHz Start Freq 2.441000000 GHz Stop Freq 2.441000000 GHz CF Step 1.000000 MHz Man Auto Freq Offset 0 Hz Scale Type Log Lin

Keysight Spectrum Analyzer - Swept SA

04:32:35 PM Jan 16, 2025

Center Freq 2.441000000 GHz

Ref Offset 4.08 dB
Ref 23.16 dBm

10 dB/div
Log

Δ Mkr1 1.650 ms
-51.31 dB

Trig Delay: 500.0 μ s
Trig: Video
Atten: 30 dB

#Avg Type: Log-Pwr

Trace 1 2 3 4 5 6
Type W W W W W W W W
Det 2 N N N N N N

Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 1.0 MHz
Sweep 10.00 ms (1001 pts)
Span 0 Hz

The screenshot shows a spectrum analyzer display with a signal at 2.441 GHz. A yellow marker labeled 'X2' is at the top left. A green marker labeled '1Δ2' is at the bottom center, indicating a level of -51.31 dB. The signal is noisy and spans a bandwidth of 1.0 MHz. The display is set to a 10 dB/div scale and a log frequency scale.

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ 2	1	t	(Δ)	1.650 ms	(Δ)	-51.31 dB	
2	F	1	t	(Δ)	480.0 μ s		1.82 dBm	
3								
4								
5								
6								
7								
8								
9								
10								
11								

MSG

STATUS

Frequency

Auto Tune

Center Freq 2.441000000 GHz

Start Freq 2.441000000 GHz

Stop Freq 2.441000000 GHz

CF Step 1.00000 MHz

Auto

Freq Offset 0 Hz

Scale Type

Log

Keysight Spectrum Analyzer - Swept SA

RL RF 50 Ω AC SENSE:PULSE 04:33:16 PM Jan 16, 2025

Center Freq 2.441000000 GHz #Avg Type: Log-Pwr

PNO: Fast → Trig: Free Run IFGain: Low Atten: 30 dB

TRACE 1 2 3 4 5 6 TYPE W W W W W W W W DET P N N N N N N


Ref Offset 4.08 dB Mkr1 30.88 s
Ref 24.08 dBm 3.71 dBm

10 dB/div Log


Center 2.441000000 GHz Span 0 Hz
Res BW 1.0 MHz #VBW 1.0 MHz Sweep 31.60 s (30001 pts)

Frequency Auto Tune Center Freq 2.441000000 GHz Start Freq 2.441000000 GHz Stop Freq 2.441000000 GHz CF Step 1.000000 MHz Mar Auto Freq Offset 0 Hz Scale Type Lin Log

Dwell_Time_(Hopping)_NVNT_ANT1_1-DH5_2441_00_One_Burst_Time



Dwell_Time_(Hopping)_NVNT_ANT1_1-DH5_2441_00_Accumulated



Dwell_Time_(Hopping)_NVNT_ANT1_2-DH3_2441_00_One_Burst_Time

Center Freq 2.441000000 GHz
PNO: Fast IFGain:Low Trig Delay-500.0 μ s #Avg Type: Log-Pwr
Trig: Video Atten: 24 dB
Ref Offset 4.08 dB
Ref 17.16 dBm
 Δ Mkr1 1.640 ms
-47.94 dBm

Center 2.441000000 GHz
Res BW 1.0 MHz #VBW 1.0 MHz Sweep 10.00 ms (1001 pts) Span 0 Hz


MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ 2	1	t	(Δ)	1.640 ms	(Δ)	-47.94 dB	
2	F	1	t		480.0 μ s		2.55 dBm	

Dwell_Time_(Hopping)_NVNT_ANT1_2-DH3_2441_00_Accumulated


Center Freq 2.441000000 GHz
PNO: Fast IFGain:Low Trig: Free Run #Avg Type: Log-Pwr
Trig: Free Run Atten: 30 dB
Ref Offset 4.08 dB
Ref 24.08 dBm
Mkr1 29.56 s
2.95 dBm

Center 2.441000000 GHz
Res BW 1.0 MHz #VBW 1.0 MHz Sweep 31.60 s (30001 pts) Span 0 Hz

Dwell_Time_(Hopping)_NVNT_ANT1_2-DH5_2441_00_One_Burst_Time



Dwell_Time_(Hopping)_NVNT_ANT1_2-DH5_2441_00_Accumulated



Keysight Spectrum Analyzer - Sweep SA

RL RF 50 Ω AC SENSE:PULSE 04:40:44 PM Jan 16, 2025

Center Freq 2.441000000 GHz PNO: Fast Trig Delay: 500.0 μ s #Avg Type: Log-Pwr TRIG: Video Atten: 24 dB TRACE 1 2 3 4 5 6 TYPE W W W W W W W W DET P N N N N N N

Ref Offset 4.08 dB Ref 17.16 dBm Δ Mkr1 1.640 ms -46.66 dB

10 dB/div Log

Center 2.441000000 GHz Span 0 Hz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 10.00 ms (1001 pts)

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ 2	1	t	(Δ)	1.640 ms	(Δ)	-46.66 dB	
2	F	1	t		480.0 μ s		2.44 dBm	
3								
4								
5								
6								
7								
8								
9								
10								
11								

MSG STATUS

Frequency Auto Tune Center Freq 2.441000000 GHz Start Freq 2.441000000 GHz Stop Freq 2.441000000 GHz CF Step 1.000000 MHz Mar Freq Offset 0 Hz Scale Type Log Lin

The screenshot shows a Keysight Spectrum Analyzer interface. The main display area shows a noisy signal centered at 2.441 GHz. The vertical axis represents power in dBm, ranging from -65.9 to 10 dBm. The horizontal axis represents frequency in GHz, ranging from 2.440 GHz to 2.442 GHz. A green marker labeled 'Mkr1' is positioned at 27.04 MHz offset with a power of 2.88 dBm. The interface includes several control panels: a top panel with settings like 'Center Freq 2.441000000 GHz', 'PNO: Fast', 'Trig: Free Run', and '#Avg Type: Log-Pwr'; a right panel with 'Frequency', 'Auto Tune', 'Center Freq', 'Start Freq', 'Stop Freq', 'CF Step', 'Freq Offset', and 'Scale Type'; and a bottom panel with 'Center 2.441000000 GHz', 'Res BW 1.0 MHz', '#VBW 1.0 MHz', 'Span 0 Hz', and 'Sweep 31.60 s (30001 pts)'. The signal is characterized by a dense forest of vertical spikes, indicating a highly noisy or modulated signal.

[illegible]

Keysight Spectrum Analyzer - Swept SA

Center Freq 2.441000000 GHz

Ref Offset 4.08 dB
Ref 24.08 dBm

Mkr1 11.13 s
2.88 dBm

10 dB/div
Log

14.1
4.08
-5.92
-15.9
-26.9
-35.9
-45.9
-55.9
-65.9

Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 1.0 MHz
Sweep 31.60 s (30001 pts)

Span 0 Hz

Frequency

Auto Tune

Center Freq
2.441000000 GHz

Start Freq
2.441000000 GHz

Stop Freq
2.441000000 GHz

CF Step
1.000000 MHz
Auto Man

Freq Offset
0 Hz

Scale Type
Log Lin

MSG STATUS

8. Out-of-band Emissions

8.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required. Please refer section RSS-GEN&15.247.

8.2. Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

8.3. Test Setup




8.4. Test Results

PASS.

The test results are listed in next pages.

Band Edge: Pass


Condition	Antenna	Modulation	TX Mode	Ref_level(dBm)	Bandedge MAX.Value	Limit	Result
NVNT	ANT1	1-DH1	2402.00	2.856	-57.523	-17.144	Pass
NVNT	ANT1	1-DH1	Hopping_LCH	3.655	-59.127	-16.345	Pass
NVNT	ANT1	1-DH1	2480.00	3.849	-57.607	-16.151	Pass
NVNT	ANT1	1-DH1	Hopping_HCH	3.426	-57.107	-16.574	Pass
NVNT	ANT1	2-DH1	2402.00	1.765	-60.687	-18.235	Pass
NVNT	ANT1	2-DH1	Hopping_LCH	2.509	-64.745	-17.491	Pass
NVNT	ANT1	2-DH1	2480.00	2.710	-62.860	-17.290	Pass
NVNT	ANT1	2-DH1	Hopping_HCH	6.716	-63.844	-13.284	Pass
NVNT	ANT1	3-DH1	2402.00	1.697	-61.105	-18.303	Pass
NVNT	ANT1	3-DH1	Hopping_LCH	2.541	-40.891	-17.459	Pass
NVNT	ANT1	3-DH1	2480.00	2.915	-63.410	-17.085	Pass
NVNT	ANT1	3-DH1	Hopping_HCH	5.585	-63.296	-14.415	Pass




1_Reference_Level_NVNT_ANT1_1-DH1_2402_00




2_Bandedge_NVNT_ANT1_1-DH1_2402_00



1_Reference_Level_Hopping_NVNT_ANT1_1-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_1-DH1_Hopping




1_Reference_Level_NVNT_ANT1_1-DH1_2480_00




2_Bandedge_NVNT_ANT1_1-DH1_2480_00




1_Reference_Level_Hopping_NVNT_ANT1_1-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_1-DH1_Hopping




1_Reference_Level_NVNT_ANT1_2-DH1_2402_00




2_Bandedge_NVNT_ANT1_2-DH1_2402_00



1_Reference_Level_Hopping_NVNT_ANT1_2-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_2-DH1_Hopping




1_Reference_Level_NVNT_ANT1_2-DH1_2480_00



2_Bandedge_NVNT_ANT1_2-DH1_2480_00



1_Reference_Level_Hopping_NVNT_ANT1_2-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_2-DH1_Hopping




1_Reference_Level_NVNT_ANT1_3-DH1_2402_00




2_Bandedge_NVNT_ANT1_3-DH1_2402_00



1_Reference_Level_Hopping_NVNT_ANT1_3-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_3-DH1_Hopping




1_Reference_Level_NVNT_ANT1_3-DH1_2480_00




2_Bandedge_NVNT_ANT1_3-DH1_2480_00



1_Reference_Level_Hopping_NVNT_ANT1_3-DH1_Hopping



2_Band_Edge_(Hopping)_NVNT_ANT1_3-DH1_Hopping



Conducted spurious emission: Pass


Condition	Antenna	Modulation	TX Mode	Ref_level(dBm)	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1-DH1	2402.00	2.856	-47.112	-17.144	Pass
NVNT	ANT1	1-DH1	2441.00	3.732	-47.093	-16.268	Pass
NVNT	ANT1	1-DH1	2480.00	3.849	-46.400	-16.151	Pass
NVNT	ANT1	2-DH1	2402.00	1.765	-49.322	-18.235	Pass
NVNT	ANT1	2-DH1	2441.00	2.432	-53.167	-17.568	Pass
NVNT	ANT1	2-DH1	2480.00	2.710	-52.597	-17.290	Pass
NVNT	ANT1	3-DH1	2402.00	1.697	-48.653	-18.303	Pass
NVNT	ANT1	3-DH1	2441.00	2.697	-53.538	-17.303	Pass
NVNT	ANT1	3-DH1	2480.00	2.915	-53.095	-17.085	Pass




1_Reference_Level_NVNT_ANT1_1-DH1_2402_00




2_Spurious_Emissions_NVNT_ANT1_1-DH1_2402_00



1_Reference_Level_NVNT_ANT1_1-DH1_2441_00




2_Spurious_Emissions_NVNT_ANT1_1-DH1_2441_00




1_Reference_Level_NVNT_ANT1_1-DH1_2480_00




2_Spurious_Emissions_NVNT_ANT1_1-DH1_2480_00



1_Reference_Level_NVNT_ANT1_2-DH1_2402_00




2_Spurious_Emissions_NVNT_ANT1_2-DH1_2402_00



1_Reference_Level_NVNT_ANT1_2-DH1_2441_00




2_Spurious_Emissions_NVNT_ANT1_2-DH1_2441_00



1_Reference_Level_NVNT_ANT1_2-DH1_2480_00




2_Spurious_Emissions_NVNT_ANT1_2-DH1_2480_00



1_Reference_Level_NVNT_ANT1_3-DH1_2402_00




2_Spurious_Emissions_NVNT_ANT1_3-DH1_2402_00



1_Reference_Level_NVNT_ANT1_3-DH1_2441_00




2_Spurious_Emissions_NVNT_ANT1_3-DH1_2441_00



1_Reference_Level_NVNT_ANT1_3-DH1_2480_00



2_Spurious_Emissions_NVNT_ANT1_3-DH1_2480_00



9. Radiated Emissions

9.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

RSS-GEN Restricted frequency band

Table 7 – Restricted frequency bands^{Note 1}

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5

8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSS.

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009-0.490	300	$2400/\text{F}(\text{KHz})$	/
0.490-1.705	30	$24000/\text{F}(\text{KHz})$	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: The peak limit is 20 dB higher than the average limit

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500


Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ($\mu\text{A}/\text{m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	$6.37/\text{F}$ (F in kHz)	300
490 - 1705 kHz	$63.7/\text{F}$ (F in kHz)	30
1.705 - 30 MHz	0.08	30


Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

9.2. Block Diagram of Test setup


9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



9.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

9.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

9.4. Test Results


We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.

Detailed information please see the following page.

From 9KHz to 30MHz:	
Test Date : 2025.01.10	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


From 30MHz to 1000MHz:	
Test Date : 2025.01.10	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz (DC 3.8V) was listed in this report.

Polarization: Vertical



Note: Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.7542	10.05	14.41	24.46	40.00	-15.54	QP
2	84.6277	14.99	9.58	24.57	40.00	-15.43	QP
3	150.6698	10.47	14.14	24.61	43.50	-18.89	QP
4	159.1552	10.49	14.33	24.82	43.50	-18.68	QP
5	364.0999	11.67	16.71	28.38	46.00	-17.62	QP
6 *	591.2328	10.72	22.65	33.37	46.00	-12.63	QP

Note: Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2024.12.10	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK, $\pi/4$ DQPSK, 8DPSK mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.


Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	60.00	-13.25	46.75	74.00	-27.25	Peak
2	4804	V	49.95	-13.25	36.70	54.00	-17.30	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	55.46	-13.25	42.21	74.00	-31.79	Peak
6	4804	H	46.69	-13.25	33.44	54.00	-20.56	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4882	V	60.10	-12.98	47.12	74.00	-26.88	Peak
2	4882	V	48.64	-12.98	35.66	54.00	-18.34	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	58.14	-12.98	45.16	74.00	-28.84	Peak
6	4882	H	46.04	-12.98	33.06	54.00	-20.94	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	57.54	-12.70	44.84	74.00	-29.16	Peak
2	4960	V	49.42	-12.70	36.72	54.00	-17.28	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	55.71	-12.70	43.01	74.00	-30.99	Peak
6	4960	H	48.50	-12.70	35.80	54.00	-18.20	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.							

Test Mode : $\pi/4$ DQPSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	56.51	-13.25	43.26	74.00	-30.74	Peak
2	4804	V	47.59	-13.25	34.34	54.00	-19.66	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	56.12	-13.25	42.87	74.00	-31.13	Peak
6	4804	H	47.80	-13.25	34.55	54.00	-19.45	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : $\pi/4$ DQPSK TX Mid								
1	4882	V	60.11	-12.98	47.13	74.00	-26.87	Peak
2	4882	V	48.60	-12.98	35.62	54.00	-18.38	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	56.01	-12.98	43.03	74.00	-30.97	Peak
6	4882	H	47.03	-12.98	34.05	54.00	-19.95	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : $\pi/4$ DQPSK TX High								
1	4960	V	59.15	-12.70	46.45	74.00	-27.55	Peak
2	4960	V	46.76	-12.70	34.06	54.00	-19.94	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	58.12	-12.70	45.42	74.00	-28.58	Peak
6	4960	H	45.36	-12.70	32.66	54.00	-21.34	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.							

Test Mode : 8DPSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	58.51	-13.25	45.26	74.00	-28.74	Peak
2	4804	V	49.63	-13.25	36.38	54.00	-17.62	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	58.25	-13.25	45.00	74.00	-29.00	Peak
6	4804	H	44.77	-13.25	31.52	54.00	-22.48	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : 8DPSK TX Mid								
1	4882	V	58.87	-12.98	45.89	74.00	-28.11	Peak
2	4882	V	48.39	-12.98	35.41	54.00	-18.59	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	56.17	-12.98	43.19	74.00	-30.81	Peak
6	4882	H	47.67	-12.98	34.69	54.00	-19.31	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : 8D PSK TX High								
1	4960	V	57.77	-12.70	45.07	74.00	-28.93	Peak
2	4960	V	46.93	-12.70	34.23	54.00	-19.77	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	57.49	-12.70	44.79	74.00	-29.21	Peak
6	4960	H	46.98	-12.70	34.28	54.00	-19.72	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

10. Band Edge Test

10.1. Block Diagram of Test Setup



10.2. Test Limit

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Please refer section RSS-GEN&15.247.

10.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

10.4. Test Results

Test Date	: 2025.01.10	Temperature	: 26°C
Test Engineer	: Felix Pang	Humidity	: 54%
Test Results	: PASS		


Frequency Range : 2310MHz~2410MHz								
Test Mode : GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	61.02	-20.45	40.57	74.00	-33.43	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	62.74	-20.41	42.33	74.00	-31.67	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	60.17	-20.45	39.72	74.00	-34.28	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	62.22	-20.41	41.81	74.00	-32.19	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : GFSK TX 2480MHz								
1	2483.5	H	63.76	-20.15	43.61	74.00	-30.39	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	65.82	-20.15	45.67	74.00	-28.33	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : $\pi/4$ DQPSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	60.01	-20.45	39.56	74.00	-34.44	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	61.11	-20.41	40.70	74.00	-33.30	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	61.31	-20.45	40.86	74.00	-33.14	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	64.77	-20.41	44.36	74.00	-29.64	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : $\pi/4$ DQPSK TX 2480MHz								
1	2483.5	H	62.19	-20.15	42.04	74.00	-31.96	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	64.55	-20.15	44.40	74.00	-29.60	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : 8DPSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	60.65	-20.45	40.20	74.00	-33.80	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	63.66	-20.41	43.25	74.00	-30.75	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	63.16	-20.45	42.71	74.00	-31.29	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	63.34	-20.41	42.93	74.00	-31.07	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : 8DPSK TX 2480MHz								
1	2483.5	H	61.04	-20.15	40.89	74.00	-33.11	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	65.63	-20.15	45.48	74.00	-28.52	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

11. Power Line Conducted Emissions

11.1. Block Diagram of Test Setup



11.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.


11.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

11.4. Test Results

Test Date	: 2025.01.17	Temperature	: 24°C
Test Engineer	: Felix Pang	Humidity	: 56%
Test Mode	: GFSK mode		
Test Results	: PASS		
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out. 4. All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz (AC 120V/ 60Hz) was listed in this report.		


Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.4980	38.72	9.90	48.62	56.03	-7.41	QP	P
2 *	0.4980	28.80	9.90	38.70	46.03	-7.33	AVG	P
3	0.6419	33.05	9.57	42.62	56.00	-13.38	QP	P
4	0.6419	21.42	9.57	30.99	46.00	-15.01	AVG	P
5	0.9980	32.47	9.41	41.88	56.00	-14.12	QP	P
6	0.9980	21.37	9.41	30.78	46.00	-15.22	AVG	P
7	1.6900	32.26	9.40	41.66	56.00	-14.34	QP	P
8	1.6900	20.47	9.40	29.87	46.00	-16.13	AVG	P
9	2.4900	27.71	9.39	37.10	46.00	-8.90	AVG	P
10	2.4900	17.16	9.39	26.55	46.00	-19.45	AVG	P
11	12.9780	40.72	9.55	50.27	60.00	-9.73	QP	P
12	12.9780	24.93	9.55	34.48	50.00	-15.52	AVG	P

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1 *	0.4940	37.27	9.77	47.04	56.10	-9.06	QP	P
2	0.4940	25.20	9.77	34.97	46.10	-11.13	AVG	P
3	0.9940	32.59	9.52	42.11	56.00	-13.89	QP	P
4	0.9940	18.71	9.52	28.23	46.00	-17.77	AVG	P
5	1.4940	31.00	9.39	40.39	56.00	-15.61	QP	P
6	1.4940	19.76	9.39	29.15	46.00	-16.85	AVG	P
7	2.0220	30.36	9.27	39.63	56.00	-16.37	QP	P
8	2.0220	16.32	9.27	25.59	46.00	-20.41	AVG	P
9	3.7060	25.46	9.56	35.02	46.00	-10.98	AVG	P
10	3.7060	11.63	9.56	21.19	46.00	-24.81	AVG	P
11	12.5020	40.90	9.65	50.55	60.00	-9.45	QP	P
12	12.5020	22.14	9.65	31.79	50.00	-18.21	AVG	P

Note: Level = Reading + Factor Margin = Level - Limit

12.Frequency stability

12.1.Test limit


Please refer section RSS-Gen.

Regulation RSS-Gen If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation. In addition, its occupied bandwidth shall be entirely outside the restricted bands and the prohibited TV bands of 54-72 MHz, 76-88 MHz, 174-216 MHz, and 470-602 MHz, unless otherwise indicated.

12.2.Test Procedure

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.3.Test Setup



12.4.Test Results

Not Applicable.

13. Antenna Requirements

13.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2.Result

The EUT antenna is internal antenna. It complies with the standard requirement.



14.Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

15.Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----

