

Temperature:	23.5°C	Relative Humidity:	45%												
Test Voltage:	AC 120V/60Hz														
Test Mode:	802.11g Mode TX 2437 MHz														
Remark:	Only worse case is reported.														
Horizontal															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dB_{UV})</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1 *</td><td>2963.500</td><td>70.57</td><td>-19.65</td></tr><tr><td>2</td><td>4876.000</td><td>63.77</td><td>-14.35</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	1 *	2963.500	70.57	-19.65	2	4876.000	63.77	-14.35
No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)												
1 *	2963.500	70.57	-19.65												
2	4876.000	63.77	-14.35												
Vertical															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dB_{UV})</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1 *</td><td>4876.000</td><td>67.16</td><td>-14.35</td></tr><tr><td>2</td><td>5947.000</td><td>61.09</td><td>-13.21</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	1 *	4876.000	67.16	-14.35	2	5947.000	61.09	-13.21
No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)												
1 *	4876.000	67.16	-14.35												
2	5947.000	61.09	-13.21												
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _{UV} /m)= Corr. (dB/m)+ Read Level (dB _{UV}) 3. Margin (dB) = Peak/AVG (dB _{UV} /m)-Limit PK/AVG(dB _{UV} /m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value.															



Temperature:	23.5°C	Relative Humidity:	45%												
Test Voltage:	AC 120V/60Hz														
Test Mode:	802.11 g Mode TX 2462 MHz														
Remark:	Only worse case is reported.														
Horizontal															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1 *</td><td>2963.500</td><td>70.55</td><td>-19.65</td></tr><tr><td>2</td><td>4927.000</td><td>62.41</td><td>-14.12</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	1 *	2963.500	70.55	-19.65	2	4927.000	62.41	-14.12
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)												
1 *	2963.500	70.55	-19.65												
2	4927.000	62.41	-14.12												
Vertical															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1</td><td>4468.000</td><td>64.03</td><td>-16.15</td></tr><tr><td>2 *</td><td>4927.000</td><td>65.81</td><td>-14.12</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	1	4468.000	64.03	-16.15	2 *	4927.000	65.81	-14.12
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)												
1	4468.000	64.03	-16.15												
2 *	4927.000	65.81	-14.12												
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value.															



Temperature:	23.5°C	Relative Humidity:	45%												
Test Voltage:	AC 120V/60Hz														
Test Mode:	802.11 n20 Mode TX 2412 MHz														
Remark:	Only worse case is reported.														
Horizontal															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1 *</td><td>2963.500</td><td>70.50</td><td>-19.65</td></tr><tr><td>2</td><td>4825.000</td><td>59.65</td><td>-14.57</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	1 *	2963.500	70.50	-19.65	2	4825.000	59.65	-14.57
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)												
1 *	2963.500	70.50	-19.65												
2	4825.000	59.65	-14.57												
Vertical															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1</td><td>4468.000</td><td>64.84</td><td>-16.15</td></tr><tr><td>2 *</td><td>4825.000</td><td>65.26</td><td>-14.57</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	1	4468.000	64.84	-16.15	2 *	4825.000	65.26	-14.57
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)												
1	4468.000	64.84	-16.15												
2 *	4825.000	65.26	-14.57												
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value.															



Temperature:	23.5°C	Relative Humidity:	45%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	802.11 n20 Mode TX 2437 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	P/F
1 *	2963.500	70.89	-19.65	51.24	74.00	-22.76	peak	P
2	4876.000	63.14	-14.35	48.79	74.00	-25.21	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	P/F
1 *	2963.500	71.05	-19.65	51.40	74.00	-22.60	peak	P
2	4876.000	63.62	-14.35	49.27	74.00	-24.73	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB _{UV} /m)= Corr. (dB/m)+ Read Level (dB _{UV})								
3. Margin (dB) = Peak/AVG (dB _{UV} /m)-Limit PK/AVG(dB _{UV} /m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	23.5°C	Relative Humidity:	45%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	802.11 n20 Mode TX 2462 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2963.500	70.46	-19.65	50.81	74.00	-23.19	peak	P
2	4927.000	64.66	-14.12	50.54	74.00	-23.46	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	4468.000	64.44	-16.15	48.29	74.00	-25.71	peak	P
2 *	4927.000	66.10	-14.12	51.98	74.00	-22.02	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	23.5°C	Relative Humidity:	45%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	802.11 n40 Mode TX 2422 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2963.500	70.06	-19.65	50.41	74.00	-23.59	peak	P
2	4468.000	59.77	-16.15	43.62	74.00	-30.38	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3728.500	61.81	-18.46	43.35	74.00	-30.65	peak	P
2 *	4468.000	64.84	-16.15	48.69	74.00	-25.31	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	23.5°C	Relative Humidity:	45%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	802.11 n40 Mode TX 2437 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2963.500	70.70	-19.65	51.05	74.00	-22.95	peak	P
2	4876.000	58.25	-14.35	43.90	74.00	-30.10	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3728.500	62.66	-18.46	44.20	74.00	-29.80	peak	P
2 *	4468.000	63.89	-16.15	47.74	74.00	-26.26	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	23.5°C	Relative Humidity:	45%			
Test Voltage:	AC 120V/60Hz					
Test Mode:	802.11 n40 Mode TX 2452 MHz					
Remark:	Only worse case is reported.					
Horizontal						
Vertical						
Remark:	<ol style="list-style-type: none">1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.5. No report for the emission which below the prescribed limit.6. The peak value < average limit, So only show the peak value.					



Temperature:	23.5°C	Relative Humidity:	45%												
Test Voltage:	AC 120V/60Hz														
Test Mode:	802.11 ax20 Mode TX 2412 MHz														
Remark:	Only worse case is reported.														
Horizontal															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1 *</td><td>2963.500</td><td>70.33</td><td>-19.65</td></tr><tr><td>2</td><td>4825.000</td><td>57.46</td><td>-14.57</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	1 *	2963.500	70.33	-19.65	2	4825.000	57.46	-14.57
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)												
1 *	2963.500	70.33	-19.65												
2	4825.000	57.46	-14.57												
Vertical															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th></tr></thead><tbody><tr><td>1</td><td>2963.500</td><td>61.04</td><td>-19.65</td></tr><tr><td>2 *</td><td>4468.000</td><td>63.65</td><td>-16.15</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	1	2963.500	61.04	-19.65	2 *	4468.000	63.65	-16.15
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)												
1	2963.500	61.04	-19.65												
2 *	4468.000	63.65	-16.15												
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value.															



Temperature:	23.5°C	Relative Humidity:	45%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	802.11 ax20 Mode TX 2437 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2963.500	70.34	-19.65	50.69	74.00	-23.31	peak	P
2	4876.000	58.39	-14.35	44.04	74.00	-29.96	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	4468.000	64.34	-16.15	48.19	74.00	-25.81	peak	P
2	4876.000	61.81	-14.35	47.46	74.00	-26.54	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	23.5°C	Relative Humidity:	45%																											
Test Voltage:	AC 120V/60Hz																													
Test Mode:	802.11 ax20 Mode TX 2462 MHz																													
Remark:	Only worse case is reported.																													
Horizontal																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_{UV})</th> <th>Factor (dB/m)</th> <th>Level (dB_{UV}/m)</th> <th>Limit (dB_{UV}/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>2963.500</td> <td>70.45</td> <td>-19.65</td> <td>50.80</td> <td>74.00</td> <td>-23.20</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2</td> <td>4927.000</td> <td>59.48</td> <td>-14.12</td> <td>45.36</td> <td>74.00</td> <td>-28.64</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	P/F	1 *	2963.500	70.45	-19.65	50.80	74.00	-23.20	peak	P	2	4927.000	59.48	-14.12	45.36	74.00	-28.64	peak	P
No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	P/F																						
1 *	2963.500	70.45	-19.65	50.80	74.00	-23.20	peak	P																						
2	4927.000	59.48	-14.12	45.36	74.00	-28.64	peak	P																						
Vertical																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_{UV})</th> <th>Factor (dB/m)</th> <th>Level (dB_{UV}/m)</th> <th>Limit (dB_{UV}/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>4468.000</td> <td>64.04</td> <td>-16.15</td> <td>47.89</td> <td>74.00</td> <td>-26.11</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2</td> <td>5947.000</td> <td>58.08</td> <td>-13.21</td> <td>44.87</td> <td>74.00</td> <td>-29.13</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	P/F	1 *	4468.000	64.04	-16.15	47.89	74.00	-26.11	peak	P	2	5947.000	58.08	-13.21	44.87	74.00	-29.13	peak	P
No.	Frequency (MHz)	Reading (dB _{UV})	Factor (dB/m)	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	P/F																						
1 *	4468.000	64.04	-16.15	47.89	74.00	-26.11	peak	P																						
2	5947.000	58.08	-13.21	44.87	74.00	-29.13	peak	P																						
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB_{UV}/m)= Corr. (dB/m)+ Read Level (dB_{UV}) 3. Margin (dB) = Peak/AVG (dB_{UV}/m)-Limit PK/AVG(dB_{UV}/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value. 																														



Temperature:	23.5°C	Relative Humidity:	45%			
Test Voltage:	AC 120V/60Hz					
Test Mode:	802.11 ax40 Mode TX 2422 MHz					
Remark:	Only worse case is reported.					
Horizontal						
Vertical						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value.						



Temperature:	23.5°C	Relative Humidity:	45%					
Test Voltage:	AC 120V/60Hz							
Test Mode:	802.11 ax40 Mode TX 2437 MHz							
Remark:	Only worse case is reported.							
Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	2963.500	70.55	-19.65	50.90	74.00	-23.10	peak	P
2	4876.000	57.30	-14.35	42.95	74.00	-31.05	peak	P
Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	4468.000	64.37	-16.15	48.22	74.00	-25.78	peak	P
2	4876.000	59.75	-14.35	45.40	74.00	-28.60	peak	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.								
5. No report for the emission which below the prescribed limit.								
6. The peak value < average limit, So only show the peak value.								



Temperature:	23.5°C	Relative Humidity:	45%																											
Test Voltage:	AC 120V/60Hz																													
Test Mode:	802.11 ax40 Mode TX 2452 MHz																													
Remark:	Only worse case is reported.																													
Horizontal																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>2963.500</td> <td>70.22</td> <td>-19.65</td> <td>50.57</td> <td>74.00</td> <td>-23.43</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2</td> <td>4901.500</td> <td>58.09</td> <td>-14.24</td> <td>43.85</td> <td>74.00</td> <td>-30.15</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	2963.500	70.22	-19.65	50.57	74.00	-23.43	peak	P	2	4901.500	58.09	-14.24	43.85	74.00	-30.15	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	2963.500	70.22	-19.65	50.57	74.00	-23.43	peak	P																						
2	4901.500	58.09	-14.24	43.85	74.00	-30.15	peak	P																						
Vertical																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>4468.000</td> <td>64.40</td> <td>-16.15</td> <td>48.25</td> <td>74.00</td> <td>-25.75</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2</td> <td>4901.500</td> <td>60.01</td> <td>-14.24</td> <td>45.77</td> <td>74.00</td> <td>-28.23</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	4468.000	64.40	-16.15	48.25	74.00	-25.75	peak	P	2	4901.500	60.01	-14.24	45.77	74.00	-28.23	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	4468.000	64.40	-16.15	48.25	74.00	-25.75	peak	P																						
2	4901.500	60.01	-14.24	45.77	74.00	-28.23	peak	P																						
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value < average limit, So only show the peak value. 																														

-----END OF THE REPORT-----

