

a YAGEO company

Series: Chip Antenna

TECHNICAL DATA SHEET

Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm

PART NUMBER: W3006



Features:

- 2.4-2.5 / 5.15-7.125GHz WIFi-6E
- Peak gain 2.2 / 5.2 dBi
- Efficiency 60 / 70 %
- Compact size W x L x H (10 x 3.2 x 1.5 mm)
- Low weight: 240 mg
- Fully SMD compatible
- Tape and reel packing
- RoHS Compliant Product
- · Moisture Sensitivity Level: MSL1

Applications:

- Layout 1 for 2.4-2.5 / 5.15-5.85GHz
- Layout 2 for 2.4-2.5 / 5.15-7.125GHz
- IEEE 802.11a/b/g/n/x
- WiFi-6E
- 5 GHz WLAN
- 2.4 GHz WLAN
- 2.4 GHz ISM Band Systems
- 5GHz ISM Band Systems
- ZigBee IEEE 802.15.4

All dimensions are in inches/mm

Issue: 2108

In the effort to improve our products, we reserve the right to make changes judged to be necessary. PROPRIETARY INFORMATION

This document contains proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

For more information:
Pulse Worldwide Headquarters
15255 Innovation Drive #100
San Diego, CA 92128
USA

Tel:1-858-674-8100

Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

Series: Chip Antenna

ELECTRICAL SPECIFICATIONS

Layout and Matching for 2.4-2.5/5.15-5.85GHz

Frequency 2.4-2.5 / 5.15-5.85 GHz

Return Loss -8 /-9 dB max

Efficiency (typical) 60 / 80 %

Peak Gain (typical) 1.8 / 4.5dBi

Layout and Matching for 2.4-2.5/5.15-7.125GHz WiFi-6E

Frequency 2.4-2.5 / 5.15-7.125 GHz

Return Loss -5 /-5 dB max

Efficiency (typical) 65 / 75 %

Peak Gain (typical) 1.6 / 4.2dBi

Nominal Impedance 50Ω

Polarization Linear

Interface SMD mount ceramic antenna



Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

Series: Chip Antenna

MECHANICAL SPECIFICATIONS

Weight 0.24g

Size 10 x 3.2 x 1.5 mm

ENVIRONMENTAL SPECIFICATIONS

Operating temperature -40~+85° C

Temperature -40~+85° C

Humidity Cyclic 6 +25° C/+55° C 95%

Vibration

Sinusoidal 2-8Hz 7.5 mm

Sinusoidal 8-200Hz 20 m/s²

Shocks 0.5 m/s

Salt mist 96 hours




Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

Series: Chip Antenna

MECHANICAL DRAWING AND TERMINAL CONFIGURATION



| No. | Terminal Name | Terminal Dimensions |
|---|---------------|---------------------|
| 1 | Feed | 1.5 x 2.75 mm |
| 2 | Support pad | 1.5 x 2.75 mm |
| Antenna feed pad can be identified by looking top surface metallization pattern | | |

 1.50 ± 0.10

Issue: 2108

support pad





Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

Series: Chip Antenna

MECHANICAL DRAWING AND TERMINAL CONFIGURATION

Ground cleared under antenna



Issue: 2108



Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm


Series: Chip Antenna

PART NUMBER: W3006


MECHANICAL DRAWING AND TERMINAL CONFIGURATION

1.Layout and Matching for 2.4-2.5/5.15-5.85GHz


Ground clearance area (11.60 x 6.25 mm)



Opening in bottom/inner ground layers



Opening in other layers (no ground/ RF)







Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006


MECHANICAL DRAWING AND TERMINAL CONFIGURATION

Recommended Antenna Pad Dimensions on PWB Layout (top surface)

Pad dimensions in top copper



Recommended test board layout for electrical characteristic measurement, test board outline size 80 x 37mm





Issue: 2108

ROHS



Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm


PART NUMBER: W3006

Series: Chip Antenna

MECHANICAL DRAWING AND TERMINAL CONFIGURATION

2.Layout and Matching for 2.4-2.5/5.15-7.125GHz

Ground clearance area (13.3 x 6.25 mm)




All metallization should be removed from all PWB layers on ground clearance area (13.3 x 6.25mm)

Opening in bottom/inner ground layers

6.25

Opening in other layers (no ground/RF)







Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

MECHANICAL DRAWING AND TERMINAL CONFIGURATION

Recommended Antenna Pad Dimensions on PWB Layout (top surface)

Pad dimensions in top copper







Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006


Test setup

1. Layout and Matching for 2.4-2.5/5.15-5.85GHz

Ground clearance area (11.60 x 6.25 mm)



Return Loss



Issue: 2108

ROHS






Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

CHARTS

1. Layout and Matching for 2.4-2.5/5.15-5.85GHz





Issue: 2108

ROHS

11






Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm


PART NUMBER: W3006

CHARTS

1. Layout and Matching for 2.4-2.5/5.15-5.85GHz







Issue: 2108






Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm


PART NUMBER: W3006

CHARTS

1. Layout and Matching for 2.4-2.5/5.15-5.85GHz







Issue: 2108






Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm


PART NUMBER: W3006

Test setup

2. Layout and Matching for 2.4-2.5/5.15-7.125GHz



Return Loss








Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

CHARTS

2. Layout and Matching for 2.4-2.5/5.15-7.125GHz












Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm


PART NUMBER: W3006

CHARTS

2. Layout and Matching for 2.4-2.5/5.15-7.125GHz












Description: 2.4-2.5/5.15-7.125GHz Dual band


Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

CHARTS

2. Layout and Matching for 2.4-2.5/5.15-7.125GHz





Issue: 2108

17



Description: 2.4-2.5/5.15-7.125GHz Dual band

Ceramic 10x3.2x1.5mm

PART NUMBER: W3006

Series: Chip Antenna

PACKAGING


1000pcs antennas per 7" reel

3pcs 7" reel per inner package box


2pcs inner box per out box

Total 6000pcs antenna per out box

Out box size: 390mmx215mmx165mm







LEVEL

NOT MOISTURE SENSITIVE



These Devices do not require special storage conditions provided:

- They are maintained at conditions equal to or less than 30℃ and 85% RH.
- 2. They are solder reflowed at a peak body temperture which does not exceed 260°C.

Note: Level and body temperture defined by IPC/JEDEC J-STD-020

