

LTE SISO

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
LTE_B5_10M_CH20525	108.6093	-61.45	-59.21	2.24	-13.00	46.21	V
	251.7559	-61.72	-59.54	2.18	-13.00	46.54	H
	1664.0000	-71.10	-55.60	15.50	-13.00	42.60	H
	2496.0000	-70.83	-49.23	21.60	-13.00	36.23	V
	3328.0000	-71.20	-58.52	12.68	-13.00	45.52	V
	4160.0000	-72.38	-56.93	15.45	-13.00	43.93	H
	4992.0000	-72.87	-55.02	17.85	-13.00	42.02	H
	5824.0000	-73.01	-53.11	19.90	-13.00	40.11	H
	6656.0000	-72.87	-51.62	21.25	-13.00	38.62	H
	7488.0000	-72.74	-48.46	24.28	-13.00	35.46	H
	8320.0000	-78.82	-57.02	21.80	-13.00	44.02	H
LTE_B38_20M_CH3800	111.5208	-62.38	-59.38	3.00	-25.00	34.38	V
	882.086	-60.79	-52.08	8.71	-25.00	27.08	H
	5170.0000	-74.37	-55.79	18.58	-25.00	30.79	H
	7755.0000	-74.31	-49.89	24.42	-25.00	24.89	V
	10340.0000	-85.07	-60.24	24.83	-25.00	35.24	V
	12925.0000	-86.36	-60.25	26.11	-25.00	35.25	V
	15510.0000	-87.05	-57.65	29.40	-25.00	32.65	V

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal

NR SA

Data List							
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.
NR_n5_20M_CH167800	111.0355	-62.18	-59.25	2.93	-13.00	46.25	V
	252.2411	-62.16	-60.14	2.02	-13.00	47.14	H
	1678.0000	-71.08	-55.26	15.82	-13.00	42.26	H
	2517.0000	-70.73	-48.60	22.13	-13.00	35.60	H
	3356.0000	-71.33	-58.27	13.06	-13.00	45.27	V
	4195.0000	-72.25	-56.80	15.45	-13.00	43.80	H
	5034.0000	-73.04	-55.17	17.87	-13.00	42.17	H
	5873.0000	-72.96	-53.70	19.26	-13.00	40.70	V
	6712.0000	-73.60	-52.62	20.98	-13.00	39.62	V
	7551.0000	-73.69	-49.89	23.80	-13.00	36.89	H
	8390.0000	-78.19	-55.51	22.68	-13.00	42.51	V
NR_n12_15M_CH141500	110.5503	-62.62	-59.81	2.81	-13.00	46.81	V
	253.6968	-61.28	-59.74	1.54	-13.00	46.74	H
	1415.0000	-71.76	-56.61	15.15	-13.00	43.61	V
	2122.5000	-70.85	-50.36	20.49	-13.00	37.36	H
	2830.0000	-70.58	-47.82	22.76	-13.00	34.82	H
	3537.5000	-71.30	-57.98	13.32	-13.00	44.98	H
	4245.0000	-72.34	-56.58	15.76	-13.00	43.58	H
	4952.5000	-72.49	-55.77	16.72	-13.00	42.77	V
	5660.0000	-72.75	-53.99	18.76	-13.00	40.99	V
	6367.5000	-72.55	-52.17	20.38	-13.00	39.17	H
	7075.0000	-73.62	-51.35	22.27	-13.00	38.35	H
NR_n26_10M_CH163800	110.5503	-61.34	-58.53	2.81	-13.00	45.53	V
	250.3002	-61.11	-59.23	1.88	-13.00	46.23	H
	1638.0000	-71.35	-56.48	14.87	-13.00	43.48	H
	2457.0000	-70.86	-49.85	21.01	-13.00	36.85	V
	3276.0000	-71.49	-58.68	12.81	-13.00	45.68	V
	4095.0000	-72.17	-56.70	15.47	-13.00	43.70	H

	4914.0000	-72.83	-55.76	17.07	-13.00	42.76	H
	5733.0000	-72.55	-53.31	19.24	-13.00	40.31	H
	6552.0000	-73.80	-52.71	21.09	-13.00	39.71	H
	7371.0000	-73.55	-50.92	22.63	-13.00	37.92	V
	8190.0000	-79.03	-57.49	21.54	-13.00	44.49	H
NR_n38_40M_CH518500	111.5208	-62.60	-59.60	3.00	-25.00	34.60	V
	251.7559	-61.77	-59.59	2.18	-25.00	34.59	H
	5146.0000	-74.02	-55.71	18.31	-25.00	30.71	V
	7719.0000	-74.28	-49.70	24.58	-25.00	24.70	H
	10292.0000	-85.44	-60.61	24.83	-25.00	35.61	V
	12865.0000	-85.95	-60.10	25.85	-25.00	35.10	V
	15438.0000	-86.99	-57.90	29.09	-25.00	32.90	V

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal