

Test Mode :	3Mbps	Temperature :	21~25 ℃
Test Channel :	00 and 78	Relative Humidity :	51~55%
		Test Engineer :	Weller Liu

Low Band Edge Plot on Channel 00



Date: 30.MAR.2019 02:50:03

High Band Edge Plot on Channel 78



Date: 30.MAR.2019 02:36:45

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 41 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	21~25 ℃
Test Engineer :	Weller Liu	Relative Humidity :	51~55%

Hopping Mode Low Band Edge Plot



Date: 19.APR.2019 17:57:41

Hopping Mode High Band Edge Plot



Date: 30.MAR.2019 01:55:26


Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 42 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A


Test Mode :	2Mbps	Temperature :	21~25 ℃
Test Engineer :	Weller Liu	Relative Humidity :	51~55%

Hopping Mode Low Band Edge Plot



Date: 30.MAR.2019 02:17:13

Hopping Mode High Band Edge Plot



Date: 30.MAR.2019 02:35:45

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 43 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A


Test Mode :	3Mbps	Temperature :	21~25 ℃
Test Engineer :	Weller Liu	Relative Humidity :	51~55%

Hopping Mode Low Band Edge Plot



Date: 30.MAR.2019 02:49:36

Hopping Mode High Band Edge Plot



Date: 30.MAR.2019 02:34:16

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 44 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 7.8.8.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup




TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 45 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	21~25 ℃
Test Channel :	00	Relative Humidity :	51~55%
		Test Engineer :	Weller Liu

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 01:31:19

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 01:31:46

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 46 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 01:46:00

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 01:46:27

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 47 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 01:56:55

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 01:57:25

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 48 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A


Test Mode :	2Mbps	Temperature :	21~25℃
Test Channel :	00	Relative Humidity :	51~55%
		Test Engineer :	Weller Liu

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 02:15:10

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 02:15:38

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 49 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 02:10:06

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 02:10:35

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 50 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 02:00:47

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 02:01:16

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 51 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A


Test Mode :	3Mbps	Temperature :	21~25℃
Test Channel :	00	Relative Humidity :	51~55%
		Test Engineer :	Weller Liu

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 02:47:11

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 02:47:38

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 52 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 02:43:20

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 30.MAR.2019 02:43:47

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 53 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 30.MAR.2019 02:30:48

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 30.MAR.2019 02:31:15

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 54 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 55 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.8.3 Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 4. Set to the maximum power setting and enable the EUT transmit continuously.
- 5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).

Duty cycle = On time/100 milliseconds

On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.

Average Emission Level = Peak Emission Level + 20*log(Duty cycle)


- 6. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.


Report No.: FR931313A

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 57 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix C.

Sporton International (Kunshan) Inc.
TEL: 86-512-57900158

FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 58 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Report No.: FR931313A

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Eroquency of emission (MUz)	Conducted limit (dBµV)			
Frequency of emission (MHz)	Quasi-peak	Average		
0.15-0.5	66 to 56*	56 to 46*		
0.5-5	56	46		
5-30	60	50		

^{*}Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.9.3 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least
 centimeters from any other grounded conducting surface.
- 10. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 11. All the support units are connecting to the other LISN.
- 12. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 13. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 14. Both sides of AC line were checked for maximum conducted interference.
- 15. The frequency range from 150 kHz to 30 MHz was searched.
- 16. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Report No.: FR931313A

Report Version : Rev. 01

3.9.4 Test Setup



AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 60 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

Non-standard antenna connector is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 61 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Report No.: FR931313A

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Mar. 27, 2019~ Apr. 23, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GH z	Jan. 14, 2019	Mar. 27, 2019~ Apr. 23, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Mar. 27, 2019~ Apr. 23, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;M ax 30dBm	Oct. 12, 2018	Apr. 15, 2019	Oct. 11, 2019	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY574710 84	10Hz-44GHz	Jun. 25, 2018	Apr. 15, 2019	Jun. 24, 2019	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Apr. 15, 2019	Oct. 18, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Apr. 15, 2019	Dec. 27, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	Apr. 15, 2019	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Apr. 15, 2019	Jan. 04, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	Apr. 15, 2019	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35- HG	2014749	18~40GHz	Jan. 14, 2019	Apr. 15, 2019	Jan. 13, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Apr. 15, 2019	Apr. 16, 2019	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY532702 03	500MHz~26.5G Hz	Apr. 18, 2018	Apr. 15, 2019	Apr. 17, 2019	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Apr. 15, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 15, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 15, 2019	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2019	Apr. 24, 2019	Apr. 15, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Apr. 24, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Apr. 24, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Apr. 24, 2019	Oct. 11, 2019	Conduction (CO01-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 62 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

<u>Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)</u>

Measuring Uncertainty for a Level of Confidence	2 04B
of 95% (U = 2Uc(y))	2.9dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Manager and the contribute formal and a form	
Measuring Uncertainty for a Level of Confidence	5.0dB
of 95% (U = 2Uc(y))	3.VUB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	:e
•	5.0dB
of 95% (U = 2Uc(y))	

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)


Measuring Uncertainty for a Level of Confidence	5.0dB
of 95% (U = 2Uc(y))	5.00B

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : 63 of 63
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01


Report No.: FR931313A

Appendix A. AC Conducted Emission Test Results



TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : A1 of A2
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A



TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : A2 of A2 Report Issued Date: Apr. 28, 2019 Report Version : Rev. 01

Report No.: FR931313A

Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

вт	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V
	*	2402	95.18	-	-	89.54	31.3	6.14	31.8	100	269	Р	Н
	*	2402	70.39	-	-	-	-	-	-	-	-	Α	Н
вт		2385.27	53.25	-20.75	74	47.64	31.27	6.14	31.8	100	269	Р	Н
CH00		2385.27	28.46	-25.54	54	-	-	ı	-	-	-	Α	Н
2402MHz	*	2402	107.55	-	-	101.91	31.3	6.14	31.8	124	195	Р	V
2402WITI2	*	2402	82.76	-	-	-	-	•	-	-	-	Α	V
		2362.13	52.97	-21.03	74	47.42	31.25	6.1	31.8	124	195	Р	V
		2362.13	28.18	-25.82	54	-	-	-	-	-	-	Α	V
	*	2480	93.47	-	-	87.67	31.44	6.16	31.8	119	262	Р	Н
	*	2480	68.68	-	-	-	-	-	-	-	-	Α	Н
		2484.11	52.58	-21.42	74	46.78	31.44	6.16	31.8	119	262	Р	Н
BT		2484.11	27.79	-26.21	54	-	-	-	-	-	-	Α	Н
CH 78 2480MHz	*	2480	109.11	-	-	103.31	31.44	6.16	31.8	173	29	Р	V
2400WITI2	*	2480	84.32	-	-	-	-	-	-	-	-	Α	V
		2483.5	62.31	-11.69	74	56.51	31.44	6.16	31.8	173	29	Р	V
		2483.5	37.52	-16.48	54	-	-		-	-	-	Α	V
Remark		o other spurio I results are P		st Peak	and Averaç	ge limit lin	e.						

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : B1 of B5
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

ВТ	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	
вт		4806	36	-38	74	53.52	35.66	8.41	61.59	100	0	Р	Н
CH 00 2402MHz		4804	37.86	-36.14	74	55.44	35.66	8.35	61.59	100	360	Р	V
BT CH 39		4884	36.6	-37.4	74	54.01	35.61	8.59	61.61	100	360	Р	Н
		7320	41.51	-32.49	74	57.55	35.9	10.4	62.34	100	360	Р	Н
		4884	38.54	-35.46	74	55.95	35.61	8.59	61.61	100	360	Р	V
2441MHz		7320	40.94	-33.06	74	56.98	35.9	10.4	62.34	100	360	Р	V
		4962	39.27	-34.73	74	56.6	35.54	8.77	61.64	100	0	Р	Н
BT CH 78 2480MHz		7440	39.68	-34.32	74	55.67	35.97	10.44	62.4	100	0	Р	Н
		4962	39.37	-34.63	74	56.7	35.54	8.77	61.64	100	360	Р	٧
		7440	39.7	-34.3	74	55.69	35.97	10.44	62.4	100	360	Р	٧

Remark

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : B2 of B5
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

Emission below 1GHz

2.4GHz BT (LF)

вт	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	$(dB\mu V/m)$	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		30	26.57	-13.43	40	31.37	25.2	0.66	30.66	100	0	Р	Н
		339.43	22.19	-23.81	46	30.3	20.16	2.34	30.61	-	-	Р	Н
		612	28	-18	46	29.69	25.69	2.9	30.28	-	-	Р	Н
		776.9	30.78	-15.22	46	29.65	27.86	3.29	30.02	-	-	Р	Н
		817.64	31.29	-14.71	46	29.51	28.42	3.36	30	-	-	Р	Н
2.4GHz		995.15	33.85	-20.15	54	29.96	30.05	3.7	29.86	-	-	Р	Н
BT LF		30.97	25.9	-14.1	40	31.25	24.65	0.66	30.66	-	-	Р	V
LF		233.7	19.83	-26.17	46	31.97	16.74	1.84	30.72	-	-	Р	V
		493.66	25.29	-20.71	46	29.31	23.65	2.62	30.29	-	-	Р	V
		573.2	27.32	-18.68	46	29.61	25.11	2.96	30.36	-	-	Р	V
		775.93	30.68	-15.32	46	29.58	27.84	3.29	30.03	-	-	Р	V
		901.06	32.56	-13.44	46	29.74	29.01	3.54	29.73	100	0	Р	V

Remark

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : B3 of B5
Report Issued Date : Apr. 28, 2019

Report No.: FR931313A

Report Version : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

^{1.} No other spurious found.

^{2.} All results are PASS against limit line.

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

Sporton International (Kunshan) Inc.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : B4 of B5
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01

Report No.: FR931313A

A calculation example for radiated spurious emission is shown as below:

Report No.: FR931313A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

1. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

 Sporton International (Kunshan) Inc.
 Page Number
 : B5 of B5


 TEL: 86-512-57900158
 Report Issued Date
 : Apr. 28, 2019

 FAX: 86-512-57900958
 Report Version
 : Rev. 01

 FCC ID: XMR201905SC66MW
 Report Template No.: BU5-FR15CBT Version 2.0

Appendix C. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



Note:

- 1. Worst case Duty cycle = on time/100 milliseconds = $2 \times 2.89 / 100 = 5.78 \%$
- 2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.76 dB
- 3. DH5 has the highest duty cycle worst case and is reported.

TEL: 86-512-57900158 FAX: 86-512-57900958 FCC ID: XMR201905SC66MW Page Number : C1 of C1
Report Issued Date : Apr. 28, 2019
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT Version 2.0

Report No.: FR931313A