

## FCC 47 CFR MPE REPORT

Zylux Acoustic Corporation

MC100Blue

Model Number: MC100Blue

FCC ID: XN6-MC100BLUE

Prepared for : Zylux Acoustic Corporation

3F, 22, Lane 35, Jihu Road, Neihu Technology Park,  
Taipei 11492, Taiwan

Prepared By :EST Technology Co., Ltd.

Santun Management Zone, Houjie District,DongGuan ,GuangDong,  
China.

Tel: 86-769-83081888-808

Fax:86-769-83081878

Report Number: ESTE-R1307028

Date of Test : June 30 ~ July 22, 2013

Date of Report : July 23, 2013



## Maximum Permissible Exposure

### 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a)、Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|---|--|
| 0.3-3.0               | 614                              | 1.63                              | (100)*                                  | 6  |
| 3.0-30                | 1842/f                           | 4.89/f                            | (900/f)*                                | 6  |
| 30-300                | 61.4                             | 0.163                             | 1.0                                     | 6  |
| 300-1500              |                                  |                                   | F/300                                   | 6  |
| 1500-10000            |                                  |                                   | 5                                       | 6  |

#### (b)、Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|---|--|
| 0.3-1.34              | 614                              | 1.63                              | (100)*                                  | 30   |
| 1.34-30               | 824/f                            | 2.19/f                            | (180/f)*                                | 30   |
| 30-300                | 27.5                             | 0.073                             | 0.2                                     | 30   |
| 300-1500              |                                  |                                   | F/1500                                  | 30   |
| 1500-10000            |                                  |                                   | 1.0                                     | 30   |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2、MPE Calculation Method

$$E \text{ (V/m)} = (30 * P * G) / (0.5 * d)$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 * P * G) / (377 * d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



### 3、Calculated Result and Limit

| Model              | Frequency<br>(MHz) | Peak<br>output<br>power<br>(dBm) | Peak<br>output<br>power<br>(mW) | Antenna gain |          | Power<br>Density (S)<br>(mW/cm <sup>2</sup> ) | Limited of<br>Power<br>Density (S)<br>(mW/cm <sup>2</sup> ) | Test<br>Result |
|--------------------|--------------------|----------------------------------|---------------------------------|--------------|----------|---|---|----------------|
|                    |                    |                                  |                                 | (dBi)        | (Linear) |   |   |                |
| BT 4.0-BLE<br>GFSK | 2402               | -2.54                            | 0.557                           | 0            | 1        | <b>0.00011</b>                                | 1   | Compiles       |
|                    | 2440               | 1.05                             | 1.274                           | 0            | 1        | <b>0.00025</b>                                | 1   | Compiles       |
|                    | 2480               | 1.78                             | 1.507                           | 0            | 1        | <b>0.00030</b>                                | 1   | Compiles       |

Note: dBm = 10log(mW)