


FCC Test Report

FCC ID : XNAWSM02
Equipment : Nokia Sleep
Model No. : WSM02
Brand Name : NOKIA
Applicant : NOKIA TECHNOLOGIES (France)
Address : 2 rue Maurice Hartmann
92130 Issy-Les-Moulineaux
France
Standard : 47 CFR FCC Part 15.247
Received Date : Sep. 28, 2017
Tested Date : Dec. 22, 2017 ~ Jan. 09, 2018


We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Testing Laboratory
2732

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION.....	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	Unwanted Emissions into Restricted Frequency Bands	14
3.3	Unwanted Emissions into Non-Restricted Frequency Bands	30
3.4	Conducted Output Power	35
3.5	Number of Hopping Frequency	37
3.6	20dB and Occupied Bandwidth	39
3.7	Channel Separation.....	41
3.8	Number of Dwell Time.....	43
4	TEST LABORATORY INFORMATION	46

Release Record

Report No.	Version	Description	Issued Date
FR792802AD	Rev. 01	Initial issue	Jan. 31, 2018

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.476MHz 31.90 (Margin -14.51dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 953.00MHz 37.33 (Margin -8.67dB) - PK	Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: -3.07	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: Bluetooth BR uses a GFSK.
 Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.

1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)	Remarks
1	Broadcom	BCM9Fractal	PCB	N/A	2.8	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from AC adapter
-------------------	----------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	AC adapter	Brand: ABP Model: SWA06B-050-1000U Power Rating: I/P: 100-240Vac, 50-60Hz, 0.3A O/P: 5Vdc, 1000mA

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	Tera Term, Version: 4.94
-----------	--------------------------


1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	2441	2480
GFSK/1Mbps	0x00	0x00	0x00
$\pi/4$ -DQPSK /2Mbps	0x00	0x00	0x00
8DPSK/3Mbps	0x00	0x00	0x00

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	Doc	---

1.3 Test Setup Chart



Note: The notebook is disconnected from EUT and removed from test table when EUT is set to transmit continuously.

1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jan. 09, 2018				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 05, 2018	Jan. 04, 2019
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2017	Nov. 12, 2018
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 18, 2017	Dec. 17, 2018
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Dec. 25, 2017				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018
Receiver	R&S	ESR3	101658	Nov. 20, 2017	Nov. 19, 2018
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 23, 2017	Nov. 22, 2018
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2017	Nov. 12, 2018
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 07, 2017	Dec. 06, 2018
Preamplifier	EMC	EMC02325	980187	Sep. 04, 2017	Sep. 03, 2018
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Nov. 27, 2017	Nov. 26, 2018
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY32487/4	Nov. 27, 2017	Nov. 26, 2018
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Nov. 27, 2017	Nov. 26, 2018
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Nov. 27, 2017	Nov. 26, 2018
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Nov. 27, 2017	Nov. 26, 2018
LF cable-13M	EMC	EMC8D-NM-NM-1300	131104	Nov. 27, 2017	Nov. 26, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Dec. 22, 2017				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018
Power Meter	Anritsu	ML2495A	1241002	Oct. 16, 2017	Oct. 15, 2018
Power Sensor	Anritsu	MA2411B	1207366	Oct. 16, 2017	Oct. 15, 2018
AC POWER SOURCE	G.W .	APS-9102	EL920581	Jun. 03, 2017	Jun. 02, 2018
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.90 dB
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.37 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 59%	Alex Tsai
Radiated Emissions	03CH03-WS	23-24°C / 64-66%	Aska Huang
RF Conducted	TH01-WS	21°C / 64%	Aska Huang

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	GFSK	2402	1Mbps	---
Radiated Emissions ≤ 1GHz	GFSK	2402	1Mbps	---
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	---
Conducted Output Power	GFSK 1/4 QDPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	---
Number of Hopping Channels	GFSK 8DPSK	2402~2480 2402~2480	1Mbps 3Mbps	---
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	---
Dwell Time	GFSK 8DPSK	2402 2402	1Mbps 3Mbps	---

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions





3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.

2. Radiated emission above 1GHz / Peak value
RBW=1MHz, VBW=3MHz and Peak detector

Radiated emission above 1GHz / Average value for harmonics


The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:

3.
$$20\log(\text{Duty cycle}) = 20\log \frac{1s / 1600 * 5}{100 \text{ ms}} = -30.1 \text{ dB}$$


4. Radiated emission above 1GHz / Average value for other emissions
RBW=1MHz, VBW=1/T and Peak detector

3.2.3 Test Setup


Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz





3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402																																																															
Polarization	Horizontal																																																																	
																																																																		
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level MHz</th> <th>Limit dBuV/m</th> <th>Margin dB</th> <th>SA reading dBuV</th> <th>Factor dB</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>38.52</td> <td>23.35</td> <td>40.00</td> <td>-16.65</td> <td>31.94</td> <td>-8.59</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>2</td> <td>192.53</td> <td>24.16</td> <td>43.50</td> <td>-19.34</td> <td>34.66</td> <td>-10.50</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>241.15</td> <td>26.52</td> <td>46.00</td> <td>-19.48</td> <td>35.79</td> <td>-9.27</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>4</td> <td>439.16</td> <td>26.18</td> <td>46.00</td> <td>-19.82</td> <td>30.16</td> <td>-3.98</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>589.44</td> <td>29.31</td> <td>46.00</td> <td>-16.69</td> <td>30.20</td> <td>-0.89</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>6</td> <td>768.52</td> <td>32.85</td> <td>46.00</td> <td>-13.15</td> <td>30.60</td> <td>2.25</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>				Freq.	Emission level MHz	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	38.52	23.35	40.00	-16.65	31.94	-8.59	Peak	---	2	192.53	24.16	43.50	-19.34	34.66	-10.50	Peak	---	3	241.15	26.52	46.00	-19.48	35.79	-9.27	Peak	---	4	439.16	26.18	46.00	-19.82	30.16	-3.98	Peak	---	5	589.44	29.31	46.00	-16.69	30.20	-0.89	Peak	---	6	768.52	32.85	46.00	-13.15	30.60	2.25	Peak	---
Freq.	Emission level MHz	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																										
1	38.52	23.35	40.00	-16.65	31.94	-8.59	Peak	---																																																										
2	192.53	24.16	43.50	-19.34	34.66	-10.50	Peak	---																																																										
3	241.15	26.52	46.00	-19.48	35.79	-9.27	Peak	---																																																										
4	439.16	26.18	46.00	-19.82	30.16	-3.98	Peak	---																																																										
5	589.44	29.31	46.00	-16.69	30.20	-0.89	Peak	---																																																										
6	768.52	32.85	46.00	-13.15	30.60	2.25	Peak	---																																																										
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>																																																																		



3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402																																																																																																		
Polarization	Horizontal																																																																																																				
																																																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dBuV</th> <th style="text-align: left;"> </th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>36.98</td> <td>54.00</td> <td>-17.02</td> <td>38.39</td> <td>-1.41</td> <td>Average</td> <td>199</td> <td>162</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.98</td> <td>74.00</td> <td>-23.02</td> <td>52.39</td> <td>-1.41</td> <td>Peak</td> <td>199</td> <td>162</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>37.37</td> <td>54.00</td> <td>-16.63</td> <td>38.43</td> <td>-1.06</td> <td>Average</td> <td>199</td> <td>162</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>51.69</td> <td>74.00</td> <td>-22.31</td> <td>52.75</td> <td>-1.06</td> <td>Peak</td> <td>199</td> <td>162</td> </tr> <tr> <td>5</td> <td>4804.00</td> <td>13.96</td> <td>54.00</td> <td>-40.04</td> <td>8.54</td> <td>5.42</td> <td>Average</td> <td>100</td> <td>25</td> </tr> <tr> <td>6</td> <td>4804.00</td> <td>44.06</td> <td>74.00</td> <td>-29.94</td> <td>38.64</td> <td>5.42</td> <td>Peak</td> <td>100</td> <td>25</td> </tr> <tr> <td>7</td> <td>12010.00</td> <td>24.62</td> <td>54.00</td> <td>-29.38</td> <td>8.77</td> <td>15.85</td> <td>Average</td> <td>100</td> <td>70</td> </tr> <tr> <td>8</td> <td>12010.00</td> <td>54.72</td> <td>74.00</td> <td>-19.28</td> <td>38.87</td> <td>15.85</td> <td>Peak</td> <td>100</td> <td>70</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dBuV		High	Table	1	2390.00	36.98	54.00	-17.02	38.39	-1.41	Average	199	162	2	2390.00	50.98	74.00	-23.02	52.39	-1.41	Peak	199	162	3	2483.50	37.37	54.00	-16.63	38.43	-1.06	Average	199	162	4	2483.50	51.69	74.00	-22.31	52.75	-1.06	Peak	199	162	5	4804.00	13.96	54.00	-40.04	8.54	5.42	Average	100	25	6	4804.00	44.06	74.00	-29.94	38.64	5.42	Peak	100	25	7	12010.00	24.62	54.00	-29.38	8.77	15.85	Average	100	70	8	12010.00	54.72	74.00	-19.28	38.87	15.85	Peak	100	70
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																													
MHz	level	dBuV/m	dB	reading	dBuV		High	Table																																																																																													
1	2390.00	36.98	54.00	-17.02	38.39	-1.41	Average	199	162																																																																																												
2	2390.00	50.98	74.00	-23.02	52.39	-1.41	Peak	199	162																																																																																												
3	2483.50	37.37	54.00	-16.63	38.43	-1.06	Average	199	162																																																																																												
4	2483.50	51.69	74.00	-22.31	52.75	-1.06	Peak	199	162																																																																																												
5	4804.00	13.96	54.00	-40.04	8.54	5.42	Average	100	25																																																																																												
6	4804.00	44.06	74.00	-29.94	38.64	5.42	Peak	100	25																																																																																												
7	12010.00	24.62	54.00	-29.38	8.77	15.85	Average	100	70																																																																																												
8	12010.00	54.72	74.00	-19.28	38.87	15.85	Peak	100	70																																																																																												
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																																																					




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).




Modulation	GFSK	Test Freq. (MHz)	2441																																																																																																		
Polarization	Vertical																																																																																																				
																																																																																																					
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th>cm</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.14</td> <td>54.00</td> <td>-16.86</td> <td>38.55</td> <td>-1.41</td> <td>Average</td> <td>106</td> <td>346</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>51.09</td> <td>74.00</td> <td>-22.91</td> <td>52.50</td> <td>-1.41</td> <td>Peak</td> <td>106</td> <td>346</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>37.41</td> <td>54.00</td> <td>-16.59</td> <td>38.47</td> <td>-1.06</td> <td>Average</td> <td>106</td> <td>346</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>50.78</td> <td>74.00</td> <td>-23.22</td> <td>51.84</td> <td>-1.06</td> <td>Peak</td> <td>106</td> <td>346</td> </tr> <tr> <td>5</td> <td>4882.00</td> <td>13.65</td> <td>54.00</td> <td>-40.35</td> <td>8.04</td> <td>5.61</td> <td>Average</td> <td>100</td> <td>0</td> </tr> <tr> <td>6</td> <td>4882.00</td> <td>43.75</td> <td>74.00</td> <td>-30.25</td> <td>38.14</td> <td>5.61</td> <td>Peak</td> <td>100</td> <td>0</td> </tr> <tr> <td>7</td> <td>7323.00</td> <td>18.99</td> <td>54.00</td> <td>-35.01</td> <td>8.09</td> <td>10.90</td> <td>Average</td> <td>100</td> <td>340</td> </tr> <tr> <td>8</td> <td>7323.00</td> <td>49.09</td> <td>74.00</td> <td>-24.91</td> <td>38.19</td> <td>10.90</td> <td>Peak</td> <td>100</td> <td>340</td> </tr> </tbody> </table>				Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm		1	2390.00	37.14	54.00	-16.86	38.55	-1.41	Average	106	346	2	2390.00	51.09	74.00	-22.91	52.50	-1.41	Peak	106	346	3	2483.50	37.41	54.00	-16.59	38.47	-1.06	Average	106	346	4	2483.50	50.78	74.00	-23.22	51.84	-1.06	Peak	106	346	5	4882.00	13.65	54.00	-40.35	8.04	5.61	Average	100	0	6	4882.00	43.75	74.00	-30.25	38.14	5.61	Peak	100	0	7	7323.00	18.99	54.00	-35.01	8.09	10.90	Average	100	340	8	7323.00	49.09	74.00	-24.91	38.19	10.90	Peak	100	340
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table deg																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm																																																																																														
1	2390.00	37.14	54.00	-16.86	38.55	-1.41	Average	106	346																																																																																												
2	2390.00	51.09	74.00	-22.91	52.50	-1.41	Peak	106	346																																																																																												
3	2483.50	37.41	54.00	-16.59	38.47	-1.06	Average	106	346																																																																																												
4	2483.50	50.78	74.00	-23.22	51.84	-1.06	Peak	106	346																																																																																												
5	4882.00	13.65	54.00	-40.35	8.04	5.61	Average	100	0																																																																																												
6	4882.00	43.75	74.00	-30.25	38.14	5.61	Peak	100	0																																																																																												
7	7323.00	18.99	54.00	-35.01	8.09	10.90	Average	100	340																																																																																												
8	7323.00	49.09	74.00	-24.91	38.19	10.90	Peak	100	340																																																																																												

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	GFSK	Test Freq. (MHz)	2480																																																																																																		
Polarization	Vertical																																																																																																				
																																																																																																					
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th>cm</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.06</td> <td>54.00</td> <td>-16.94</td> <td>38.47</td> <td>-1.41</td> <td>Average</td> <td>102</td> <td>347</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.57</td> <td>74.00</td> <td>-23.43</td> <td>51.98</td> <td>-1.41</td> <td>Peak</td> <td>102</td> <td>347</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>37.66</td> <td>54.00</td> <td>-16.34</td> <td>38.72</td> <td>-1.06</td> <td>Average</td> <td>102</td> <td>347</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>50.98</td> <td>74.00</td> <td>-23.02</td> <td>52.04</td> <td>-1.06</td> <td>Peak</td> <td>102</td> <td>347</td> </tr> <tr> <td>5</td> <td>4960.00</td> <td>14.41</td> <td>54.00</td> <td>-39.59</td> <td>8.63</td> <td>5.78</td> <td>Average</td> <td>100</td> <td>100</td> </tr> <tr> <td>6</td> <td>4960.00</td> <td>44.51</td> <td>74.00</td> <td>-29.49</td> <td>38.73</td> <td>5.78</td> <td>Peak</td> <td>100</td> <td>100</td> </tr> <tr> <td>7</td> <td>7440.00</td> <td>19.75</td> <td>54.00</td> <td>-34.25</td> <td>8.48</td> <td>11.27</td> <td>Average</td> <td>100</td> <td>65</td> </tr> <tr> <td>8</td> <td>7440.00</td> <td>49.85</td> <td>74.00</td> <td>-24.15</td> <td>38.58</td> <td>11.27</td> <td>Peak</td> <td>100</td> <td>65</td> </tr> </tbody> </table>				Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm		1	2390.00	37.06	54.00	-16.94	38.47	-1.41	Average	102	347	2	2390.00	50.57	74.00	-23.43	51.98	-1.41	Peak	102	347	3	2483.50	37.66	54.00	-16.34	38.72	-1.06	Average	102	347	4	2483.50	50.98	74.00	-23.02	52.04	-1.06	Peak	102	347	5	4960.00	14.41	54.00	-39.59	8.63	5.78	Average	100	100	6	4960.00	44.51	74.00	-29.49	38.73	5.78	Peak	100	100	7	7440.00	19.75	54.00	-34.25	8.48	11.27	Average	100	65	8	7440.00	49.85	74.00	-24.15	38.58	11.27	Peak	100	65
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table deg																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm																																																																																														
1	2390.00	37.06	54.00	-16.94	38.47	-1.41	Average	102	347																																																																																												
2	2390.00	50.57	74.00	-23.43	51.98	-1.41	Peak	102	347																																																																																												
3	2483.50	37.66	54.00	-16.34	38.72	-1.06	Average	102	347																																																																																												
4	2483.50	50.98	74.00	-23.02	52.04	-1.06	Peak	102	347																																																																																												
5	4960.00	14.41	54.00	-39.59	8.63	5.78	Average	100	100																																																																																												
6	4960.00	44.51	74.00	-29.49	38.73	5.78	Peak	100	100																																																																																												
7	7440.00	19.75	54.00	-34.25	8.48	11.27	Average	100	65																																																																																												
8	7440.00	49.85	74.00	-24.15	38.58	11.27	Peak	100	65																																																																																												


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK


Modulation	8DPSK	Test Freq. (MHz)	2402																																																																																									
Polarization	Horizontal																																																																																											
																																																																																												
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level MHz</th> <th>Limit dBuV/m</th> <th>Margin dB</th> <th>SA reading dBuV</th> <th>Factor dB</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.19</td> <td>54.00</td> <td>-16.81</td> <td>38.60</td> <td>-1.41</td> <td>Average</td> <td>196</td> <td>159</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.32</td> <td>74.00</td> <td>-23.68</td> <td>51.73</td> <td>-1.41</td> <td>Peak</td> <td>196</td> <td>159</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>37.76</td> <td>54.00</td> <td>-16.24</td> <td>38.82</td> <td>-1.06</td> <td>Average</td> <td>196</td> <td>159</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>51.16</td> <td>74.00</td> <td>-22.84</td> <td>52.22</td> <td>-1.06</td> <td>Peak</td> <td>196</td> <td>159</td> </tr> <tr> <td>5</td> <td>4804.00</td> <td>13.99</td> <td>54.00</td> <td>-40.01</td> <td>8.57</td> <td>5.42</td> <td>Average</td> <td>100</td> <td>270</td> </tr> <tr> <td>6</td> <td>4804.00</td> <td>44.09</td> <td>74.00</td> <td>-29.91</td> <td>38.67</td> <td>5.42</td> <td>Peak</td> <td>100</td> <td>270</td> </tr> <tr> <td>7</td> <td>12010.00</td> <td>24.70</td> <td>54.00</td> <td>-29.30</td> <td>8.85</td> <td>15.85</td> <td>Average</td> <td>100</td> <td>230</td> </tr> <tr> <td>8</td> <td>12010.00</td> <td>54.80</td> <td>74.00</td> <td>-19.20</td> <td>38.95</td> <td>15.85</td> <td>Peak</td> <td>100</td> <td>230</td> </tr> </tbody> </table>				Freq.	Emission level MHz	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	2390.00	37.19	54.00	-16.81	38.60	-1.41	Average	196	159	2	2390.00	50.32	74.00	-23.68	51.73	-1.41	Peak	196	159	3	2483.50	37.76	54.00	-16.24	38.82	-1.06	Average	196	159	4	2483.50	51.16	74.00	-22.84	52.22	-1.06	Peak	196	159	5	4804.00	13.99	54.00	-40.01	8.57	5.42	Average	100	270	6	4804.00	44.09	74.00	-29.91	38.67	5.42	Peak	100	270	7	12010.00	24.70	54.00	-29.30	8.85	15.85	Average	100	230	8	12010.00	54.80	74.00	-19.20	38.95	15.85	Peak	100	230
Freq.	Emission level MHz	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																				
1	2390.00	37.19	54.00	-16.81	38.60	-1.41	Average	196	159																																																																																			
2	2390.00	50.32	74.00	-23.68	51.73	-1.41	Peak	196	159																																																																																			
3	2483.50	37.76	54.00	-16.24	38.82	-1.06	Average	196	159																																																																																			
4	2483.50	51.16	74.00	-22.84	52.22	-1.06	Peak	196	159																																																																																			
5	4804.00	13.99	54.00	-40.01	8.57	5.42	Average	100	270																																																																																			
6	4804.00	44.09	74.00	-29.91	38.67	5.42	Peak	100	270																																																																																			
7	12010.00	24.70	54.00	-29.30	8.85	15.85	Average	100	230																																																																																			
8	12010.00	54.80	74.00	-19.20	38.95	15.85	Peak	100	230																																																																																			
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																																												




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).




Modulation	8DPSK	Test Freq. (MHz)	2441																																																																																																		
Polarization	Vertical																																																																																																				
																																																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>36.88</td> <td>54.00</td> <td>-17.12</td> <td>38.29</td> <td>-1.41</td> <td>Average</td> <td>108</td> <td>345</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.34</td> <td>74.00</td> <td>-23.66</td> <td>51.75</td> <td>-1.41</td> <td>Peak</td> <td>108</td> <td>345</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>37.17</td> <td>54.00</td> <td>-16.83</td> <td>38.23</td> <td>-1.06</td> <td>Average</td> <td>108</td> <td>345</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>50.16</td> <td>74.00</td> <td>-23.84</td> <td>51.22</td> <td>-1.06</td> <td>Peak</td> <td>108</td> <td>345</td> </tr> <tr> <td>5</td> <td>4882.00</td> <td>12.62</td> <td>54.00</td> <td>-41.38</td> <td>7.01</td> <td>5.61</td> <td>Average</td> <td>100</td> <td>250</td> </tr> <tr> <td>6</td> <td>4882.00</td> <td>42.72</td> <td>74.00</td> <td>-31.28</td> <td>37.11</td> <td>5.61</td> <td>Peak</td> <td>100</td> <td>250</td> </tr> <tr> <td>7</td> <td>7323.00</td> <td>18.92</td> <td>54.00</td> <td>-35.08</td> <td>8.02</td> <td>10.90</td> <td>Average</td> <td>100</td> <td>210</td> </tr> <tr> <td>8</td> <td>7323.00</td> <td>49.02</td> <td>74.00</td> <td>-24.98</td> <td>38.12</td> <td>10.90</td> <td>Peak</td> <td>100</td> <td>210</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	2390.00	36.88	54.00	-17.12	38.29	-1.41	Average	108	345	2	2390.00	50.34	74.00	-23.66	51.75	-1.41	Peak	108	345	3	2483.50	37.17	54.00	-16.83	38.23	-1.06	Average	108	345	4	2483.50	50.16	74.00	-23.84	51.22	-1.06	Peak	108	345	5	4882.00	12.62	54.00	-41.38	7.01	5.61	Average	100	250	6	4882.00	42.72	74.00	-31.28	37.11	5.61	Peak	100	250	7	7323.00	18.92	54.00	-35.08	8.02	10.90	Average	100	210	8	7323.00	49.02	74.00	-24.98	38.12	10.90	Peak	100	210
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																													
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																													
1	2390.00	36.88	54.00	-17.12	38.29	-1.41	Average	108	345																																																																																												
2	2390.00	50.34	74.00	-23.66	51.75	-1.41	Peak	108	345																																																																																												
3	2483.50	37.17	54.00	-16.83	38.23	-1.06	Average	108	345																																																																																												
4	2483.50	50.16	74.00	-23.84	51.22	-1.06	Peak	108	345																																																																																												
5	4882.00	12.62	54.00	-41.38	7.01	5.61	Average	100	250																																																																																												
6	4882.00	42.72	74.00	-31.28	37.11	5.61	Peak	100	250																																																																																												
7	7323.00	18.92	54.00	-35.08	8.02	10.90	Average	100	210																																																																																												
8	7323.00	49.02	74.00	-24.98	38.12	10.90	Peak	100	210																																																																																												

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement


1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


3.3.3 Test Setup




3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands


GFSK





8DPSK





3.4 Conducted Output Power

3.4.1 Limit of Conducted Output Power

- 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
- 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.
- 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power sensor and meter is 50MHz
2. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



3.4.4 Test Result of Conducted Output Power

Modulation Mode	Freq. (MHz)	Output Power (mW)	Output Power (dBm)	Limit (mW)
GFSK	2402	0.49	-3.07	125
GFSK	2441	0.43	-3.62	125
GFSK	2480	0.36	-4.47	125
$\pi/4$ DQPSK	2402	0.23	-6.44	125
$\pi/4$ DQPSK	2441	0.19	-7.16	125
$\pi/4$ DQPSK	2480	0.18	-7.37	125
8DPSK	2402	0.24	-6.18	125
8DPSK	2441	0.21	-6.84	125
8DPSK	2480	0.19	-7.12	125

Modulation Mode	Freq. (MHz)	AV Output Power (mW)	AV Output Power (dBm)
GFSK	2402	0.45	-3.47
GFSK	2441	0.39	-4.07
GFSK	2480	0.32	-5.01
$\pi/4$ DQPSK	2402	0.13	-9.03
$\pi/4$ DQPSK	2441	0.11	-9.77
$\pi/4$ DQPSK	2480	0.10	-9.99
8DPSK	2402	0.13	-9.02
8DPSK	2441	0.11	-9.76
8DPSK	2480	0.10	-9.98

Note: Average power is for reference only.

3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.


3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2. Allow trace to stabilize.

3.5.3 Test Setup



3.5.4 Test Result of Number of Hopping Frequency



3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures


20dB Bandwidth

1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak, Trace max hold
2. Allow trace to stabilize
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth


1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Sample, Trace max hold
2. Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



3.6.3 Test result of 20dB and Occupied Bandwidth

Modulation Mode	Freq. (MHz)	20dB Bandwidth (MHz)	Occupied Bandwidth (MHz)
GFSK	2402	1.017	0.927
GFSK	2441	1.026	0.927
GFSK	2480	1.022	0.933
8DPSK	2402	1.326	1.211
8DPSK	2441	1.326	1.211
8DPSK	2480	1.326	1.210



3.7 Channel Separation


3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures


1. Set RBW=100kHz, VBW=300kHz, Sweep time = Auto, Detector=Peak Trace max hold
2. Allow trace to stabilize
3. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.
The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



3.7.4 Test result of Channel Separation

Modulation Mode	Freq. (MHz)	Channel Separation (MHz)	20dB Bandwidth (MHz)	Minimum Limit (MHz)
GFSK	2402	1.003	1.017	0.678
GFSK	2441	1.003	1.026	0.684
GFSK	2480	1.003	1.022	0.681
8DPSK	2402	1.003	1.326	0.884
8DPSK	2441	1.003	1.326	0.884
8DPSK	2480	1.003	1.326	0.884



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures


1. Set RBW=100kHz, VBW=300kHz, Sweep time = 500us(DH1), 2ms(DH3), 4ms(DH5), Detector=Peak, Span=0Hz, Trace max hold
2. Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds, or 0.625ms. DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.
4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds, or 1.875ms. DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
5. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds

3.8.3 Test Setup




3.8.4 Test Result of Dwell Time

Modulation Mode	Freq. (MHz)	Length of Transmission Time (msec)	Number of Transmission in a 31.6 (79 Hopping*0.4)	Result (s)	Limit (s)
GFSK-DH1	2402	0.44638	320	0.143	0.4
GFSK-DH3	2402	1.72319	160	0.276	0.4
GFSK-DH5	2402	2.97536	106.6	0.317	0.4
8DPSK-DH1	2402	0.44058	320	0.141	0.4
8DPSK-DH3	2402	1.74058	160	0.278	0.4
8DPSK-DH5	2402	2.90870	106.6	0.310	0.4




8DPSK


3DH1



3DH5



3DH3



--

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

—END—