FCC RADIO TEST REPORT FCC ID: XNBTX7

Product: Digital Clock(TX)

Trade Name: N/A

Model Name: TX7

Serial Model: N/A

Prepared for

Fuzhou Rise Electronic Co., Ltd.

Bldg 15, Zone C, Pushang Industial Area, No.6, Hongjiang RD, Fuzhou, Fujian, China

Prepared by

DongGuan Precise Testing Service Co.,Ltd.

Room 203-204, 2F, Xinye Building, No.67 Shijing, Guanzhang Road, Dongguan, China

Page 2 of 26 Report No.: PT1401064005E

TEST RESULT CERTIFICATION

Applicant's name:	Fuzhou Rise Electronic Co., Ltd.						
Address:	Bldg 15, Zone C, Pushang Industial Area, No.6, Hongjiang RD, Fuzhou, Fujian, China						
Manufacture's Name:	Fuzhou Rise Electronic Co., Ltd.						
Address:	Bldg 15, Zone C, Pushang Industial Area, No.6, Hongjiang RD, Fuzhou, Fujian, China						
Product description							
Product name:	Digital Clock(TX)						
Model and/or type reference :	TX7						
Rating(s):	DC 3V						
Standards:	FCC Part15.231						
Test procedure	ANSI C63.4-2003						
	is been tested by PTS, and the test results show that the n compliance with the FCC requirements. And it is applicable only n the report.						
document may be altered or rev the document. Date of Test							
Date (s) of performance of tests.							
Date of Issue	: 13 Jun. 2014						
Test Result	Pass						
Testing Engine							
	Assistant						
Technical Man	Consid ria						
	Supervisor						
Authorized Sig	gnatory: Jarky En						
	Jacky Ou / Manager						



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . ANTENNA REQUIREMENT	11
3.1 STANDARD REQUIREMENT	11
3.2 EUT ANTENNA	11
3.3 CONDUCTED EMISSION MEASUREMENT	12
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.3.2 TEST PROCEDURE 3.3.3 DEVIATION FROM TEST STANDARD	13 13
3.3.4 TEST SETUP	13
3.2.5 TEST RESULT	14
3.4 RADIATED EMISSION MEASUREMENT	15
3.4.1 RADIATED EMISSION LIMITS	15
3.4.2 TEST PROCEDURE	16
3.4.3 DEVIATION FROM TEST STANDARD	16
3.4.4 TEST SETUP 3.4.5 TEST RESULTS (BLOW 30MHZ)	17 19
3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)	20
4 . BANDWIDTH TEST	22
4.1 TEST PROCEDURE	22
4.2 DEVIATION FROM STANDARD	22
4.3 TEST SETUP	22
4.4 TEST RESULTS	23
5. TRANSMITTER TIMEOUT	24
5.1 REQUIREMENTS	24
6 . EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	26



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.231)					
Standard Section	Test Item	Judgment	Remark		
15.207	Conducted Emission	N/A	Note(1)		
15.203	Antenna Requirement	Pass			
15.231	Radiated Spurious Emission	Pass			
15.231	Occupied Bandwidth	Pass			
15.231	Transmitter Timeout	Pass			

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.

Page 5 of 26 Report No.: PT1401064005E

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District,

Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Digital Clock(TX)				
Model Name	TX7				
Serial Model	N/A				
Model Difference	N/A				
	The EUT is a Digital Clo	, ,			
	Product Type	Remote Control			
	Operation Frequency:	433.92MHz			
	Modulation Type:	ASK			
	Antenna Designation:	extension wire antenna			
Product Description	Antenna Gain(Peak)	0 dBi			
	Output Power:	67.75 dBuV/m (AV Max.)			
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.				
Channel List	N/A				
Adapter	N/A				
Battery	DC 3.0V				

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	extension wire Antenna	NA	0	Antenna



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Emission			
Final Test Mode	Description		
1	1		

For Radiated Emission		
Final Test Mode	Description	
Mode 1	TX	

Note:

(1) The EUT use new battery.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test

E-1 EUT

•



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Digital Clock(TX)	N/A	TX7	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2013.07.06	2014.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2013.07.06	2014.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-101 80	2011071402	2013.07.06	2014.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2013.07.06	2014.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2013.07.06	2014.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2013.07.06	2014.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufactu rer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Test Receiver	R&S	ESCI	101160	2013.06.06	2014.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year



3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is integral Antenna. It comply with the standard requirement.



3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A	A (dBuV) Class B (dBuV)		Standard	
FREQUENCT (MITZ)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5		66 - 56 *	56 - 46 *	LP002.
0.50 -5.0		56.00	46.00	LP002.
5.0 -30.0		60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.3.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

Page 14 of 26 Report No.: PT1401064005E

3.2.5 TEST RESULT

EUT:	Digital Clock(TX)	Model Name. :	TX7
Temperature :	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	N/A	Test Mode:	N/A

Note: Due to the EUT is powered by batteries, this test item is not applicable.

•



3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.231)

,				
Fundamental Frequency (MHz)	Field Strength of fundamental (microvolts/meter)	Field Strength of Unwanted Emissions (microvolts/meter)		
40.66 - 40.70	1000	100		
70 - 130	500	50		
130 - 174	500 to 1500 **	50 to 150 **		
174 - 260	3750.00	375.00		
260 - 470	1500 to 5000 **	150 to 500 **		
Above 470	5000	500		

Notes:

(1) ** linear interpolations

age 16 of 26	Report No.: PT1401064005E

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.4.3 DEVIATION FROM TEST STANDARD

No deviation




3.4.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



Page 18 of 26 Report No.: PT1401064005E

(C) Radiated Emission Test-Up Frequency Above 1GHz





3.4.5 TEST RESULTS (BLOW 30MHz)

EUT:	Digital Clock(TX)	Model Name. :	TX7
Temperature :	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =20 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)


Note: After we search the relevant pulse train again and again, we found below test plot is the one which owns the maximum Ton during each 100ms.

The duty cycle is simply the on time divided by the period(100ms):


Ton=47*0.48=22.56ms

DC = 22.56ms/100ms = 0.2256

Therefore, the average factor is found by 20log0.22568 = -12.933dB



Date: 23.MAY.2014 14:36:11



Date: 23.MAY.2014 15:24:03

Page 21 of 26 Report No.: PT1401064005E

EUT:	Digital Clock(TX)	Model Name :	TX7
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX	Polarization :	Horizontal

Frequency	Average Factor	Field Strength	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dB	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	State
433.92	-12.933	80.68	67.747	92.86	72.86	pass
867.48	-12.933	60.38	47.447	74.00	54.00	pass
1299.044	-12.933	48.16	35.227	74.00	54.00	pass
				74.00	54.00	pass

EUT:	Digital Clock(TX)	Model Name :	TX7
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX	Polarization :	Vertical

Frequency	Average Factor	Field Strength	Field Strength	Limit(PK)	Limit(AV)	State
MHz	dB	dBuV/m (PK)	dBuV/m (AV)	dBuV/m	dBuV/m	State
433.92	-12.933	79.38	66.447	92.86	72.86	pass
867.48	-12.933	58.37	45.437	74.00	54.00	pass
1299.044	-12.933	47.16	34.227	74.00	54.00	pass
				74.00	54.00	pass

NoTE:

- 1. Emissions attenuated more than 20 dB below the permissible value are not reported.
- 2. *: Denotes restricted band of operation.

Measurements were made using a peak detector and average detector. Any emission falling within the restricted bands of FCC Part 15 Section 15.205 were compliance with the emission limit of FCC Part 15 Section 15.209.



4. BANDWIDTH TEST

4.1 TEST PROCEDURE

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER




Page 23 of 26 Report No.: PT1401064005E

4.4 TEST RESULTS

EUT:	Digital Clock(TX)	Model Name :	TX7
Temperature :	26 ℃	Relative Humidity:	53%
Pressure :	1020 hPa	Test Power :	DC 3.0V
Test Mode :	TX		

Frequency	20 dBc Bandwidth	Limit
(MHz)	(kHz)	(kHz)
433.92	54.995	1084.8



Date: 23.MAY.2014 15:31:32



5. TRANSMITTER TIMEOUT

5.1 REQUIREMENTS

1 A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Result: The EUT does not have a automatically activated transmitter

2 A transmitter activated automatically shall cease transmission within 5 seconds after activation.


Result: The EUT does not have a automatically activated transmitter

- 3 devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.
 - Result: The EUT have a employ periodic transmission. please refer to below detail data
- 4 Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Result: The section is not applicable to EUT.

Power On: the EUT transmits data (0.54 ms) in a fixed interval(66.4s)


Note: The EUT is an outdoor temperature sensor which transmits the measured temperature values at a regular predetermined interval to the associated receiver. Therefore, the EUT is subject to FCC15.231 (e) requirement.



Date: 3.JUN.2014 04:41:26

Page 25 of 26

Report No.: PT1401064005E



Date: 13.JUN.2014 03:12:16

THE SILENT PERIOD BETWEEN TRANSMISSIONS	LIMIT	RESULT
66.4s	>10s	PASS





RECISE TESTING

6. EUT TEST PHOTO



