

Date: 2017-09-09

Report Number: 60.790.17.023.03

Model No.: SF-BTHFRD

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT are 15.56MHz, 2402-2480MHz, the test separation distance is ≤ 50mm.

(Manufacturer specified the separation distance is: 20mm)

Step a)

- >> Numeric threshold (2402MHz), mW / 20mm * $\sqrt{2.402}$ GHz ≤ 3.0 Numeric threshold (2402MHz) ≤ 38.713 mW
- >> Numeric threshold (2440MHz), mW / 20mm * $\sqrt{2.440}$ GHz ≤ 3.0 Numeric threshold (2440MHz) ≤ 38.411 mW
- >> Numeric threshold (2480MHz), mW / 20mm * $\sqrt{2.480}$ GHz ≤ 3.0 Numeric threshold (2480MHz) ≤ 38.100 mW
- >> The power of EUT measured (2402MHz) is: -3.13dBm = 0.486mW The power of EUT measured (2440MHz) is: -4.62dBm = 0.345mW The power of EUT measured (2480MHz) is: -5.77dBm = 0.265mW

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.

Page 1 of 2 TÜV SÜD Hong Kong Ltd.

3/F, West Wing, Phase 2, 10 Science Park West Avenue, Hong Kong Science Park, Shatin, Hong Kong



Date: 2017-09-09

Report Number: 60.790.17.023.03

Model No.: SF-BTHFRD

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1, For frequencies below 100 MHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR

Step b)

{[Power allowed at numeric threshold for 50mm in step a)] + [(test separation distance – 50mm) · (f(MHz)/150)]} mW

Step c) 1)

For test separation distances > 50mm and < 200mm, the power threshold at the corresponding test separation distance at 100MHz in step b) is multiplied by $[1 + \log(100/f(MHz))]$

Step c) 2)

For test separation distances \leq 50mm, the power threshold determined by the equation in c) 1) for 50mm and 100MHz is multiplied by $\frac{1}{2}$.

>> The fundamental frequency of the EUT is 13.56MHz, the test separation distance is ≤ 50mm. (Manufacturer specified the separation distance is: 20mm)

Step a)

>> Numeric threshold, mW / 50mm * √0.1GHz ≤ 3.0 * Numeric threshold ≤ 474.3mW

Step b)

>> Numeric threshold ≤ 474.3mW + (50mm-50mm * 100MHz/150) Numeric threshold ≤ 474.3mW

Step c) 1) & c) 2)

>> Numeric threshold \leq 474.3mW * [1 + log 100/100MHz] * ½ Numeric threshold \leq 237.15mW

>> The power of EUT measured is: -42.77dBm = 0.000053mW

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.

Page 2 of 2 TÜV SÜD Hong Kong Ltd.

3/F, West Wing, Phase 2, 10 Science Park West Avenue, Hong Kong Science Park, Shatin, Hong Kong