

## RF exposure analysis

**u-blox AG**  
Zürcherstrasse 68  
8800 Thalwil  
Switzerland  
Phone +41 44 722 74 44  
Fax +41 44 722 74 47  
info@u-blox.com

MWSt Nr 424 417

Zürcher Kantonalbank  
BC-Nr. 700,  
S.W.I.F.T. ZKBK CH ZZ 80A

1100-0243.614 (CHF)  
IBAN CH96 0070 0110 0002 4361 4  
1300-00293.032 (USD)  
IBAN CH18 0070 0130 0002 9303 2  
1300-00293.040 (EUR)  
IBAN CH93 0070 0130 0002 9304 0  
1300-07001.827 (JPY)  
IBAN CH62 0070 0130 0070 0182 7

American Certification Body, Inc.  
6731 Whittier Avenue  
Suite C110  
McLean, VA 22101

Date: **Dec. 02, 2013**

Subject: **RF exposure analysis for: FCC ID: XPYLEONG100N; IC: 8595A-LEONG100N**

The device (FCC ID: **XPYLEONG100N**; IC: **8595A-LEONG100N**) is a module designed to be installed in other devices. This device is to be used only for fixed and mobile applications. If the final product after integration is intended for portable use, new applications and FCC and IC are required.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all the persons and must not be co-located or operating in conjunction with any other antenna or transmitter except as under the conditions described KDB 447498 D01 General RF Exposure Guidance.

### MPE exposure limits

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
300 – 1500	$f$ (MHz) /1500	30
1500 – 100.000	1,0	30

The table below is excerpted from RSS-102, Issue 4, 4.2, titled "RF Limits for Devices used by the General Public":

Frequency Range (MHz)	Power density (W/m <sup>2</sup> )	Averaging time (minutes)
300 – 1500	$f$ (MHz) /150	6
1500 – 100.000	10	6

Author	Giulio Comar	Department:	cert	Page: 1/2
Filename	RF exposure_v0_1.docx			
M87 Rev. 3	Copyright © 2013 u-blox Italia S.p.A. All rights reserved		Confidential	

**EIRP/ERP limits**

For 850 MHz frequency band and according to FCC §22.913 the maximum ERP of the device is 7 W (equivalent to 11,48 W EIRP) while IC SRSP-503 defines an EIRP limit of 11,5 W. For 1900 MHz frequency band and according to FCC §24.232 and IC SRSP-510, the maximum EIRP of the device should be lower than 2 W.

$$S = \frac{PG}{4\pi R^2}$$

Using the equation to calculate the exposure to electromagnetic fields

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

compliance with FCC/IC MPE and EIRP limits is demonstrated following the calculations shown in the following page.

Band	Modulation	Test Mode	Channel		Frequency (MHz)	Max. Avg. burst Conducted power (per tune up) (dBm)	Duty cycle (%)	FCC/IC MPE limit (mW/cm <sup>2</sup> )	FCC ERP limit per §22.913 and §24.232 (W)	IC ERP limit per SRSP-503 and SRSP-510 (W)	Evaluation distance for compliance with MPE limits (cm)	Antenna gain to meet FCC/IC MPE limit (dB)	Antenna gain to meet FCC ERP limit (dB)	Antenna gain to meet IC ERP limit (dB)	Maximum antenna gain to meet all the limits (dB)	Maximum antenna gain to meet all the limits per frequency band (dB)
GSM/GPRS 850	GMSK	2 of 8 transmission slots Duty factor 1/4	Lowest	128	824.2	33.20	25.0%	0.55	11.48	11.50	20	7.23	7.39	7.40	7.23	7.23
GSM/GPRS 1900	GMSK	2 of 8 transmission slots Duty factor 1/4	Lowest	512	1850.2	30.20	25.0%	1.00	2.00	2.00	20	12.83	2.81	2.81	2.81	2.81

Sincerely,

By:  
 Title:  
 Company:  
 Telephone / Fax:  
 e-mail:

**Giulio Comar**  
**Certification Manager**  
**u-blox AG, Zuercherstrasse 68, 8800 Thalwil, Switzerland**  
**+41 44 722 7462 / +41 44 722 2477**

  
 (Signature)

Author	Giulio Comar	Department:	cert	Page: 2/2
Filename	RF exposure_v0_1.docx			
M87 Rev. 3	Copyright © 2011 u-blox Italia S.p.A. All rights reserved			Confidential