

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 2 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4880.000                                              | 46.18                   | 0.14           | 46.32                      | 74                 | -27.68         | peak       |
| 4880.000                                              | 35.62                   | 0.14           | 35.76                      | 54                 | -18.24         | AVG        |
| 7320.000                                              | 38.54                   | 2.36           | 40.9                       | 74                 | -33.1          | peak       |
| 7320.000                                              | 28.37                   | 2.36           | 30.73                      | 54                 | -23.27         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 2 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4880.000                                              | 48.16                   | 0.14           | 48.3                       | 74                 | -25.7          | peak       |
| 4880.000                                              | 37.15                   | 0.14           | 37.29                      | 54                 | -16.71         | AVG        |
| 7320.000                                              | 42.59                   | 2.36           | 44.95                      | 74                 | -29.05         | peak       |
| 7320.000                                              | 33.126                  | 2.36           | 35.486                     | 54                 | -18.514        | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 3 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4960.000                                              | 46.29                   | 0.22           | 46.51                      | 74                 | -27.49         | peak       |
| 4960.000                                              | 35.17                   | 0.22           | 35.39                      | 54                 | -18.61         | AVG        |
| 7440.000                                              | 40.25                   | 2.64           | 42.89                      | 74                 | -31.11         | peak       |
| 7440.000                                              | 26.17                   | 2.64           | 28.81                      | 54                 | -25.19         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 3 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4960.000                                              | 45.38                   | 0.22           | 45.6                       | 74                 | -28.4          | peak       |
| 4960.000                                              | 36.47                   | 0.22           | 36.69                      | 54                 | -17.31         | AVG        |
| 7440.000                                              | 39.61                   | 2.64           | 42.25                      | 74                 | -31.75         | peak       |
| 7440.000                                              | 29.87                   | 2.64           | 32.51                      | 54                 | -21.49         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

**RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



#### Antenna 4

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 1 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz) | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|--------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4804.000           | 46.94                   | 0.08           | 46.16                      | 74                 | -27.84         | peak       |
| 4804.000           | 35.67                   | 0.08           | 37.48                      | 54                 | -16.52         | AVG        |
| 7206.000           | 42.18                   | 2.21           | 42.15                      | 74                 | -31.85         | peak       |
| 7206.000           | 31.27                   | 2.21           | 32.14                      | 54                 | -21.86         | AVG        |
|                    |                         |                |                            |                    |                |            |
|                    |                         |                |                            |                    |                |            |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 1 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz) | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|--------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4804.000           | 46.19                   | 0.08           | 45.34                      | 74                 | -28.66         | peak       |
| 4804.000           | 35.18                   | 0.08           | 34.18                      | 54                 | -19.82         | AVG        |
| 7206.000           | 39.47                   | 2.21           | 40.27                      | 74                 | -33.73         | peak       |
| 7206.000           | 30.48                   | 2.21           | 31.15                      | 54                 | -22.85         | AVG        |
|                    |                         |                |                            |                    |                |            |
|                    |                         |                |                            |                    |                |            |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 2 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4880.000                                              | 46.18                   | 0.14           | 46.19                      | 74                 | -27.81         | peak       |
| 4880.000                                              | 35.62                   | 0.14           | 37.48                      | 54                 | -16.52         | AVG        |
| 7320.000                                              | 38.54                   | 2.36           | 41.23                      | 74                 | -32.77         | peak       |
| 7320.000                                              | 28.37                   | 2.36           | 30.48                      | 54                 | -23.52         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 2 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4880.000                                              | 48.16                   | 0.14           | 46.15                      | 74                 | -27.85         | peak       |
| 4880.000                                              | 37.15                   | 0.14           | 35.18                      | 54                 | -18.82         | AVG        |
| 7320.000                                              | 42.59                   | 2.36           | 42.18                      | 74                 | -31.82         | peak       |
| 7320.000                                              | 33.126                  | 2.36           | 32.48                      | 54                 | -21.52         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 3 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4960.000                                              | 46.29                   | 0.22           | 45.26                      | 74                 | -28.74         | peak       |
| 4960.000                                              | 35.17                   | 0.22           | 34.18                      | 54                 | -19.82         | AVG        |
| 7440.000                                              | 40.25                   | 2.64           | 40.28                      | 74                 | -33.72         | peak       |
| 7440.000                                              | 26.17                   | 2.64           | 30.15                      | 54                 | -23.85         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B400      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 3 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4960.000                                              | 45.38                   | 0.22           | 46.15                      | 74                 | -27.85         | peak       |
| 4960.000                                              | 36.47                   | 0.22           | 37.54                      | 54                 | -16.46         | AVG        |
| 7440.000                                              | 39.61                   | 2.64           | 40.48                      | 74                 | -33.52         | peak       |
| 7440.000                                              | 29.87                   | 2.64           | 31.59                      | 54                 | -22.41         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

## RESULT: PASS

### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B406      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 1 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4804.000                                              | 49.46                   | 0.08           | 49.54                      | 74                 | -24.46         | peak       |
| 4804.000                                              | 38.15                   | 0.08           | 38.23                      | 54                 | -15.77         | AVG        |
| 7206.000                                              | 42.57                   | 2.21           | 44.78                      | 74                 | -29.22         | peak       |
| 7206.000                                              | 33.68                   | 2.21           | 35.89                      | 54                 | -18.11         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B406      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 1 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4804.000                                              | 47.61                   | 0.08           | 47.69                      | 74                 | -26.31         | peak       |
| 4804.000                                              | 38.35                   | 0.08           | 38.43                      | 54                 | -15.57         | AVG        |
| 7206.000                                              | 43.59                   | 2.21           | 45.8                       | 74                 | -28.2          | peak       |
| 7206.000                                              | 31.53                   | 2.21           | 33.74                      | 54                 | -20.26         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B406      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 2 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4880.000                                              | 45.62                   | 0.14           | 45.76                      | 74                 | -28.24         | peak       |
| 4880.000                                              | 34.58                   | 0.14           | 34.72                      | 54                 | -19.28         | AVG        |
| 7320.000                                              | 43.18                   | 2.36           | 45.54                      | 74                 | -28.46         | peak       |
| 7320.000                                              | 32.15                   | 2.36           | 34.51                      | 54                 | -19.49         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B406      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 2 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4880.000                                              | 46.93                   | 0.14           | 47.07                      | 74                 | -26.93         | peak       |
| 4880.000                                              | 39.45                   | 0.14           | 39.59                      | 54                 | -14.41         | AVG        |
| 7320.000                                              | 41.33                   | 2.36           | 43.69                      | 74                 | -30.31         | peak       |
| 7320.000                                              | 32.56                   | 2.36           | 34.92                      | 54                 | -19.08         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B406      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 3 | <b>Antenna</b>           | Horizontal     |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4960.000                                              | 46.23                   | 0.22           | 46.45                      | 74                 | -27.55         | peak       |
| 4960.000                                              | 38.14                   | 0.22           | 38.36                      | 54                 | -15.64         | AVG        |
| 7440.000                                              | 42.16                   | 2.64           | 44.8                       | 74                 | -29.2          | peak       |
| 7440.000                                              | 31.59                   | 2.64           | 34.23                      | 54                 | -19.77         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

|                    |        |                          |                |
|--------------------|--------|--------------------------|----------------|
| <b>EUT</b>         | u-blox | <b>Model Name</b>        | NINA-B406      |
| <b>Temperature</b> | 25° C  | <b>Relative Humidity</b> | 55.4%          |
| <b>Pressure</b>    | 960hPa | <b>Test Voltage</b>      | Normal Voltage |
| <b>Test Mode</b>   | Mode 3 | <b>Antenna</b>           | Vertical       |

| Frequency<br>(MHz)                                    | Meter Reading<br>(dBμV) | Factor<br>(dB) | Emission Level<br>(dBμV/m) | Limits<br>(dBμV/m) | Margin<br>(dB) | Value Type |
|-------------------------------------------------------|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 4960.000                                              | 45.61                   | 0.22           | 45.83                      | 74                 | -28.17         | peak       |
| 4960.000                                              | 36.48                   | 0.22           | 36.7                       | 54                 | -17.3          | AVG        |
| 7440.000                                              | 40.44                   | 2.64           | 43.08                      | 74                 | -30.92         | peak       |
| 7440.000                                              | 31.92                   | 2.64           | 34.56                      | 54                 | -19.44         | AVG        |
|                                                       |                         |                |                            |                    |                |            |
|                                                       |                         |                |                            |                    |                |            |
| Remark:                                               |                         |                |                            |                    |                |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |                         |                |                            |                    |                |            |

## RESULT: PASS

### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/






# TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS


## Antenna 1

|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd


Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Vertical       |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Vertical       |

PK



AV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/







## Antenna 2

|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Horizontal     |

## PK



## AV



**RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd


Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Vertical       |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Vertical       |

PK



AV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/







### Antenna 3

|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Horizontal     |

### PK



### AV



**RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd


Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Vertical       |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Vertical       |

PK



AV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/







#### Antenna 4

|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Vertical       |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B400      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Vertical       |

PK



AV



**RESULT: PASS**

**Note:** The factor had been edited in the “Input Correction” of the Spectrum Analyzer.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/






|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B406      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B406      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 1 | Antenna           | Vertical       |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B406      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Horizontal     |

PK



AV



RESULT: PASS


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/




|             |        |                   |                |
|-------------|--------|-------------------|----------------|
| EUT         | u-blox | Model Name        | NINA-B406      |
| Temperature | 25° C  | Relative Humidity | 55.4%          |
| Pressure    | 960hPa | Test Voltage      | Normal Voltage |
| Test Mode   | Mode 3 | Antenna           | Vertical       |

PK



AV



**RESULT: PASS**

**Note:** The factor had been edited in the “Input Correction” of the Spectrum Analyzer.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





## 12. FCC LINE CONDUCTED EMISSION TEST


### 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency     | Maximum RF Line Voltage |                |
|---------------|-------------------------|----------------|
|               | Q.P.( dBuV)             | Average( dBuV) |
| 150kHz~500kHz | 66-56                   | 56-46          |
| 500kHz~5MHz   | 56                      | 46             |
| 5MHz~30MHz    | 60                      | 50             |

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST


1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipment received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC 3.3V power from control board which received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.



**12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST****Model: NINA-B400****Line Conducted Emission Test Line 1-L****MEASUREMENT RESULT**

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.158000         | 49.30         | 11.3         | 66            | 16.3         | QP       | L1   |
| 0.194000         | 42.60         | 11.3         | 64            | 21.3         | QP       | L1   |
| 0.226000         | 38.90         | 11.3         | 63            | 23.7         | QP       | L1   |
| 0.250000         | 37.80         | 11.3         | 62            | 24.0         | QP       | L1   |
| 0.310000         | 32.40         | 11.3         | 60            | 27.6         | QP       | L1   |
| 0.606000         | 28.10         | 11.3         | 56            | 27.9         | QP       | L1   |

**MEASUREMENT RESULT**

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.158000         | 35.30         | 11.3         | 56            | 20.3         | AV       | L1   |
| 0.186000         | 30.80         | 11.3         | 54            | 23.4         | AV       | L1   |
| 0.218000         | 27.30         | 11.3         | 53            | 25.6         | AV       | L1   |
| 0.250000         | 24.20         | 11.3         | 52            | 27.6         | AV       | L1   |
| 0.310000         | 22.10         | 11.3         | 50            | 27.9         | AV       | L1   |
| 0.598000         | 21.00         | 11.3         | 46            | 25.0         | AV       | L1   |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std &amp; Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



## Line Conducted Emission Test Line 2-N



## MEASUREMENT RESULT

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.162000         | 48.90         | 11.3         | 65            | 16.5         | QP       | N    |
| 0.174000         | 47.20         | 11.3         | 65            | 17.6         | QP       | N    |
| 0.218000         | 43.70         | 11.3         | 63            | 19.2         | QP       | N    |
| 0.266000         | 33.00         | 11.3         | 61            | 28.2         | QP       | N    |
| 0.310000         | 30.60         | 11.3         | 60            | 29.4         | QP       | N    |
| 0.590000         | 30.10         | 11.3         | 56            | 25.9         | QP       | N    |

## MEASUREMENT RESULT

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.166000         | 32.40         | 11.3         | 55            | 22.8         | AV       | N    |
| 0.174000         | 33.20         | 11.3         | 55            | 21.6         | AV       | N    |
| 0.218000         | 26.00         | 11.3         | 53            | 26.9         | AV       | N    |
| 0.262000         | 15.50         | 11.3         | 51            | 35.9         | AV       | N    |
| 0.310000         | 18.90         | 11.3         | 50            | 31.1         | AV       | N    |
| 0.574000         | 17.70         | 11.3         | 46            | 28.3         | AV       | N    |

## RESULT: PASS

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd


Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





**Model: NINA-B406**  
**Line Conducted Emission Test Line 1-L**



**MEASUREMENT RESULT**

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.162000         | 44.50         | 10.8         | 65            | 20.9         | QP       | L1   |
| 0.226000         | 36.10         | 10.9         | 63            | 26.5         | QP       | L1   |
| 0.606000         | 25.20         | 10.7         | 56            | 30.8         | QP       | L1   |
| 4.030000         | 31.40         | 11.6         | 56            | 24.6         | QP       | L1   |
| 13.802000        | 29.50         | 12.1         | 60            | 30.5         | QP       | L1   |
| 24.986000        | 20.50         | 12.7         | 60            | 39.5         | QP       | L1   |

**MEASUREMENT RESULT**


| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.186000         | 24.80         | 10.9         | 54            | 29.4         | AV       | L1   |
| 0.226000         | 22.50         | 10.9         | 53            | 30.1         | AV       | L1   |
| 0.606000         | 19.50         | 10.7         | 46            | 26.5         | AV       | L1   |
| 4.030000         | 19.70         | 11.6         | 46            | 26.3         | AV       | L1   |
| 13.650000        | 18.50         | 12.1         | 50            | 31.5         | AV       | L1   |
| 24.986000        | 15.40         | 12.7         | 50            | 34.6         | AV       | L1   |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



### Line Conducted Emission Test Line 2-N



### MEASUREMENT RESULT

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.158000         | 42.80         | 10.3         | 66            | 22.8         | QP       | N    |
| 0.214000         | 29.60         | 10.3         | 63            | 33.4         | QP       | N    |
| 0.258000         | 28.50         | 10.2         | 62            | 33.0         | QP       | N    |
| 0.310000         | 21.50         | 10.2         | 60            | 38.5         | QP       | N    |
| 0.410000         | 22.90         | 10.4         | 58            | 34.7         | QP       | N    |
| 3.998000         | 36.20         | 11.1         | 56            | 19.8         | QP       | N    |

### MEASUREMENT RESULT

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line |
|------------------|---------------|--------------|---------------|--------------|----------|------|
| 0.158000         | 15.90         | 10.3         | 56            | 39.7         | AV       | N    |
| 0.210000         | 12.20         | 10.3         | 53            | 41.0         | AV       | N    |
| 0.262000         | 11.70         | 10.2         | 51            | 39.7         | AV       | N    |
| 0.310000         | 9.70          | 10.2         | 50            | 40.3         | AV       | N    |
| 0.418000         | 15.50         | 10.5         | 48            | 32.0         | AV       | N    |
| 3.998000         | 24.00         | 11.1         | 46            | 22.0         | AV       | N    |

### RESULT: PASS

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/





## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### RADIATED EMISSION TEST SETUP BELOW 1GHZ



### RADIATED EMISSION TEST SETUP ABOVE 1GHZ



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



### CONDUCTED EMISSION TEST SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>





## APPENDIX B: PHOTOGRAPHS OF EUT

Refer to Attached file (APPENDIX I).

----END OF REPORT----

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agc-cert.com](mailto:agc@agc-cert.com) Web: <http://cn.agc-cert.com/>



## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. The non-CMA report issued by AGC is only permitted to be used by the client as internal reference use and shall not be used for public demonstration purpose.
5. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
6. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
7. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
9. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
10. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc@agc-cert.com](mailto:agc@agc-cert.com).

