

InterLab®

RF Exposure and Maximum ERP/EIRP Assessment

For

GPRS/ Cat-M1

SARA-R422M8S / SARA-R422S / SARA-R422

FCC ID: XPYUBX20VA01

IC: 8595A-UBX20VA01

Assessment Reference: MDE_UBLOX_2005_MPE_03_rev01

Test Laboratory:

7layers GmbH
Borsigstraße 11
40880 Ratingen
Germany

Note:
The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7layers GmbH
Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350
www.7layers.com

Registergericht registered in:
Geschäftsführer /
Managing Directors:
Frank Spiller
Bernhard Retka
Alexandre Norré-Oudard

Düsseldorf, HRB 75554
USt-IdNr VAT No.:
DE203159652
TAX No. 147/5869/0385
A Bureau Veritas Group Company



Table of Contents

0	Summary	3
0.1	Technical Report Summary	3
1	Administrative Data	4
1.1	Testing Laboratory	4
1.2	Project Data	4
1.3	Applicant Data	4
1.4	Manufacturer Data	4
2	Test object Data	5
2.1	General EUT Description	5
2.2	EUT Main components	5
2.3	Ancillary Equipment	5
2.4	Auxiliary Equipment	6
3	Evaluation Results	7
3.1	Maximum ERP / EIRP	7
3.2	RF Exposure Evaluation for Module	8

0 Summary

0.1 Technical Report Summary

Type of Report

RF Exposure and Maximum ERP/EIRP Assessment

Applicable FCC and ISED Rules

For RF Exposure:

OET Bulletin 65 Edition 97-01 August 1997

FCC 47 CFR §1.1307

FCC 47 CFR §1.1310

ISED RSS-102 Issue 5 – March 2015

For Maximum ERP/EIRP:

FCC 47 CFR §22.913

ISED RSS-132, Issue 3

FCC 47 CFR §24.232

ISED RSS-133 Issue 6, Amendment 1

FCC 47 CFR §27.50 (b), (c), (d)

ISED RSS-139, Issue 2 / SRSP-513, RSS-130, Issue 3

FCC 47 CFR §90.635

ISED RSS-140, Issue 1

Report version control			
Rev Version	Release date	Changes	Version validity
-	05.02.2021	Initial version	invalid
Rev01	11.03.2021	E.R.P limits have been changed	valid

Responsible for
Accreditation Scope:

M. Müller

Responsible
for Report:

S. Pan



7 layers GmbH, Borsigstr. 11
40880 Ratingen, Germany
Phone +49 (0)2102 749 0

1 Administrative Data

1.1 Testing Laboratory

Company Name: 7layers GmbH

Address Borsigstr. 11
40880 Ratingen
Germany

FCC accreditation Designation Number: DE0015
Test Firm Registration #: 929146

Industry Canada Test Site Acceptance CAB identifier: DE0007
Test Firm Registration #: 3699A

The test facility is also accredited by the following accreditation organisation:

Laboratory accreditation no.: DAkkS D-PL-12140-01-01
DAkkS D-PL-12140-01-02
DAkkS D-PL-12140-01-03

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka
Dipl.-Ing. Robert Machulec
Dipl.-Ing. Andreas Petz
Dipl.-Ing. Marco Kullik

Report Template Version: 2020-03-26

1.2 Project Data

Responsible for assessment and report: Mr. Roseelan Sathiyaseelan

Date of Report: 11.03.2021

1.3 Applicant Data

Company Name: u-blox AG

Address: Zürcherstrasse 68,
CH-8800 Thalwil
Switzerland

Contact Person: Giulio Comar

1.4 Manufacturer Data

Company Name: please see applicant data

Address:

Contact Person:

2 Test object Data

2.1 General EUT Description

Equipment under Test	SARA-R422M8S / SARA-R422S / SARA-R422
Kind of Device:	LTE CAT-M1 / NB-IoT / GPRS module
FCC ID:	XPYUBX20VA01
IC:	8595A-UBX20VA01

General product description:

The EUT is Cellular radio module supporting LTE CAT-M1 / NB-IoT / GPRS module.

2.2 EUT Main components

Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	HW Status	SW Status
EUT A Code: DE1015120	SARA-R422M8S	360DA1	00.06
EUT A Code: DE1015129	SARA-R422S	360DB0	00.04
EUT A Code: DE1015129	SARA-R422	360DB0	00.04

Remark: EUT A is equipped with a temporary antenna connector. The Module is not sold with a predefined antenna.

NOTE: The short description is used to simplify the identification of the EUT in this test report.

2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless, Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	HW Status	SW Status	Serial no.	FCC ID
NA					—	

2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless, Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
N/A					—	—

3 Evaluation Results

3.1 Maximum ERP / EIRP

Standard	Frequency Band
FCC 47 CFR §22.913 ISED RSS-132, Issue 3	GSM 850/eFDD5/eFDD26
FCC 47 CFR §24.232 ISED RSS-133 Issue 6	GSM 1900/eFDD2/eFDD25
FCC 47 CFR §27.50(d) ISED RSS-139, Issue 3	eFDD4/eFDD66
FCC 47 CFR §27.50(c) ISED RSS-130, Issue 3	eFDD12
FCC 47 CFR §27.1507(a)	eFDD8
FCC 47 CFR §27.50(b) ISED RSS-130, Issue 3	eFDD13
FCC 47 CFR §90.635	eFDD26

3.1.1 Test Limits

For the 850MHz band, FCC §22.913 states that the maximum ERP of this device shall not exceed 7 Watts. IC SRSP-503 Issue 7, states that this device shall not exceed a maximum EIRP of 11.5 Watts

For the purposes of this test report, the 7 Watt ERP limit stipulated in FCC §22.913 has been converted to an equivalent EIRP value of 11.5 Watts.

For all other limits, refer to the values stipulated in the corresponding tables.

3.1.2 Test Protocol

Maximum antenna gain to comply with EIRP limits for FCC and Industry Canada

Band	Mode	Duty Cycle	Frequency Range (MHz)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	FCC EIRP limit (mW)	Maximum antenna gain to meet EIRP Limit (dBi)
850	GSM	12.5%	824.2 - 848.8	32.25	1678.804	11500	8.4
850	EDGE	50.0%	824.2 - 848.8	28	630.957344	11500	12.6
1900	GSM	12.5%	1850.2 - 1909.8	29.05	803.52612	2000	4.0
1900	EDGE	50.0%	1850.2 - 1909.8	26.89	488.652359	2000	6.1
eFDD 2	Cat-M1	100.0%	1850-1910	22.81	190.985326	2000	10.2
eFDD 4	Cat-M1	100.0%	1710-1755	22.86	193.196832	1000	7.1
eFDD 5	Cat-M1	100.0%	824 - 849	22.67	184.926862	11500	17.9
eFDD 13	Cat-M1	100.0%	777-787	22.86	193.196832	3000	11.9
eFDD 12	Cat-M1	100.0%	699-716	22.79	190.107828	3000	12.0
eFDD 66	Cat-M1	100.0%	1710-1780	22.74	187.931682	1000	7.3
eFDD 25	Cat-M1	100.0%	1850-1915	22.99	199.067334	2000	10.0
eFDD 26	Cat-M1	100.0%	814-849	22.83	191.866874	11500	17.8
eFDD 8	Cat-M1	100.0%	898-890	22.83	191.866874	3000	11.9

3.1.3 Conclusion

Band	Max gain to be used to comply with EIRP Limits	Max gain to be used to comply with FCC MPE Limits	Max gain to be used to comply with IC MPE Limits	Maximum gain to be compliant with all limits
850 GSM	8.4	9.9	6.7	6.7
850 EDGE	12.6	9.9	6.7	6.7
1900 GSM	4.0	20.2	16.6	4.0
1900 EDGE	6.1	20.2	8.5	8.5
eFDD 2	10.2	12.0	8.5	8.5
eFDD 4	7.1	12.0	8.3	7.1
eFDD 5	17.9	9.4	6.1	6.1
eFDD 13	11.9	9.2	6.0	6.0
eFDD 12	12.0	8.7	5.6	5.6
eFDD 66	7.3	12.0	8.3	7.3
eFDD 25	10.0	12.9	8.5	8.5
eFDD 26	17.8	9.4	6.1	6.1
eFDD 8	11.9	9.8	NA	9.8

Antenna Gain in dbi

3.2 RF Exposure Evaluation for Module

Standards
OET Bulletin 65 Edition 97-01 August 1997
RSS-102 Issue 5 – March 2015

3.2.1 Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)
300 – 6000	0.02619 f ^{0.6834}	mW/cm ² = W/m ² * 0.1

$$\text{Equation OET bulletin 65, page 18, edition 97-01: } S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3.2.2 Test Protocol

Maximum antenna gain to comply with MPE limits for Industry Canada

Band	Mode	Duty Cycle	Frequency (MHz)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm ²)	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
850	GSM	12.5%	824.2	33.5	2238.72	279.90	0.2576	6.7	20
850	EDGE	50.0%	824.2	28.0	630.96	78.89	0.2576	12.2	20
1900	GSM	12.5%	1850.7	26.0	398.11	49.77	0.4477	16.6	20
1900	EDGE	50.0%	1850.7	27.0	501.19	62.66	0.4477	15.6	20
eFDD 2	Cat-M1	100%	1850.7	25.0	316.23	316.23	0.4477	8.5	20
eFDD 4	Cat-M1	100%	1710.7	25.0	316.23	316.23	0.4243	8.3	20
eFDD 5	Cat-M1	100%	824.7	25.0	316.23	316.23	0.2577	6.1	20
eFDD 13	Cat-M1	100%	779.5	25.0	316.23	316.23	0.2480	6.0	20
eFDD 12	Cat-M1	100%	699.7	25.0	316.23	316.23	0.2303	5.6	20
eFDD 66	Cat-M1	100%	1710.7	25.0	316.23	316.23	0.4243	8.3	20
eFDD 25	Cat-M1	100%	1850.7	25.0	316.23	316.23	0.4477	8.5	20
eFDD 26	Cat-M1	100%	824.7	25.0	316.23	316.23	0.2577	6.1	20

Maximum antenna gain to comply with MPE limits for FCC

Band	Mode	Duty Cycle	Frequency (MHz)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm ²)	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
850	GSM	12.5%	824.2	33.5	2238.72	279.90	0.5495	9.9	20
850	EDGE	50.0%	824.2	28	630.96	78.89	0.5495	15.4	20
1900	GSM	12.5%	1850.7	26	398.11	49.77	1.0000	20.0	20
1900	EDGE	50.0%	1850.7	27	501.19	62.66	1.0000	19.0	20
eFDD 2	Cat-M1	100.0%	1850.7	25	316.23	316.23	1.0000	12.0	20
eFDD 4	Cat-M1	100.0%	1710.7	25	316.23	316.23	1.0000	12.0	20
eFDD 5	Cat-M1	100.0%	824.7	25	316.23	316.23	0.5498	9.4	20
eFDD 13	Cat-M1	100.0%	777.0	25	316.23	316.23	0.5197	9.2	20
eFDD 12	Cat-M1	100.0%	699.7	25	316.23	316.23	0.4665	8.7	20
eFDD 66	Cat-M1	100.0%	1710.7	25	316.23	316.23	1.0000	12.0	20
eFDD 25	Cat-M1	100.0%	1850.7	25	316.23	316.23	1.2338	12.9	20
eFDD 26	Cat-M1	100.0%	824.7	25	316.23	316.23	0.5498	9.4	20
eFDD 8	Cat-M1	100.0%	898.2	25	316.23	316.23	0.5988	9.8	20

3.2.3 Conclusion

Band	Max gain for FCC MPE Limits	Max gain for Industry Canada MPE Limits	Maximum gain to be compliant with all MPE limits
850 GSM	9.9	6.7	6.7
850 EDGE	15.4	12.2	12.2
1900 GSM	20.2	16.6	16.6
1900 EDGE	19.0	15.6	15.6
eFDD 2	12.0	8.5	8.5
eFDD 4	12.0	8.3	8.3
eFDD 5	9.4	6.1	6.1
eFDD 13	9.2	6.0	6.0
eFDD 12	8.7	5.6	5.6
eFDD 66	12.0	8.3	8.3
eFDD 25	12.9	8.5	8.5
eFDD 26	9.4	6.1	6.1
eFDD 8	9.8	NA	9.8

Gain expressed in dBi