

FCC Radio Test Report FCC ID: XQBFLR24

This report concerns (check one) : Original Grant Class I Change

Issued Date : Sep. 21, 2009 **Project No.** : R0909003

Equipment: High Powered IEEE 802.11bg miniPCI

Module

Model Name: FLR24G30

Applicant: Xagyl Communications

Address: 570 Industrial Avenue, Unit 10 Ottawa,

ON, K1G 0Y9 Canada

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Test:

Sep. 09, 2009 ~ Sep. 11, 2009

Testing Engineer

(Rush Kao)

Technical Manager

(Jeff Yang

Authorized Signatory

(Andy Chiu

Neutron Engineering Inc.

B1, No. 37, Lane 365, YangGuang St. NeiHu District 114, Taipei, Taiwan.

TEL: +886-2-2657-3299 FAX: +886-2-2657-3331









Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: NEI-FCCP-1-R0909003 Page 2 of 78

Table of Contents	Page
1. CERTIFICATION	5
2 . SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 11
3.4 DESCRIPTION OF SUPPORT UNITS	12
4 . EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION	13
4.1.2 MEASUREMENT INSTRUMENTS LIST	13
4.1.3 TEST PROCEDURE	14
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP 4.1.6 EUT OPERATING CONDITIONS	14 15
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	18
4.2.1 RADIATED EMISSION LIMITS	18
4.2.2 MEASUREMENT INSTRUMENTS LIST	19
4.2.3 TEST PROCEDURE	19
4.2.4 DEVIATION FROM TEST STANDARD	19
4.2.5 TEST SETUP	20
4.2.6 EUT OPERATING CONDITIONS	20
4.2.7 TEST RESULTS-BETWEEN 30MHZ - 1000MHZ 4.2.8 TEST RESULTS - ABOVE 1000MHZ	21
4.2.9 TEST RESULTS - ABOVE TOUDMINZ 4.2.9 TEST RESULTS-RESTRICTED BANDS REQUIREMENTS	23 47
5 . BANDWITH TEST	55
5.1 APPLIED PROCEDURES / LIMIT	55
5.1.1 MEASUREMENT INSTRUMENTS LIST	55
5.1.2 TEST PROCEDURE	55
5.1.3 DEVIATION FROM STANDARD	55
5.1.4 TEST SETUP	55
5.1.5 EUT OPERATION CONDITIONS	55
5.1.6 TEST RESULTS	56

Report No.: NEI-FCCP-1-R0909003 Page 3 of 78

Table of Contents	Page
6 . PEAK OUTPUT POWER TEST	60
6.1 APPLIED PROCEDURES / LIMIT	60
6.1.1 MEASUREMENT INSTRUMENTS LIST	60
6.1.2 TEST PROCEDURE	60
6.1.3 DEVIATION FROM STANDARD	60
6.1.4 TEST SETUP	60
6.1.5 EUT OPERATION CONDITIONS 6.1.6 TEST RESULTS	60 61
	-
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	62
7.1 APPLIED PROCEDURES / LIMIT	62
7.1.1 MEASUREMENT INSTRUMENTS LIST	62
7.1.2 TEST PROCEDURE	62
7.1.3 DEVIATION FROM STANDARD	62
7.1.4 TEST SETUP 7.1.5 EUT OPERATION CONDITIONS	62 62
7.1.6 TEST RESULTS	63
8 . POWER SPECTRAL DENSITY TEST	67
8.1 APPLIED PROCEDURES / LIMIT	67
8.1.1 MEASUREMENT INSTRUMENTS LIST	67
8.1.2 TEST PROCEDURE	67
8.1.3 DEVIATION FROM STANDARD	67
8.1.4 TEST SETUP 8.1.5 EUT OPERATION CONDITIONS	67 67
8.1.6 TEST RESULTS	68
9 . RF EXPOSURE TEST	72
9.1 APPLIED PROCEDURES / LIMIT	72
9.1.1 MEASUREMENT INSTRUMENTS LIST	72
9.1.2 MPE CALCULATION METHOD	72
9.1.3 DEVIATION FROM STANDARD	73
9.1.4 TEST SETUP	73
9.1.5 EUT OPERATION CONDITIONS 9.1.6 TEST RESULTS - CHIP	73 74
10. EUT TEST PHOTO	75

Report No.: NEI-FCCP-1-R0909003 Page 4 of 78

1. CERTIFICATION

Equipment: High Powered IEEE 802.11bg miniPCI Module

Brand Name: N/A

Model Name: FLR24G30

Applicant: Xagyl Communications

Date of Test: Sep. 09, 2009 ~ Sep. 11, 2009

Standards: FCC Part15, Subpart C / ANCI C63.4: 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-R0909003) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: NEI-FCCP-1-R0909003 Page 5 of 78

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

	FCC Part15, Subpart C							
Standard Section FCC	Test Item Judgment Ren							
15.207	Conducted Emission	Conducted Emission PASS						
15.247 (c)	Antenna conducted Spurious Emission	PASS						
15.247 (a)(2)	6dB Bandwidth	PASS						
15.247 (b)	Peak Output Power	PASS						
15.247 (c)	Radiated Spurious Emission	PASS						
15.247 (d)	Power Spectral Density	PASS						
15.203	Antenna Requirement	PASS						
1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	PASS						

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Report No.: NEI-FCCP-1-R0909003 Page 6 of 78

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **CB08(FCC R.N.: 614388)** at the location of 1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % \circ

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)	NOTE
OS-01	ANSI	30MHz ~ 200MHz	V	2.86	
		30MHz ~ 200MHz	Н	2.56	
		200MHz ~ 1,000MHz	V	2.88	
		200MHz ~ 1,000MHz	Н	2.98	
OS-02	ANSI	30MHz ~ 200MHz	V	2.48	
		30MHz ~ 200MHz	Н	2.16	
		200MHz ~ 1,000MHz	V	2.50	
		200MHz ~ 1,000MHz	Н	2.66	

Report No.: NEI-FCCP-1-R0909003 Page 7 of 78



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	High Powered IEEE 802.11bg miniPCI Module			
Brand Name	N/A			
Model Name	FLR24G30			
OEM Brand/Model Name	N/A			
Model Difference	N/A			
	The EUT is a High Pow Module.	vered IEEE 802.11bg miniPCI		
	Operation Frequency:	2412~2462 MHz		
	Modulation Type:	802.11b:CCK, DQPSK, DBPSK 802.11g:OFDM		
	Bit Rate of Transmitter:	802.11b: 11/5.5/2/1 Mbps		
		802.11g:		
Doe doest December in		54/48/36/24/18/12/9/6 Mbps		
Product Description	Number Of Channel:	11CH .Please see Note 2.		
	Antenna Designation:	Please see Note 3.		
	Antenna Gain(Peak):			
	Output Power(Max):	802.11b: 18.21dBm (Max.) 802.11g: 29.23dBm (Max.)		
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.			
Channel List	Please refer to the Note 2.			
Power Source	Supplied from miniPCI Slot.			
Power Rating	N/A			
Connecting I/O Port(s)	Please refer to the Use	er's Manual		
Products Covered	Antenna: Please refer	to the Note 3.		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Report No.: NEI-FCCP-1-R0909003 Page 8 of 78



2. CH 01 – CH 11 for 802.11b, 802.11g

	Channel List						
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)		
01	2412	05	2432	09	2452		
02	2417	06	2437	10	2457		
03	2422	07	2442	11	2462		
04	2427	08	2447				

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Dipole	UFL	2.0

4 The EUT incorporates SISO function. Physically, the EUT provides two completed transmitters and three receivers (1T1R)

Modulated type	TX Function
802.11b	1TX
802.11g	1TX

Report No.: NEI-FCCP-1-R0909003 Page 9 of 78

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Test Mode	TX	RX	Description
Mode 1	٧		802.11b/CH01, CH06, CH11
Mode 2	٧		802.11g/CH01, CH06, CH11

For Conducted Test					
Final Test Mode	TX	RX	Description		
Mode 1	٧		802.11b/CH06		

For Radiated Test < 1GHz					
Final Test Mode	TX	RX	Description		
Mode 1	٧		802.11b/CH06		


For Radiated Test > 1GHz					
Final Test Mode TX RX Description					
Mode 1	٧		802.11b/CH01, CH06, CH11		
Mode 2	٧		802.11g/CH01, CH06, CH11		

For Antenna Port Conducted Measurement					
Final Test Mode TX RX Description					
Mode 1	٧		802.11b/CH01, CH06, CH11		
Mode 2	٧		802.11g/CH01, CH06, CH11		

Report No.: NEI-FCCP-1-R0909003 Page 10 of 78



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



Report No.: NEI-FCCP-1-R0909003 Page 11 of 78

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	High Powered IEEE 802.11bg miniPCI Module	N/A	FLR24G30	XQBFLR24	N/A	EUT
E-2	PC	DELL	DIMENSION2400	DOC	0Y09197082160FN	
E-3	19" LCD Monitor	ACER	X193HQ	DOC	92203073185	
E-4	USB K/B	DELL	SK-8115	DOC	ODJ3257161693R07EF	
E-5	Comfort Optical Mouse 3000	Microsoft	1043	DOC	7687300022052	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	YES	NO	0.1M	ANT cable
C-2	YES	YES	1.8M	Monitor VGA cable
C-3	YES	YES	1.7M	Mouse USB cable
C-4	YES	YES	2.0M	Keyboard USB cable

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.

Report No.: NEI-FCCP-1-R0909003 Page 12 of 78

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A	(dBuV)	Class B (dBuV)	
PREQUENCY (MITZ)	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Cable	N/A	SR03_C_01 &02	N/A	Aug. 18, 2010
2	LISN	EMCO	3816/2	00042991	Jan. 21, 2010
3	Pulse Limiter	Electro-Metrics	EM-7600	112644	Dec. 28, 2009
4	50Ω BNC TYPE Terminator	N/A	N/A	01	May 25, 2011
5	EMI Test Receiver	R&S	ESCI	100082	Mar. 17, 2010
6	LISN	EMCO	4825/2	00028234	Jul. 13, 2010

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Report No.: NEI-FCCP-1-R0909003 Page 13 of 78


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Report No.: NEI-FCCP-1-R0909003 Page 14 of 78



Report No.: NEI-FCCP-1-R0909003 Page 15 of 78


4.1.7 TEST RESULTS

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b/CH06		

Freq.	Terminal	Measured(dBuV)		Limits(dBuV)		Margin	Note
(MHz)	L/N	QP-Mode	AV-Mode	QP-Mode	AV-Mode	(dB)	NOLE
0.18	Line	50.83	*	64.71	54.71	-13.88	(QP)
0.23	Line	37.67	*	62.41	52.41	-24.74	(QP)
0.58	Line	34.71	*	56.00	46.00	-21.29	(QP)
1.09	Line	35.59	*	56.00	46.00	-20.41	(QP)
16.30	Line	40.86	*	60.00	50.00	-19.14	(QP)
18.35	Line	38.12	*	60.00	50.00	-21.88	(QP)

Remark

- (1) Reading in which marked as QP means measurements by using are Quasi-Peak Mode with Detector BW=9KHz;SPA setting in RBW=10KHz,VBW =10KHz, Swp. Time = 0.3 sec./MHz∘ Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW=1MHz,VBW=10Hz, Swp. Time =0.3 sec./MHz∘
- (2) All readings are QP Mode value unless otherwise stated AVG in column of Note ... If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform In this case, a " * " marked in AVG Mode column of Interference Voltage Measured •
- (3) Measuring frequency range from 150KHz to 30MHz \circ




Report No.: NEI-FCCP-1-R0909003 Page 16 of 78



EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b/CH06		

Freq.	Terminal	Measured(dBuV)		Limits(dBuV)		Margin	Note
(MHz)	L/N	QP-Mode	AV-Mode	QP-Mode	AV-Mode	(dB)	NOLE
0.17	Neutral	47.51	*	64.74	54.74	-17.23	(QP)
0.64	Neutral	35.17	*	56.00	46.00	-20.83	(QP)
0.87	Neutral	35.69	*	56.00	46.00	-20.31	(QP)
1.16	Neutral	35.62	*	56.00	46.00	-20.38	(QP)
12.20	Neutral	34.75	*	60.00	50.00	-25.25	(QP)
16.30	Neutral	41.50	*	60.00	50.00	-18.50	(QP)

- (1) Reading in which marked as QP means measurements by using are Quasi-Peak Mode with Detector BW=9KHz;SPA setting in RBW=10KHz,VBW =10KHz, Swp. Time = 0.3 sec./MHz ∘ Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW=1MHz,VBW=10Hz, Swp. Time =0.3 sec./MHz ∘
- (2) All readings are QP Mode value unless otherwise stated AVG in column of Note ... If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform on this case, a " * " marked in AVG Mode column of Interference Voltage Measured on the North AVG Mode column of Interference Voltage Measured on
- (3) Measuring frequency range from 150KHz to 30MHz o



Report No.: NEI-FCCP-1-R0909003 Page 17 of 78

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBu	ıV/m) (at 3m)	Class B (dBuV/m) (at 3m)		
	PEAK	AVERAGE	PEAK	AVERAGE	
Above 1000	80	60	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Report No.: NEI-FCCP-1-R0909003 Page 18 of 78

4.2.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LogBicon Ant	Schwarzbeck	VULB9168-352	9168-352	Jun. 17, 2010
2	Test Cable	N/A	966_12M	1(12M)	Jun. 18, 2010
3	Test Cable	N/A	966_3M	1(10M)	Jun. 18, 2010
4	Pre-Amplifier	EMC	EMC-330	980001	Jun. 04, 2010
5	Spectrum Analyzer	R&S	FSP30	100854	Apr. 16, 2010
6	EMI Measuring Receiver	SHCAFFNER	SCR 3501	408	Nov. 24.2009
7	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010
8	Horn Ant	Schwarzbeck	BBHA-9120	D-546	Jun. 17, 2010
9	Pre-Amplifier	Agilent	8449B	3008A01714	Apr. 20, 2010
10	Microflex Cable	N/A	1M	N/A	May. 20, 2010
11	Microflex Cable	AISI	S104-SMAP-1	S104-SMAP-1	Aug. 23, 2010
12	Microflex Cable	N/A	3M	3M	Aug. 23, 2010

Remark: "N/A" denotes No Model Name / Serial No. and No Calibration specified.

4.2.3 TEST PROCEDURE

- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m or 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

Report No.: NEI-FCCP-1-R0909003 Page 19 of 78




4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **4.1.6** Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-R0909003 Page 20 of 78


4.2.7 TEST RESULTS-BETWEEN 30MHZ - 1000MHZ

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b/CH06		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
119.24	V	62.58	-20.70	41.88	43.50	- 1.62	(QP)
144.46	V	50.66	-18.81	31.85	43.50	- 11.65	(QP)
249.22	V	46.88	-20.81	26.07	46.00	- 19.93	(QP)
359.80	V	51.18	-18.01	33.17	46.00	- 12.83	(QP)
720.64	V	42.01	-10.72	31.29	46.00	- 14.71	(QP)
912.70	V	42.16	-8.43	33.73	46.00	- 12.27	(QP)

Remark:

- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency \circ "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (4) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission •
- (5) Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.




Report No.: NEI-FCCP-1-R0909003 Page 21 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b/CH06		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
119.24	Н	56.41	-20.70	35.71	43.50	- 7.79	(QP)
144.46	Н	53.08	-18.81	34.27	43.50	- 9.23	(QP)
216.24	Н	48.33	-22.00	26.33	46.00	- 19.67	(QP)
249.22	Н	56.86	-20.81	36.05	46.00	- 9.95	(QP)
375.32	Н	53.90	-17.65	36.25	46.00	- 9.75	(QP)
912.70	Н	43.34	-8.43	34.91	46.00	- 11.09	(QP)

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ∘
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency of "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (4) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission •
- (5) Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Report No.: NEI-FCCP-1-R0909003 Page 22 of 78

4.2.8 TEST RESULTS - ABOVE 1000MHZ


EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b/CH01		

Freq.	Ant.Pol.	Read	ling	Ant./CF	A	ct.	Lir	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2385.20	\ \	29.71	22.48	31.91	61.62	54.39	74.00	54.00	X/H
2413.00	V	75.20	71.58	32.02	107.22	103.60			X/F
4824.00	V	51.59	48.36	3.75	55.34	52.11	74.00	54.00	X/H
7234.40	٧	45.66	34.91	9.02	54.68	43.93	74.00	54.00	X/H

Remark:

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 23 of 78




EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b/CH01		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2385.80	Н	23.10	14.79	31.91	55.01	46.70	74.00	54.00	X/H
2414.80	Н	66.12	62.48	32.02	98.14	94.50			X/F
4823.98	Н	47.27	41.72	3.75	51.02	45.47	74.00	54.00	X/H
7237.40	Н	45.13	33.49	9.02	54.15	42.51	74.00	54.00	X/H

- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ∘
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 25 of 78




EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b/CH06		

Freq.	Ant.Pol.	Rea	ding	Ant./CF	Α	ct.	Lir	nit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2434.40	V	72.46	69.55	32.10	104.56	101.65			X/F
4874.01	V	51.09	47.65	3.90	54.99	51.55	74.00	54.00	X/H
7312.72	V	44.51	32.65	9.15	53.66	41.80	74.00	54.00	X/H

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 27 of 78




Report No.: NEI-FCCP-1-R0909003

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b/CH06		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2436.40	Н	65.54	61.80	32.11	97.65	93.91			X/F
4873.94	Н	48.69	41.36	3.90	52.59	45.26	74.00	54.00	X/H
7310.76	Н	43.87	30.96	9.14	53.01	40.10	74.00	54.00	X/H

- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 29 of 78



Report No.: NEI-FCCP-1-R0909003 Page 30 of 78

11200.00 13750.00 16300.00 18850.00 21400.00

26500.00 MHz

20.0

1000.000 3550.00

6100.00


8650.00

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b/CH11		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2462.80	V	71.57	67.87	32.21	103.78	100.08			X/F
2488.10	V	25.65	17.31	32.30	57.95	49.61	74.00	54.00	X/H
4923.96	V	51.11	48.11	4.06	55.17	52.17	74.00	54.00	X/H
7387.08	V	44.79	33.73	9.27	54.06	43.00	74.00	54.00	X/H

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 31 of 78




Report No.: NEI-FCCP-1-R0909003

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b/CH11		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2462.80	H	62.53	58.77	32.21	94.74	90.98			X/F
2487.50	Н	22.13	13.78	32.30	54.43	46.08	74.00	54.00	X/H
4924.03	Н	46.65	40.49	4.06	50.71	44.55	74.00	54.00	X/H
7385.52	Н	45.51	32.81	9.26	54.77	42.07	74.00	54.00	X/H

- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 33 of 78



EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11g/CH01		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	38.59	19.59	31.93	70.52	51.52	74.00	54.00	X/H
2414.00	V	75.59	66.38	32.02	107.61	98.40			X/F
4824.70	V	49.02	37.09	3.75	52.77	40.84	74.00	54.00	X/H
7236.20	٧	44.86	33.55	9.02	53.88	42.57	74.00	54.00	X/H


- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 35 of 78

Neutron Engineering Inc.= Orthogonal Axis: X 802.11g/CH01 (Above 1000 MHz, Vertical) 120.0 dBuV/m 70 20.0 2362.000 2372.00 2382.00 2392.00 2402.00 2412.00 2422.00 2432.00 2442.00 120.0 dBuV/m

Limit: AVG:

2462.00 MHz




Report No.: NEI-FCCP-1-R0909003 Page 36 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11g/CH01		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	Н	31.99	14.79	31.93	63.92	46.72	74.00	54.00	X/H
2410.40	Н	67.97	59.27	32.01	99.98	91.28			X/F
4823.91	Н	43.77	32.15	3.75	47.52	35.90	74.00	54.00	X/H
235.96	Н	44.12	31.85	9.02	53.14	40.87	66.00	46.00	X/H

- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 37 of 78




Page 38 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11g/CH06		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	37.32	21.77	31.93	69.25	53.70			X/F
2434.00	V	80.89	70.35	32.10	112.99	102.45	74.00	54.00	X/H
2483.50	V	34.95	19.52	32.29	67.24	51.81	74.00	54.00	X/H
4873.80	V	58.01	45.11	3.90	61.91	49.01	74.00	54.00	X/H
7310.50	V	50.02	37.59	9.14	59.16	46.73	74.00	54.00	X/H

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ∘
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 39 of 78




Report No.: NEI-FCCP-1-R0909003


EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11g/CH06		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	I	25.45	15.57	31.93	57.38	47.50			X/F
2433.80	Н	70.80	61.40	32.10	102.90	93.50	74.00	54.00	X/H
2483.50	Н	24.79	14.13	32.29	57.08	46.42	74.00	54.00	X/H
4874.80	Н	50.90	38.15	3.91	54.81	42.06	74.00	54.00	X/H
7310.20	Н	46.13	33.28	9.14	55.27	42.42	74.00	54.00	X/H

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 41 of 78






EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11g/CH11		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2463.80	V	77.21	68.32	32.21	109.42	100.53			X/F
2483.50	V	39.56	19.22	32.29	71.85	51.51	74.00	54.00	X/H
4923.60	V	53.00	40.27	4.06	57.06	44.33	74.00	54.00	X/H
7386.10	V	48.63	36.70	9.27	57.90	45.97	74.00	54.00	X/H

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 43 of 78



Report No.: NEI-FCCP-1-R0909003


Page 44 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11g/CH11		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2460.20	I	67.93	59.55	32.20	100.13	91.75			X/F
2483.50	Н	33.86	14.17	32.29	66.15	46.46	74.00	54.00	X/H
4926.60	Н	44.97	34.40	4.07	49.04	38.47	74.00	54.00	X/H
7385.30	Н	45.25	32.23	9.26	54.51	41.49	74.00	54.00	X/H

- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (8) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.

Report No.: NEI-FCCP-1-R0909003 Page 45 of 78



4.2.9 TEST RESULTS-RESTRICTED BANDS REQUIREMENTS


EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	25°C	Relative Humidity:	43%
Test Voltage :	AC 120V/60Hz		
Test Mode :	802.11b (Vertical)		
Note:	The emission of the carrier radi (Peak and AV) as following: 1. The transmitter was then cor to transmit at the lowest char measured at 2310-2390 MH: 2. The transmitter was configur transmit at the highest chanr measured at 2483.5-2500 M	nfigured with the wor nnel (CH01). Then th z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2385.20	V	29.71	22.48	31.91	61.62	54.39	74.00	54.00	X
2488.10	V	25.65	17.31	32.30	57.95	49.61	74.00	54.00	Χ

Remark:

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (3) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-R0909003 Page 47 of 78




Report No.: NEI-FCCP-1-R0909003 Page 48 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30			
Temperature:	25°C	Relative Humidity:	43%			
Test Voltage :	AC 120V/60Hz					
Test Mode :	802.11b (Horizontal)					
Note:	The emission of the carrier radi (Peak and AV) as following: 1. The transmitter was then cor to transmit at the lowest char measured at 2310-2390 MH; 2. The transmitter was configur transmit at the highest chanr measured at 2483.5-2500 M	nfigured with the wor nnel (CH01). Then th z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to			

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2385.80	I	23.10	14.79	31.91	55.01	46.70	74.00	54.00	X
2487.50	Н	22.13	13.78	32.30	54.43	46.08	74.00	54.00	Χ

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (3) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-R0909003 Page 49 of 78




EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30		
Temperature:	25°C	Relative Humidity:	43%		
Test Voltage :	AC 120V/60Hz				
Test Mode :	802.11g (Vertical)				
Note:	The emission of the carrier radi (Peak and AV) as following: 1. The transmitter was then cor to transmit at the lowest char measured at 2310-2390 MH: 2. The transmitter was configur transmit at the highest chanr measured at 2483.5-2500 M	nfigured with the wor nnel (CH01). Then th z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to		

ſ	Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
			Peak	AV		Peak	AV	Peak	AV	Note
	(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
	2390.00	V	38.59	19.59	31.93	70.52	51.52	74.00	54.00	Х
	2483.50	V	39.56	19.22	32.29	71.85	51.51	74.00	54.00	Χ

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (3) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-R0909003 Page 51 of 78




Page 52 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30		
Temperature:	25°C	Relative Humidity:	43%		
Test Voltage :	AC 120V/60Hz				
Test Mode :	802.11g (Horizontal)				
Note:	The emission of the carrier radi (Peak and AV) as following: 1. The transmitter was then cor to transmit at the lowest char measured at 2310-2390 MH; 2. The transmitter was configur transmit at the highest chanr measured at 2483.5-2500 M	nfigured with the wor nnel (CH01). Then th z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	I	31.99	14.79	31.93	63.92	46.72	74.00	54.00	Χ
2483.50	Н	33.86	14.17	32.29	66.15	46.46	74.00	54.00	Χ

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (3) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-R0909003 Page 53 of 78



5. BANDWITH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C						
Test Item Limit Frequency Range (MHz) Result						
Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS			

5.1.1 MEASUREMENT INSTRUMENTS LIST

Iten	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

5.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

5.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing. Chip antenna measurement result.


Report No.: NEI-FCCP-1-R0909003 Page 55 of 78

5.1.6 TEST RESULTS

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b CH01, CH06, CH11		

Test Channel	Frequency (MHz)	Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	LIMIT (MHz)
CH01	2412	12.72	15.52	>=500KHz
CH06	2437	12.16	15.56	>=500KHz
CH11	2462	12.20	15.56	>=500KHz

CH01




Report No.: NEI-FCCP-1-R0909003 Page 56 of 78

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11g CH01, CH06, CH11		


Test Channel	Frequency (MHz)	Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	LIMIT (MHz)
CH01	2412	16.56	16.52	>=500KHz
CH06	2437	16.52	16.52	>=500KHz
CH11	2462	16.48	16.52	>=500KHz

CH01



Report No.: NEI-FCCP-1-R0909003 Page 58 of 78

Neutron Engineering Inc.



2 MHz/

Span 20 MHz

Center 2.462 GHz

6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

7(1 - E1ED 1 1(00ED01(E0 / E1III))					
FCC Part15, Subpart C					
Test Item Limit Frequency Range (MHz) Result					
Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS		

6.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487A	6K00004714	Feb. 10, 2010
2	Power Meter Sensor	Anritsu	MA2491A	34138	Feb. 10, 2010

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

6.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto.

6.1.3 DEVIATION FROM STANDARD

No deviation.

6.1.4 TEST SETUP

FIIT	Power Meter
EUI	Fower Meter

6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing. Chip antenna measurement result.

Report No.: NEI-FCCP-1-R0909003 Page 60 of 78

6.1.6 TEST RESULTS

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b /CH01, CH06, CH11		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH01	2412	17.90	30	1
CH06	2437	18.21	30	1
CH11	2462	15.47	30	1

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11g /CH01, CH06, CH11		

Test Channel	Frequency	Peak Output Power	LIMIT	LIMIT
103t Orlanno	(MHz)	(dBm)	(dBm)	(W)
CH01	2412	22.40	30	1
CH06	2437	29.23	30	1
CH11	2462	22.31	30	1

Remark

(1) The SISO test requirement, RF conducted output power shall measure each transmitter chain by using channel power method. And after obtain each individual transmitter chain power, then sum the output power by using the following formula: ((dBm/Chain 1)/10^Log) + ((dBm/Chain 2)/10^log) + ((dBm/ChainN)/10^log) = Combined peak output power in mW.

(2) Antenna Gain=2.0 dBi.

Report No.: NEI-FCCP-1-R0909003 Page 61 of 78

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C					
Test Item	Limit	Frequency Range (MHz)	Result		
Antenna conducted Spurious Emission	20dB less than the peak value of fundamental frequency	30-25000	PASS		

7.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

7.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

7.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing. Chip antenna measurement result.

Report No.: NEI-FCCP-1-R0909003 Page 62 of 78

7.1.6 TEST RESULTS


EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b CH01, CH11		

Channel of Worst Data: CH1,CH11				
The max. radio frequency power in any 100kHz bandwidth outside the frequency band bandwidth within the frequency band.				
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)	
2389.2 -44.09 2483.5 -46.53				
	Re	eult		

Result

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.

Report No.: NEI-FCCP-1-R0909003 Page 63 of 78



Report No.: NEI-FCCP-1-R0909003 Page 64 of 78




EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11g CH01, CH11		

Channel of Worst Data: CH1,CH11				
The max. radio frequency power in any 100kHz bandwidth outside the frequency band bandwidth within the frequency band.				
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)	
2390.0 -45.29 2485.7 -45.17				
	Re	sult		

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.

Page 65 of 78 Report No.: NEI-FCCP-1-R0909003



8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart C					
Test Item Limit Frequency Range (MHz) Result					
Power Spectral Density	•		PASS		

8.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Apr. 16, 2010

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

8.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=30KHz, Sweep time = 500s.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

8.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing. Chip antenna measurement result.


Report No.: NEI-FCCP-1-R0909003 Page 67 of 78

8.1.6 TEST RESULTS

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b CH01, CH06, CH11		


Test Channel	Frequency (MHz)	Power Density (dBm)	LIMIT (dBm)
CH01	2412	-13.13	8
CH06	2437	-12.35	8
CH11	2462	-16.04	8

CH01




Report No.: NEI-FCCP-1-R0909003 Page 68 of 78

Neutron Engineering Inc.=



CH11




Report No.: NEI-FCCP-1-R0909003

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11g CH01, CH06, CH11		


Test Channel	Frequency	Power Density	LIMIT
rest Chamilei	(MHz)	(dBm)	(dBm)
CH01	2412	-16.29	8
CH06	2437	-8.12	8
CH11	2462	-16.36	8

CH01



Report No.: NEI-FCCP-1-R0909003 Page 70 of 78

Neutron Engineering Inc.=



150 kHz/

Span 1.5 MHz

Center 2.462354 GHz



9. RF EXPOSURE TEST

9.1 APPLIED PROCEDURES / LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ²or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

9.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487A	6K00004714	Feb. 10, 2010
2	Power Meter Sensor	Anritsu	MA2491A	34138	Feb. 10, 2010

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

9.1.2 MPE CALCULATION METHOD

E (V/m)
$$=\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: Pd (W/m²) $=\frac{E^2}{377}$

 $\mathbf{E} = \text{Electric field (V/m)}$

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

Report No.: NEI-FCCP-1-R0909003 Page 72 of 78



No deviation.

9.1.4 TEST SETUP

EUT	SPECTRUM	
	ANALYZER	

9.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-R0909003 Page 73 of 78

9.1.6 TEST RESULTS - CHIP

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11b		

Frequency (MHz)	Antenna Gain (dBi)				Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm²)
2412	2.00	1.5849	17.9000	61.6595	0.019451	1
2437	2.00	1.5849	18.2100	66.2217	0.020891	1
2462	2.00	1.5849	15.4700	35.2371	0.011116	1

EUT:	High Powered IEEE 802.11bg miniPCI Module	Model Name :	FLR24G30
Temperature:	17 ℃	Relative Humidity:	89 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	802.11g		

Frequency (MHz)	Antenna Gain (dBi)				Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm²)
2412	2.00	1.5849	22.4000	173.7801	0.054821	1
2437	2.00	1.5849	29.2300	837.5293	0.264211	1
2462	2.00	1.5849	22.3100	170.2159	0.053697	1

Remark:

(1) The SISO test requirement, MPE shall measure by using the total sum power of each transmitter chain.

Report No.: NEI-FCCP-1-R0909003 Page 74 of 78