



Test Report No.: RF2506WDG0158



TEST REPORT

Applicant:	NKOK, Inc.
Address:	5354 Irwindale Ave Unit A Irwindale CA 91706

Manufacturer or Supplier	NKOK, Inc.
Address	5354 Irwindale Ave Unit A Irwindale CA 91706
Product:	R/C Toy
Brand Name:	NKOK, Inc.
Model:	83011
Additional Model & Model Difference	83012
Date of tests:	Jun. 26, 2025

the tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C, Section 15.249

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Andrew Sha Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department

Date: Aug. 13, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS.....	4
2 MEASUREMENT UNCERTAINTY.....	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF EUT	5
3.2 DESCRIPTION OF TEST MODES	6
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4 DESCRIPTION OF SUPPORT UNITS	7
3.5 CONFIGURATION OF SYSTEM UNDER TEST	7
3.6 DUTY CYCLE OF TESET SIGNAL.....	8
4. TEST TYPES AND RESULTS.....	9
4.1 RADIATED EMISSION MEASUREMENT	9
4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT	9
4.1.2 TEST INSTRUMENTS.....	10
4.1.3 TEST PROCEDURES	11
4.1.4 DEVIATION FROM TEST STANDARD	11
4.1.5 TEST SETUP.....	12
4.1.6 EUT OPERATING CONDITIONS.....	13
4.1.7 TEST RESULTS	14
4.2 20DB BANDWIDTH MEASUREMENT	21
4.2.1 LIMITS OF 20DB BANDWIDTH MEASUREMENT.....	21
4.2.2 TEST INSTRUMENTS	21
4.2.3 TEST PROCEDURE	22
4.2.4 DEVIATION FROM TEST STANDARD	22
4.2.5 TEST SETUP	22
4.2.6 EUT OPERATING CONDITIONS.....	22
4.2.7 TEST RESULTS	23
5. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	25
6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	26



Test Report No.: RF2506WDG0158

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2506WDG0158	Original release	Aug. 13, 2025



Test Report No.: RF2506WDG0158

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.249)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
§15.203	Antenna Requirement	PASS	No antenna connector is used
§15.207 (a)	Conducted Emission	N/A	Powered from battery
§15.205	Restricted Band of Operation	PASS	Compliant
§15.209 §15.249(a)	Radiated Emission	PASS	Compliant
§15.215(c)	20dB Bandwidth Test	PASS	Compliant

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	+/- 2.48dB
	30MHz ~ 1GHz	+/- 4.32dB
	1GHz ~ 18GHz	+/- 4.76dB
	18GHz ~ 40GHz	+/- 4.50dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	R/C Toy
MODEL NO.	83011
ADDITIONAL MODEL	83012
FCC ID	XQPDKT062524TX
NOMINAL VOLTAGE	DC 3V(1.5V*AA*2) From Battery
MODULATION TECHNOLOGY	GFSK
OPERATING FREQUENCY	2410MHz ~ 2470MHz
ANTENNA TYPE	PCB Antenna, with 0dBi gain
I/O PORTS	N/A
CABLE SUPPLIED	N/A

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2506WDG0158) for detailed product photo.
4. Additional models 83012 are identical with the test model 83011 except the model name for trading purpose.



3.2 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type. The worst case was found when the EUT was positioned on Y axis for radiated emission. The EUT was tested under the following mode.

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	BW	
A	√	√	-	√	DC 3V from New Battery

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
BW: 20db bandwidth

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	TESTED FREQUENCY
Low	2410 MHz
Middle	2442 MHz
High	2470 MHz

Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410	12	2433	23	2454
2	2413	13	2434	24	2457
3	2414	14	2437	25	2458
4	2417	15	2438	26	2461
5	2418	16	2440	27	2462
6	2421	17	2442	28	2465
7	2422	18	2445	29	2466
8	2425	19	2446	30	2469
9	2426	20	2449	31	2470
10	2429	21	2450		
11	2430	22	2453		

Note: The more detailed channel, please refer to the product specifications

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE	25deg. C, 55%RH	DC 3V from New Battery	Zeke
BW	25deg. C, 55%RH	DC 3V from New Battery	Vincent
PLC	-	-	-



Test Report No.: RF2506WDG0158

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.249

ANSI C63.10-2020


All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without any other necessary accessories or support units

3.5 CONFIGURATION OF SYSTEM UNDER TEST

RADIATED EMISSION TEST:





Test Report No.: RF2506WDG0158


3.6 DUTY CYCLE OF TESET SIGNAL

T_p = 1.5942ms

T_{on} = 0.99275ms

Duty Cycle = T_{on} / T_p * 100% = 0.99275 / 1.5942 * 100% \approx 62.27%

AV factor=20 log (Duty cycle) = 20 log (62.27%) \approx -4.11dB





4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{uV}/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Oct. 10, 25
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Apr. 07, 26
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	Apr. 13, 26
Amplifier (9KHz -1GHz)	Burjeon	BPA-530	100210	Feb. 21, 26
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 25, 25
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	0085519	Oct. 19, 25
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Apr. 12, 26
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 17, 26
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Feb. 21, 26
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 28 25
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A

NOTES:

1. The test was performed in 966 Chamber.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 749762. Designation Number: CN1174.
5. Test site: No. 122, Houjie Avenue West Houjie Town, Dongguan City Guangdong Province, 523960, People's Republic of China.



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1.3m above the ground.
- g. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTES:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. Average value =PK Emission +AV Factor.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP


Below 30MHz test setup



Below 1GHz test setup



Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Turned on the power of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



Test Report No.: RF2506WDG0158

4.1.7 TEST RESULTS


BELOW 1GHz WORST-CASE DATA

CHANNEL	TX Middle Channel	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.22	12.21 QP	40.00	-27.79	1.54 H	24	31.04	-18.83
2	54.87	11.40 QP	40.00	-28.60	1.00 H	57	28.86	-17.46
3	154.36	12.64 QP	43.50	-30.86	1.00 H	40	29.21	-16.57
4	224.31	10.65 QP	46.00	-35.35	1.78 H	72	29.21	-18.56
5	326.91	13.85 QP	46.00	-32.15	1.23 H	88	28.48	-14.63
6	440.38	17.18 QP	46.00	-28.82	1.00 H	106	28.41	-11.23

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value.






Test Report No.: RF2506WDG0158

CHANNEL	TX Middle Channel	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.22	11.55	40.00	-28.45	112	146	30.38	-18.83
2	54.87	10.20	40.00	-29.80	100	162	27.66	-17.46
3	162.13	11.40	43.50	-32.10	154	126	28.23	-16.83
4	283.38	12.78	46.00	-33.22	100	107	28.65	-15.87
5	358.00	15.53	46.00	-30.47	178	74	29.41	-13.89
6	446.60	17.09	46.00	-28.91	100	181	28.10	-11.01

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value.





ABOVE 1GHz WORST-CASE DATA:

CHANNEL	TX Low Channel	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	56.95 PK	74.00	-17.05	1.95 H	184	54.04	2.91
2	2400.00	41.84 AV	54.00	-12.16	1.95 H	184	38.93	2.91
3	*2410.00	87.58 PK	114.00	-26.42	1.85 H	147	84.65	2.93
4	*2410.00	83.47 AV	94.00	-10.53	1.85 H	147	80.54	2.93
5	4820.00	53.94 PK	74.00	-20.06	1.94 H	183	46.93	7.01
6	4820.00	49.83 AV	54.00	-4.17	1.94 H	183	42.82	7.01
7	7230.00	55.01 PK	74.00	-18.99	1.01 H	190	44.10	10.91
8	7230.00	50.90 AV	54.00	-3.10	1.01 H	190	39.99	10.91

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	46.17 PK	74.00	-27.83	1.17 V	106	43.26	2.91
2	2400.00	42.06 AV	54.00	-11.94	1.17 V	106	39.15	2.91
3	*2410.00	84.91 PK	114.00	-29.09	1.91 V	180	81.98	2.93
4	*2410.00	80.80 AV	94.00	-13.20	1.91 V	180	77.87	2.93
5	4820.00	53.12 PK	74.00	-20.88	1.12 V	101	53.12	7.01
6	4820.00	49.01 AV	54.00	-4.99	1.12 V	101	49.01	7.01
7	7230.00	53.88 PK	74.00	-20.12	1.88 V	177	53.88	10.91
8	7230.00	49.77 AV	54.00	-4.23	1.88 V	177	49.77	10.91

REMARK:


1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. Average value =PK Emission +20*log(duty cycle)Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (62.27%) ≈ -4.11dB, Please see page 8 for plotted duty.




Test Report No.: RF2506WDG0158

Band edge Plot

2410MHz Horizontal



2410MHz Vertical





CHANNEL	TX Middle Channel	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2442.00	87.41 PK	114.00	-26.59	1.41 H	130	84.38	3.03
2	*2442.00	83.30 AV	94.00	-10.70	1.41 H	130	80.27	3.03
3	4884.00	50.99 PK	74.00	-23.01	1.99 H	188	43.79	7.20
4	4884.00	46.88 AV	54.00	-7.12	1.99 H	188	39.68	7.20
5	7326.00	54.87 PK	74.00	-19.13	1.87 H	176	43.64	11.23
6	7326.00	50.76 AV	54.00	-3.24	1.87 H	176	39.53	11.23
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2442.00	84.42 PK	114.00	-29.58	1.42 V	131	81.39	3.03
2	*2442.00	80.31 AV	94.00	-13.69	1.42 V	131	77.28	3.03
3	4884.00	50.38 PK	74.00	-23.62	1.38 V	122	43.18	7.20
4	4884.00	46.27 AV	54.00	-7.73	1.38 V	122	39.07	7.20
5	7326.00	54.25 PK	74.00	-19.75	1.25 V	114	43.02	11.23
6	7326.00	50.14 AV	54.00	-3.86	1.25 V	114	38.91	11.23

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. Average value =PK Emission +20*log(duty cycle)Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (62.27%) ≈ -4.11dB, Please see page 8 for plotted duty.



Test Report No.: RF2506WDG0158

CHANNEL	TX High Channel	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2470.00	87.19 PK	114.00	-26.81	1.19 H	108	84.08	3.11
2	*2470.00	83.08 AV	94.00	-10.92	1.19 H	108	79.97	3.11
3	2483.50	44.42 PK	74.00	-29.58	1.42 H	131	41.26	3.16
4	2483.50	40.31 AV	54.00	-13.69	1.42 H	131	37.15	3.16
5	2485.96	48.39 PK	74.00	-25.61	1.39 H	21	45.23	3.16
6	2485.96	44.28 AV	54.00	-9.72	1.39 H	21	41.12	3.16
7	4940.00	50.39 PK	74.00	-23.61	1.39 H	128	43.04	7.35
8	4940.00	46.28 AV	54.00	-7.72	1.39 H	128	38.93	7.35
9	7410.00	54.23 PK	74.00	-19.77	1.23 H	112	42.73	11.50
10	7410.00	50.12 AV	54.00	-3.88	1.23 H	112	38.62	11.50

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2470.00	84.56 PK	114.00	-29.44	1.56 V	145	81.45	3.11
2	*2470.00	80.45 AV	94.00	-13.55	1.56 V	145	77.34	3.11
3	2483.50	43.58 PK	74.00	-30.42	1.58 V	147	40.42	3.16
4	2483.50	39.47 AV	54.00	-14.53	1.58 V	147	36.31	3.16
5	2485.06	47.46 PK	74.00	-26.54	1.46 V	134	44.30	3.16
6	2485.06	43.35 AV	54.00	-10.65	1.46 V	134	40.19	3.16
7	4940.00	50.00 PK	74.00	-24.00	1.00 V	189	42.65	7.35
8	4940.00	45.89 AV	54.00	-8.11	1.00 V	189	38.54	7.35
9	7410.00	54.37 PK	74.00	-19.63	1.37 V	126	42.87	11.50
10	7410.00	50.26 AV	54.00	-3.74	1.37 V	126	38.76	11.50

REMARK:


1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. Average value =PK Emission +20*log(duty cycle)Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (62.27%) ≈ -4.11dB, Please see page 8 for plotted duty.




Test Report No.: RF2506WDG0158

Band edge Plot

2470MHz Horizontal



2470MHz Vertical





4.2 20dB BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY57320002	Apr. 07, 26
Digital Multimeter	FLUKE	15B	A1220010DG	N/A
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Oct. 10, 25
Oscilloscope	Agilent	DSO9254A	MY51260160	Jul. 07, 25
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Oct. 09, 25
Signal Generator	Agilent	N5183A	MY50140980	Jul. 11, 25
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jul. 11, 25
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A
Test software	ADT	ADT_RF Test Software V6.6.5.3	N/A	N/A

NOTES:

1. The test was performed in RF Oven room.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.



4.2.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP




4.2.6 EUT OPERATING CONDITIONS

- a) Turned on the power of all equipment.
- b) EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

4.2.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2410	0.6621
Middle	2442	0.6708
High	2470	0.6795


Test Data: Low channel






Test Report No.: RF2506WDG0158

Test Data: Middle channel



Test Data: High channel





Test Report No.: RF2506WDG0158

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF2506WDG0158

6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---