

MRT Technology (Suzhou) Co., Ltd Phone: +86-512-66308358

Web: www.mrt-cert.com

Report No.: 1803RSU003-U3 Report Version: V01 Issue Date: 08-14-2018

MEASUREMENT REPORT

FCC PART 15.247 Bluetooth

FCC ID: XR3-MAX2

APPLICANT: ONYX INTERNATIONAL INC.

Application Type: Certification

Product: E-reader

Model No.: Max2

Serial No.: Max2 Pro, Max2 Lite

Brand Name: BOOX

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part 15 Subpart C (Section 15.247)

Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v04

Test Date: March 02 ~ 16, 2018

Reviewed By : Com Como

(Kevin Guo)

Approved By : Robin Wu

(Robin Wu)





The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01v04. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

FCC ID: XR3-MAX2 Page Number: 1 of 49



Revision History

Report No.	Version	Description	Issue Date	Note
1803RSU003-U3	Rev. 01	Initial Report	08-14-2018	Valid

FCC ID: XR3-MAX2 Page Number: 2 of 49



CONTENTS

Des	scriptio	on	Page
1.	INTR	ODUCTION	6
	1.1.	Scope	6
	1.2.	MRT Test Location	6
2.	PROI	DUCT INFORMATION	7
	2.1.	Feature of Equipment under Test	7
	2.2.	Product Specification Subjective to this Report	7
	2.3.	Working Frequencies	8
	2.4.	Device Capabilities	9
	2.5.	Test Configuration	9
	2.6.	EMI Suppression Device(s)/Modifications	9
	2.7.	Labeling Requirements	9
	2.8.	Test Software	9
3.	DESC	CRIPTION OF TEST	10
	3.1.	Evaluation Procedure	10
	3.2.	AC Line Conducted Emissions	10
	3.3.	Radiated Emissions	11
4.	ANTE	ENNA REQUIREMENTS	12
5.	TEST	EQUIPMENT CALIBRATION DATE	13
6.	MEAS	SUREMENT UNCERTAINTY	14
7.	TEST	RESULT	15
	7.1.	Summary	15
	7.2.	6dB Bandwidth Measurement	
	7.2.1.	Test Limit	16
	7.2.2.	Test Procedure used	16
	7.2.3.	Test Setting	16
	7.2.4.	Test Setup	16
	7.2.5.	Test Result	17
	7.3.	Output Power Measurement	18
	7.3.1.	Test Limit	18
	7.3.2.	Test Procedure Used	18
	7.3.3.	Test Setting	18
	7.3.4.		
	7.3.5.	Test Result of Output Power	19



7.4.	Power Spectral Density Measurement	20
7.4.1.	Test Limit	20
7.4.2.	Test Procedure Used	20
7.4.3.	Test Setting	20
7.4.4.	Test Setup	20
7.4.5.	Test Result	21
7.5.	Conducted Band Edge and Out-of-Band Emissions	22
7.5.1.	Test Limit	22
7.5.2.	Test Procedure Used	22
7.5.3.	Test Settitng	22
7.5.4.	Test Setup	23
7.5.5.	Test Result	24
7.6.	Radiated Spurious Emission Measurement	26
7.6.1.	Test Limit	26
7.6.2.	Test Procedure Used	26
7.6.3.	Test Setting	26
7.6.4.	Test Setup	28
7.6.5.	Test Result	30
7.7.	Radiated Restricted Band Edge Measurement	35
7.7.1.	Test Limit	35
7.7.2.	Test Procedure Used	36
7.7.3.	Test Setting	36
7.7.4.	Test Setup	37
7.7.5.	Test Result	38
7.8.	AC Conducted Emissions Measurement	46
7.8.1.	Test Limit	46
7.8.2.	Test Setup	46
7.8.3.	Test Result	47
CONC	N LISION	40



§2.1033 General Information

Applicant:	ONYX INTERNATIONAL INC.
Applicant Address:	ROOM C301, BUILDING 2, #21 HEJING SOUTH ROAD, LIWAN
	DISTRICT, GUANGZHOU, China
Manufacturer:	ONYX INTERNATIONAL INC.
Manufacturer Address:	ROOM C301, BUILDING 2, #21 HEJING SOUTH ROAD, LIWAN
	DISTRICT, GUANGZHOU, China
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong
	Economic Development Zone, Suzhou, China
FCC Registration No.:	893164
Test Device Serial No.:	N/A ☐ Production ☐ Pre-Production ☐ Engineering

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in ANSI C63.4-2014.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications, Radio and SAR testing.



FCC ID: XR3-MAX2 Page Number: 5 of 49



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The measurement facility compliant with the test site requirements specified in ANSI C63.4-2014.



FCC ID: XR3-MAX2 Page Number: 6 of 49



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name:	E-reader
Model No.:	Max2
Serial No.:	Max2 Pro, Max2 Lite
Brand Name:	BOOX
Wi-Fi Specification:	802.11b/g/n-HT20
Bluetooth Specification:	v4.1 dual mode
Components	
Adapter	M/N: ASSA93w2-050240
	INPUT: 100-240V ~ 50/60Hz, 0.5A
	OUTPUT: 5Vdc, 2.4A

Note: The different models are only for marketing different clients. The other was the same. All the materials are the same.

2.2. Product Specification Subjective to this Report

Bluetooth Frequency	2402~2480MHz
Bluetooth Version	v4.0
Data Rate	1Mbps(GFSK)
Antenna Type	PIFA Antenna
Antenna Gain	1.5dBi

Note: For other features of this EUT, test report will be issued separately.

FCC ID: XR3-MAX2 Page Number: 7 of 49



2.3. Working Frequencies

Channel List for BLE

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz				

FCC ID: XR3-MAX2 Page Number: 8 of 49



2.4. Device Capabilities

This device contains the following capabilities: 2.4GHz WLAN (DTS), Bluetooth (v4.1 dual mode).

2.5. Test Configuration

The **E-reader** was tested per the guidance of KDB 558074 D01v04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.6. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.7. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

2.8. Test Software

The test utility software used during testing was "RFTestTool", and the version was "5.5".

FCC ID: XR3-MAX2 Page Number: 9 of 49



3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v04 were used in the measurement of the **E-reader.**

Deviation from measurement procedure......None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50uH$ Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

FCC ID: XR3-MAX2 Page Number: 10 of 49



3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the Antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive Antenna height using a broadband Antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn Antennas were used. For frequencies below 30MHz, a calibrated loop Antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband Antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive Antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn Antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive Antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive Antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn Antenna, the horn Antenna should be always directed to the EUT when rising height.

FCC ID: XR3-MAX2 Page Number: 11 of 49



4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the E-reader is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

FCC ID: XR3-MAX2 Page Number: 12 of 49



5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2018/08/18
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2019/06/15
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2019/06/15
Thermohygrometer	Testo	608-H1	MRTSUE06404	1 year	2018/08/14

Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2018/09/13
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2018/08/18
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2018/11/17
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2018/11/20
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2018/11/18
Broad Band Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06023	1 year	2018/10/21
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2018/12/14
Amplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2019/06/13
Thermohygrometer	Testo	608-H1	MRTSUE06403	1 year	2018/08/14
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2019/05/02

Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2019/04/24
Power Meter	Agilent	U2021XA	MRTSUE06030	1 year	2018/12/06
Thermohygrometer	Testo	608-H1	MRTSUE06401	1 year	2018/08/14

Software	Version	Function
e3	V8.3.5	EMI Test Software

FCC ID: XR3-MAX2 Page Number: 13 of 49



6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement - SR2

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

150kHz~30MHz: 3.46dB

Radiated Emission Measurement - AC1

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB

Spurious Emissions, Conducted - TR3

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

0.78dB

Output Power - TR3

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

1.13dB

Power Spectrum Density - TR3

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

1.15dB

Occupied Bandwidth - TR3

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

0.28%

FCC ID: XR3-MAX2 Page Number: 14 of 49



7. TEST RESULT

7.1. Summary

Company Name: ONYX INTERNATIONAL INC.

FCC ID: XR3-MAX2

FCC	Test Description	Test Limit	Test	Test	Reference
Section(s)			Condition	Result	
15.247(a)(2)	6dB Bandwidth	≥ 500kHz		Pass	Section 7.2
15.247(b)(3)	Output Power	≤ 30dBm		Pass	Section 7.3
15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Conducted	Pass	Section 7.4
15 047/d\	Band Edge / Out-of-Band	< 20dPo(Pook)		Pass	Section 7.5
15.247(d)	Emissions	≤ 20dBc(Peak)			Section 7.5
	General Field Strength	Emissions in restricted			
15.205	Limits (Restricted Bands	bands must meet the	Radiated	Pass	Section
15.209	and Radiated Emission	radiated limits detailed	Radiated	Pass	7.6 & 7.7
	Limits)	in 15.209			
15.207	AC Conducted Emissions	< FCC 15.207 limits	Line	Door	Section 7.8
10.207	150kHz - 30MHz	< FGG 15.207 IIIIIIIS	Conducted	Pass	Section 7.6

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

FCC ID: XR3-MAX2 Page Number: 15 of 49



7.2. 6dB Bandwidth Measurement

7.2.1.Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2.Test Procedure used

KDB 558074 D01v04 - Section 8.2 Option 2

7.2.3.Test Setting

- The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. Set RBW = 100 kHz
- 3. VBW ≥ 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace was allowed to stabilize

7.2.4.Test Setup




FCC ID: XR3-MAX2 Page Number: 16 of 49



7.2.5.Test Result

Product	E-reader	Temperature	25°C
Test Engineer	Amy Zhang	Relative Humidity	52%
Test Site	TR3	Test Date	2018/03/07

Test Mode	Data Rate	Channel No.	Frequency	6dB Bandwidth	Limit	Result
	(Mbps)		(MHz)	(MHz)	(MHz)	
BLE	1	00	2402	0.71	≥ 0.5	Pass
BLE	1	19	2440	0.70	≥ 0.5	Pass
BLE	1	39	2480	0.69	≥ 0.5	Pass



FCC ID: XR3-MAX2 Page Number: 17 of 49



7.3. Output Power Measurement

7.3.1.Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2.Test Procedure Used

KDB 558074 D01v04 - Section 9.1.3 PKPM1 Peak-reading power meter method

KDB 558074 D01v04 - Section 9.2.3.2 AVGPM-G

7.3.3.Test Setting


PKPM1 Peak-reading power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Method AVGPM-G (Measurement using a gated RF average-reading power meter)

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

7.3.4.Test Setup



FCC ID: XR3-MAX2 Page Number: 18 of 49



7.3.5.Test Result of Output Power

Product	E-reader	Temperature	25°C
Test Engineer	Amy Zhang	Relative Humidity	52%
Test Site	TR3	Test Date	2018/03/04

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result	
Test Result of	Test Result of Peak Output Power						
BLE	1	00	2402	5.88	≤ 30	Pass	
BLE	1	19	2440	4.27	≤ 30	Pass	
BLE	1	39	2480	2.33	≤ 30	Pass	
Test Result of	Average Outp	ut Power (Repo	orting Only)				
BLE	1	00	2402	5.71	≤ 30	Pass	
BLE	1	19	2440	3.99	≤ 30	Pass	
BLE	1	39	2480	2.04	≤ 30	Pass	

FCC ID: XR3-MAX2 Page Number: 19 of 49



7.4. Power Spectral Density Measurement

7.4.1.Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

7.4.2.Test Procedure Used

KDB 558074 D01v04 - Section 10.2 Method PKPSD

7.4.3.Test Setting

- 1. Analyzer was set to the center frequency of the DTS channel under investigation
- 2. Span = 1.5 times the DTS channel bandwidth
- 3. RBW = 3kHz
- 4. VBW = 10kHz
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Trace was allowed to stabilize

7.4.4.Test Setup

Spectrum Analyzer Attenuator EUT


FCC ID: XR3-MAX2 Page Number: 20 of 49



7.4.5.Test Result

Product	E-reader	Temperature	25°C
Test Engineer	Amy Zhang	Relative Humidity	52%
Test Site	TR3	Test Date	2018/03/07

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
BLE	1	00	2402	-7.13	≤ 8.00	Pass
BLE	1	19	2440	-7.77	≤ 8.00	Pass
BLE	1	39	2480	-8.35	≤ 8.00	Pass



FCC ID: XR3-MAX2 Page Number: 21 of 49



7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1.Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

7.5.2.Test Procedure Used

KDB 558074 D01v04 - Section 11.2 & Section 11.3

7.5.3.Test Settitng

Reference level measurement

- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to ≥ 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW ≥ 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize

Emission level measurement

Set the center frequency and span to encompass frequency range to be measured

RBW = 100kHz

VBW = 300kHz

Detector = Peak

Number of sweep points ≥ 2 x Span/RBW

Trace mode = max hold


Sweep time = auto couple

FCC ID: XR3-MAX2 Page Number: 22 of 49



The trace was allowed to stabilize

7.5.4.Test Setup



FCC ID: XR3-MAX2 Page Number: 23 of 49



7.5.5.Test Result


Product	E-reader	Temperature	25°C
Test Engineer	Amy Zhang	Relative Humidity	52%
Test Site	TR3	Test Date	2018/03/07

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit	Result
BLE	1	00	2402	20dBc	Pass
BLE	1	19	2440	20dBc	Pass
BLE	1	39	2480	20dBc	Pass



FCC ID: XR3-MAX2 Page Number: 24 of 49





FCC ID: XR3-MAX2 Page Number: 25 of 49



7.6. Radiated Spurious Emission Measurement

7.6.1.Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC	FCC Part 15 Subpart C Paragraph 15.209						
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]					
0.009 - 0.490	2400/F (kHz)	300					
0.490 - 1.705	24000/F (kHz)	30					
1.705 - 30	30	30					
30 - 88	100	3					
88 - 216	150	3					
216 - 960	200	3					
Above 960	500	3					

7.6.2.Test Procedure Used

KDB 558074 D01v04 - Section 12.2.3 (quasi-peak measurements)

KDB 558074 D01v04 - Section 12.2.4 (peak power measurements)

KDB 558074 D01v04 - Section 12.2.5 (average power measurements)

7.6.3.Test Setting

Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 D01v04

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in Table 1
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple

FCC ID: XR3-MAX2 Page Number: 26 of 49



- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements per Section 12.2.4 of KDB 558074 D01v04


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ 1/T
- 4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
- 5. Detector = Peak
- 6. Sweep time = auto
- 7. Trace mode = max hold
- 8. Allow max hold to run for at least 50 times (1/duty cycle) traces

FCC ID: XR3-MAX2 Page Number: 27 of 49




7.6.4.Test Setup

9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



FCC ID: XR3-MAX2 Page Number: 28 of 49



1GHz ~ 25GHz Test Setup:



FCC ID: XR3-MAX2 Page Number: 29 of 49



7.6.5.Test Result

Test Mode:	BLE	Test Site:	AC1			
Test Channel:	00	Test Engineer:	Dandy Li			
Remark:	Average measurement was not performed if peak level lower than average					
	limit.					
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show					
	in the report.					


Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	5114.0	37.6	6.6	44.2	74.0	-29.8	Peak	Horizontal
*	5641.0	37.0	7.0	44.0	85.2	-41.2	Peak	Horizontal
	7536.5	37.0	12.9	49.9	74.0	-24.1	Peak	Horizontal
*	7978.5	36.9	13.6	50.5	85.2	-34.7	Peak	Horizontal
	4978.0	40.4	6.2	46.6	74.0	-27.4	Peak	Vertical
*	6431.5	37.6	9.5	47.1	85.2	-38.1	Peak	Vertical
	7443.0	37.0	12.9	49.9	74.0	-24.1	Peak	Vertical
*	8684.0	37.2	13.1	50.3	85.2	-34.9	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (105.2dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

FCC ID: XR3-MAX2 Page Number: 30 of 49





Test Mode:	BLE	Test Site:	AC1			
Test Channel:	19	Test Engineer:	Dandy Li			
Remark:	Average measurement was not performed if peak level lower than average					
	limit.					
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show					
	in the report.					

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	5054.5	36.9	6.5	43.4	74.0	-30.6	Peak	Horizontal
*	6261.5	36.7	8.6	45.3	85.2	-39.9	Peak	Horizontal
	7468.5	36.3	12.9	49.2	74.0	-24.8	Peak	Horizontal
*	7995.5	36.3	13.7	50.0	85.2	-35.2	Peak	Horizontal
	4995.0	39.7	6.3	46.0	74.0	-28.0	Peak	Vertical
*	5913.0	35.2	7.8	43.0	85.2	-42.2	Peak	Vertical
	7604.5	34.9	12.7	47.6	74.0	-26.4	Peak	Vertical
*	8684.0	36.6	13.1	49.7	85.2	-35.5	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (105.2dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

FCC ID: XR3-MAX2 Page Number: 31 of 49





Test Mode:	BLE	Test Site:	AC1			
Test Channel:	39	Test Engineer:	Dandy Li			
Remark:	Average measurement was not performed if peak level lower than average					
	limit.					
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show					
	in the report.					

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	4986.5	38.3	6.2	44.5	74.0	-29.5	Peak	Horizontal
*	5785.5	36.8	7.5	44.3	85.3	-41.0	Peak	Horizontal
	7468.5	35.6	12.9	48.5	74.0	-25.5	Peak	Horizontal
*	8922.0	36.7	13.3	50.0	85.3	-35.3	Peak	Horizontal
	4986.5	38.8	6.2	45.0	74.0	-29.0	Peak	Vertical
*	5615.5	36.5	7.0	43.5	85.3	-41.8	Peak	Vertical
	7366.5	35.5	12.7	48.2	74.0	-25.8	Peak	Vertical
*	7919.0	37.0	13.4	50.4	85.3	-34.9	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (105.3dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

FCC ID: XR3-MAX2 Page Number: 32 of 49



The worst case of Radiated Emission below 1GHz:

EUT: E-reader Power: By Battery Worse Case Mode: Transmit by BLE at channel 2402MHz					
EUT: E-reader	Dower: Dy Pottory				
Probe: VULB 9168 _20-2000MHz	Polarity: Horizontal				
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni				
Site: AC1	Time: 2018/03/12 - 11:52				



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	34.850	21.639	7.668	-18.361	40.000	13.972	QP
2			38.730	19.481	5.002	-20.519	40.000	14.479	QP
3			156.585	21.744	6.448	-21.756	43.500	15.296	QP
4			188.110	24.075	12.118	-19.425	43.500	11.957	QP
5			396.175	27.514	11.007	-18.486	46.000	16.507	QP
6			674.080	22.907	1.119	-23.093	46.000	21.788	QP

Note 1: Measure Level $(dB\mu V/m)$ = Reading Level $(dB\mu V)$ + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: $9kHz \sim 30MHz$, $18GHz \sim 25GHz$), therefore no data appear in the report.

FCC ID: XR3-MAX2 Page Number: 33 of 49



Site: AC1	Time: 2018/03/12 - 12:00			
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni			
Probe: VULB 9168 _20-2000MHz	Polarity: Vertical			
EUT: E-reader	Power: By Battery			
Worse Case Mode: Transmit by BLE at channel 2402MHz				



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			34.365	20.936	7.005	-19.064	40.000	13.931	QP
2			156.585	21.067	5.771	-22.433	43.500	15.296	QP
3		*	187.140	25.701	13.630	-17.799	43.500	12.071	QP
4			396.175	27.515	11.008	-18.485	46.000	16.507	QP
5			670.685	23.742	2.002	-22.258	46.000	21.740	QP
6			791.935	25.369	2.118	-20.631	46.000	23.251	QP

Note 1: Measure Level ($dB\mu V/m$) = Reading Level ($dB\mu V$) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: $9kHz \sim 30MHz$, $18GHz \sim 25GHz$), therefore no data appear in the report.

FCC ID: XR3-MAX2 Page Number: 34 of 49



7.7. Radiated Restricted Band Edge Measurement

7.7.1.Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency	Frequency	Frequency	Frequency
(MHz)	(MHz)	(MHz)	(GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

FCC ID: XR3-MAX2 Page Number: 35 of 49



All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209							
Frequency Field Strength Measured Distance							
[MHz]	[uV/m]	[Meters]					
0.009 - 0.490	2400/F (kHz)	300					
0.490 - 1.705	24000/F (kHz)	30					
1.705 - 30	30	30					
30 - 88	100	3					
88 - 216	150	3					
216 - 960	200	3					
Above 960	500	3					

7.7.2.Test Procedure Used

ANSI C63.10 Section 6.3 (General Requirements)

ANSI C63.10 Section 6.6 (Standard test method above 1GHz)

7.7.3.Test Setting

Peak Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in Table 1
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

FCC ID: XR3-MAX2 Page Number: 36 of 49




Average Field Strength Measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ 1/T
- 4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
- 5. Detector = Peak
- 6. Sweep time = auto
- 7. Trace mode = max hold
- 8. Allow max hold to run for at least 50 times (1/duty cycle) traces

7.7.4.Test Setup

1GHz ~ 18GHz Test Setup:




FCC ID: XR3-MAX2 Page Number: 37 of 49



7.7.5.Test Result

Site: AC1	Time: 2018/03/09 - 02:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: E-reader	Power: By Battery
Test Mode: Transmit by BLE at channel 2402MHz	



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2383.198	57.960	25.624	-16.040	74.000	32.336	PK
2			2390.000	55.695	23.368	-18.305	74.000	32.327	PK
3		*	2402.150	105.219	72.915	N/A	N/A	32.304	PK


Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 38 of 49



Site: AC1	Time: 2018/03/09 - 02:49
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: E-reader	Power: By Battery
Test Mode: Transmit by BLE at channel 2402MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2376.262	43.762	11.416	-10.238	54.000	32.345	AV
2			2390.000	42.736	10.409	-11.264	54.000	32.327	AV
3		*	2402.150	104.431	72.127	N/A	N/A	32.304	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 39 of 49



Site: AC1	Time: 2018/03/09 - 02:50
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: E-reader	Power: By Battery
Test Mode: Transmit by BLE at channel 2402MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2387.615	58.645	26.315	-15.355	74.000	32.330	PK
2			2390.000	55.432	23.105	-18.568	74.000	32.327	PK
3		*	2401.627	100.011	67.706	N/A	N/A	32.306	PK

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 40 of 49



Site: AC1	Time: 2018/03/09 - 02:51
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: E-reader	Power: By Battery
Test Mode: Transmit by BLE at channel 2402MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2389.325	43.973	11.645	-10.027	54.000	32.328	AV
2			2390.000	42.782	10.455	-11.218	54.000	32.327	AV
3		*	2402.055	98.985	66.681	N/A	N/A	32.304	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 41 of 49



Site: AC1	Time: 2018/03/09 - 02:52
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: E-reader	Power: By Battery
Test Mode: Transmit by BLE at channel 2480MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2479.990	105.280	72.955	N/A	N/A	32.325	PK
2			2483.500	65.320	32.981	-8.680	74.000	32.340	PK
3			2483.509	66.435	34.096	-7.565	74.000	32.340	PK

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 42 of 49



Site: AC1	Time: 2018/03/09 - 02:54
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: E-reader	Power: By Battery
Test Mode: Transmit by BLE at channel 2480MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2480.001	104.251	71.926	N/A	N/A	32.325	AV
2			2483.500	44.729	12.390	-9.271	54.000	32.340	AV
3			2484.567	45.043	12.700	-8.957	54.000	32.344	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 43 of 49



Site: AC1	Time: 2018/03/09 - 02:54				
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li				
Probe: BBHA9120D_1-18GHz	Polarity: Vertical				
EUT: E-reader	Power: By Battery				
Test Mode: Transmit by BLE at channel 2480MHz					




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2479.909	98.545	66.220	N/A	N/A	32.325	PK
2			2483.500	59.161	26.822	-14.839	74.000	32.340	PK
3			2483.935	61.596	29.255	-12.404	74.000	32.340	PK

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 44 of 49



Site: AC1	Time: 2018/03/09 - 02:56				
Limit: FCC_Part15.209_RE(3m)	Engineer: Dandy Li				
Probe: BBHA9120D_1-18GHz	Polarity: Vertical				
EUT: E-reader	Power: By Battery				
Test Mode: Transmit by BLE at channel 2480MHz					



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2479.979	97.586	65.261	N/A	N/A	32.325	AV
2			2483.500	43.416	11.077	-10.584	54.000	32.340	AV
3			2489.523	44.621	12.258	-9.379	54.000	32.363	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: XR3-MAX2 Page Number: 45 of 49



7.8. AC Conducted Emissions Measurement


7.8.1.Test Limit

FCC 15.207 Limits								
Frequency (MHz)	QP (dBuV)	AV (dBuV)						
0.15 ~ 0.50	66 ~ 56	56 ~ 46						
0.50 ~ 5.0	56	46						
5.0 ~ 30	60	50						

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2.Test Setup




FCC ID: XR3-MAX2 Page Number: 46 of 49



7.8.3.Test Result

Worst Case Mode: Transmit by BLE at channel 2402MHz						
EUT: E-reader	Power: AC 120V/60Hz					
Probe: ENV216_101683_Filter On	Polarity: Line					
Limit: FCC_Part15.207_CE_AC Power	Engineer: Vince Yu					
Site: SR2	Time: 2018/08/09 - 17:03					



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV)	(dB)	
				(dBuV)	(dBuV)				
1			0.158	45.996	35.685	-19.572	65.568	10.311	QP
2			0.158	30.406	20.095	-25.162	55.568	10.311	AV
3			0.490	43.608	33.450	-12.559	56.168	10.158	QP
4			0.490	25.410	15.252	-20.758	46.168	10.158	AV
5			2.366	40.221	30.359	-15.779	56.000	9.862	QP
6			2.366	22.721	12.859	-23.279	46.000	9.862	AV
7			2.706	39.620	29.770	-16.380	56.000	9.850	QP
8			2.706	23.462	13.612	-22.538	46.000	9.850	AV
9			9.058	45.214	35.056	-14.786	60.000	10.158	QP
10			9.058	32.811	22.652	-17.189	50.000	10.158	AV
11		*	17.714	49.678	39.583	-10.322	60.000	10.095	QP
12			17.714	31.269	21.174	-18.731	50.000	10.095	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

FCC ID: XR3-MAX2 Page Number: 47 of 49



Worst Case Mode: Transmit by BLE at channel 2402MHz						
EUT: E-reader	Power: AC 120V/60Hz					
Probe: ENV216_101683_Filter On	Polarity: Neutral					
Limit: FCC_Part15.207_CE_AC Power	Engineer: Vince Yu					
Site: SR2	Time: 2018/03/11 - 17:07					

No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV)	(dB)	71 -
				(dBuV)	(dBuV)			, ,	
1			0.398	46.544	36.433	-11.351	57.895	10.111	QP
2			0.398	34.463	24.352	-13.433	47.895	10.111	AV
3			0.482	46.921	36.748	-9.383	56.305	10.173	QP
4			0.482	34.918	24.745	-11.387	46.305	10.173	AV
5		*	0.642	46.940	36.832	-9.060	56.000	10.108	QP
6			0.642	33.962	23.855	-12.038	46.000	10.108	AV
7			2.478	42.634	32.773	-13.366	56.000	9.861	QP
8			2.478	25.155	15.294	-20.845	46.000	9.861	AV
9			9.466	45.513	35.346	-14.487	60.000	10.166	QP
10			9.466	34.608	24.442	-15.392	50.000	10.166	AV
11			17.106	43.629	33.500	-16.371	60.000	10.129	QP
12			17.106	31.060	20.930	-18.940	50.000	10.129	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

FCC ID: XR3-MAX2 Page Number: 48 of 49



8. CONCLUSION

The data collected relate only the item(s) tested and show that the **E-reader** is in compliance with Part 15C of the FCC Rules.

———— The End

FCC ID: XR3-MAX2 Page Number: 49 of 49