



## FCC SAR

# TEST REPORT

of

### Mobile telephone

Model Name: X10  
Trade Name: LANIX  
Report No.: SZ09080026S01  
FCC ID: XR7TOCSM004

*prepared for*

### SUNTECH TECHNOLOGIES CO.,LTD.

Rm419--420,Merchants Building,Shuiwan Road,SheKou,Nanshan District,  
shenzhen,China

*prepared for*  
Shenzhen Electronic Product Quality Testing Center  
Morlab Laboratory  
3/F, Electronic Testing Building, Shahe Road, Xili,  
Nanshan District, Shenzhen, 518035 P. R. China  
Tel: +86 755 86130398  
Fax: +86 755 86130218



CTIA Authorized Test Lab  
LAB CODE 20081223-00

*NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant, it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.*

## Contents

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
<b>1.1. Notes .....</b>	<b>3</b>
<b>1.2. Organization item.....</b>	<b>3</b>
<b>1.3. Conclusion.....</b>	<b>3</b>
<b>2. TESTING LABORATORY.....</b>	<b>4</b>
<b>2.1. Identification of the Responsible Testing Laboratory.....</b>	<b>4</b>
<b>2.2. Identification of the Responsible Testing Location .....</b>	<b>4</b>
<b>2.3. Accreditation Certificate .....</b>	<b>4</b>
<b>2.4. List of Test Equipments .....</b>	<b>4</b>
<b>3. TECHNICAL INFORMATION .....</b>	<b>5</b>
<b>3.1. Identification of Applicant.....</b>	<b>5</b>
<b>3.2. Identification of Manufacturer .....</b>	<b>5</b>
<b>3.3. Equipment Under Test (EUT) .....</b>	<b>5</b>
<b>3.3.1. Photographs of the EUT .....</b>	<b>6</b>
<b>3.3.2. Identification of all used EUTs.....</b>	<b>6</b>
<b>4. TEST RESULTS.....</b>	<b>6</b>
<b>4.1. Applied Reference Documents .....</b>	<b>6</b>
<b>4.2. Test Environment/Conditions .....</b>	<b>7</b>
<b>4.3. Operational Conditions During Test .....</b>	<b>7</b>
<b>4.3.1. Informations On The Testing .....</b>	<b>8</b>
<b>4.3.2. The Measurement System .....</b>	<b>10</b>
<b>4.3.3. Uncertainty Assessment.....</b>	<b>12</b>
<b>4.4. MEASUREMENT PROCEDURES .....</b>	<b>13</b>
<b>4.4.1. Procedures Used To Establish Test Signal.....</b>	<b>14</b>
<b>4.5. Items used in the Test Results List.....</b>	<b>15</b>
<b>4.6. Test Results List.....</b>	<b>16</b>
<b>ANNEX A ACCREDITATION CERTIFICATE.....</b>	<b>18</b>
<b>ANNEX B PHOTOGRAPHS OF THE EUT .....</b>	<b>19</b>
<b>ANNEX C GRAPH TEST RESULTS .....</b>	<b>23</b>

## General Information

### 1.1. Notes

The test results of this test report relate exclusively to the information specified in section 3.3. Shenzhen Electronic Product Quality Testing Center Morlab Laboratory does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the identification. The test report may only be reproduced or published in full. Reproduction or publications of extracts from the test report requires the prior written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test report shall be invalid without all the signatures of testing the Project Manager, the Deputy Project Manager and the Test Lab Manager. Any objections must be raised to Morlab within 30 days since the date when the report is received. It will not be taken into consideration beyond this limit.


### 1.2. Organization item

Report No.:	SZ09080026S01
Date of Issue:	Oct 16, 2009
Date of Tests:	Sep 28, 2009 – Sep 28, 2009
Responsible for Accreditation:	Shu luan
Project Manager:	Li lei
Deputy Project Manager:	Chen chao

### 1.3. Conclusion

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory has verified that all tests as listed in the section 4.5 of this report have been performed successfully with the tested equipment.

 Chen chao  
*Tested by*  
(Responsible for the Test Report)

 Li lei  
*Reviewed by*  
(Verification of the Test Report)

 Shu luan  
*Approved by*  
(Responsible Test Lab Manager)



## 2. Testing Laboratory

### 2.1. Identification of the Responsible Testing Laboratory

Company Name: Shenzhen Electronic Product Quality Testing Center  
Department: Morlab Laboratory  
Address: 3/F, Electronic Testing Building, Shahe Road, Nanshan District, Shenzhen, 518055 P. R. China  
Responsible Test Lab Manager: Mr. Shu Luan  
Telephone: +86 755 86130268  
Facsimile: +86 755 86130218

### 2.2. Identification of the Responsible Testing Location

Name: Shenzhen Electronic Product Quality Testing Center Morlab Laboratory  
Address: 3/F, Electronic Testing Building, Shahe Road, Nanshan District, Shenzhen, 518055 P. R. China

### 2.3. Accreditation Certificate

Accredited Testing Laboratory: No. CNAS L1659 (see Annex A)

### 2.4. List of Test Equipments

No.	Instrument	Type
1	PC	Dell (Pentium IV 2.4GHz, SN:X10-23533)
2	Network Emulator	Rohde&Schwarz (CMU200, SN:105894)
3	Voltmeter	Keithley (2000, SN:1000572)
4	Synthetizer	Rohde&Schwarz (SML_03, SN:101868)
5	Amplifier	Nucl udes (ALB216, SN:10800)
6	Power Meter	Rohde&Schwarz (NRVD, SN:101066)
7	Probe	Antennessa (SN:SN_3708_EP80)
8	Phantom	Antennessa (SN:SN_36_08_SAM62)
9	Liquid	Antennessa (Last Calibration:21 08 04)

### 3. Technical Information

Note: the following data is based on the information by the applicant.

#### 3.1. Identification of Applicant

Company Name: SUNTECH TECHNOLOGIES CO.,LTD.  
Address: Rm419--420,Merchants Building,Shuiwan Road,SheKou,Nanshan District,shenzhen,China

#### 3.2. Identification of Manufacturer

Company Name: SUNTECH TECHNOLOGIES CO.,LTD.  
Address: Rm419--420,Merchants Building,Shuiwan Road,SheKou,Nanshan District,shenzhen,China

#### 3.3. Equipment Under Test (EUT)

Brand Name: LANIX  
Type Name: LANIX  
Marking Name: X10  
Hardware Version: E502 V0.2  
Software Version: X10.PR.R1.0.V030\_TELCEL  
Frequency Bands: GSM 850MHz (channel 128:824.20MHz,channel 190:836.59MHz, channel 251:848.29MHz)  
PCS 1900MHz (channel 512:1850.19MHz,channel 661:1880.00MHz, channel 810:1909.80MHz)  
Modulation Mode: GMSK  
Antenna type: Build inside  
Accessories: Charger; Battery  
Battery Model: X10  
Battery specification: 1000mAh 3.7V  
Development Stage: Identical prototype  
Multislot Class: GPRS: Multislot Class 12

### 3.3.1. Photographs of the EUT

Please see for photographs of the EUT.

### 3.3.2. Identification of all used EUTs

The EUT Identity consists of numerical and letter characters (see the table below), the first five numerical characters indicates the Type of the EUT defined by Morlab, the next letter character indicates the test sample, and the following two numerical characters indicates the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	E502 V0.2	X10.PR.R1.0.V030_TELCEL

## 4. Test Results

### 4.1. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	<b>47 CFR § 2. 1093</b>	Radiofrequency Radiation Exposure Evaluation: Portable Devices
2	<b>FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01)</b>	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
3	<b>ANSI C95.1-1999</b>	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 GHz
4	<b>IEEE 1528-2003</b>	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techuiques.

## 4.2. Test Environment/Conditions

Normal Temperature (NT):	20 ... 25 °C
Relative Humidity:	30 ... 75 %
Air Pressure:	980 ... 1020 hPa
Details of Power Supply:	220V/50Hz AC
Extreme Temperature:	Low Temperature (LT) = -10°C High Temperature (HT) = 55°C
Extreme Voltage of the EUT:	Normal Voltage (NV) = 3.70V Low Voltage (LV) = 3.60V High Voltage (HV) = 4.20V
Test frequency:	GSM 850MHz PCS 1900MHz
Operation mode:	Call established
Power Level:	GSM 850 MHz Maximum output power(level 5) PCS 1900 MHz Maximum output power(level 0)

During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established.

The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 125, 190 and 251 respectively in the case of GSM 850 MHz, or to 512, 661 and 810 respectively in the case of PCS 1900 MHz, The EUT, The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset.

The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 35 dB.

## 4.3. Operational Conditions During Test

### 4.3.1. Informations On The Testing

#### I. INFORMATIONS ON THE TESTING


##### I.1. Normative reference

IEEE 1528: Recommended Practice for determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques. Institute of Electrical and Electronics Engineers, INC., 2003.

##### I.3. Positions and test conditions of the mobile phone under test

The mobile phone antenna and battery are those specified by the manufacturer. The battery is fully charged before each measurement. The output power and frequency are controlled using a base station simulator. The mobile phone is set to transmit at its highest output peak power level.

The mobile phone is test in the “cheek” and “tilted” positions on the left and right sides of the phantom. The mobile phone is placed with the vertical centre line of the body of the mobile phone and the horizontal line crossing the centre of the earpiece in a plane parallel to the sagittal plane of the phantom.



Description of the « cheek » position:

The mobile phone is well placed in the reference plane and the earpiece is in contact with the ear. Then the mobile phone is moved until any point on the front side get in contact with the cheek of the phantom or until contact with the ear is lost.

Description of the « tilted » position:


The mobile phone is well place in the “cheek” position as described above. Then the mobile phone is moved outward away from the mouth by an angle of 15 degrees or until contact with the ear lost.

### 4.3.2. The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



COMOSAR bench

The mobile phone under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10 g mass.

#### III.1. Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2 mm +/- 0,2 mm. It enables the dosimetric evaluation of left and right hand phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

#### III.2. Probe

For the measurements the Specific Dosimetric E-Field Probe SSE5 with following specifications is used.

- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 5 mm

- Distance between probe tip and sensor center : 2.5 mm
- Distance between sensor center and the inner phantom surface: 4 mm (repeatability better than +/- 1mm).
- Probe linearity : <0.25 dB
- Axial Isotropy : <0.25 dB
- Spherical Isotropy : <0.50 dB
- Calibration range : 835 to 2500 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line : less than 30°

### II.3. Measurement procedure

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16 mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors can not directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8 \* 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

### II.4 Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine these highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

### 4.3.3. Uncertainty Assessment

The following table includes the uncertainty table of the IEEE 1528.

The values are determined by Antennessa.

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	$\infty$
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1 C_p)^{1/2}$	$(1 C_p)^{1/2}$	1.02	1.02	$\infty$
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	1.63	1.63	$\infty$
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	$\infty$
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	$\infty$
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	$\infty$
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	$\infty$
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	$\infty$
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	$\infty$
Test sample Related									
Test sample positioning	E.4.2.1	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR drift measurement	6.6.2	4.76	R	$\sqrt{3}$	1	1	2.75	2.75	$\infty$
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	$\infty$
Liquid conductivity - deviation from target value	E.3.2	0.57	R	$\sqrt{3}$	0.64	0.43	0.21	0.14	$\infty$

Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	M
Liquid permittivity - deviation from target value	E.3.2	3.66	R	$\sqrt{3}$	0.6	0.49	1.27	1.04	$\infty$
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty			RSS				11.28	10.78	
Expanded Uncertainty (95% Confidence interval)			k				21.99	21.03	

#### 4.3.4. Equipments and results of validation testing

Equipments :

name	Type and specification
Signal generator	E4433B
Directional coupler	450MHz-3GHz
Amplifier	3W 502(10-2500MHz)
Reference dipole	SN 36/08 DIPF 101

Results:

Frequency	835MHz	1900MHz
Target value (1g)	10.8 W/Kg(body)	39.7 W/Kg
250 mW input power	2.709 W/Kg (head) 2.701 W/Kg (body)	9.843 W/Kg (head) 10.22 W/Kg (body)
Test value (1g)	10.836 W/Kg (head) 10.804 W/Kg (body)	39.372 W/Kg (head) 40.88 W/Kg (body)

Note:Please refer to check the system performance data, the first 133-144 page. 250 mW input power

#### 4.3.5. Dielectric Performance

The measured 1-gram averaged SAR values of the device against the head and the body are provided in Tables 1 and 2 respectively. The humidity and ambient temperature of test facility were 54% ~60% and 23.0 °C ~23.8°C respectively. The SAM head phantom (SN 0381 SH) were full of the head tissue simulating liquid. The depth of the body tissue was 15.1cm. The distance between the back of the device and the bottom of the flat phantom is 1.5cm (taking into account of the IEEE 1528 and the place of the antenna). A base station simulator was used to control the device during the SAR measurement. The phone was supplied with full-charged battery for each measurement.

For head measurement, the device was tested at the lowest, middle and highest frequencies in the transmit band.

**Table 1: Dielectric Performance of Head Tissue Simulating Liquid**

Temperature: 23.0~23.8°C, humidity: 54~60%.			
/	Frequency	Permittivity $\epsilon$	Conductivity $\sigma$ (S/m)
<b>Target value</b>	835 MHZ	41.5	0.90
<b>Validation value (Sep 28)</b>	835 MHZ	41.790001	0.866612
<b>Target value</b>	1900 MHZ	40	1.40
<b>Validation value (Sep 28)</b>	1900 MHZ	39.481223	1.395758

For body-worn measurements, the device was tested against flat phantom representing the user body. Under measurement phone was put on in the belt holder.

**Table 2: Dielectric Performance of Body Tissue Simulating Liquid**

Temperature: 23.0~23.8°C, humidity: 54~60%.			
/	Frequency	Permittivity $\epsilon$	Conductivity $\sigma$ (S/m)
<b>Target value</b>	835 MHz	55.0	0.95
<b>Validation value (Sep 28)</b>	835 MHz	54.872231	1.054822
<b>Target value</b>	1900 MHz	53.3	1.52

<b>Validation value (Sep 28)</b>	1900 MHz	52.548876	1.573978
--------------------------------------	----------	-----------	----------

#### 4.3.6. Simulant liquids

Simulant liquids that are used for testing at frequencies of GSM 850MHz and GSM 1900MHz, which are made mainly of sugar, salt and water solutions may be left in the phantoms. Approximately 20litres are needed for an upright head compared to about 20litres for a horizontal bath phantom.

Ingredients (% by weight )	Frequency Band		Frequency Band	
	835MHz		1900MHz	
Tissue Type	Head	Body	Head	Body
Water	41.45	52.4	55.36	40.4
Salt(NaCl)	1.45	1.4	0.35	0.5
Sugar	56.0	45.0	30.45	58.0
HEC	1.0	1.0	0.0	1.0
Bactericide	0.1	0.1	0.0	0.1
Triton	0.0	0.0	0.0	0.0
DGBE	0.0	0.0	13.84	0.0
Acticide SPX	0.0	0.0	0.0	0.0
Dielectric Constant	42.45	56.1	41.00	54.0
Conductivity (S/m)	0.91	0.95	1.38	1.45

#### 4.4. Items used in the Test Results List

Terms in the column “Verdict” for the test results list of the section 4.5:

Verdict	Description
PASS	EUT passed this test case
FAIL	EUT failed this test case
INC.	EUT did not pass and did not fail this test case, therefore the verdict is inconclusive
Decl.	“Declaration”: Morlab has received documents from the applicant and/or manufacturer which show conformity to the applied standards for this test case.
N/A	Test case not applicable for the EUT, see the column “Note” for detailed

## 4.5. Test Results List

Summary of Measurement Results (GSM 850MHz Band)  
SAR Values (GSM 850MHz Band), Measured against the head.

Temperature: 23.0~23.8°C, humidity: 54~60%.		
Limit of SAR (W/kg)	1 g Average	
	1.6	
Test Case	Measurement Result (W/kg)	
Left head, Touch cheek, Channel Low	1 g Average (W/kg)	Power level (dBm)
Left head, Touch cheek, Channel Middle	0.082	30.79
Left head, Touch cheek, Channel High	0.104	30.64
Left head, Tilt 15 Degree, Channel Low	0.136	30.76
Left head, Tilt 15 Degree, Channel Middle	0.071	30.79
Left head, Tilt 15 Degree, Channel High	0.089	30.64
Right head, Touch cheek, Channel Low	0.117	30.76
Right head, Touch cheek, Channel Middle	0.082	30.79
Right head, Touch cheek, Channel High	0.097	30.64
Right head, Tilt 15 Degree, Channel Low	0.124	30.76
Right head, Tilt 15 Degree, Channel Middle	0.091	30.79
Right head, Tilt 15 Degree, Channel High	0.112	30.64
Right head, Tilt 15 Degree, Channel Low	0.131	30.76

Summary of Measurement Results (GSM 1900MHz Band)  
SAR Values (GSM 1900MHz Band), Measured against the head.

Temperature: 23.0~23.8°C, humidity: 54~60%.		
Limit of SAR (W/kg)	1 g Average	
	1.6	
Test Case	Measurement Result (W/kg)	
Left head, Touch cheek, Channel Low	1 g Average (W/kg)	Power level (dBm)
Left head, Touch cheek, Channel Middle	0.258	28.34
Left head, Touch cheek, Channel High	0.236	28.74
Left head, Tilt 15 Degree, Channel Low	0.172	31.04
Left head, Tilt 15 Degree, Channel Middle	0.234	28.34
Left head, Tilt 15 Degree, Channel High	0.219	28.74
Right head, Touch cheek, Channel Low	0.171	31.04
Right head, Touch cheek, Channel High	0.348	28.34

Right head, Touch cheek, Channel Middle	0.292	28.74
Right head, Touch cheek, Channel High	0.238	31.04
Right head, Tilt 15 Degree, Channel Low	0.254	28.34
Right head, Tilt 15 Degree, Channel Middle	0.232	28.74
Right head, Tilt 15 Degree, Channel High	0.188	31.04

SAR Values (GSM 850MHz Band), Measured against the body.

Temperature: 23.0~23.8°C, humidity: 54~60%.		
Limit of SAR (W/kg)		1 g Average
		1.6
Test Case		Measurement Result (W/kg)
		1 g Average (W/kg) Power level (dBm)
Side, Low frequency	0.462	30.79
Side, Middle frequency	0.541	30.64
Side, High frequency	0.623	30.76
Side, High frequency(back)	0.172	30.76
Side, High frequency(with GPRS)	1.559	30.76
Side, High frequency(with earphone)	0.590	30.76

SAR Values (GSM 1900MHz Band), Measured against the body.

Temperature: 23.0~23.8°C, humidity: 54~60%.		
Limit of SAR (W/kg)		1 g Average
		1.6
Test Case		Measurement Result (W/kg)
		1 g Average (W/kg) Power level (dBm)
Side, Low frequency	0.452	28.34
Side, Middle frequency	0.517	28.74
Side, High frequency	0.337	31.04
Side, Middle frequency(back)	0.119	31.04
Side, Middle frequency(with GPRS)	0.954	31.04
Side, Middle frequency(with earphone)	0.493	31.04


**Note:** The depth of the body tissue was 15.1cm. The distance between the back of the device and the bottom of the flat phantom is 1.5cm(taking into account of the IEEE 1528 and the place of the antenna)

## Annex A Accreditation Certificate



## Annex B Photographs of the EUT


### 1 EUT Left Head Touch Cheek Position



### 2 EUT Left Head Tilt15 Position



## 3 EUT Right Head Touch Cheek Position



## 4 EUT Right Head Tilt15 Position



5 spacer 1.5cm



6 Side Position



7 with earphone



## Annex C Graph Test Results

<u>TYPE</u>	<u>BAND</u>	<u>PARAMETERS</u>
	<u>GSM850</u>	<p><u>Measurement 1:</u> Right Head with Cheek device position on Low Channel in GSM mode</p> <p><u>Measurement 2:</u> Right Head with Cheek device position on Middle Channel in GSM mode</p> <p><u>Measurement 3:</u> Right Head with Cheek device position on High Channel in GSM mode</p> <p><u>Measurement 4:</u> Right Head with Tilt device position on Low Channel in GSM mode</p> <p><u>Measurement 5:</u> Right Head with Tilt device position on Middle Channel in GSM mode</p> <p><u>Measurement 6:</u> Right Head with Tilt device position on High Channel in GSM mode</p> <p><u>Measurement 7:</u> Left Head with Cheek device position on Low Channel in GSM mode</p> <p><u>Measurement 8:</u> Left Head with Cheek device position on Middle Channel in GSM mode</p> <p><u>Measurement 9:</u> Left Head with Cheek device position on High Channel in GSM mode</p> <p><u>Measurement 10:</u> Left Head with Tilt device position on Low Channel in GSM mode</p> <p><u>Measurement 11:</u> Left Head with Tilt device position on Middle Channel in GSM mode</p> <p><u>Measurement 12:</u> Left Head with Tilt device position on High Channel in GSM mode</p> <p><u>Measurement 13:</u> Validation Plane with Body device position on Low Channel in GSM mode</p> <p><u>Measurement 14:</u> Validation Plane with Body device position on Middle Channel in GSM mode</p> <p><u>Measurement 15:</u> Validation Plane with Body device position on High Channel in GSM mode</p> <p><u>Measurement 16:</u> Validation Plane with Body device position on High Channel in GSM mode (back)</p> <p><u>Measurement 17:</u> Validation Plane with Body device position on High Channel in GSM mode (with earphone)</p> <p><u>Measurement 18:</u> Validation Plane with Body device position on High Channel in GSM mode (with GRPS)</p>

		<p><u>Measurement 19:</u> Right Head with Cheek device position on Low Channel in GSM mode</p> <p><u>Measurement 20:</u> Right Head with Cheek device position on Middle Channel in GSM mode</p> <p><u>Measurement 21:</u> Right Head with Cheek device position on High Channel in GSM mode</p> <p><u>Measurement 22:</u> Right Head with Tilt device position on Low Channel in GSM mode</p> <p><u>Measurement 23:</u> Right Head with Tilt device position on Middle Channel in GSM mode</p> <p><u>Measurement 24:</u> Right Head with Tilt device position on High Channel in GSM mode</p> <p><u>Measurement 25:</u> Left Head with Cheek device position on Low Channel in GSM mode</p> <p><u>Measurement 26:</u> Left Head with Cheek device position on Middle Channel in GSM mode</p> <p><u>Measurement 27:</u> Left Head with Cheek device position on High Channel in GSM mode</p> <p><u>Measurement 28:</u> Left Head with Tilt device position on Low Channel in GSM mode</p> <p><u>Measurement 29:</u> Left Head with Tilt device position on Middle Channel in GSM mode</p> <p><u>Measurement 30:</u> Left Head with Tilt device position on High Channel in GSM mode</p> <p><u>Measurement 31:</u> Validation Plane with Body device position on Low Channel in GSM mode</p> <p><u>Measurement 32:</u> Validation Plane with Body device position on Middle Channel in GSM mode</p> <p><u>Measurement 33:</u> Validation Plane with Body device position on High Channel in GSM mode</p> <p><u>Measurement 34:</u> Validation Plane with Body device position on Low Channel in GSM mode (back)</p> <p><u>Measurement 35:</u> Validation Plane with Body device position on Low Channel in GSM mode (with earphone)</p> <p><u>Measurement 36:</u> Validation Plane with Body device position on Low Channel in GSM mode (with GPRS)</p>
	<p><u><b>GSM</b></u></p> <p><u><b>1900</b></u></p>	

## MEASUREMENT 1

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 28 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM850
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 128):

<b>Frequency (MHz)</b>	824.200012
<b>Relative permittivity (real part)</b>	41.790001
<b>Relative permittivity</b>	18.926250

<b>Conductivity (S/m)</b>	0.866612
<b>Variation (%)</b>	-2.190000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-32.00, Y=-9.00**

<b>SAR 10g (W/Kg)</b>	0.057549
<b>SAR 1g (W/Kg)</b>	0.081752

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0858	0.0639	0.0453	0.0352	0.0246	0.0180

**SAR, Z Axis Scan (X = -32, Y = -9)**

## MEASUREMENT 2

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 32 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM850
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 190):

<b>Frequency (MHz)</b>	836.599976
<b>Relative permittivity (real part)</b>	40.669998
<b>Relative permittivity</b>	19.120001

<b>Conductivity (S/m)</b>	0.888655
<b>Variation (%)</b>	-1.010000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-32.00, Y=-14.00**

<b>SAR 10g (W/Kg)</b>	0.067731
<b>SAR 1g (W/Kg)</b>	0.096934

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0974	0.0733	0.0548	0.0415	0.0301	0.0226

**SAR, Z Axis Scan (X = -32, Y = -14)**

## MEASUREMENT 3

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 36 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	41.675999
<b>Relative permittivity</b>	18.967199

<b>Conductivity (S/m)</b>	0.894409
<b>Variation (%)</b>	-1.370000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-32.00, Y=-15.00**

<b>SAR 10g (W/Kg)</b>	0.087430
<b>SAR 1g (W/Kg)</b>	0.124481

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1253	0.0963	0.0720	0.0515	0.0391	0.0283

**SAR, Z Axis Scan (X = -32, Y = -15)**

## MEASUREMENT 4

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 27 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM850
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 128):

<b>Frequency (MHz)</b>	824.200012
<b>Relative permittivity (real part)</b>	41.790001
<b>Relative permittivity</b>	18.926250

<b>Conductivity (S/m)</b>	0.866612
<b>Variation (%)</b>	-4.410000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-6.00, Y=14.00**

<b>SAR 10g (W/Kg)</b>	0.055708
<b>SAR 1g (W/Kg)</b>	0.091142

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0938	0.0580	0.0370	0.0237	0.0158	0.0106

**SAR, Z Axis Scan (X = -6, Y = 14)**

## MEASUREMENT 5

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 26 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM850
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 190):

<b>Frequency (MHz)</b>	836.599976
<b>Relative permittivity (real part)</b>	40.669998
<b>Relative permittivity</b>	19.120001

<b>Conductivity (S/m)</b>	0.888655
<b>Variation (%)</b>	0.150000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-2.00, Y=10.00**

<b>SAR 10g (W/Kg)</b>	0.068339
<b>SAR 1g (W/Kg)</b>	0.112462

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1194	0.0719	0.0438	0.0285	0.0192	0.0128

**SAR, Z Axis Scan (X = -2, Y = 10)**

## MEASUREMENT 6

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 23 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	41.675999
<b>Relative permittivity</b>	18.967199

<b>Conductivity (S/m)</b>	0.894409
<b>Variation (%)</b>	-2.570000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-6.00, Y=15.00**

<b>SAR 10g (W/Kg)</b>	0.077356
<b>SAR 1g (W/Kg)</b>	0.130693

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1388	0.0793	0.0497	0.0328	0.0218	0.0146

**SAR, Z Axis Scan (X = -6, Y = 15)**

## MEASUREMENT 7

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 27 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM850
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 128):

<b>Frequency (MHz)</b>	824.200012
<b>Relative permittivity (real part)</b>	41.790001
<b>Relative permittivity</b>	18.926250

<b>Conductivity (S/m)</b>	0.866612
<b>Variation (%)</b>	-0.730000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-25.00, Y=-8.00**

<b>SAR 10g (W/Kg)</b>	0.059951
<b>SAR 1g (W/Kg)</b>	0.082296

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0846	0.0658	0.0500	0.0385	0.0294	0.0215

**SAR, Z Axis Scan (X = -25, Y = -8)**

## MEASUREMENT 8

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 28 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM850
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 190):

<b>Frequency (MHz)</b>	836.599976
<b>Relative permittivity (real part)</b>	40.669998
<b>Relative permittivity</b>	19.120001

<b>Conductivity (S/m)</b>	0.888655
<b>Variation (%)</b>	-0.340000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-29.00, Y=-9.00**

<b>SAR 10g (W/Kg)</b>	0.075013
<b>SAR 1g (W/Kg)</b>	0.103749

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1080	0.0821	0.0639	0.0478	0.0366	0.0264

**SAR, Z Axis Scan (X = -29, Y = -9)**



## MEASUREMENT 9

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 24 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	41.675999
<b>Relative permittivity</b>	18.967199

<b>Conductivity (S/m)</b>	0.894409
<b>Variation (%)</b>	-0.370000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-26.00, Y=-8.00**

<b>SAR 10g (W/Kg)</b>	0.098381
<b>SAR 1g (W/Kg)</b>	0.135667

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1399	0.1070	0.0840	0.0623	0.0472	0.0335

**SAR, Z Axis Scan (X = -26, Y = -8)**



## MEASUREMENT 10

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 21 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM850
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 128):

<b>Frequency (MHz)</b>	824.200012
<b>Relative permittivity (real part)</b>	41.790001
<b>Relative permittivity</b>	18.926250

<b>Conductivity (S/m)</b>	0.866612
<b>Variation (%)</b>	0.340000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=1.00, Y=1.00**

<b>SAR 10g (W/Kg)</b>	0.046763
<b>SAR 1g (W/Kg)</b>	0.071301

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0740	0.0486	0.0325	0.0229	0.0166	0.0113

**SAR, Z Axis Scan (X = 1, Y = 1)**

## MEASUREMENT 11

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 21 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM850
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 190):

<b>Frequency (MHz)</b>	836.599976
<b>Relative permittivity (real part)</b>	40.669998
<b>Relative permittivity</b>	19.120001

<b>Conductivity (S/m)</b>	0.888655
<b>Variation (%)</b>	0.020000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=1.00, Y=0.00**

<b>SAR 10g (W/Kg)</b>	0.058130
<b>SAR 1g (W/Kg)</b>	0.088795

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0925	0.0605	0.0405	0.0291	0.0194	0.0144

**SAR, Z Axis Scan (X = 1, Y = 0)**

## MEASUREMENT 12

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 27/9/2009

Measurement duration: 7 minutes 16 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	41.675999
<b>Relative permittivity</b>	18.967199

<b>Conductivity (S/m)</b>	0.894409
<b>Variation (%)</b>	0.200000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=1.00, Y=0.00**

<b>SAR 10g (W/Kg)</b>	0.076962
<b>SAR 1g (W/Kg)</b>	0.116836

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1219	0.0794	0.0531	0.0369	0.0251	0.0178

**SAR, Z Axis Scan (X = 1, Y = 0)**

## MEASUREMENT 13

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 1 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM850
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 128):

<b>Frequency (MHz)</b>	824.200012
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity</b>	21.284550

<b>Conductivity (S/m)</b>	0.974596
<b>Variation (%)</b>	-1.090000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=0.00, Y=-8.00**

<b>SAR 10g (W/Kg)</b>	0.324352
<b>SAR 1g (W/Kg)</b>	0.461561

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.4753	0.3415	0.2577	0.1883	0.1364	0.0992

SAR, Z Axis Scan (X = 0, Y = -8)



## MEASUREMENT 14

Type: Phone measurement (Complete)

Area scan resolution:  $dx=8\text{mm}, dy=8\text{mm}$

Zoom scan resolution:  $dx=8\text{mm}, dy=8\text{mm}, dz=5\text{mm}$

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 8 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM850
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 190):

<b>Frequency (MHz)</b>	836.599976
<b>Relative permittivity (real part)</b>	55.709999
<b>Relative permittivity</b>	21.709999

<b>Conductivity (S/m)</b>	1.009033
<b>Variation (%)</b>	-1.120000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-1.00, Y=-7.00**

<b>SAR 10g (W/Kg)</b>	0.382700
<b>SAR 1g (W/Kg)</b>	0.540726

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.5595	0.4178	0.2974	0.2210	0.1608	0.1172

SAR, Z Axis Scan (X = -1, Y = -7)



## MEASUREMENT 15

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 1 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	54.014999
<b>Relative permittivity</b>	21.332850

<b>Conductivity (S/m)</b>	1.005962
<b>Variation (%)</b>	-0.590000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=0.00, Y=-2.00**

<b>SAR 10g (W/Kg)</b>	0.431323
<b>SAR 1g (W/Kg)</b>	0.622645

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.6472	0.4518	0.3401	0.2426	0.1811	0.1261

SAR, Z Axis Scan (X = 0, Y = -2)



## MEASUREMENT 16

Type: Phone measurement (Complete)

Area scan resolution:  $dx=8\text{mm}, dy=8\text{mm}$

Zoom scan resolution:  $dx=8\text{mm}, dy=8\text{mm}, dz=5\text{mm}$

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 5 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	54.014999
<b>Relative permittivity</b>	21.332850

<b>Conductivity (S/m)</b>	1.005962
<b>Variation (%)</b>	1.050000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=0.00, Y=-16.00**

<b>SAR 10g (W/Kg)</b>	0.120827
<b>SAR 1g (W/Kg)</b>	0.171661

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1746	0.1304	0.0966	0.0718	0.0516	0.0383

**SAR, Z Axis Scan (X = 0, Y = -16)**



## MEASUREMENT 17

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 7 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GPRS

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	54.014999
<b>Relative permittivity</b>	21.332850

<b>Conductivity (S/m)</b>	1.005962
<b>Variation (%)</b>	-1.490000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:2





**Maximum location: X=-1.00, Y=-9.00**

<b>SAR 10g (W/Kg)</b>	1.069449
<b>SAR 1g (W/Kg)</b>	1.558697

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	1.6345	1.1463	0.8215	0.6040	0.4356	0.3297

SAR, Z Axis Scan (X = -1, Y = -9)



## MEASUREMENT 18

Type: Phone measurement (Complete)

Area scan resolution:  $dx=8\text{mm}, dy=8\text{mm}$

Zoom scan resolution:  $dx=8\text{mm}, dy=8\text{mm}, dz=5\text{mm}$

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 7 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM850
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 251):

<b>Frequency (MHz)</b>	848.799988
<b>Relative permittivity (real part)</b>	54.014999
<b>Relative permittivity</b>	21.332850

<b>Conductivity (S/m)</b>	1.005962
<b>Variation (%)</b>	-1.490000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:8





**Maximum location: X=-1.00, Y=-9.00**

<b>SAR 10g (W/Kg)</b>	0.392612
<b>SAR 1g (W/Kg)</b>	0.590234

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	1.6345	1.1463	0.8215	0.6040	0.4356	0.3297

SAR, Z Axis Scan (X = -1, Y = -9)



## MEASUREMENT 19

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 29 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM1900
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 512):

<b>Frequency (MHz)</b>	1850.199951
<b>Relative permittivity (real part)</b>	39.993999
<b>Relative permittivity</b>	12.991650

<b>Conductivity (S/m)</b>	1.335397
<b>Variation (%)</b>	0.590000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-31.00, Y=2.00**

<b>SAR 10g (W/Kg)</b>	0.197407
<b>SAR 1g (W/Kg)</b>	0.347997

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.3703	0.2145	0.1326	0.0807	0.0488	0.0299

**SAR, Z Axis Scan (X = -31, Y = 2)**

## MEASUREMENT 20

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 33 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	38.509998
<b>Relative permittivity</b>	13.750000

<b>Conductivity (S/m)</b>	1.436111
<b>Variation (%)</b>	-0.250000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-29.00, Y=5.00**

<b>SAR 10g (W/Kg)</b>	0.165731
<b>SAR 1g (W/Kg)</b>	0.292209

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.3120	0.1855	0.1081	0.0656	0.0406	0.0249

**SAR, Z Axis Scan (X = -29, Y = 5)**

## MEASUREMENT 21

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 29 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM1900
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 810):

<b>Frequency (MHz)</b>	1909.800049
<b>Relative permittivity (real part)</b>	39.929001
<b>Relative permittivity</b>	13.156500

<b>Conductivity (S/m)</b>	1.395905
<b>Variation (%)</b>	0.320000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-31.00, Y=1.00**

<b>SAR 10g (W/Kg)</b>	0.134287
<b>SAR 1g (W/Kg)</b>	0.237521

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2425	0.1444	0.0856	0.0526	0.0316	0.0185

**SAR, Z Axis Scan (X = -31, Y = 1)**

## MEASUREMENT 22

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 25 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM1900
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 512):

<b>Frequency (MHz)</b>	1850.199951
<b>Relative permittivity (real part)</b>	39.993999
<b>Relative permittivity</b>	12.991650

<b>Conductivity (S/m)</b>	1.335397
<b>Variation (%)</b>	0.670000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-7.00, Y=14.00**

<b>SAR 10g (W/Kg)</b>	0.148084
<b>SAR 1g (W/Kg)</b>	0.253785

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2682	0.1560	0.0941	0.0548	0.0334	0.0202

**SAR, Z Axis Scan (X = -7, Y = 14)**

## MEASUREMENT 23

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 25 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	38.509998
<b>Relative permittivity</b>	13.750000

<b>Conductivity (S/m)</b>	1.436111
<b>Variation (%)</b>	-1.570000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-7.00, Y=15.00**

<b>SAR 10g (W/Kg)</b>	0.134437
<b>SAR 1g (W/Kg)</b>	0.231720

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2445	0.1448	0.0847	0.0473	0.0285	0.0161

**SAR, Z Axis Scan (X = -7, Y = 15)**



## MEASUREMENT 24

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 19 seconds

### A. Experimental conditions.


<b>Phantom File</b>	zinf3.txt
<b>Phantom</b>	Right head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM1900
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 810):

<b>Frequency (MHz)</b>	1909.800049
<b>Relative permittivity (real part)</b>	39.929001
<b>Relative permittivity</b>	13.156500

<b>Conductivity (S/m)</b>	1.395905
<b>Variation (%)</b>	0.300000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-7.00, Y=15.00**

<b>SAR 10g (W/Kg)</b>	0.107583
<b>SAR 1g (W/Kg)</b>	0.187950

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1974	0.1095	0.0611	0.0355	0.0213	0.0115

**SAR, Z Axis Scan (X = -7, Y = 15)**

## MEASUREMENT 25

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 25 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM1900
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 512):

<b>Frequency (MHz)</b>	1850.199951
<b>Relative permittivity (real part)</b>	39.993999
<b>Relative permittivity</b>	12.991650

<b>Conductivity (S/m)</b>	1.335397
<b>Variation (%)</b>	1.030000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-17.00, Y=-26.00**

<b>SAR 10g (W/Kg)</b>	0.153603
<b>SAR 1g (W/Kg)</b>	0.258344

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2728	0.1702	0.1010	0.0634	0.0388	0.0244

**SAR, Z Axis Scan (X = -17, Y = -26)**

## MEASUREMENT 26

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 20 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	38.509998
<b>Relative permittivity</b>	13.750000

<b>Conductivity (S/m)</b>	1.436111
<b>Variation (%)</b>	-0.290000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-18.00, Y=-26.00**

<b>SAR 10g (W/Kg)</b>	0.137319
<b>SAR 1g (W/Kg)</b>	0.235544

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2497	0.1424	0.0894	0.0583	0.0341	0.0208

SAR, Z Axis Scan (X = -18, Y = -26)



## MEASUREMENT 27

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 24 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Cheek
<b>Band</b>	GSM1900
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 810):

<b>Frequency (MHz)</b>	1909.800049
<b>Relative permittivity (real part)</b>	39.929001
<b>Relative permittivity</b>	13.156500

<b>Conductivity (S/m)</b>	1.395905
<b>Variation (%)</b>	-2.610000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-16.00, Y=-24.00**

<b>SAR 10g (W/Kg)</b>	0.102970
<b>SAR 1g (W/Kg)</b>	0.171933

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1777	0.1101	0.0716	0.0457	0.0270	0.0166

**SAR, Z Axis Scan (X = -16, Y = -24)**



## MEASUREMENT 28

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 23 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM1900
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 512):

<b>Frequency (MHz)</b>	1850.199951
<b>Relative permittivity (real part)</b>	39.993999
<b>Relative permittivity</b>	12.991650

<b>Conductivity (S/m)</b>	1.335397
<b>Variation (%)</b>	-1.640000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-2.00, Y=-7.00**

<b>SAR 10g (W/Kg)</b>	0.141386
<b>SAR 1g (W/Kg)</b>	0.234208

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2448	0.1555	0.0990	0.0628	0.0400	0.0249

**SAR, Z Axis Scan (X = -2, Y = -7)**



## MEASUREMENT 29

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 23 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	38.509998
<b>Relative permittivity</b>	13.750000

<b>Conductivity (S/m)</b>	1.436111
<b>Variation (%)</b>	-0.770000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-2.00, Y=-7.00**

<b>SAR 10g (W/Kg)</b>	0.129661
<b>SAR 1g (W/Kg)</b>	0.218534

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.2286	0.1377	0.0876	0.0551	0.0334	0.0218

**SAR, Z Axis Scan (X = -2, Y = -7)**

## MEASUREMENT 30

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 7 minutes 27 seconds

### A. Experimental conditions.


<b>Phantom File</b>	sam_direct_droit2_surf8mm.txt
<b>Phantom</b>	Left head
<b>Device Position</b>	Tilt
<b>Band</b>	GSM1900
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 810):

<b>Frequency (MHz)</b>	1909.800049
<b>Relative permittivity (real part)</b>	39.929001
<b>Relative permittivity</b>	13.156500

<b>Conductivity (S/m)</b>	1.395905
<b>Variation (%)</b>	-0.400000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-3.00, Y=-5.00**

<b>SAR 10g (W/Kg)</b>	0.101114
<b>SAR 1g (W/Kg)</b>	0.170741

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1777	0.1087	0.0686	0.0449	0.0265	0.0177

**SAR, Z Axis Scan (X = -3, Y = -5)**

## MEASUREMENT 31

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 9 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	Low
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR (Channel 512):

<b>Frequency (MHz)</b>	1850.199951
<b>Relative permittivity (real part)</b>	39.929001
<b>Relative permittivity</b>	12.000000

<b>Conductivity (S/m)</b>	1.233467
<b>Variation (%)</b>	0.500000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=14.00, Y=46.00**

<b>SAR 10g (W/Kg)</b>	0.259457
<b>SAR 1g (W/Kg)</b>	0.451864

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.4758	0.2787	0.1701	0.0975	0.0583	0.0327

**SAR, Z Axis Scan (X = 14, Y = 46)**

## MEASUREMENT 32

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 8 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	51.540001
<b>Relative permittivity</b>	15.070000

<b>Conductivity (S/m)</b>	1.573978
<b>Variation (%)</b>	-1.940000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=14.00, Y=47.00**

<b>SAR 10g (W/Kg)</b>	0.288565
<b>SAR 1g (W/Kg)</b>	0.516540

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.5335	0.3105	0.1839	0.1083	0.0623	0.0369

SAR, Z Axis Scan (X = 14, Y = 47)



## MEASUREMENT 33

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 7 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	High
<b>Signal</b>	GSM

### B. SAR Measurement Results

Higher Band SAR (Channel 810):

<b>Frequency (MHz)</b>	1909.800049
<b>Relative permittivity (real part)</b>	51.540001
<b>Relative permittivity</b>	12.000000

<b>Conductivity (S/m)</b>	1.273200
<b>Variation (%)</b>	-2.930000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=16.00, Y=41.00**

<b>SAR 10g (W/Kg)</b>	0.189397
<b>SAR 1g (W/Kg)</b>	0.337269

**Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.3478	0.2015	0.1193	0.0695	0.0415	0.0235

**SAR, Z Axis Scan (X = 16, Y = 41)**

## MEASUREMENT 34

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 7 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	51.540001
<b>Relative permittivity</b>	15.070000

<b>Conductivity (S/m)</b>	1.573978
<b>Variation (%)</b>	-1.210000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=-14.00, Y=37.00**

<b>SAR 10g (W/Kg)</b>	0.071919
<b>SAR 1g (W/Kg)</b>	0.119023

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.1237	0.0762	0.0502	0.0300	0.0181	0.0109

**SAR, Z Axis Scan (X = -14, Y = 37)**



## MEASUREMENT 35

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 8 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GPRS

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	51.540001
<b>Relative permittivity</b>	15.070000

<b>Conductivity (S/m)</b>	1.573978
<b>Variation (%)</b>	-1.940000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:2





**Maximum location: X=14.00, Y=47.00**

<b>SAR 10g (W/Kg)</b>	0.638565
<b>SAR 1g (W/Kg)</b>	0.954854

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.5335	0.3105	0.1839	0.1083	0.0623	0.0369

SAR, Z Axis Scan (X = 14, Y = 47)



## MEASUREMENT 36

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 28/9/2009

Measurement duration: 9 minutes 8 seconds

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	Middle
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR (Channel 661):

<b>Frequency (MHz)</b>	1880.000000
<b>Relative permittivity (real part)</b>	51.540001
<b>Relative permittivity</b>	15.070000

<b>Conductivity (S/m)</b>	1.573978
<b>Variation (%)</b>	-1.940000
<b>Ambient Temperature:</b>	22.3°C
<b>Liquid Temperature:</b>	21.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:8





**Maximum location: X=14.00, Y=47.00**

<b>SAR 10g (W/Kg)</b>	0.265924
<b>SAR 1g (W/Kg)</b>	0.493758

### Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.5335	0.3105	0.1839	0.1083	0.0623	0.0369

SAR, Z Axis Scan (X = 14, Y = 47)



## System Performance Check Data(835MHz Head)

Type: Phone measurement (Complete)

Date of measurement: 28/9/2009

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM 835MHz
<b>Channels</b>	
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR:

<b>Frequency (MHz)</b>	835.00000
<b>Relative permittivity (real part)</b>	41.790001
<b>Relative permittivity</b>	18.926250
<b>Conductivity (S/m)</b>	0.866612


<b>Variation (%)</b>	-0.050000
<b>Ambient Temperature:</b>	22.5°C
<b>Liquid Temperature:</b>	22.4°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:1



<b>SAR 10g (W/Kg)</b>	1.875252
<b>SAR 1g (W/Kg)</b>	2.709422

**Z Axis Scan**

<b>Z (mm)</b>	0.00	4.00	9.00	14.00	19.00
<b>SAR (W/Kg)</b>	0.0000	2.6486	1.2069	0.5583	0.3002

**SAR, Z Axis Scan (X = 5, Y = 1)**

## System Performance Check Data(835MHz Body)

Type: Phone measurement (Complete)

Date of measurement: 28/9/2009

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM 835MHz
<b>Channels</b>	
<b>Signal</b>	GSM

### B. SAR Measurement Results

Middle Band SAR:

<b>Frequency (MHz)</b>	835.000000
<b>Relative permittivity (real part)</b>	54.872231
<b>Relative permittivity</b>	15.070000
<b>Conductivity (S/m)</b>	1.054822

<b>Variation (%)</b>	-0.140000
<b>Ambient Temperature:</b>	23.5°C
<b>Liquid Temperature:</b>	22.8°C
<b>ConvF:</b>	28.479,25.214,27.196
<b>Crest factor:</b>	1:1




**Maximum location: X=5.00, Y=1.00**

<b>SAR 10g (W/Kg)</b>	1.652852
<b>SAR 1g (W/Kg)</b>	2.701584

**Z Axis Scan**

<b>Z (mm)</b>	0.00	4.00	9.00	14.00	19.00
<b>SAR (W/Kg)</b>	0.0000	2.8536	1.3061	0.6041	0.3211

**SAR, Z Axis Scan (X = 5, Y = 1)**

## System Performance Check Data(1900MHz Head)

Type: Phone measurement (Complete)

Date of measurement: 28/9/2009

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR:

<b>Frequency (MHz)</b>	1900.000000
<b>Relative permittivity (real part)</b>	39.481223
<b>Relative permittivity (</b>	12.991650
<b>Conductivity (S/m)</b>	1.395758

<b>Variation (%)</b>	0.570000
<b>Ambient Temperature:</b>	23.5°C
<b>Liquid Temperature:</b>	22.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:1




**Maximum location: X=7.00, Y=8.00**

<b>SAR 10g (W/Kg)</b>	5.873331
<b>SAR 1g (W/Kg)</b>	9.843651

**Z Axis Scan**

<b>Z (mm)</b>	0.00	4.00	9.00	14.00	19.00
<b>SAR (W/Kg)</b>	0.0000	1.3503	0.3791	0.0904	0.0338

**SAR, Z Axis Scan (X = 7, Y = 8)**

## System Performance Check Data(1900MHz Body)

Type: Phone measurement (Complete)

Date of measurement: 28/9/2009

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

### A. Experimental conditions.


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	GSM1900
<b>Channels</b>	
<b>Signal</b>	GSM

### B. SAR Measurement Results

Lower Band SAR:

<b>Frequency (MHz)</b>	1900.000000
<b>Relative permittivity (real part)</b>	52.548876
<b>Relative permittivity (imaginary part)</b>	12.991650

<b>Conductivity (S/m)</b>	1.573978
<b>Variation (%)</b>	0.570000
<b>Ambient Temperature:</b>	23.5°C
<b>Liquid Temperature:</b>	22.8°C
<b>ConvF:</b>	40.136,34.843,38.721
<b>Crest factor:</b>	1:1



<b>SAR 10g (W/Kg)</b>	5.487222
<b>SAR 1g (W/Kg)</b>	10.225723

**Z Axis Scan**

<b>Z (mm)</b>	0.00	4.00	9.00	14.00	19.00
<b>SAR (W/Kg)</b>	0.0000	1.3503	0.3791	0.0904	0.0338

**SAR, Z Axis Scan (X = 7, Y = 8)**