

國際電器認證中心有限公司 International Electrical Certification Centre Ltd.

提供電器產品測試國際認證及諮詢服務 Technical Services in Electrical Product Testing, International Certification & Information

FCC - Test Report

Date: 2011-11-10

No. 55629-1

Page 1 of 14

LABORATORY - REPORT

APPLICANT:

EB BRANDS (HK)

ADDRESS:

Unit 705 & 706, Enterprise Square, Phase 1

Tower III, 9 Sheung Yuet Road

Kowloon Bay, Kowloon

Hong Kong

DATE OF SAMPLE RECEIVED:

2011-11-03

DATE OF TESTING:

2011-11-04 to 2011-11-07

DESCRIPTION OF SAMPLE:

Product:

1:24 Hummer

Model number:

5857

Product class:

Low Power Communication Device – Transmitter (49 MHz)

FCC ID number:

XRB5857YE49TX

Rating:

DC 3V (AA size battery x 2)

CONDITION OF TEST SAMPLE:

The received sample was under good condition.

INVESTIGATIONS

REQUESTED:

Measurements to the relevant clauses of F.C.C. Rules and Regulations Part

15 Subpart C - Intentional Radiators.

RESULTS:

See the attached sheets.

CONCLUSIONS:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirements for the relevant clauses of Federal

Communications Commission Rules as specified above.

Stephen C.N. Wong Technical Manager



FCC - Test Report

No. 55629-1

Page 2 of 14

Date: 2011-11-10


TABLE OF CONTENTS

- 1. Laboratory Report Cover
- 2. Table of Contents
- 3. Test Location and Summary of Test Results
- 4. Test Equipment List
- 5. Radiated Emission Test Setup
- 6. Conducted Emission Test Setup
- 7. Test Procedure
- 8. Test Results
- 9-13. Measurement Data
- 14. Photo of sample

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室

E-mail 電子郵件: info@iecc.com.hk Home Page 網頁: <u>http://www.iecc.com.hk</u>

Tel 電話: (852) 2305 2570





Date: 2011-11-10

FCC - Test Report

No. 55629-1 Page 3 of 14

Test Location

International Electrical Certification Centre Ltd. Units 602-605, 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong

Tel: +852 23052570 Fax: +852 27564480 Email: info@iecc.com.hk

Summary of Test Results

Radiated Emission:

Test result: O.K.

Test data: See attached data sheet

Conducted Emission:

Test result: Not Applicable Test data: Not Applicable

Measurement of Emissions within Band Edges

Test result: O.K.

Test data: See attached data sheet

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室

E-mail 電子郵件: info@iecc.com.hk Home Page 網頁: http://www.iecc.com.hk

Tel 電話: (852) 2305 2570



FCC - Test Report

Date: 2011-11-10

No. 55629-1

Page 4 of 14

TEST EQUIPMENT LIST


Equipment	Manufacturer	Model	Serial No.	Last Calibration Date	Next Calibration Date	
Test Receiver	Rohde & Schwarz	ESVS 30	828525/006	09/08/2011	08/08/2012	
Antenna	Schaffner	CBL6111C	2791	30/09/2010	29/09/2012	
Antenna Mast System	Schwarzbeck	AM9104				
Turntable with Controller	Drehtisch	DT312				
Spectrum Analyzer with Q. Peak	Advantest	R3132	140101852	09/08/2011	08/08/2012	

FCC - Test Report

No. 55629-1

Date: 2011-11-10 Page 5 of 14

Radiated Emission Test Setup (3 m diatance) (> 30MHz)



Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室

E-mail 電子郵件: info@iecc.com.hk Home Page 網頁: http://www.iecc.com.hk


FCC - Test Report

No. 55629-1

Page 6 of 14

Date: 2011-11-10

Conducted Emission Test Setup



LEGEND:

- Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long (see 6.1.4 and 11.2.4).
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.1.4).
- 3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference groundplane (see 5.2.3 and 7.2.1).
 - 3.1) All other equipment powered from additional LISN(s).
 - 3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3) LISN at least 80 cm from nearest part of EUT chassis.
- 4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use (See 6.2.1.3 and 11.2.4).
- Non-EUT components of EUT system being tested (see also Figure 13).
- Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.1.1 and 6.2.1.2).
- Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the groundplane (see 5.2.2 for options).

Tel 電話: (852) 2305 2570



FCC - Test Report

No. 55629-1

Page 7 of 14

Date: 2011-11-10

Test Procedure

Radiated Emission:

The EUT was tested according to ANSI 63.4-2003 for the requirements of FCC Part 15 Subpart C Section 15.209 and 15.235.

During the test, the sample was placed on a turn table and operated with new batteries. The table is 0.8 meter above the reference ground plane on the Open Aera Test Site and can rotate 360 degrees to determine the position of the maximum emission level. A broad-band antenna for the frequency range 30 - 1000 MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The antenna is capable of measuring both horizontal and vertical polarizations. The antenna was raised from 1 to 4 meters to find out the maximum emission level from the EUT.

An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes. Final measurement (30 MHz -1000 MHz) was then performed to record the data for the emissions under worst-case condition for combination of the antenna orientation / height and turn table position.

- Note: 1. Fundamental emission for this pulse modulated device was measured with the peak detector function of the test receiver and was properly adjusted for the duty cycle correction factor as pulse desensitization to calculate the average emission value.
 - 2. The Open Aera Test Site located at IECC was placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (FCC Registration No.: 97774).

Conducted Emission:

Not Applicable

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室

E-mail 電子郵件: info@iecc.com.hk Home Page 網頁: http://www.iecc.com.hk

Tel 電話: (852) 2305 2570



FCC - Test Report

Date: 2011-11-10

No. 55629-1

Page 8 of 14

Test Results

Radiated Emission:

Test Requirement: FCC Part 15 Subpart C Section 15.209 and 15.235

Test Method: ANSI C63.4: 2003

Deviations from Standard Test Method: Nil

30MHz - 1000MHz Frequency Range:

Measurement Distance: 3 m

Detector: Peak (for fundamental frequency)

Quasi-Peak (for frequencies outside the operation band)

Tel 電話: (852) 2305 2570

Fax 傅真: (852) 2756 4480

Refer to page 9-13 for measurement data.

Conducted Emission:

Not Applicable

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室



FCC – Test Report Date: 2011-11-10

No. 55629-1

Page 9 of 14

Radiated Emission

Measurement of Radiated Emissions FCC Part 15 Subpart C (15.235)

 IECC Ref:
 55629-1
 Test Equipment

 Model:
 5857
 Receiver: Rohde & Schwarz ESVS 30

 Applicant:
 EB BRANDS (HK)
 Antenna: Schaffner CBL6111C

Sample No.: 1

 Set under test:
 1:24 Hummer

 Connected sets:

 Operating mode:
 Operate (forward)

Radiation Measurement

a. Fundamental Frequency

 Frequency (MHz)
 Maximum Test Result (dB(μV/m))
 FCC Limit (dB(μV/m))

 Peak
 Average
 *
 Peak
 Average

 49.8775
 64.4
 58.9
 100
 80

Note: (1) The above peak value is the maximum value of the measurement in 3 orthogonal planes

(2) * Calculation for radiation (average):

Formula:

Duty cycle = (N1L1 + N2L2 + ... + Nn-1Ln-1 + NnLn) / 100 or T

where N1 is number of type 1 pluse, L1 is length of type 1 pulse, etc. T is the period of the pulse train (if less than 100 ms)

According to the time domain plots shown in page 11 & 12 : Duty cycle of the EUT = $(1\times0.98 + 2\times0.66 + 26\times0.34) / 20.96 = 0.53$

Av correction factor = 20 x log(0.53) dB = -5.5 dB

Radiation (average) = Radiation (peak) + Av correction factor

Radiation (average) of the EUT = 64.4 - 5.5 dB(μ V/m) = 58.9 dB(μ V/m)

b. The measured radiation outside the operation band were checked and found to comply with 15.235(b).
 (refer to page 12 and 13 for measurement data)

Tel 電話: (852) 2305 2570




FCC - Test Report

No. 55629-1


Radiated Emission

Date: <u>2011-11-10</u>
Page 10 of 14





Pulse cycle period = 20.96 ms



Pulse width = 0.98 ms (total number of pulse: 1)




FCC - Test Report

No. 55629-1


Date: 2011-11-10 Page 11 of 14

Radiated Emission

Transmitter Emission - Time Domain Plots



Pulse width = 0.66 ms (total number of pulse : 2)



Pulse width = 0.34 ms (total number of pulse : 26)

Operator: WH

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室

Tel 電話: (852) 2305 2570 Fax 傳真: (852) 2756 4480

E-mail 電子郵件: info@iecc.com.hk Home Page 網頁: http://www.iecc.com.hk

Test Equipment

Receiver: Rohde & Schwarz ESVS 30

Antenna: Schaffner CBL6111C



提供電器產品測試國際認證及諮詢服務 Technical Services in Electrical Product Testing, International Certification & Information

FCC - Test Report

No. 55629-1

Date: 2011-11-10

Page 12 of 14

Radiated Emission

Measurement of Radiated Emissions Acc: FCC Part 15 Subpart C (15.235 & 15.209)

Frequency (MHz)	Н	orz. Reading dΒ(μV)	Ve	rt. Reading dΒ(μV)	Corr. Factor (dB)		Horiz. Test Result dB(μV/m)		Vert. Test Result dB(μV/m)	Limit dB(μV/m)
30	<	16	٧	16	20.5	<	36.5	<	36.5	40.0
99.75		16.5		19.5	12.0		28.5		31.5	43.5
149.63	<	16	٧	16	13.4	<	29.4	<	29.4	43.5
199.51	<	16	٧	16	10.9	<	26.9	<	26.9	43.5
249.39		18.5	٧	16	14.8	Г	33.3	<	30.8	46.0
299.27		23.5	٧	16	15.8	Г	39.3	<	31.8	46.0
349.14	<	16	٧	16	17.0	<	33.0	<	33.0	46.0
399.02	<	16	٧	16	18.6	<	34.6	<	34.6	46.0
500	<	16	٧	16	20.6	<	36.6	<	36.6	46.0
700	<	16	٧	16	23.8	<	39.8	<	39.8	46.0
1000	<	16	٧	16	28.0	<	44.0	<	44.0	54.0

Note: 1. Unless otherwise indicated, the recorded readings are in quasi-peak values.

The above results were the worst case results with the sample positioned in all 3 axis during the test.The sample was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively. The antenna of the sample was fully extended during the test.

Operator: WH

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong. 香港新界粉嶺安樂村樂業路 31 號 6 樓 602-605 室

E-mail 電子郵件: info@iecc.com.hk Home Page 網頁: http://www.iecc.com.hk

Tel 電話: (852) 2305 2570




FCC - Test Report

No. 55629-1

Date: 2011-11-10 Page 13 of 14

Measurement Data of Emissions within Band Edges



Result: The field strength of any emission within the operation band did not exceed 80 $dB(\mu V/m)$ for average value or 100 $dB(\mu V/m)$ for peak value. Refer to page 9 for the recorded value for the emission at the fundamental frequency.

Tel 電話: (852) 2305 2570



FCC - Test Report

No. 55629-1

Date: 2011-11-10 Page 14 of 14

Photo of Sample

