

## FCC – Test Report

Date: 2009-10-14


No. 52751-1

Page 1 of 15

## LABORATORY - REPORT

**APPLICANT:** EB BRANDS (HK)**ADDRESS:** Unit 705 & 706 Enterprise Square Phase 1, Tower III  
9 Sheung Yuet Road  
Kowloon Bay, Kowloon  
Hong Kong**DATE OF SAMPLE RECEIVED:** 2009-10-05**DATE OF TESTING:** 2009-10-09 to 2009-10-13**DESCRIPTION OF SAMPLE:**

Product: 1:64 Scale Lamborghini  
Model number: 9331Y  
Product class: Low Power Communication Device - Transmitter  
FCC ID number: XRB9331Y27TX  
Rating: DC 4.5V (AA size battery x 3)

**CONDITION OF TEST SAMPLE:** The received sample was under good condition.**INVESTIGATIONS REQUESTED:** Measurements to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart C - Intentional Radiators.**RESULTS:** See the attached sheets.**CONCLUSIONS:** From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.  
IECC  
INTERNATIONAL ELECTRICAL CERTIFICATION CENTRE LTD.  
Stephen C.N. Wong  
Technical Manager

# FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 2 of 15

## TABLE OF CONTENTS

1. Laboratory Report Cover
2. Table of Contents
3. Test Location and Summary of Test Results
4. Test Equipment List
- 5-6. Radiated Emission Test Setup
7. Conducted Emission Test Setup
8. Test Procedure
9. Test Results
- 10-14. Measurement Data
15. Photo of sample

## FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 3 of 15

### Test Location

International Electrical Certification Centre Ltd.  
Unit 602-605, 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong  
Tel : +852 23052570  
Fax : +852 27564480  
Email : [info@iecc.com.hk](mailto:info@iecc.com.hk)

### Summary of Test Results

#### Radiated Emission:

Test result: O.K.  
Test data: See attached data sheet

#### Conducted Emission:

Test result: Not Applicable  
Test data: Not Applicable

#### Measurement of Emissions within Band Edges

Test result: O.K.  
Test data: See attached data sheet

Address 地址

Units 602-605, 6/F , 31 Lok Yip Rd , On Lok Tsuen, Fanling, N.T , Hong Kong  
香港新界粉嶺安樂村樂業路31號6樓602-605室

China 中國

IECC (Guangzhou) Services Co . Ltd 廣州匯立進技術服務有限公司

Address 地址

Flat A, 2/F , Block 3, 56 Shuiyin Road, Guangzhou, P R of China  
廣州市水蔭路56號3樓2A室Tel 電話 (852) 2305 2570  
Fax 傳真: (852) 2756 4480Tel 電話 (86-20) 8768 4838  
Fax 傳真: (86-20) 8768 3918E-mail 電子郵件: [info@iecc.com.hk](mailto:info@iecc.com.hk)Home Page 網頁: <http://www.iecc.com.hk>E-mail 電子郵件: [info@iecc.net.cn](mailto:info@iecc.net.cn)Home Page 網頁: <http://www.iecc.net.cn>

**FCC – Test Report**Date: 2009-10-14**No. 52751-1**


Page 4 of 15

**TEST EQUIPMENT LIST**

Equipment	Manufacturer	Model	Serial No.	Last Calibration Date	Next Calibration Date
Test Receiver	Rohde & Schwarz	ESCS 30	100388	10/9/2009	9/9/2010
Test Receiver	Rohde & Schwarz	ESHS 30	839667/002	07/01/2009	06/01/2010
Loop Antenna	Rohde & Schwarz	HFH2-Z2	871336/48	7/12/2006	6/12/2009
Antenna	Schaffner	CBL6111C	2791	22/07/2008	21/07/2010
Antenna Mast System	Schwarzbeck	AM9104	--	--	--
Turntable with Controller	Drehtisch	DT312	--	--	--
Spectrum Analyzer with Q. Peak	Advantest	R3132	140101852	1/06/2009	31/05/2010

**FCC – Test Report**Date: 2009-10-14**No. 52751-1**

Page 5 of 15

**Radiated Emission Test Setup ( 9kHz – 30MHz)**


## FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 6 of 15

## Radiated Emission Test Setup (3 m diatance) (&gt; 30MHz)




## FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 7 of 15

## Conducted Emission Test Setup



**LEGEND:**

- 1) Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long (see 6.1.4 and 11.2.4).
- 2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.1.4).
- 3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference groundplane (see 5.2.3 and 7.2.1).
  - 3.1) All other equipment powered from additional LISN(s).
  - 3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - 3.3) LISN at least 80 cm from nearest part of EUT chassis.
- 4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use (See 6.2.1.3 and 11.2.4).
- 5) Non-EUT components of EUT system being tested (see also Figure 13).
- 6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.1.1 and 6.2.1.2).
- 7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the groundplane (see 5.2.2 for options).

## FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 8 of 15

## Test Procedure

### Radiated Emission :

The EUT was tested according to ANSI 63.4-2003 for the requirements of FCC Part 15 Subpart C Section 15.209 and 15.227.

#### 1. Measurement Frequencies below 30MHz :

During the test, the sample was placed on a turn table and operated under various modes with supply from new batteries. The table is 0.8 meter and can rotate 360 degrees to determine the position of the maximum emission level. A loop antenna for the frequency range 9kHz - 30MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The center of the loop was 1 m above the floor, positioned with its plane vertical at the specified distance and rotated about its vertical axis and placed horizontal for maximum response at each azimuth about the EUT.

An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes. Final measurement was then performed to record the data for fundamental emission within the operation band and spurious emissions outside the band under worst-case condition for combination of the antenna orientation and turn table position.

Note : Fundamental emission for this pulse modulated device was measured with the peak detector function of the test receiver and was properly adjusted for the duty cycle correction factor as pulse desensitization to calculate the average emission value.

#### 2. Measurement Frequencies 30MHz – 1000 MHz :

During the test, the sample was placed on a turn table and operated with supply from new batteries. The table is 0.8 meter above the reference ground plane on the Open Aera Test Site and can rotate 360 degrees to determine the position of the maximum emission level. A broad-band antenna for the frequency range 30 - 1000 MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The antenna is capable of measuring both horizontal and vertical polarizations. The antenna was raised from 1 to 4 meters to find out the maximum emission level from the EUT.

An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes. Final measurement (30 MHz –1000 MHz) was then performed to record the data for the emissions under worst-case condition for combination of the antenna orientation / height and turn table position.

Note : The Open Aera Test Site located at IECC was placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (FCC Registration No. : 97774).

### Conducted Emission :

Not Applicable

## FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 9 of 15

## Test Results

### Radiated Emission :

Test Requirement:	FCC Part 15 Subpart C Section 15.209 and 15.227
Test Method:	ANSI C63.4 : 2003
Deviations from Standard Test Method:	Nil
Frequency Range:	9kHz – 1000MHz
Measurement Distance:	3 m
Detector:	Peak (for fundamental frequency) Quasi-Peak (for frequencies outside the operation band)

Refer to page 10 - 14 for measurement data.

### Conducted Emission :

Not Applicable

Address 地址

Units 602-605, 6/F , 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T ., Hong Kong  
香港新界粉嶺安樂邨樂景路31號6樓602-605室

China 中國:

IECC (Guangzhou) Services Co , Ltd. 廣州時宜達技術服務有限公司

Address 地址

Flat A, 2/F , Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China

廣州市水荫路56號3樓2A室

Tel 電話: (852) 2305 2570  
Fax 傳真: (852) 2756 4480E-mail 電子郵件: info@iecc.com.hk  
Home Page 網頁: <http://www.iecc.com.hk>

Tel 電話: (86-20) 8768 4838

Fax 傳真: (86-20) 8768 3918

E-mail 電子郵件: info@iecc.net.cn

Home Page 網頁: <http://www.iecc.net.cn>

## Radiated Emission

Date : 2009-10-14

Page 10 of 15

### Measurement of Radiated Emissions FCC Part 15 Subpart C (15.227)

IECC Ref:	52751-1
Model:	9331Y
Applicant:	EB BRANDS (HK)
Sample No.:	1
Set under test:	1:64 Scale Lamborghini
Connected sets:	-
Operating mode:	Operate

#### Test Equipment

Receiver: ESCS 30 Rohde & Schwarz  
Antenna: HFH2-ZZ Rohde & Schwarz

#### Radiation Measurement (3 m) below 30MHz

##### a. Fundamental Frequency

Frequency (MHz)	Maximum Test Result (dB(μV/m))		FCC Limit (dB(μV/m))	
	Peak	Average *	Peak	Average
27.145	61.0	57.5	100	80

Note : (1) The above peak value is the maximum value of the measurement in 3 orthogonal planes

(2) \* Calculation for radiation (average) :

Formula :

$$\text{Duty cycle} = (N1L1 + N2L2 + \dots + Nn-1Ln-1 + NnLn) / 100 \text{ or } T$$

where N1 is number of type 1 pulse, L1 is length of type 1 pulse, etc.  
T is the period of the pulse train (if less than 100 ms)

According to the time domain plots shown in page 11 & 12 :

$$\text{Duty cycle of the EUT} = (4 \times 1.5 + 10 \times 0.54) / 16.98 = 0.67$$

$$\begin{aligned} \text{Av correction factor} &= 20 \times \log(0.67) \text{ dB} \\ &= -3.48 \text{ dB} \end{aligned}$$

$$\text{Radiation (average)} = \text{Radiation (peak)} + \text{Av correction factor}$$

$$\begin{aligned} \text{Radiation (average) of the EUT} &= 61.0 - 3.48 \text{ dB}(\mu\text{V/m}) \\ &= 57.5 \text{ dB}(\mu\text{V/m}) \end{aligned}$$


b. The measured radiation outside the operation band were negligible

## Radiated Emission

Date : 2009-10-14

Page 11 of 15

## Transmitter Emission - Time Domain Plots



Pulse cycle period = 16.98 ms

Address 地址

Units 602-605, 6/F, 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong  
香港新界粉嶺安樂村樂業路31號6樓602-605室

China 中國

IECC (Guangzhou) Services Co., Ltd 廣州時並達技術服務有限公司  
Flat A, 2/F., Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China  
廣州市水蔭路56號3樓2A室Tel 電話 (852) 2305 2570  
Fax 傳真 (852) 2758 4480E-mail 電子郵件: info@iecc.com.hk  
Home Page 網頁: http://www.iecc.com.hk

Address 地址


Tel 電話 (86-20) 8768 4838  
Fax 傳真 (86-20) 8768 3918E-mail 電子郵件: info@iecc.net.cn  
Home Page 網頁: http://www.iecc.net.cn

## Radiated Emission


Date : 2009-10-14

Page 12 of 15

## Transmitter Emission - Time Domain Plots



Pulse width = 1.5 ms (total number of pulse : 4)



Pulse width = 0.54 ms (total number of pulse : 10)

Address 地址：

Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong  
香港新界粉嶺安樂村樂業路31號6樓602-605室

China 中国

Address 地址：  
IECC (Guangzhou) Services Co., Ltd. 廣州勝亞達技術服務有限公司  
Flat A, 2/F, Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China  
廣州市水蔭路56號3棟2A室Tel 電話 (852) 2305 2570  
Fax 傳真 (852) 2756 4480E-mail 發子郵件 info@iecc.com.hk  
Home Page 網頁 <http://www.iecc.com.hk>Tel 電話 (86-20) 8768 4838  
Fax 傳真 (86-20) 8768 3918E-mail 發子郵件 info@iecc.net.cn  
Home Page 網頁 <http://www.iecc.net.cn>

## Interference Radiation

Date : 2009-10-14

Measurement of Radiated Emissions  
Acc: FCC Part 15 Subpart C (15.227 & 15.209)

Page 13 of 15

IECC Ref:	52751-1
Model:	9331Y
Applicant:	EB BRANDS (HK)
Ser.Nr.:	--
Set under test:	1:64 Scale Lamborghini
Connected sets:	-
Operating mode:	Operate

Test Equipment  
Receiver: Rohde & Schwarz ESCS 30  
Antenna: Schaffner CBL6111C

Frequency (MHz)	Horz. Reading dB(µV)	Vert. Reading dB(µV)	Corr. Factor (dB)	Horiz. Test Result dB(µV/m)	Vert. Test Result dB(µV/m)	Limit dB(µV/m)
30	< 16	< 16	19.1	< 35.1	< 35.1	40.0
54.29	19	27	7.0	26.0	34.0	43.5
81.435	< 16	19	8.0	< 24.0	27.0	46.0
108.58	< 16	< 16	10.9	< 26.9	< 26.9	46.0
135.725	< 16	< 16	10.9	< 26.9	< 26.9	46.0
162.87	< 16	< 16	10.7	< 26.7	< 26.7	46.0
190.015	< 16	< 16	9.2	< 25.2	< 25.2	54.0
217.2	< 16	< 16	9.5	< 25.5	< 25.5	46.0
250	< 16	< 16	13.6	< 29.6	< 29.6	46.0
300	< 16	< 16	14.2	< 30.2	< 30.2	46.0
500	< 16	< 16	18.9	< 34.9	< 34.9	46.0
1000	< 16	< 16	26.2	< 42.2	< 42.2	54.0

Note : 1. Unless otherwise indicated, the recorded readings are in quasi-peak values.  
 2. The above results were the worst case results with the sample positioned in all 3 axis during the test.  
 The worst case data were recorded with the antenna of the sample fully extended. The sample was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.

Operator : WH


## FCC – Test Report

Date: 2009-10-14

No. 52751-1

Page 14 of 15

# Measurement Data of Emissions within Band Edges



Result : The field strength of any emission within the operation band did not exceed 80 dB( $\mu$ V/m) for average value or 100 dB( $\mu$ V/m) for peak value. Refer to page 10 for the recorded value for the emission at the fundamental frequency.

**FCC – Test Report**

Date: 2009-10-14

**No. 52751-1**

Page 15 of 15

**Photo of Sample**