

## FCC CLASS B CONFORMITY REPORT

**Product Name** : Wireless Projector Adaptor Receiver  
**Trade Name** : N/A  
**Model Number** : PTXXXR Series  
**FCC ID** : XSDPTXXXR  
**Report Number** : SZEE091012430911-3  
**Date** : October 30, 2009

Standards	Results
<input checked="" type="checkbox"/> FCC Part 15B: 2008	PASS

Prepared for:

**Advanced Sun Wah Electronic Co., Ltd**  
**Unit 10,19F/,Kowloon Plaza, No.485 Castle Peak Road, Lai Chi Kok,**  
**Kowloon,Hongkong,China**  
**TEL: +86-755-2784 2833**  
**FAX: +86-755-2784 2170**

Prepared by:

**CENTRE TESTING INTERNATIONAL CORPORATION**  
**Building C, Hongwei Industrial Zone, Baoan 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

**This report shall not be reproduced, except in full, without the written approval of**  
**CENTRE TESTING INTERNATIONAL CORPORATION**

**Building C, Hongwei Industrial Zone, Baoan 70 District, Shenzhen**

## TABLE OF CONTENTS

Description	Page
<b>1. CERTIFICATION OF CONFORMITY .....</b>	<b>3</b>
<b>2. TEST SUMMARY .....</b>	<b>4</b>
<b>3. MEASUREMENT UNCERTAINTY .....</b>	<b>4</b>
<b>4. PRODUCT INFORMATION .....</b>	<b>4</b>
<b>5. FACILITIES AND ACCREDITATIONS .....</b>	<b>4</b>
<b>6. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>5</b>
<b>7. FCC CONDUCTED EMISSION TEST.....</b>	<b>6</b>
7.1 LIMITS OF FCC CONDUCTED EMISSION TEST .....	6
7.2 BLOCK DIAGRAM OF TEST SETUP .....	6
7.3 PROCEDURE OF CONDUCTED EMISSION TEST.....	6
7.4 TEST RESULT OF CONDUCTED EMISSION TEST .....	7
<b>8. FCC RADIATED EMISSION TEST .....</b>	<b>8</b>
8.1 LIMITS OF FCC RADIATED EMISSION TEST.....	8
8.2 BLOCK DIAGRAM OF TEST SETUP .....	8
8.3 PROCEDURE OF RADIATED EMISSION TEST .....	9
8.4 TEST RESULT OF RADIATED EMISSION TEST .....	9
<b>APPENDIX 1 PHOTOGRAPHS OF TEST SETUP.....</b>	<b>11</b>
<b>APPENDIX 2 EXTERNAL PHOTOS OF EUT .....</b>	<b>13</b>
<b>APPENDIX 3 INTERNAL PHOTOS OF EUT .....</b>	<b>14</b>

## 1. Certification of Conformity

**Applicant & Address:** Advanced Sun Wah Electronic Co., Ltd  
Unit 10,19F/, Kowloon Plaza, No.485 Castle Peak Road,  
Lai Chi Kok, Kowloon,Hongkong,China

**Manufacturer Site:** Advanced Sun Wah Electronic Co., Ltd  
Unit 10,19F/,Kowloon Plaza, No.485 Castle Peak Road,  
Lai Chi Kok, Kowloon,Hongkong,China

**Type of Test:** FCC Part 15B

**Product Name:** Wireless Projector Adaptor Receiver

**Model Number:** PTXXXR(XXX stand for 000-999)

**FCC ID Number:** XSDPTXXXR

**Test Model:** PT501R

**Model Discrepancy :** The models of Wireless Projector Adaptor Receiver is PTXXXR, all the models are identical except for the color, the appearance and the model name. And the test model is PT501R, all the test results are applicable to the other models.

**Date of test:** October 26, 2009 to October 30, 2009

**Condition of Test Sample:** Normal


The above equipment was tested by Centre Testing International for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, Subpart B and the measurement procedure according to ANSI C63.4.

The test results of this report relate only to the tested sample identified in this report.


Prepared by :

  
Saky Yan

Reviewed by :

  
Louisa Lu

Approved by :

  
Jim Zhang

Manager

Date

: October 30, 2009

## 2. TEST SUMMARY

The EUT has been tested according to the following specifications:

EMISSION			
Standard	Test Type	Result	Remark
FCC Part 15	Conducted emission at AC power port	PASS	See clause 7 in this report
	Radiated emission	PASS	See clause 8 in this report

## 3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement items	Value
Conducted emission	3.2 dB
Radiated emission	4.6 dB

## 4. PRODUCT INFORMATION

Technical Data: DC 5V by PC USB Port

## 5. FACILITIES AND ACCREDITATIONS

### 5.1 TEST FACILITY

All measurement facilities used to collect the measurement data are located at Building C, Hongwei Industrial Zone, Baoan 70 District, Shenzhen, Guangdong, China. The sites are constructed in conformance with the requirements of ANSI C63.4, and CISPR 16.

### 5.2 TEST EQUIPMENT LIST

**Instrumentation:** The following list contains equipments used at CTI for testing.

The calibrations of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors applied in accordance with instructions contained in the manual for the measuring instrument.

### Equipment used during the tests:

3M Semi-anechoic Chamber — Radiation Test Site				
Equipment Type	Manufacturer	Model Number	Serial Number	Due Date
10M Chamber & Accessories	Rainford	N/A	N/A	06/19/2011
Spectrum Analyzer	Agilent	E4443A	MY46185649	01/29/2010
Loop Antenna	ETS-LINDGREN	6502	00071730	08/25/2010
Biconilog Antenna	A.H.System	SAS-521-2	487	06/05/2010
Multi device Controller	ETS-LINGREN	2090	00057230	01/29/2010

Shielding Room No. 1 — Conduction Test Site				
Equipment Type	Manufacturer	Model Number	Serial Number	Due Date
Receiver	R&S	ESCI	100435	08/25/2010
LISN	R&S	ENV216	100098	08/25/2010

### 5.3 LABORATORY ACCREDITATIONS AND LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by China National Accreditation Board for Laboratories (CNAS). Electromagnetic Interference tests according to ANSI C63.4 and CISPR 16 requirements.

## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

1. See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.
2. Make sure EUT work normally during the whole test.

### 6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	Data Cable	Power Cord
1.	Notebook PC	Sony	PCG-3G1T	282170999014058	Notebook PC	Sony

### Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


## 7. FCC CONDUCTED EMISSION TEST

### 7.1 LIMITS OF FCC CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P. ( dBuV)	Average( dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

**Note:** the tighter limit applies at the band edges.

### 7.2 BLOCK DIAGRAM OF TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

### 7.3 PROCEDURE OF CONDUCTED EMISSION TEST

- The EUT was placed 0.4 meters from the conducting wall of the shielded room and connected to the main through Line Impedance Stability Network (LISN). This provided a 50ohm coupling impedance for the tested equipments.
- The bandwidth of the field strength meter (Receiver) was set at 9kHz in 150kHz ~ 30MHz.
- The disturbance levels and the frequencies of at least two highest disturbances were recorded from each power line which comprises the EUT.

## 7.4 TEST RESULT OF CONDUCTED EMISSION TEST

FCC Conducted Emission Test Result														
Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limits (dBuV)		Margin		Result (P/F)	Remarks (L/N)	
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.			
0.4060	41.18	38.59	23.33	9.99	51.17	48.58	33.32	57.73	47.73	-9.15	-14.41	P	L	
0.4380	42.06	39.49	22.26	10.00	52.06	49.49	32.26	57.10	47.10	-7.61	-14.84	P	L	
0.5140	41.19	37.73	23.74	10.01	51.20	47.74	33.75	56.00	46.00	-8.26	-12.25	P	L	
0.9020	40.05	33.77	19.10	9.88	49.93	43.65	28.98	56.00	46.00	-12.35	-17.02	P	L	
1.5580	38.46	32.59	17.89	9.84	48.30	42.43	27.73	56.00	46.00	-13.57	-18.27	P	L	
2.2580	35.93	31.90	16.85	9.82	45.75	41.72	26.67	56.00	46.00	-14.28	-19.33	P	L	
0.3899	39.72	35.01	22.92	9.99	49.71	45.00	32.91	58.06	48.06	-13.06	-15.15	P	N	
0.4580	40.47	36.60	23.41	10.00	50.47	46.60	33.41	56.73	46.73	-10.13	-13.32	P	N	
0.5940	40.90	37.70	22.79	9.98	50.88	47.68	32.77	56.00	46.00	-8.32	-13.23	P	N	
0.8340	38.25	34.01	18.43	9.90	48.15	43.91	28.33	56.00	46.00	-12.09	-17.67	P	N	
1.6780	37.01	32.97	18.30	9.84	46.85	42.81	28.14	56.00	46.00	-13.19	-17.86	P	N	

Frequency  
Reading level  
Correct Factor  
Measurement  
Limit (dBuV)  
Margin(dB)  
“ “ “

- = Emission frequency in MHz
- = Uncorrected receiver reading
- = Cable loss + LISN inserting loss
- = Reading level + Factor
- = Limit stated in standard
- = Reading in reference to limit
- = The emission level complied with the Average limits, with at least 10 dB margin, so no further recheck.

## 8. FCC RADIATED EMISSION TEST


### 8.1 LIMITS OF FCC RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit** (dBuV/m Q.P.)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0


**Note:** the tighter limit applies at the band edges.

### 8.2 BLOCK DIAGRAM OF TEST SETUP

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30 - 1000MHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

### 8.3 PROCEDURE OF RADIATED EMISSION TEST

- a. The EUT was placed on the top of a turntable 0.8 meters above the ground in the chamber, 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The table was rotated 360 degrees and the broadband antenna is varied from one to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set to make the measurement.
- b. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- c. The test frequency analyzer system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

### 8.4 TEST RESULT OF RADIATED EMISSION TEST

Note 1: Limit dB $\mu$ V/m @1m = Limit dB $\mu$ V/m @300m+ 90

Limit dB $\mu$ V/m @1m = Limit dB $\mu$ V/m @30m + 50

Limit dB $\mu$ V/m @1m = Limit dB $\mu$ V/m @3m +10

Note 2: No additional spurious emissions detected between lowest internal used/generated radio frequency and 30 MHz.

FCC Radiated Emission Test Result													
Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		Result (P/F)	Remarks (H/V)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	QP	Avg		
91.4333	9.36	--	--	10.04	19.40	--	--	43.50	--	<-10	--	P	H
308.0667	9.49	--	--	16.16	25.65	--	--	46.00	--	<-10	--	P	H
469.7332	9.43	--	--	19.88	29.31	--	--	46.00	--	<-10	--	P	H
629.7833	10.09	--	--	23.27	33.36	--	--	46.00	--	<-10	--	P	H
747.7999	9.90	--	--	24.66	34.56	--	--	46.00	--	<-10	--	P	H
891.6833	9.98	--	--	26.46	36.44	--	--	46.00	--	<-10	--	P	H
57.4833	11.71	--	--	8.54	20.25	--	--	40.00	--	<-10	--	P	V
128.6167	14.43	11.02	--	9.07	23.50	20.09	--	43.50	--	-23.41	--	P	V
290.2833	9.00	--	--	15.43	24.43	--	--	46.00	--	<-10	--	P	V
542.4833	8.95	--	--	21.27	30.22	--	--	46.00	--	<-10	--	P	V
699.3000	9.39	--	--	24.72	34.11	--	--	46.00	--	<-10	--	P	V
869.0500	9.79	--	--	25.97	35.76	--	--	46.00	--	<-10	--	P	V

Frequency

= Emission frequency in MHz

Reading level

= Uncorrected frequency analyzer reading

Correct Factor

= Correction factors of antenna factor and cable loss

Measurement

= Reading level + Correct factor

Limit (dBuV/m)

= Limit stated in standard

Margin (dB)

= Reading in reference to limit


PK

= Peak

QP

= Quasi-peak

**APPENDIX 1 PHOTOGRAPHS OF TEST SETUP****TEST SETUP OF CONDUCTED EMISSION****TEST SETUP OF RADIATED EMISSION (9kHz-30MHz)**

**TEST SETUP OF RADIATED EMISSION (30MHz-1GHz)**


**APPENDIX 2 EXTERNAL PHOTOS OF EUT**

View of EUT-1




View of EUT-2

**APPENDIX 3 INTERNAL PHOTOS OF EUT****Uncovered View of EUT-1****Uncovered View of EUT-2**



Front view of PCB1



Back view of PCB1

----- End of report -----