

## **Operational Description of the equipment**

### **Instruction**

- 2.1. Default Factory:
  - Bluetooth Audio Device Name: GP-71X
  - Bluetooth Pairing key: 0000
  - Webs IP Address: <http://192.168.0.249>
  - Webs Gateway IP: <http://192.168.0.1>
  - Webs Login Name: admin
  - Webs Login Password: voip
- 2.2. Prepare Bluetooth mobile and GP-71X to pair
- 2.3. Use Web Browser to set appropriate IP Address.
- 2.4. Set SIP Account or not (If you need, you can set SIP Account)
- 2.5. Set Downlink Route, (From VoIP to Bluetooth Mobile) or  
Set FIX Dial, Free Dial or Called Number Dial
- 2.6. Set Uplink Route (From Bluetooth Mobile to VoIP) or  
Set FIX Dial or Free Dial

### **Setup Your Bluetooth Mobile**

Users have to prepare common Bluetooth mobile and GP-71X to pair.

Bluetooth mobile pairs successfully that users turn on GP-71X, Bluetooth on your mobile phone and search Audio Device, it will find "GP-710(GP-712-1 and GP-712-2)" on your searching list then enter the password "0000" to connect with. It finishes pairing that BT/1 LED on GP-71X is on for 0.1 seconds and off for 0.9 seconds.

After that users can use VoIP to dial out or switch the call to VoIP by this Mobile. Except that you remove the paired or Out of Range.