

# MPE Report For On-Ramp Wireless eNode

FCC ID: XTE-ULPENODE110 IC: 8655A- ULPENODE110

## Project Code C-0095298

(Report C-0095298-RA-3-1) Revision: 1

October 15, 2010

Prepared for: On-Ramp Wireless Inc

Author: Deniz Demirci

Senior Wireless / EMC Technologist

Approved by: Nick Kobrosly

Director of Canadian operations

Confidentiality Statement: This report and the information contained herein represent the results of testing articles/products identified and selected by the client. The tests were performed to specifications and/or procedures approved by the client. National Technical Systems ("NTS") makes no representations expressed or implied that such testing fully demonstrates efficiency, performance, reliability, or any other characteristic of the articles being tested, or similar products. This report should not be relied upon as an endorsement or certification by NTS of the equipment tested, nor does it represent any statement whatsoever as to its merchantability or fitness of the test article or similar products for a particular purpose. This document shall not be reproduced except in full without written approval from National Technical Systems ("NTS") and the customer.



Test Facility:	National Technical Systems, Canada Product Integrity Laboratory 5151-47 <sup>th</sup> Street, N.E. Calgary Alberta T3J 3R2
Accreditation Numbers:	0214.22 Electrical 0214.23 Mechanical Accredited by A2LA The American Association for Laboratory Accreditation  CLIENTS SERVED: All interested parties FIELDS OF TESTING: Electrical/Electronic, Mechanical/Physical ACCREDITATION DATE:: May 14, 2009 VALID TO: February 28, 2010
Applicant:	On-Ramp Wireless Inc. 10902 Via Frontera, Suite 200 San Diego, CA 92127 USA Tel: (858) 592-6008
Customer Representative:	Rob Boesel / Jason Wilson Tel: (852) 312-8361 rob@onrampwireless.com / Jason.wilson@onrampwireless.com

## C-0095298-RA-3-1 On Ramp



Model ULPN110 FCC ID: XTE-ULPENODE110 IC: 8655A-ULPENODE110

## **Register of revisions**

Revision	Date	Description of Revisions
1	October 15, 2010	Initial release

### 1.0 INTRODUCTION

#### 1.1 PURPOSE

This Maximum Permissive Exposure report demonstrates compliance with FCC CFR 47 1.1310, 2.1091 and RSS-102 Issue 4, RF Exposure evaluation for Model ULPN110 which is categorized as "mobile". The mobile classification applies when 20 cm or greater separation distance is maintained between the end user and all transmission antennas.

The user documentation available to consumers indicates that the Module and antenna must not be used closer than 20 cm to head or body.

#### 1.2 ANTENNA SPECIFICATIONS

The Model ULPN110 has the following antenna gain specifications:

- 5dBi Antenna NEARSON Part # S151FL-L-RMM-2450S
- 2dBi Antenna NEARSON Part # S181FL-L-RMM- 2450S
- 1dBi Antenna Hyperlink Technologies Part # HG2401RD-MMCX

### 2.0 RF EXPOSURE LIMITS AND EQUATIONS

In compliance with FCC CFR 47 1.1310, the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1303 (b).

### **Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mw/cm2)	Average Time (minutes)	
(A) Limits for Occupational/Control Exposures (f=frequency)					
30-300	61.4	0.2	1.0	6.0	
300-1500	-	-	f/300	6.0	
1500-100,000	-	-	5.0	6.0	
(B) Limits for General Population/Uncontrolled Exposure (f=frequency)					
30-300	27.5	0.1	0.2	30.0	
300-1500	-	-	f/1500	30.0	
1500-100,000	-	-	1.0	30.0	

#### Friis Transmission Formula:

 $Pd = (Pout * G) / (4\pi R^2)$ 

Where.

Pd = power density (mW/cm²)

Pout = output power to antenna (mW)

G = gain of antenna in linear scale

R = distance between observation point and center of the radiator (cm)

The resulted power density at a distance of 20cm can be calculated as follows:

Power Density = (EIRP \* Duty cycle) /  $(4\pi R^2)$ 



3.0 MPE FIGURE

For the purposes of this report worst case MPE value is provided for highest gain antenna

#### 3.1 OPERATING MODE: 2.4 GHz

Maximum EIRP = Conducted power + Antenna gain = 20.10 + 5.0 = 25.10 dBm or 324 mW

Worst Case = 100% duty cycle

S (power density) = (EIRP \* Duty Cycle) /  $(4\pi R^2)$  = (324 mW \*1.0 )/  $(4\pi^* 20^2)$  = 0.0644 mW/cm<sup>2</sup>

S (power density) =  $0.00644 \text{ W/m}^2$ 

Duty cycle corrected maximum EIRP mW	RF Exposure @ d= 20 cm mW/cm²	Limit mW/cm²
324	0.0644	1.00

#### Result

Compliant.

Note: For the purposes of this report worst case MPE value is provided for highest gain antenna

## 4.0 RSS-102 ISSUE 4, RF EXPOSURE EVALUATION

#### 2.5.1 Exemption from Routine Evaluation Limits – SAR Evaluation

The chapter 4.3 (Page 8) of eNode User Manual defines the distance as;

This device must be installed to ensure a separation distance of at least 20 cm (8 inches) from the antenna to a person.

#### 2.5.2 Exemption from Routine Evaluation Limits – RF Exposure Evaluation

The peak power output of the device is 20.10 dBm at 2402 MHz

The maximum antenna gain is 5 dBi

The calculated maximum radiated e.i.r.p. is 25.10 dBm (0.324 W) which is less than 5 W

Therefore the unit is exempt from RSS-102 Issue 4, routine evaluation limits



## **END OF DOCUMENT**