

FCC PART 22H & 24E



MEASUREMENT AND TEST REPORT

For

LiveFree Emergency Response, Inc.

3780 Woodhaven Lane, Idaho Falls, Idaho 83404, USA

FCC ID: XTX-LF500

Report Type: **Product Type:** Original Report GPS Watch Tracker Phoening lin **Test Engineer:** Phoenix Liu **Report Number:** RSZ10081201 **Report Date:** 2010-08-30 Merry Zhao meny, Thus **Reviewed By:** EMC Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) **Prepared By:** 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government. * This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY TEST FACILITY	
SYSTEM TEST CONFIGURATION	
JUSTIFICATION	
EQUIPMENT MODIFICATIONS	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §1.1307 & §2.1093 - RF EXPOSURE INFORMATION	8
APPLICABLE STANDARD	
TEST RESULT	
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC §2.1046, §22.913 (A) & §24.232 (C) - RF OUTPUT POWER	10
APPLICABLE STANDARD	
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS	10
TEST DATA	
FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	
APPLICABLE STANDARDS	
TEST PROCEDURE	
TEST DATA	
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	
Applicable Standards	
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	21
APPLICABLE STANDARDS.	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
FCC §22.917(A) & §24.238(A) - BAND EDGES	
APPLICABLE STANDARDS	
TEST PROCEDURE	23
TEST EQUIPMENT LIST AND DETAILS	23
TEST DATA	23

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	7
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TECT DATA	29

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The LiveFree Emergency Response, Inc.'s product, model number: LF500 (FCC ID: XTX-LF500) or the "EUT" as referred to in this report is a GPS Watch Tracker, which measures approximately: 6.6 cm (L) x 4.8 cm (W) x 2.1 cm (H), rated input voltage: DC 3.7 V Li-ion battery.

Frequency Range:

Cellular Band: 824 -849 MHz (T_X), 869-894 MHZ (R_X) PCS Band: 1850-1910 MHz (T_X), 1930-1990 MHz (R_X)

Modulation Mode: GMSK

Transmitter Output Power:

Cellular Band: ≤33 dBm, PCS Band: ≤30 dBm

* All measurement and test data in this report was gathered from production sample serial number: 1008054 (Assigned by BACL, Shenzhen). The EUT was received on 2010-08-12.

Objective

This type approval report is prepared on behalf of *LiveFree Emergency Response*, *Inc.* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2003.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-C.


The GSM/PCS item test was performed with the EUT operating at normal mode.

The GPRS item test was performed with the EUT operating at engineering mode.


Equipment Modifications

No modifications were made to the EUT.

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307; §2.1093	RF Exposure Info (SAR)	Compliance*
\$2.1046; \$22.913 (a); \$24.232 (c)	RF Output Power	Compliance
§2.1047	Modulation Characteristics	N/A
§2.1049; §22.905 §22.917; §24.238	99% & -26 dB Occupied Bandwidth	Compliance
\$2.1051; \$22.917 (a); \$24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
\$2.1053; \$22.917 (a); \$24.238 (a)	Field Strength of Spurious Radiation	Compliance
§22.917 (a); §24.238 (a)	Out of band emission, Band Edge	Compliance
\$2.1055 \$22.355; \$24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Compliance*-- SAR report released by BACL, Report Number: R1008235-FCC-SAR Rev A.

FCC §1.1307 & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC §1.1307 and §2.1093.

Test Result

Compliance

The EUT is a portable device and needed the SAR evaluation; please refer to BACL SAR Report: R1008235-FCC-SAR Rev A.

Report No.: RSZ10081201

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC $\S 2.1047(d)$, Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC §2.1046, §22.913 (a) & §24.232 (c) - RF OUTPUT POWER

Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), in no case may the peak output power of a base station transmitter exceed 2 watt EIRP.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2010-05-05	2011-05-04
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-03-11	2011-03-11
HP	Amplifier	2VA-213+	T-E27H	2010-03-08	2011-03-07
HP	Signal Generator	HP8657A	2849U00982	2009-10-28	2010-10-27
HP	Amplifier	HP8447D	2944A09795	2010-08-02	2011-08-02
HP	Synthesized Sweeper	8341B	2624A00116	2009-11-07	2010-11-06
COM POWER	Dipole Antenna	AD-100	041000	2009-09-25	2010-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2010-05-17	2011-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Phoenix Liu on 2010-08-12.

Conducted Power:

Cellular Band (Part 22H)

Mode	Channel Frequency (MHz)		Output Power (dBm)	Limit (dBm)
GSM	128	824.2	31.95	38.45
	190	836.6	31.92	38.45
	251	848.8	31.87	38.45

Mode	Channel	Frequency		Output Po	wer (dBm)	
Mode	Channel	(MHz)	1 slot	2 slots	3 slots	4 slots
GPRS	128	824.2	31.76	31.72	/	/
	190	836.6	31.73	31.73	/	/
	251	848.8	31.65	61.67	/	/

PCS Band (Part 24E)

Mode	Channel Frequency (MHz)		Output Power (dBm)	Limit (dBm)
	512	1850.2	29.50	33
GSM	661	1880.0	29.45	33
	810	1909.8	29.52	33

Mode	Channel	Frequency		Output Po	wer (dBm)	
Mode	Channel	(MHz)	1 slot	2 slots	3 slots	4 slots
GPRS	512	1850.2	29.39	29.48	/	/
	661	1880.0	29.35	29.20	/	/
	810	1909.8	29.39	29.30	/	/

ERP & EIRP:

ERP for Cellular Band (Part 22H)

Indic	ated	Table	Test A	ntenna	Su	ıbstituted					Cable	Absolute	Part 22H
Frequency (MHz)	Receiver Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Gain Correction (dB)	Loss (dB)	Level (dBm)	Limit (dBm)		
Low Channel													
824.2	121.32	170	2.0	Н	824.2	31.2	Н	0	0.9	30.3	38.45		
824.2	119.20	20	1.2	V	824.2	30.1	V	0	0.9	29.2	38.45		

EIRP PCS Band (Part 24E)

	Indic	ated	Table	Test Antenna		Substituted		Antenna	Cable	Absolute	Part 24E	
	Frequency (MHz)	Receiver Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Gain Correction (dBi)	Loss (dB)	Level (dBm)	Limit (dBm)
I	High Channel											
I	1909.8	119.25	20	1.9	Н	1909.8	23.1	Н	6.2	1.11	28.19	33
	1909.8	117.81	82	1.1	V	1909.8	21.6	V	6.2	1.11	26.69	33

FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH


Applicable Standards

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 30 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2009-11-24	2010-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Phoenix Liu on 2010-08-10.

GMSK:

Cellular Band (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
190	836.6	252	334


PCS Band (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
661	1880.0	250	338

Please refer to the following plots.


Cellular Band (Part 22H)

99% Occupied Bandwidth



Date: 10.AUG.2010 10:12:29

26 dB Occupied Bandwidth




Date: 10.AUG.2010 10:13:08

Report No.: RSZ10081201


PCS Band (Part 24E)

99% Occupied Bandwidth



Date: 10.AUG.2010 10:08:59

26 dB Occupied Bandwidth



Date: 10.AUG.2010 10:15:26

Report No.: RSZ10081201

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standards

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in §2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10^{th} harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2009-11-24	2010-11-23

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Phoenix Liu on 2010-08-10 to 2010-08-15.

Please refer to the following plots.


Cellular Band (Part 22H)

30 - 1000 MHz - Middle Channel




Date: 10.AUG.2010 10:18:30

1 – 10 GHz - Middle Channel




PCS Band (Part24E)

30 - 1000 MHz - Middle Channel




Date: 10.AUG.2010 10:22:50

1 - 2 GHz - Middle Channel



Date: 10.AUG.2010 10:48:18

2 – 20 GHz - Middle Channel



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standards

FCC §2.1053, §22.917 and §24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in $dB = 10 \lg (TXpwr in Watts/0.001) - the absolute level$

Spurious attenuation limit in $dB = 43 + 10 \text{ Log}_{10}$ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2010-05-05	2011-05-04
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-03-11	2011-03-11
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07
НР	Amplifier	2VA-213+	T-E27H	2010-03-08	2011-03-07
НР	Signal Generator	HP8657A	2849U00982	2009-10-28	2010-10-27
НР	Amplifier	HP8447D	2944A09795	2010-08-02	2011-08-02
НР	Synthesized Sweeper	8341B	2624A00116	2009-11-07	2010-11-06
COM POWER	Dipole Antenna	AD-100	041000	2009-09-25	2010-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2010-05-17	2011-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Phoenix Liu on 2010-08-24.

Test mode: Transmitting

Cellular Band (Part 22H)

Indica	ted	Table	Test Aı	ntenna		Substitu	ited		Absolute		
Frequency (MHz)	Receiver Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
				Middle	e Channel, E	Below 1	GHz				
167	31.5	10	1	Н	167	-63.0	0	0.36	-63.36	-13	50.36
32.75	28.3	50	1.5	Н	32.75	-65.5	0	0.25	-65.75	-13	52.75
167	28.6	70	1.5	V	167	-65.7	0	0.36	-66.06	-13	53.06
32.75	27.6	40	1.2	V	32.75	-66.8	0	0.25	-67.05	-13	54.05
				Middle	e Channel, A	bove 1	GHz				
1673.2	48.67	210	1	V	1673.2	-45.4	6.2	0.94	-40.14	-13	27.14
1673.2	47.52	110	1.9	Н	1673.2	-46.5	6.2	0.94	-41.24	-13	28.24
2509.8	44.63	100	1.5	V	2509.8	-48.3	7.3	1.19	-42.19	-13	29.19
2509.8	43.16	200	1.8	Н	2509.8	-49.5	7.3	1.19	-43.39	-13	30.39
4183	42.35	120	1.6	Н	4183	-50.5	7.6	1.88	-44.78	-13	31.78
4183	44.63	150	1.4	V	4183	-51.7	7.6	1.88	-45.98	-13	32.98

PCS Band (Part 24E)

Indica	ited	Table	Test Aı	itenna		Substitu	ted		Absolute		
Frequency (MHz)	Receiver Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
	Middle Channel, Below 1 GHz										
140.1	29.5	70	1.5	V	140.1	-63.4	0	0.3	-63.7	-13	50.70
32.75	30.4	42	1.2	V	32.75	-64.0	0	0.25	-64.25	-13	51.25
140.1	29.8	10	1	Н	140.1	-64.9	0	0.3	-65.2	-13	52.20
32.75	28.1	50	1.5	Н	32.75	-65.9	0	0.25	-66.15	-13	53.15
				Middle	e Channel, A	bove 1	GHz				
5640	51.71	80	1.5	V	5640	-44.6	8.3	2.76	-39.06	-13	26.06
5640	46.51	170	1.6	Н	5640	-46.3	8.3	2.76	-40.76	-13	27.76
3760	43.92	200	1.6	V	3760	-50.4	6.9	1.47	-44.97	-13	31.97
3760	42.41	190	1.9	Н	3760	-51.7	6.9	1.47	-46.27	-13	33.27

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standards


According to FCC 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to FCC \$24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2009-11-24	2010-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Report No.: RSZ10081201

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Phoenix Liu on 2010-08-10.

Please refer to the following tables and plots.


Cellular Band (Part 22H)

Band Edge	Emission (dBm)	Limit (dBm)
Left Side	-16.30	-13
Right Side	-14.28	-13

PCS Band (Part 24E)


Band Edge	Emission (dBm)	Limit (dBm)
Left Side	-17.86	-13
Right Side	-18.57	-13

Cellular Band, Lowest Channel




Date: 10.AUG.2010 09:59:19

Cellular Band, Highest Channel




Date: 10.AUG.2010 10:00:12

PCS Band, Lowest Channel



Date: 10.AUG.2010 10:01:52

PCS Band, Highest Channel



Date: 10.AUG.2010 10:04:58

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC §2.1055 (a), §2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

	Frequency	Tolerance for	r Transmitters	in the Public	Mobile Services
--	-----------	---------------	----------------	---------------	-----------------

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2010-06-04	2011-06-03
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10
ZAOXIN	DC Power Supply	RXN-605D	20030842184	2009-10-16	2010-10-16

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C	
Relative Humidity:	56 %	
ATM Pressure:	100.0 kPa	

The testing was performed by Phoenix Liu on 2010-08-15.

Cellular Band (Part 22H)

Middle Channel, f _o = 836.6 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-20		-12	-0.0143	2.5
-10		-16	-0.0191	2.5
0		-18	-0.0215	2.5
10		-19	-0.0227	2.5
20	3.7	-15	-0.0179	2.5
30		-13	-0.0155	2.5
40		-13	-0.0155	2.5
50		-12	-0.0143	2.5
55		-18	-0.0215	2.5
25	4.2	-13	-0.0155	2.5
23	3.5	-12	-0.0143	2.5

PCS Band (Part 24E)

Middle Channel, f _o = 1880 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Results
-20		-18	-0.0215	Pass
-10		-13	-0.0155	Pass
0		-15	-0.0080	Pass
10		-11	-0.0059	Pass
20	3.7	-18	-0.0215	Pass
30		-17	-0.0090	Pass
40		-13	-0.0155	Pass
50		-26	-0.0138	Pass
55		-25	-0.0133	Pass
25	4.2	-16	-0.0085	Pass
23	3.5	-19	-0.0101	Pass

***** END OF REPORT *****