

RF EXPOSURE REPORT

REPORT NO.: SA131223E02

MODEL NO.: TEW-818DRU

FCC ID: XU8TEW818DRU

RECEIVED: Dec. 23, 2013

TESTED: Jan. 02, 2014

ISSUED: Jan. 14, 2014

APPLICANT: TRENDnet, Inc.

ADDRESS: 20675 Manhattan Place, Torrance, CA

90501

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,

R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,

R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,

R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	. 4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	. 5
4.	CLASSIFICATION	. 5
5.	ANTENNA GAIN	. 6
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	. 7



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA131223E02	Original release	Jan. 14, 2014

Report No.: SA131223E02 3 of 9 Report Format Version 5.0.0



1. CERTIFICATION

PRODUCT: AC1900 Dual Band Wireless Router

BRAND NAME: TRENDnet

MODEL NO.: TEW-818DRU

TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: TRENDnet, Inc.

TESTED DATE: Jan. 02, 2014

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (Model: TEW-818DRU) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: Drowing, DATE: Jan. 14, 2014

(Phoenix Huang, Specialist)

(May Chen, Manager)



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	_	AVERAGE TIME (minutes)				
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 29cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Ant. No.	Transmitter Circuit	Gain (dBi) (Include cable loss)	Antenna Type	Connecter Type	Frequency range (GHz to GHz)	Cable Length (mm)
1	Chain (0)	2.5	Dipole	i-pex (MHF)	2.4~2.4835	78
1	Chain (2)	4.8		Dipole 1-pex (IVII IF	i-pex (ivinr)	5.15~5.85
2	Chain (1)	6	Dipole	ala : nav. (NALIE)	2.4~2.4835	00
2	Chain (1) 6	б		i-pex (MHF)	5.15~5.85	90
3	Chain (2)	5.5	Dinala	i pov (MUE)	2.4~2.4835	105
3	Chain (0)	6	Dipole	i-pex (MHF)	5.15~5.85	185

- Note: 1. From above antennas, 802.11b mode will fix transmission on Chain (0).
 2. From above antennas, 802.11g mode the worst case was found in Chain (1).
 3. From above antennas, 802.11a mode the worst case was found in Chain (0). Therefore only the test data of the mode was recorded in this report.



6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For 15.247 (2.4GHz):

802.11b:

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm²)
2412 - 2462	218.273	2.5	29	0.03673	1.00

802.11g:

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
2412 - 2462	412.098	5.5	29	0.13835	1.00

802.11n (HT20):

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
2412 - 2462	705.471	9.57	29	0.60461	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.57dBi$

802.11n (HT40):

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm²)
2422 - 2452	263.260	9.57	29	0.22562	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.57dBi$



For 15.247 (5GHz):

802.11a:

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5745 - 5825	503.501	6	29	0.18967	1.00

802.11ac (VHT20):

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm²)
5745 - 5825	357.489	10.39	29	0.37005	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 10.39dBi$

802.11ac (VHT40):

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm²)
5755 - 5795	359.219	10.39	29	0.37184	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 10.39dBi$

802.11ac (VHT80):

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5775	350.574	10.39	29	0.36289	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 10.39 dBi$



For 15.407 (5GHz):

802.11a:

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5180 - 5240	46.132	6	29	0.01738	1.00

802.11n (HT20):

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5180 - 5240	18.067	10.39	29	0.01870	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 10.39dBi$

802.11n (HT40):

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5190 - 5230	17.615	10.39	29	0.01823	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 10.39dBi$

802.11n (HT40):

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5210	17.630	10.39	29	0.01825	1.00

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 10.39 dBi$

CONCLUSION:

Both of the WLAN (2.4GHz & 5GHz) can transmit simultaneously, the formula of calculated the MPE is:

 $CPD_1/LPD_1 + CPD_2/LPD_2 + \dots etc. < 1$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is 0.60461 / 1 + 0.37184 / 1 = 0.976, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---