

RF Exposure Report

Report No.: SA181025C10D

FCC ID: XU8TEW830MDR

Test Model: TEW-830MDR

Series Model: TEW-830MDR2K, TEW-830MDR3K

Received Date: Jun. 21, 2019

Test Date: Jul. 04 ~ Jul. 10, 2019

Issued Date: Jul. 23, 2019

Applicant: TRENDnet, Inc.

Address: 20675 Manhattan Place, Torrance, CA 90501 U.S.A.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA181025C10D Page No. 1 / 5 Report Format Version: 6.1.1 Reference No.: 190621C19



Table of Contents

Rele	ase Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	. 5
2.	1 Limits for Maximum Permissible Exposure (MPE)	. 5
3	Calculation Result of Maximum Conducted Power	. 5



Release Control Record

Issue No.	Description	Date Issued
SA181025C10D	Original release.	Jul. 23, 2019

Report No.: SA181025C10D Page No. 3 / 5 Report Format Version: 6.1.1

Report No.: SA181025C10D Reference No.: 190621C19



1 Certificate of Conformity

Product: AC2200 WiFi Mesh Router, AC2200 WiFi Mesh Router System

Brand: TRENDnet

Test Model: TEW-830MDR

Series Model: TEW-830MDR2K, TEW-830MDR3K

Sample Status: Engineering sample

Applicant: TRENDnet, Inc.

Test Date: Jul. 04 ~ Jul. 10, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.3-2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: Pettle Chem, Date: Jul. 23, 2019

Pettie Chen / Senior Specialist

Approved by: Jul. 23, 2019

Bruce Chen / Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Magnetic Field Strength (V/m) Strength (A/m)		Power Density (mW/cm²)	Average Time (minutes)			
Limits For General Population / Uncontrolled Exposure							
300-1500			F/1500	30			
1500-100,000			1.0	30			

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

Radio	Frequency Band (MHz)	Mode	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
1	WLAN	CDD	22.74	7.04	20	0.189	1
'	2412~2462	Beamforming	22.47	7.04	20	0.178	1
2	WLAN	CDD	21.13	8.65	20	0.189	1
	5745~5825	Beamforming	21.13	8.65	20	0.189	1
2	WLAN	CDD	21.98	8.17	20	0.206	1
3	5180~5240	Beamforming	21.98	8.17	20	0.206	1

Note:

1. Directional Gain:

2412~2462MHz Max. Directional Gain = 4.03dBi + 10log(2) = 7.04dBi

5180~5240MHz Max. Directional Gain = 5.16dBi + 10log(2) = 8.17dBi

5745~5825MHz Max. Directional Gain = 5.64dBi + 10log(2) = 8.65dBi

2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Radio 1 + Radio 2 + Radio 3 = 0.189 / 1 + 0.189 / 1 + 0.206 / 1 = 0.584 < 1

---END---

Report No.: SA181025C10D Page No. 5 / 5 Report Format Version: 6.1.1 Reference No.: 190621C19