

RF Exposure Report

Report No.: SA180503C11D

FCC ID: XU8TEW841APBO

Test Model: TEW-841APBO

Received Date: May 31, 2019

Test Date: Jun. 14 ~ Jul. 03, 2019

Issued Date: Jul. 11, 2019

Applicant: TRENDnet, Inc.

Address: 20675 Manhattan Place, Torrance, CA 90501 U.S.A.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

Report No.: SA180503C11D Report Format Version: 6.1.1 Page No. 1 / 6 Reference No.: 190531C20



Table of Contents

Rele	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.2	Limits for Maximum Permissible Exposure (MPE) MPE Calculation Formula	5
3	Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA180503C11D	Original release	Jul. 11, 2019

Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA180503C11D Reference No.: 190531C20



1 Certificate of Conformity

Product: 5 dBi Wireless AC1300 Outdoor PoE+ Omni-Directional Access Point

Brand: TRENDnet

Test Model: TEW-841APBO

Sample Status: Engineering sample

Applicant: TRENDnet, Inc.

Test Date: Jun. 14 ~ Jul. 03, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: Jul. 11, 2019

Polly Chien / Specialist

Approved by: Jul. 11, 2019

Bruce Chen / Project Engineer

Page No. 4 / 6 Report Format Version: 6.1.1



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)			Power Density (mW/cm²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

Report No.: SA180503C11D Page No. 5 / 6 Report Format Version: 6.1.1

Reference No.: 190531C20



3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)			
CDD Mode								
2412-2462	23.55	8.18	20	0.296	1			
5180-5240	16.16	8.18	20	0.054	1			
5745-5825	23.07	8.18	20	0.265	1			
Beamforming Mode								
2412-2462	20.03	8.18	20	0.132	1			
5180-5240	13.15	8.18	20	0.027	1			
5745-5825	20.06	8.18	20	0.133	1			

Note:

- 1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2. Directional gain = 5.17dBi + 10log(2) = 8.18dBi

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.296 + 0.265 = 0.561 < 1

---END---