



FCC TEST REPORT

FCC ID: XUJOCP349P702

On Behalf of

Launch Tech Co., Ltd.

Professional Diagnostic Tool

Model No.: Creader Professional 919S(359), Creader Professional 919X 2.0, Creader Professional 919E 2.0, Creader Professional 919I 2.0, Creader Professional 919 EV, Millennium Max, Creader Professional 919y 2.0 (y=A~Z, indicate configuration difference)

Prepared for : Launch Tech Co., Ltd.
Address : Launch Industrial Park, North of Wuhe Rd. Banxuegang, Longgang, Shenzhen, China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Report Number : A2403109-C01-R13
Date of Receipt : July 09, 2024
Date of Test : July 09, 2024 - July 26, 2024
Date of Report : July 26, 2024
Version Number : V0
Test Result : Pass

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. Summary of Standards And Results -----	5
1.1. Description of Standards and Results -----	5
2. General Information -----	6
2.1. Description of Device (EUT) -----	6
2.2. Accessories of Device (EUT) -----	7
2.3. Tested Supporting System Details -----	7
2.4. Block Diagram of connection between EUT and simulators -----	7
2.5. Test Mode Description-----	8
2.6. Test Conditions-----	9
2.7. Test Facility-----	9
2.8. Measurement Uncertainty -----	9
2.9. Test Equipment List -----	10
3. Spurious Emission -----	11
3.1. Test Limits -----	11
3.2. Test Procedure -----	14
3.3. Test Setup -----	14
3.4. Test Results -----	15
4. Power line Conducted Emission -----	28
4.1. Test Limits -----	28
4.2. Test Procedure -----	28
4.3. Test Setup -----	28
4.4. Test Results -----	28
5. Conducted Maximum Output Power -----	31
5.1. Test limits -----	31
5.2. Test Procedure -----	31
5.3. Test Setup -----	31
5.4. Test Results -----	31
6. Peak Power Spectral Density -----	39
6.1. Test limits -----	39
6.2. Test Procedure -----	39
6.3. Test Setup -----	39
6.4. Test Results -----	40
7. Bandwidth -----	47
7.1. Test limits -----	47
7.2. Test Procedure -----	47
7.3. Test Setup -----	47
7.4. Test Results -----	47
8. Band Edge Check -----	61
8.1. Test limits -----	61
8.2. Test Procedure -----	61
8.3. Test Setup -----	61
8.4. Test Results -----	61
9. Antenna Requirement -----	68
9.1. Standard Requirement -----	68
9.2. Antenna Connected Construction -----	68
9.3. Results -----	68
10. Test setup photo -----	69
10.1. Photos of Radiated emission -----	69
10.2. Photos of Conducted Emission test -----	70

TEST REPORT DECLARATION

Applicant : Launch Tech Co., Ltd.
Address : Launch Industrial Park, North of Wuhe Rd. Banxuegang, Longgang, Shenzhen, China
Manufacturer : Launch Tech Co., Ltd.
Address : Launch Industrial Park, North of Wuhe Rd. Banxuegang, Longgang, Shenzhen, China
EUT Description : Professional Diagnostic Tool
(A) Model No. : Creader Professional 919S(359), Creader Professional 919X 2.0, Creader Professional 919E 2.0, Creader Professional 919I 2.0, Creader Professional 919 EV, Millennium Max, Creader Professional 919y 2.0 (y=A~Z, indicate configuration difference)
(B) Trademark : LAUNCH

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

RSS-247 Issue 3, RSS-Gen Issue 5, ANSI C63.10:2013, CISPR 16-1-4:2010

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen
Project Engineer



Approved by (name + signature).....: Jack Xu
Project Manager



Date of issue.....: July 26, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	July 26, 2024	Initial released Issue	Yannis Wen

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Conducted Emission	FCC Part 15: 15.207	P
Occupied Channel Bandwidth&-6dB Bandwidth	FCC PART 15:15.247(a)(2)	P
Output Power	FCC Part 15: 15.247(b)(3)	P
Radiated Spurious Emission	FCC Part 15: 15.209, FCC Part 15: 15.247(d)	P
Conducted Spurious & Band Edge Emission	FCC Part 15: 15.247(d)	P
Power Spectral Density	FCC PART 15:15.247(e)	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d)	P
Antenna Requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.		

1. Pass: The EUT complies with the essential requirements in the standard.
2. Frequency Stability: The manufacturer stated in the user's manual.
3. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT Name	:	Professional Diagnostic Tool
Model No.	:	Creader Professional 919S(359), Creader Professional 919X 2.0, Creader Professional 919E 2.0, Creader Professional 919I 2.0, Creader Professional 919 EV, Millennium Max, Creader Professional 919y 2.0 (y=A~Z, indicate configuration difference)
DIFF.	:	The products of the above models are the same except for the color of shell or rubber sleeves and the model name. All the test were performed on the model Creader Professional 919S(359).
Power supply	:	DC 3.7V by battery, DC 5V from adapter
2.4G WIFI	:	
Operation frequency	:	2412MHz-2462MHz for IEEE 802.11 b, g, n/HT20 2422MHz-2452MHz for IEEE 802.11 n/HT40
Channel No.	:	802.11b/802.11g /802.11n(HT20): 11CH 802.11n(HT40): 9CH
Modulation type	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n :OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	:	FPC antenna, Maximum Gain is 4.49dBi (Antenna information is provided by applicant.)
Software version	:	V100
Hardware version	:	V1
Intend use environment	:	Residential, commercial and light industrial environment
Note	:	/


2.2. Accessories of Device (EUT)

Accessories 1 : SWITCHING POWER SUPPLY
Manufacturer : SHENZHEN PENGSHENGYE ELECTRONIC CO.,LTD
Model : PSY0502000 18
Ratings : INPUT:100-240V~50/60Hz 0.6A Max
OUTPUT: 5.0V=2.0A
Accessories 2 : Switching Power Supply
Manufacturer : Dong Guan Royal Intelligent Co., Ltd.
Model : BI12T-050200-IU
Ratings : INPUT: 100-240V~50/60Hz, 0.5A Max.
INPUT :5.0VDC, 2.0A, 10.0W

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1	Notebook PC	Lenovo	Thinkpad E14	--	--

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Duty cycle :100%Keeping TX			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11 n/HT40	13	Low :CH3	2422
	13	Middle: CH6	2437
	13	High: CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate. So those data rate were used for all test.			

Channel list:					
For IEEE 802.11b, g, n/HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		
For IEEE 802.11 n/HT40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2422	CH5	2442		
CH2	2427	CH6	2447		
CH3	2432	CH7	2452		
CH4	2437				

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

Designation Number: CN1236

July 15, 2019 Certificated by IC

Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2023.08.16	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2023.08.16	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2023.08.16	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2023.08.16	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	1Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2023.08.19	1Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	1Year
RF Cable	Resenberger	Cable 1	/	RE1	2023.08.16	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2023.08.16	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2023.08.16	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2023.08.16	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2023.08.16	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2023.08.16	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2023.08.16	1Year
Horn Antenna	SCHWARZBECK	BBHA 9170	/	00946	2023.08.19	1Year
Preamplifier	SKET	LNPA_1840 -50	/	SK2018101801	2023.08.16	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2023.08.16	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2023.08.16	1 Year
Temp. & Humid. Chamber	Teelong	TL-HW408S	/	TL-20191205-01	2023.07.25	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2023.08.16	1 Year
Adjustable attenuator	MWRFTtest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. SPURIOUS EMISSION

3.1. Test Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

RSS-GEN Restricted frequency band

Table 7 – Restricted frequency bands ^{Note 1}

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8

6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	
Note 1: The peak limit is 20 dB higher than the average limit			
Note 2: Peak limit applies (AVG limit + 20 dB) as well as RSS-247 Section 5.5			

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength ($\mu\text{V/m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ($\mu\text{A/m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	$6.37/F$ (F in kHz)	300
490 - 1705 kHz	$63.7/F$ (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

3.2. Test Procedure


The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz. The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above 1GHz testing, the table was rotated 360 degrees to determine the position of the highest radiation. The Test antenna shall vary between 1m and 4m, both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting radiated emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Quasi Peak Detector mode premeasured


If Peak value comply with QP limit below 1GHz, the EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test setup, please see the test setup photo.


3.3. Test Setup



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the EUT from 9kHz up to the 10th harmonic of the fundamental.

Detailed information please see the following page.


From 9KHz to 30MHz: Conclusion: PASS

Note: 1.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2.Only show the test data of the worst Channel in this report.


From 30MHz to 1000MHz: Conclusion: PASS

Vertical:



Note: 1. *:Maximum data; x:Over limit; !:over margin.

2. Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	
		MHz	Level	Factor	ment			
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		61.8213	20.58	12.88	33.46	40.00	-6.54	peak
2		118.1447	18.74	12.81	31.55	43.50	-11.95	peak
3	*	180.0164	24.42	12.68	37.10	43.50	-6.40	QP
4		240.7459	26.11	12.57	38.68	46.00	-7.32	QP
5		300.0514	23.15	14.10	37.25	46.00	-8.75	peak
6		480.0221	20.77	17.95	38.72	46.00	-7.28	peak

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

Remark: All modes have been tested, and only worst data of b mode, Channel 2412MHz was listed in this report.

From 1G-25GHz

Test Mode: IEEE 802.11b TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824	43.64	V	33.95	10.18	34.26	53.51	74	-20.49	PK
4824	37.00	V	33.95	10.18	34.26	46.87	54	-7.13	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
4824	44.63	H	33.95	10.18	34.26	54.50	74	-19.50	PK
4824	36.43	H	33.95	10.18	34.26	46.30	54	-7.70	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11b TX Mid									
4874	44.80	V	33.93	10.2	34.29	54.64	74	-19.36	PK
4874	30.67	V	33.93	10.2	34.29	40.51	54	-13.49	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
4874	45.29	H	33.93	10.2	34.29	55.13	74	-18.87	PK
4874	32.26	H	33.93	10.2	34.29	42.10	54	-11.90	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11b TX High									
4924	45.98	V	33.98	10.22	34.25	55.93	74	-18.07	PK
4924	33.87	V	33.98	10.22	34.25	43.82	54	-10.18	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/
4924	46.33	H	33.98	10.22	34.25	56.28	74	-17.72	PK
4924	33.99	H	33.98	10.22	34.25	43.94	54	-10.06	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Test Mode: IEEE 802.11g TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824	44.12	V	33.95	10.18	34.26	53.99	74	-20.01	PK
4824	33.71	V	33.95	10.18	34.26	43.58	54	-10.42	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
4824	43.08	H	33.95	10.18	34.26	52.95	74	-21.05	PK
4824	36.55	H	33.95	10.18	34.26	46.42	54	-7.58	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11g TX Mid									
4874	43.92	V	33.93	10.2	34.29	53.76	74	-20.24	PK
4874	32.55	V	33.93	10.2	34.29	42.39	54	-11.61	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
4874	45.48	H	33.93	10.2	34.29	55.32	74	-18.68	PK
4874	34.49	H	33.93	10.2	34.29	44.33	54	-9.67	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11g TX High									
4924	45.20	V	33.98	10.22	34.25	55.15	74	-18.85	PK
4924	34.86	V	33.98	10.22	34.25	44.81	54	-9.19	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/
4924	46.23	H	33.98	10.22	34.25	56.18	74	-17.82	PK
4924	35.02	H	33.98	10.22	34.25	44.97	54	-9.03	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Test Mode: IEEE 802.11n HT20 TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4824	45.64	V	33.95	10.18	34.26	55.51	74	-18.49	PK
4824	35.10	V	33.95	10.18	34.26	44.97	54	-9.03	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
4824	44.65	H	33.95	10.18	34.26	54.52	74	-19.48	PK
4824	34.26	H	33.95	10.18	34.26	44.13	54	-9.87	AV
7236	/	/	/	/	/	/	/	/	/
9648	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11n HT20 TX Mid									
4874	46.62	V	33.93	10.2	34.29	56.46	74	-17.54	PK
4874	32.54	V	33.93	10.2	34.29	42.38	54	-11.62	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
4874	45.66	H	33.93	10.2	34.29	55.50	74	-18.50	PK
4874	34.37	H	33.93	10.2	34.29	44.21	54	-9.79	AV
7311	/	/	/	/	/	/	/	/	/
9748	/	/	/	/	/	/	/	/	/
Test Mode: IEEE 802.11n HT20 TX High									
4924	48.13	V	33.98	10.22	34.25	58.08	74	-15.92	PK
4924	34.72	V	33.98	10.22	34.25	44.67	54	-9.33	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/
4924	46.32	H	33.98	10.22	34.25	56.27	74	-17.73	PK
4924	35.11	H	33.98	10.22	34.25	45.06	54	-8.94	AV
7386	/	/	/	/	/	/	/	/	/
9848	/	/	/	/	/	/	/	/	/

Note:



1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Note:

$$1, \text{ Result} = \text{Read level} + \text{Antenna factor} + \text{cable loss-Amp factor}$$

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Conducted RF Spurious Emission**Tx. Spurious NVNT b 2412MHz Ant1 Emission****Tx. Spurious NVNT b 2437MHz Ant1 Emission**

Tx. Spurious NVNT b 2462MHz Ant1 Emission




Date: 12.JUL.2024 18:13:28

Tx. Spurious NVNT g 2412MHz Ant1 Emission




Date: 12.JUL.2024 18:19:50

Tx. Spurious NVNT g 2437MHz Ant1 Emission




Date: 12.JUL.2024 18:22:12

Tx. Spurious NVNT g 2462MHz Ant1 Emission




Date: 12.JUL.2024 18:25:35

Tx. Spurious NVNT n20 2412MHz Ant1 Emission




Date: 12.JUL.2024 18:31:52

Tx. Spurious NVNT n20 2437MHz Ant1 Emission




Date: 12.JUL.2024 18:35:29

Tx. Spurious NVNT n20 2462MHz Ant1 Emission




Date: 12.JUL.2024 18:38:21

Tx. Spurious NVNT n40 2422MHz Ant1 Emission




Date: 15.JUL.2024 15:10:40

Tx. Spurious NVNT n40 2437MHz Ant1 Emission



Date: 15.JUL.2024 15:13:07

Tx. Spurious NVNT n40 2452MHz Ant1 Emission



Date: 15.JUL.2024 15:15:29

4. POWER LINE CONDUCTED EMISSION

4.1. Test Limits

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in the rang of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup




☐ :50 Ω Terminator

4.4. Test Results

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit

Line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1859	45.37	9.92	55.29	64.22	-8.93	QP	
2		0.3719	34.80	9.95	44.75	58.46	-13.71	peak	
3		1.8419	31.85	9.89	41.74	56.00	-14.26	peak	
4		3.4740	32.50	9.96	42.46	56.00	-13.54	peak	
5		6.2670	31.93	10.09	42.02	60.00	-17.98	peak	
6		16.1722	30.94	10.36	41.30	60.00	-18.70	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1859	41.56	9.92	51.48	64.22	-12.74	peak	
2		0.3689	33.78	9.95	43.73	58.53	-14.80	peak	
3		0.4470	33.34	9.95	43.29	56.93	-13.64	peak	
4		0.7980	26.81	9.94	36.75	56.00	-19.25	peak	
5		3.6000	28.41	9.96	38.37	56.00	-17.63	peak	
6		8.8916	27.66	10.18	37.84	60.00	-22.16	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Note: All modes and channels have been tested and only the B mode 2412MHz mode with the worst data is listed.

5. CONDUCTED MAXIMUM OUTPUT POWER

5.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)

5.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02


5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Connected the EUT's antenna port to peak power meter by 20dB attenuator.

5.2.3 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.3. Test Setup



5.4. Test Results

PASS

Detailed information please see the following page.


Condition	Mode	Frequency (MHz)	Antenna	Duty Factor (dB)	Conducted Power (dBm)	EIRP Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	0.01	11.106	15.596	30	Pass
NVNT	b	2437	Ant1	0.01	11.197	15.687	30	Pass
NVNT	b	2462	Ant1	0.01	11.247	15.737	30	Pass
NVNT	g	2412	Ant1	0.11	11.661	16.151	30	Pass
NVNT	g	2437	Ant1	0.11	11.571	16.061	30	Pass
NVNT	g	2462	Ant1	0.11	10.694	15.184	30	Pass
NVNT	n20	2412	Ant1	0.11	11.559	16.049	30	Pass
NVNT	n20	2437	Ant1	0.12	10.804	15.294	30	Pass
NVNT	n20	2462	Ant1	0.12	10.22	14.71	30	Pass
NVNT	n40	2422	Ant1	0.23	11.417	15.907	30	Pass
NVNT	n40	2437	Ant1	0.23	11.606	16.096	30	Pass
NVNT	n40	2452	Ant1	0.23	12.055	16.545	30	Pass

EIRP(dBm)= Conducted Power (dBm)+Gain(dBi)

Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)
NVNT	b	2412	Ant1	99.66	0.01
NVNT	b	2437	Ant1	99.67	0.01
NVNT	b	2462	Ant1	99.68	0.01
NVNT	g	2412	Ant1	97.55	0.11
NVNT	g	2437	Ant1	97.54	0.11
NVNT	g	2462	Ant1	97.57	0.11
NVNT	n20	2412	Ant1	97.39	0.11
NVNT	n20	2437	Ant1	97.34	0.12
NVNT	n20	2462	Ant1	97.37	0.12
NVNT	n40	2422	Ant1	94.88	0.23
NVNT	n40	2437	Ant1	94.87	0.23
NVNT	n40	2452	Ant1	94.9	0.23

Duty Cycle NVNT b 2412MHz Ant1




Date: 12.JUL.2024 18:06:54

Duty Cycle NVNT b 2437MHz Ant1




Date: 12.JUL.2024 18:09:21

Duty Cycle NVNT b 2462MHz Ant1




Date: 12.JUL.2024 18:11:46

Duty Cycle NVNT g 2412MHz Ant1




Date: 12.JUL.2024 18:18:39

Duty Cycle NVNT g 2437MHz Ant1




Date: 12.JUL.2024 18:20:59

Duty Cycle NVNT g 2462MHz Ant1




Date: 12.JUL.2024 18:24:12

Duty Cycle NVNT n20 2412MHz Ant1




Date: 12.JUL.2024 18:30:33

Duty Cycle NVNT n20 2437MHz Ant1




Date: 12.JUL.2024 18:34:21

Duty Cycle NVNT n20 2462MHz Ant1




Date: 12.JUL.2024 18:36:52

Duty Cycle NVNT n40 2422MHz Ant1




Date: 15.JUL.2024 15:08:27

Duty Cycle NVNT n40 2437MHz Ant1



Date: 15.JUL.2024 15:11:45

Duty Cycle NVNT n40 2452MHz Ant1



Date: 15.JUL.2024 15:13:56

6. PEAK POWER SPECTRAL DENSITY

6.1. Test limits

6.1.1 Please refer RSS-247 & FCC PART 15: 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

6.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.


6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as $RBW = 3\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$.), $VBW = 10\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), $\text{span} \geq 1.5 \times \text{DTS bandwidth}$., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.


6.3. Test Setup



6.4. Test Results


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	6.272	8	Pass
NVNT	b	2437	Ant1	6.326	8	Pass
NVNT	b	2462	Ant1	6.553	8	Pass
NVNT	g	2412	Ant1	-2.404	8	Pass
NVNT	g	2437	Ant1	-0.382	8	Pass
NVNT	g	2462	Ant1	-1.344	8	Pass
NVNT	n20	2412	Ant1	-0.249	8	Pass
NVNT	n20	2437	Ant1	-1.093	8	Pass
NVNT	n20	2462	Ant1	-1.409	8	Pass
NVNT	n40	2422	Ant1	-5.93	8	Pass
NVNT	n40	2437	Ant1	-5.666	8	Pass
NVNT	n40	2452	Ant1	-5.279	8	Pass

PSD NVNT b 2412MHz Ant1




Date: 12.JUL.2024 18:07:47

PSD NVNT b 2437MHz Ant1




Date: 12.JUL.2024 18:10:19

PSD NVNT b 2462MHz Ant1




Date: 12.JUL.2024 18:12:45

PSD NVNT g 2412MHz Ant1




Date: 12.JUL.2024 18:19:11

PSD NVNT g 2437MHz Ant1




Date: 12.JUL.2024 18:21:40

PSD NVNT g 2462MHz Ant1




Date: 12.JUL.2024 18:24:56

PSD NVNT n20 2412MHz Ant1




Date: 12.JUL.2024 18:31:14

PSD NVNT n20 2437MHz Ant1



Date: 12.JUL.2024 18:35:03

PSD NVNT n20 2462MHz Ant1



Date: 12.JUL.2024 18:37:41