



**Report No.: SZ13050128E01**



# FCC TEST REPORT

*Issued to*

Launch Tech Co., Ltd.

For

RCU

Model Name: RCU-G  
Trade Name: LAUNCH  
Brand Name: LAUNCH  
FCC ID: XUJRCUG  
Standard: 47 CFR Part 15 Subpart B  
Test date: June 21, 2013– June 30, 2013  
Issue date: July 4, 2013


By

Shenzhen Morlab Communications Technology Co., Ltd.

Tested by Yang Yong  
Yang Yong  
(Test Engineer)  
Date 2013.7.4



Review by Huang Pulong  
(EMC Manager)  
Date 2013.7.4



IEEE 1325

IEEE 1725

81A



EGG

Reg. No.

Reg. No.  
**695796**

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer, Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>3</b>
<b>1.1 EUT Description .....</b>	<b>3</b>
<b>1.2 Test Standards and Results .....</b>	<b>4</b>
<b>1.3 Facilities and Accreditations.....</b>	<b>5</b>
1.3.1 Facilities .....	5
1.3.2 Test Environment Conditions.....	5
1.3.3 Measurement Uncertainty .....	5
<b>2. TEST CONDITIONS SETTING.....</b>	<b>6</b>
<b>2.1 Test Mode .....</b>	<b>6</b>
<b>2.2 Test Setup and Equipments List.....</b>	<b>7</b>
2.2.1 Radiated Emission.....	7
<b>3. 47 CFR PART 15B REQUIREMENTS .....</b>	<b>10</b>
<b>3.1 Radiated Emission .....</b>	<b>10</b>
3.1.1 Requirement .....	10
3.1.2 Test Description .....	10
3.1.3 Frequency range of measurement .....	11
3.1.4 Test Result.....	11

Change History		
Issue	Date	Reason for change
1.0	July 4, 2013	First edition

## 1. GENERAL INFORMATION

### 1.1 EUT Description

EUT Type..... RCU  
Serial No. .... (n.a., marked #1 by test site)  
Hardware Version ..... V1.00.002  
Software Version..... V1.00.001  
Applicant..... Launch Tech Co., Ltd.  
Launch Industrial Park, North of Wuhe Rd., Banxuegang, Longgang,  
Shenzhen, China  
Manufacturer..... Launch Tech Co., Ltd.  
Launch Industrial Park, North of Wuhe Rd., Banxuegang, Longgang,  
Shenzhen, China  
Power supply ..... 12VDC  
Speed of the processor .. 120MHz (generated by the CPU)  
32.768KHz (generated by the crystal oscillator)

#### Note:

1. The EUT is a RCU which is the first telematics product integrated GPS/GPRS/3G/G-Sensor and other modules in the industry based on the system-wide data collection, it equipped with a Micro-USB port which can be connected to the PC for local upgrade and data upload.
2. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
2	15.109	Radiated Emission	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4 2009.

## 1.3 Facilities and Accreditations

### 1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China 518101. The test site is constructed in conformance with the requirements of ANSI C63.4(2009) and CISPR Publication 22(2010); the FCC registration number is 695796.

### 1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 -106

### 1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Radiated Emission:	±3.1dB
-----------------------------------	--------

## 2. TEST CONDITIONS SETTING

### 2.1 Test Mode

The test mode (USB)

The EUT configuration of the emission tests is EUT + DC Power Source + PC.


During the measurement, the EUT was connected with a PC via the Micro-USB port, it was working normally, meanwhile, the EUT was powered by a DC Power Source.

## 2.2 Test Setup and Equipments List


### 2.2.1 Radiated Emission

#### A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



## 3) For radiated emissions above 1GHz



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

## 1) In the frequency range of 9KHz to 30MHz, magnetic field is measured with Loop Test Antenna.

The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

## 2) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

**B. Equipments List:**

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
EMC Analyzer	Agilent	E7405A	US44210471	12/05/2013	11/05/2014
Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	12/05/2012	11/05/2014
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	12/05/2012	11/05/2014



Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	9120D-963	12/05/2012	11/05/2014
Test Antenna -Loop	Schwarzbeck	FMZB 1519	1519-022	12/05/2012	11/05/2014
PC	Lenovo	ThinkPadT61	ZZF3077	(n.a.)	(n.a.)

### 3. 47 CFR PART 15B REQUIREMENTS

#### 3.1 Radiated Emission

##### 3.1.1 Requirement

According to FCC section 15.109(a)(e), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	μV/m	Dist	(uV/m)	(dBuV/m)
0.009 - 0.490	2400/F(KHz)	300m	10000* 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 - 1.705	2400/F(KHz)	30m	100* 2400/F(KHz)	20log 2400/F(KHz) + 40
1.705 - 30.00	30	30m	100*30	20log 30 + 40
30.0 - 88.0	100	3m	100	20log 100
88.0 - 216.0	150	3m	150	20log 150
216.0 - 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

Note: The limits of frequency below 30MHz is quoted from the FCC section 15.209.

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by 20log Emission Level(uV/m).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $Ld1 = Ld2 * (d2/d1)^2$ .

Example:

F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = Ld2 * (10)^2 = 100 * 30uV/m$$

##### 3.1.2 Test Description

See section 2.2.1 of this report.

### 3.1.3 Frequency range of measurement

Highest frequency generated or used in the device is the highest speed of the processor, lowest frequency generated or used in the device is the lowest frequency of the oscillator. According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:

Frequency	Frequency generated or used in the device	Frequency range of radiated measurement in the report
Highest	120MHz	2GHz
Lowest	32.768KHz	9KHz

### 3.1.4 Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

#### A. Test Plots and Suspicious Points:

NOTE: The emissions are too small to be measured and are at least 6 dB below the limit, So all the data of marked are pass.




(Plot A: 9K – 30M)



(Plot A: 30MHz – 6GHz, Test Antenna Vertical)

NO.	Fre. (MHz)	Pk	QP	AV	Limit- PK	Limit- QP	Limit- AV	Antenna	Verdict
1	165.461	N.A	28.97	N.A	N.A	43.5	N.A	Vertical	Pass
2	276.733	N.A	38.58	N.A	N.A	46.0	N.A	Vertical	Pass
3	332.369	N.A	37.91	N.A	N.A	46.0	N.A	Vertical	Pass
4	414.613	N.A	35.32	N.A	N.A	46.0	N.A	Vertical	Pass
5	663.766	N.A	34.32	N.A	N.A	46.0	N.A	Vertical	Pass
6	1498.753	41.87	N.A	35.19	74.0	N.A	54.0	Vertical	Pass



(Plot B: 30MHz – 6GHz, Test Antenna Horizontal)

NO.	Fre. (MHz)	Pk	QP	AV	Limit- PK	Limit- QP	Limit- AV	Antenna	Verdict
1	242.868	N.A	39.77	N.A	N.A	46.0	N.A	Horizontal	Pass
2	276.733	N.A	39.73	N.A	N.A	46.0	N.A	Horizontal	Pass
3	663.766	N.A	36.80	N.A	N.A	46.0	N.A	Horizontal	Pass
4	1498.753	43.04	N.A	36.45	74.0	N.A	54.0	Horizontal	Pass

**Test Result: Pass**

\*\* END OF REPORT \*\*