



REPORT No. : SZ17110212W01

# TEST REPORT

**APPLICANT** : Y Soft Corporation, a.s.

**PRODUCT NAME** : Ultralight P&C Multireader MF+

**MODEL NAME** : ML01065

**BRAND NAME** : Y Soft SafeQ

**FCC ID** : XUY0YX0ML01065

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**TEST DATE** : 2017-12-23 to 2017-12-28

**ISSUE DATE** : 2018-01-23

Tested by:

Peng Shiqing (Test Engineer)

Approved by:

Andy Yeh (Technical Director)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn





## DIRECTORY

<b>1. Technical Information .....</b>	<b>4</b>
<b>1.1. Applicant and Manufacturer Information.....</b>	<b>4</b>
<b>1.2. Equipment Under Test (EUT) Description.....</b>	<b>4</b>
<b>1.3. Test Standards and Results .....</b>	<b>5</b>
<b>1.4. Environmental Conditions .....</b>	<b>5</b>
<b>2. 47 CFR Part 15C Requirements.....</b>	<b>6</b>
<b>2.1. Antenna requirement.....</b>	<b>6</b>
<b>2.2. Conducted Emission.....</b>	<b>7</b>
<b>2.3. Radiated Emission.....</b>	<b>10</b>
<b>2.4. 20dB Bandwidth .....</b>	<b>16</b>
<b>Annex A Test Uncertainty .....</b>	<b>18</b>
<b>Annex B Testing Laboratory Information.....</b>	<b>19</b>

**Change History**

Issue	Date	Reason for change
1.0	2018-01-03	First edition
2.0	2018-01-23	Second edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Y Soft Corporation, a.s.
<b>Applicant Address:</b>	U Kněžské louky 2151/18, Praha 3, 130 00, Czech Republic
<b>Manufacturer:</b>	Y Soft Corporation, a.s.
<b>Manufacturer Address:</b>	U Kněžské louky 2151/18, Praha 3, 130 00, Czech Republic

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Ultralight P&C Multireader MF+
<b>Serial No:</b>	(N/A, marked #1 by test site)
<b>Hardware Version:</b>	N/A
<b>Software Version:</b>	N/A
<b>Operating Frequency:</b>	125 kHz
<b>Transmit Power:</b>	< 100mW
<b>Modulation Type:</b>	ASK,FSK
<b>Antenna Type:</b>	PCB Antenna
<b>Power Supply:</b>	AC Adaptor

**Note 1:** The EUT supports two type of modulation ASK and FSK, both of the two modulation type are tested, only the worst test result(ASK) were recorded in the test report.

**Note 2:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Engineer	Result
1	15.203	Antenna Requirement	Peng Shiqing	PASS
2	15.207	Conducted Emission	Peng Shiqing	PASS
3	15.209(a)	Radiated Emission	Peng Shiqing	PASS
4	15.215(c)	20dB Bandwidth	Peng Shiqing	PASS

**Note:** The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013. The EUT has been tested under continuous operating condition.

## 1.4. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



## 2. 47 CFR Part 15C Requirements

### 2.1. Antenna requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Result:

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

**Result: Compliant**

## 2.2. Conducted Emission

### 2.2.1. Test Requirement


According to FCC section 15.207, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:


- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.2.2. Test Setup




The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50 $\Omega$ /50 $\mu$ H of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

## 2.2.3. Test Result



(Plot A: L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.15	38.18	32.39	66.00	56.00	Line	PASS
2	0.44	35.04	28.49	57.16	47.16		PASS
3	1.05	24.19	18.27	56.00	46.00		PASS
4	6.25	26.34	20.71	60.00	50.00		PASS
5	13.64	20.10	13.14	60.00	50.00		PASS
6	25.00	31.79	30.20	60.00	50.00		PASS



(Plot B: N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.18	36.42	30.52	64.51	54.51	Neutral	PASS
2	0.43	34.41	27.89	57.18	47.18		PASS
3	0.67	26.57	20.64	56.00	46.00		PASS
4	5.04	28.25	21.01	60.00	50.00		PASS
5	13.59	24.62	16.52	60.00	50.00		PASS
6	25.00	30.76	28.89	60.00	50.00		PASS



## 2.3. Radiated Emission

### 2.3.1. Test Requirement

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other Sections within this Part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emissions and not the fundamental frequency. However, the level of any unwanted emission shall not exceed the level of the fundamental frequency.

The emission limits shown in the following table are based on measurements employing a CISPR quasi-peak detector except for the frequency 9-90kHz, 110-490kHz and above 1000MHz.

Radiated emission limits in these three bands are based on measurements employing an average detector.

Frequency range (MHz)	Field Strength( $\mu$ V/m)	Distance(m)
0.009 ~ 0.490	2400/F(KHz)	300
0.490 ~ 1.705	24000/F(KHz)	30
1.705 ~ 30	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- Field Strength (dB $\mu$ V/m) = 20\*log[Field Strength ( $\mu$ V/m)].
- If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $Ld1 = Ld2 * (d2/d1)^2$ .

Example:


F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = 30uV/m * (10)^2 = 100 * 30uV/m$$


- In the emission tables above, the tighter limit applies at the band edges.

### 2.3.2. Test Setup

#### 1) For radiated emissions below 30MHz



#### 2) For radiated emissions from 30MHz to 1GHz



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

In the frequency range of 9 kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

### 2.3.3. Test Result

#### A. Fundamental


Fre. (KHz)	PK Reading (dB $\mu$ V)	AV Reading (dB $\mu$ V)	Correction Factor (dB)	PK Result (dB $\mu$ V/m)	AV Result (dB $\mu$ V/m)	PK Limits (dB $\mu$ V/m)	AV Limits (dB $\mu$ V/m)	Verdict
125	52.91	47.88	25.75	78.66	73.63	105.7	85.7	PASS

Please refer to the following plot:




**B. Radiated Emission <30MHz (9 kHz-30MHz)**

NOTE: The emissions are too small to be measured and are at least 6 dB below the limit, so all the data of marked are pass.




## C. Radiated Emission &gt;30MHz (30MHz-1GHz)



(30MHz – 1GHz, Test Antenna Horizontal)

No.	Fre. MHz	Pk dB $\mu$ V/m	QP dB $\mu$ V/m	AV dB $\mu$ V/m	Limit-PK dB $\mu$ V/m	Limit-QP dB $\mu$ V/m	Limit-AV dB $\mu$ V/m	ANT	Verdict
1	31.940	24.05	N/A	N/A	N/A	40.00	N/A	H	Pass
2	90.140	20.76	N/A	N/A	N/A	43.50	N/A	H	Pass
3	250.190	36.20	N/A	N/A	N/A	46.00	N/A	H	Pass
4	399.570	39.24	N/A	N/A	N/A	46.00	N/A	H	Pass
5	500.450	34.12	N/A	N/A	N/A	46.00	N/A	H	Pass
6	900.090	33.80	N/A	N/A	N/A	46.00	N/A	H	Pass



(30MHz – 1GHz, Test Antenna Vertical)


No.	Fre. MHz	Pk dB $\mu$ V/m	QP dB $\mu$ V/m	AV dB $\mu$ V/m	Limit-PK dB $\mu$ V/m	Limit-QP dB $\mu$ V/m	Limit-AV dB $\mu$ V/m	ANT	Verdict
1	31.940	26.21	N/A	N/A	N/A	40.00	N/A	V	Pass
2	99.840	23.35	N/A	N/A	N/A	43.50	N/A	V	Pass
3	275.410	36.03	N/A	N/A	N/A	46.00	N/A	V	Pass
4	350.100	36.43	N/A	N/A	N/A	46.00	N/A	V	Pass
5	549.920	29.81	N/A	N/A	N/A	46.00	N/A	V	Pass
6	849.650	33.57	N/A	N/A	N/A	46.00	N/A	V	Pass

## 2.4. 20dB Bandwidth

### 2.4.1. Standard Applicable

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.


### 2.4.2. Test Setup



### 2.4.3. Test Result

Frequency(kHz)	20dB Bandwidth (kHz)	Verdict
125	0.435	PASS

Please refer to the following plot:





REPORT No. : SZ17110212W01

## Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Radiated Emission:	±3.1dB
Conducted Emission:	±1.8dB
Bandwidth	±5%



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Company Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Department:</b>	Morlab Laboratory
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Responsible Test Lab Manager:</b>	Mr. Su Feng
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192.



#### 4. Test Equipments Utilized

##### 4.1 Test Equipments

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	KEYSIGHT	N9038A	MY56400093	2017.07.13	2018.07.12
LISN	Schwarzbeck	NSLK 8127	812744	2017.05.17	2018.05.16
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	2017.05.17	2018.05.16
Coaxial Cable	Morlab	EMC01	CB01	(n.a.)	(n.a.)
Coaxial Cable	Morlab	EMC02	CB02	(n.a.)	(n.a.)
Anechoic Chamber	CRT	9m*6m*6m	N/A	2017.11.19	2020.11.18
Test Antenna – Bi-Log	Schwarzbeck	VULB 9163	9163-519	2017.05.14	2018.05.13
Test Antenna -Loop	Schwarzbeck	FMZB 1519	1519-022	2017.03.07	2018.03.06

##### 4.2 Test Software Utilized

Model	Version Number	Producer
TS+ -[ JS32-CE]	Version 2.5.0.0	Tonscend
MORLAB EMCR V1.2	Version 1.0	MORLAB

— END OF REPORT —