

Report No. : FG372503

Partial FCC RF Test Report

APPLICANT : Silicon Controls Pty. Ltd. EQUIPMENT : GASLOG Cellular Dialer

BRAND NAME : GASLOG

MODEL NAME : SC414C7714

MARKETING NAME : GASLOG Cellular Dialer

FCC ID : XV2SC414002

STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was integrated the WWAN Module (FCC ID: RI7CE910-DUAL) during the test. This is a partial report which is only included the conducted power, ERP/EIRP and radiated spurious emissions test items. The product was received on Jul. 25, 2013 and completely tested on Aug. 03, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 1 of 22
Report Issued Date : Aug. 22, 2013



TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAF	RY OF TEST RESULT	4
1	GENI	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	
	1.3	Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	6
	1.6	Maximum ERP/EIRP Power	6
	1.7	Testing Site	6
	1.8	Applied Standards	7
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	8
	2.2	Connection Diagram of Test System	
	2.3	Support Unit used in test configuration and system	
	2.4	Measurement Results Explanation Example	
3	TEST	RESULT	10
	3.1	Conducted Output Power Measurement	10
	3.2	Effective Radiated Power and Effective Isotropic Radiated Power Measurement	12
	3.3	Field Strength of Spurious Radiation Measurement	
4	LIST	OF MEASURING EQUIPMENT	21
5	UNCI	ERTAINTY OF EVALUATION	22
ΑP	PEND	IX A. SETUP PHOTOGRAPHS	

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 2 of 22

Report No. : FG372503

Report Issued Date: Aug. 22, 2013



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG372503	Rev. 01	Initial issue of report	Aug. 22, 2013

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 3 of 22 Report Issued Date : Aug. 22, 2013

Report No.: FG372503



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 24.13 dB at 3760.000 MHz

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 4 of 22

Report No. : FG372503

Report Issued Date : Aug. 22, 2013 Report Version : Rev. 01



1 General Description

1.1 Applicant

Silicon Controls Pty. Ltd.

Suite 2, Level 1; 12 Waterloo Road; Macquarie Park NSW 2113 Australia

1.2 Manufacturer

Silicon Controls Pty. Ltd.

Suite 2, Level 1; 12 Waterloo Road; Macquarie Park NSW 2113 Australia

1.3 Feature of Equipment Under Test

Product Feature					
Equipment	GASLOG Cellular Dialer				
Brand Name	GASLOG				
Model Name	SC414C7714				
Marketing Name	GASLOG Cellular Dialer				
FCC ID	XV2SC414002				
EUT supports Radios application	CDMA				
HW Version	101592 rev 1				
SW Version	Module CE-910; F/W version 18.11.001				
OVV VEISIOII	Application F/W: CDMA Compliance Test Suite build 174				
EUT Stage	Identical Prototype				

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard					
Tx Frequency	CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz				
TAT Toquotioy	CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz				
Rx Frequency	CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz				
IXX I requericy	CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz				
Maximum Output Power to Antenna	CDMA2000 BC0 : 25.31 dBm				
Maximum Output Fower to Antenna	CDMA2000 BC1 : 25.12 dBm				
Antenna Type	PCB Antenna				
Antenna Gain	CDMA2000 BC0: -0.5 dBi				
Antenna Gam	CDMA2000 BC1: -2.5 dBi				
Type of Modulation	CDMA2000 1xRTT : QPSK				

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755- 3320-2398

FCC ID: XV2SC414002

Page Number : 5 of 22 Report Issued Date : Aug. 22, 2013

Report No.: FG372503



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)
Part 22	CDMA2000 BC0 1xRTT	QPSK	0.1629
Part 24	CDMA2000 BC1 1xRTT	QPSK	0.2512

Report No. : FG372503

: 6 of 22

: Rev. 01

Page Number

1.7 Testing Site

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.				
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.				
	TEL: +86-755- 3320-2398				
Took Site No	s	porton Site N	0.	FCC/IC Registration No.	
Test Site No.	TH01-SZ	03CH01-SZ	OTA01-SZ	831040/4086F-1	

TEL: 86-755- 3320-2398 Report Issued Date: Aug. 22, 2013 FCC ID: XV2SC414002 Report Version

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 7 of 22 Report Issued Date : Aug. 22, 2013

Report No. : FG372503



2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

- 1. 30 MHz to 9000 MHz for CDMA2000 BC0.
- 30 MHz to 19000 MHz for CDMA2000 BC1.

Test Modes							
Band	Conducted TCs						
CDMA2000 BC0	■ 1xRTT Link Mode	■ 1xRTT Link Mode					
CDMA2000 BC1	■ 1xRTT Link Mode	■ 1xRTT Link Mode					

Note: The maximum RF output power levels are 1xRTT RC3+SO32 mode for CDMA2000 BC0 on QPSK Link and 1xRTT RC3+SO55 mode for CDMA2000 BC1 on QPSK Link; only these modes were used for all tests.

The conducted power table is as follows:

Conducted Power (*Unit: dBm)							
Band	CI	MA2000 B	C0	CDMA2000 BC1			
Channel	1013	1013 384 777			600	1175	
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75	
1xRTT RC1 SO55	25.13	24.76	24.65	25.09	24.92	24.45	
1xRTT RC3 SO55	25.30	25.05	24.91	<mark>25.12</mark>	25.03	24.45	
1xRTT RC3 SO32(+ F-SCH)	25.28	24.92	24.83	25.10	24.96	24.55	
1xRTT RC3 SO32(+SCH)	<mark>25.31</mark>	24.97	24.88	25.04	24.97	24.54	


TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 8 of 22 Report Issued Date : Aug. 22, 2013

Report No.: FG372503



Report No.: FG372503

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

ltem	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ = 4.2 + 10 = 14.2 (dB)

SPORTON INTERNATIONAL (SHENZHEN) INC.

: 9 of 22 Page Number TEL: 86-755- 3320-2398 Report Issued Date: Aug. 22, 2013 FCC ID: XV2SC414002 : Rev. 01 Report Version



RF Test Report No. : FG372503

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to base station.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. Set EUT at maximum power through base station.
- 4. Select lowest, middle, and highest channels for each band and different modulation.
- Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 10 of 22
Report Issued Date : Aug. 22, 2013

3.1.5 Test Result of Conducted Output Power

CDMA2000 BC0						
Test Mode	CDMA 2000 1xRTT					
Test Status	RC3+SO32 1013 (Low) 384 (Mid) 777 (High)					
Channel						
Frequency (MHz)	824.7	836.52	848.31			
Conducted Power (dBm)	25.31	24.97	24.88			
Conducted Power (Watts)	0.34 0.31 0.31					

CDMA2000 BC1						
Test Mode	CDMA 2000 1xRTT					
Test Status	RC3+SO55					
Channel	25 (Low) 600 (Mid) 1175 (Hig					
Frequency (MHz)	1851.25	1880	1908.75			
Conducted Power (dBm)	25.12	25.03	24.45			
Conducted Power (Watts)	0.33 0.32 0.28					

Note: Maximum average power for CDMA2000.

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 11 of 22
Report Issued Date : Aug. 22, 2013

Report No. : FG372503

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

Report No.: FG372503

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- 1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
- 2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst; UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
- The table was rotated 360 degrees to determine the position of the highest radiated power. 4.
- 5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
- 6. Taking the record of maximum ERP/EIRP.
- 7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. The conducted power at the terminal of the dipole antenna is measured.
- Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna. 9.
- 10. ERP/EIRP = Ps + Et Es + Gs = Ps + Rt Rs + Gs

Ps (dBm): Input power to substitution antenna.

Gs (dBi or dBd): Substitution antenna Gain.

Et = Rt + AF

Es = Rs + AF

AF (dB/m): Receive antenna factor

Rt: The highest received signal in spectrum analyzer for EUT.


Rs: The highest received signal in spectrum analyzer for substitution antenna.

: 12 of 22 Page Number TEL: 86-755- 3320-2398 Report Issued Date: Aug. 22, 2013 FCC ID: XV2SC414002 Report Version : Rev. 01



Report No. : FG372503

3.2.4 Test Setup



TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 13 of 22
Report Issued Date : Aug. 22, 2013



3.2.5 Test Result of ERP

	CDMA2000 BC0 1xRTT_RC3+SO32 Radiated Power ERP								
	Horizontal Polarization								
Frequency	Rt	Rs	Ps	Gs	ERP	ERP			
(MHz)	(dBm)	(dBm)	(dBm)	(dBd)	(dBm)	(W)			
824.70	-25.35	-48.12	0.00	-1.08	21.69	0.1476			
836.52	-25.87	-48.28	0.00	-0.93	21.48	0.1406			
848.31	-26.59	-48.35	0.00	-0.76	21.00	0.1259			
		Ve	rtical Polarizat	ion					
Frequency	Rt	Rs	Ps	Gs	ERP	ERP			
(MHz)	(dBm)	(dBm)	(dBm)	(dBd)	(dBm)	(W)			
824.70	-24.77	-47.97	0.00	-1.08	22.12	0.1629			
836.52	-25.09	-48.01	0.00	-0.93	21.99	0.1581			
848.31	-25.51	-48.05	0.00	-0.76	21.78	0.1507			

3.2.6 Test Result of EIRP

	CDMA2000 BC1 1xRTT_RC3+SO55 Radiated Power EIRP									
		Hori	zontal Polariza	tion						
Frequency (MHz)	cy Rt Rs Ps Gs EIRP EIRP (dBm) (dBm) (dBi) (dBm) (W)									
1851.25	-29.84	-51.88	0.00	1.96	24.00	0.2512				
1880.00	-31.18	-52.99	0.00	2.00	23.81	0.2404				
1908.75	-32.89	-54.28	0.00	1.98	23.37	0.2173				
		Ve	rtical Polarizati	on						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)				
1851.25	-31.29	-52.13	0.00	1.96	22.80	0.1905				
1880.00	-32.54	-53.17	0.00	2.00	22.63	0.1832				
1908.75	-33.66	-54.13	0.00	1.98	22.45	0.1758				

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 14 of 22
Report Issued Date : Aug. 22, 2013

Report No. : FG372503



3.3 Field Strength of Spurious Radiation Measurement

3.3.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43+10log₁₀(P[Watts]) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - $= [30 + 10\log(P)] (dBm) [43 + 10\log(P)] (dB)$
 - = -13dBm.


Report No.: FG372503




Report No.: FG372503

3.3.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.3.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


: 16 of 22 Page Number TEL: 86-755- 3320-2398 Report Issued Date: Aug. 22, 2013 FCC ID: XV2SC414002 Report Version : Rev. 01



3.3.6 Test Result of Field Strength of Spurious Radiated

Band :	CDMA2000 BC0	Temperature : 23~25°C						
Test Mode :	1xRTT_RC3+SO32 Link	Relative Humidity :	49~53%					
Test Engineer :	Savin Zhang Polarization : Horizontal							
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.							

0 Level (dBm)



: 03CH01-SZ

: -13DBM HF_EIRP_H_130101 HORIZONTAL : (FG) 372503 Condition

Project


Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-54.93	-13	-41.93	-67.85	-55.58	0.57	3.37	Н	Pass
2510	-46.12	-13	-33.12	-68.90	-48.35	0.78	5.16	Н	Pass
3346	-49.45	-13	-36.45	-60.05	-53.09	0.87	6.66	Н	Pass
4182	-58.97	-13	-45.97	-73.73	-63.56	0.97	7.71	Н	Pass

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002

Page Number : 17 of 22 Report Issued Date: Aug. 22, 2013

Report No. : FG372503

Band :	CDMA2000 BC0 Temperature : 23~25°						
Test Mode :	1xRTT_RC3+SO32 Link	Relative Humidity :	49~53%				
Test Engineer :	Gavin Zhang Polarization: Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line						



Site

: 03CH01-SZ : -13DBM HF_EIRP_V_130101 VERTICAL Condition

: (FG) 372503 Project


Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-59.27	-13	-46.27	-69.90	-59.92	0.57	3.37	V	Pass
2510	-51.81	-13	-38.81	-70.74	-54.04	0.78	5.16	V	Pass
3346	-43.64	-13	-30.64	-56.98	-47.28	0.87	6.66	V	Pass
4182	-58.23	-13	-45.23	-73.45	-62.82	0.97	7.71	V	Pass

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002

: 18 of 22 Page Number Report Issued Date: Aug. 22, 2013 Report Version : Rev. 01

Report No. : FG372503

Band :	CDMA2000 BC1	2000 BC1 Temperature : 23~25°C					
Test Mode :	1xRTT_RC3+SO55 Link	Relative Humidity :	49~53%				
Test Engineer :	Gavin Zhang Polarization : Horizon						
Remark ·	Spurious emissions within 30-1000MHz were found more than 20dB below limit line						



Site : 03CH01-SZ

Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL


Project : (FG) 372503

Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-46.52	-13	-33.52	-61.11	-53.26	1.28	8.02	Н	Pass
5640	-55.86	-13	-42.86	-73.85	-64.28	1.58	10.00	Н	Pass
7520	-53.77	-13	-40.77	-75.71	-64.09	1.78	12.10	Н	Pass
9400	-55.50	-13	-42.50	-77.62	-66.28	2.22	13.00	Н	Pass

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 19 of 22
Report Issued Date : Aug. 22, 2013
Report Version : Rev. 01

Report No. : FG372503

Band :	CDMA2000 BC1	Temperature :	23~25°C				
Test Mode :	1xRTT_RC3+SO55 Link	Relative Humidity :	49~53%				
Test Engineer :	Gavin Zhang Polarization : Vertical						
Remark:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line						



Site : 03CH01-SZ

Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Project : (FG) 372503

Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-37.13	-13	-24.13	-54.86	-43.87	1.28	8.02	V	Pass
5640	-56.29	-13	-43.29	-73.37	-64.71	1.58	10	V	Pass
7520	-52.83	-13	-39.83	-75.08	-63.15	1.78	12.1	V	Pass
9400	-54.23	-13	-41.23	-77.85	-65.01	2.22	13	V	Pass

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 20 of 22
Report Issued Date : Aug. 22, 2013

Report No. : FG372503



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 28, 2013	Aug. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	N/A	Mar. 28, 2013	Aug. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	N/A	Mar. 28, 2013	Aug. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
ESCI TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Mar. 28, 2013	Aug. 03, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP30	101362	9kHz~30GHz	Oct. 11, 2012	Aug. 03, 2013	Oct. 10, 2013	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 12, 2012	Aug. 03, 2013	Oct. 11, 2013	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Nov. 03, 2012	Aug. 03, 2013	Nov. 02, 2013	Radiation (03CH01-SZ)
Turn Table	EM Electronic	EM 1000	N/A	0 ~ 360 degree	N/A	Aug. 03, 2013	N/A	Radiation (03CH01-SZ)
Antenna Mast	EM Electronic	EM 1000	N/A	1 m - 4 m	N/A	Aug. 03, 2013	N/A	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3GHz Gain 30dB	Mar. 28, 2013	Aug. 03, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	Aug. 03, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
SHF-EHF -Horn	Schwarzbeck	BBHA9170	BBHA917024 9	14GHz~40GHz	Nov. 23, 2012	Aug. 03, 2013	Nov. 22, 2013	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Aug. 22, 2012	Aug. 01, 2013	Aug. 21, 2013	ERP/EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MH z	N/A	Aug. 01, 2013	N/A	ERP/EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	Aug. 01, 2013	N/A	ERP/EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	Aug. 01, 2013	N/A	ERP/EIRP (OTA01-SZ)

TEL: 86-755- 3320-2398 FCC ID: XV2SC414002 Page Number : 21 of 22
Report Issued Date : Aug. 22, 2013

Report No. : FG372503



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2.54
Confidence of 95% (U = 2Uc(y))	2.54

<u>Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)</u>

Measuring Uncertainty for a Level of	4.72
Confidence of 95%(U = 2Uc(y))	4.72

TEL: 86-755- 3320-2398 Report Is FCC ID: XV2SC414002 Report V

Page Number : 22 of 22

Report Issued Date: Aug. 22, 2013

Report Version : Rev. 01

Report No. : FG372503