

# **FCC Test Report**

Report No.: RF160713C04

FCC ID: XVG50-0100-MC-20

Test Model: Kamai 650m, Amulet 655m

Series Model: Kamai 6XYzzzzzz, Amulet 6XYzzzzzz (where "X" can be 0-9, "Y" can be

0-9, "zzzzzz" can be any combination of "0-9", "a-z", "-", or "/" or blank for

marketing purpose) (Refer to item 3.1 for more details)

Received Date: Jul. 13, 2016

**Test Date:** Jul. 15 ~ Aug. 08, 2016

**Issued Date:** Aug. 09, 2016

Applicant: Amino Communications Ltd

Address: Buckingway Business Park, Anderson Road Swavesey, Cambridge, United

Kingdom

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



# **Table of Contents**

R	Release Control Record4					
1		Certificate of Conformity	5			
2		Summary of Test Results	6			
	2.1	Measurement Uncertainty	6			
	2.2	Modification Record	6			
3		General Information	7			
	3.1	General Description of EUT				
	3.2	Description of Test Modes				
	3.2.1	ht A				
	3.3	Description of Support Units				
	3.3.1 3.4	Configuration of System under Test				
	_	·				
4		Test Types and Results	14			
	4.1	Radiated Emission and Bandedge Measurement	14			
		Limits of Radiated Emission and Bandedge Measurement				
		2 Test Instruments				
		3 Test Procedures				
		5 Test Setup				
		5 FUT Operating Conditions				
		7 Test Results				
	4.2	Conducted Emission Measurement				
	4.2.1	1 Limits of Conducted Emission Measurement				
	4.2.2	2 Test Instruments	23			
		3 Test Procedures				
		Deviation from Test Standard				
		5 Test Setup				
		6 EUT Operating Conditions				
	4.2.7	7 Test Results				
	4.3 4.3.1					
		2 Test Setup				
		3 Test Instruments				
		1 Test Procedure				
	4.3.5	5 Deviation from Test Standard	29			
	4.3.6	6 EUT Operating Conditions	29			
		7 Test Result				
	4.4					
		Limits of Conducted Output Power Measurement				
		2 Test Setup				
		3 Test Instruments				
		5 Deviation from Test Standard				
		5 EUT Operating Conditions				
		7 Test Results				
	4.5	Power Spectral Density Measurement				
		Limits of Power Spectral Density Measurement				
		2 Test Setup				
		3 Test Instruments				
		Test Procedure				
		5 Deviation from Test Standard				
		S EUT Operating Condition				
	4.5.7	7 Test Results	<b>3</b> 3			



4.6	Conducted Out of Band Emission Measurement	34
4.6.1	Limits of Conducted Out of Band Emission Measurement	34
4.6.2	Test Setup	34
4.6.3	Test Instruments	34
4.6.4	Test Procedure	34
4.6.5	Deviation from Test Standard	34
4.6.6	EUT Operating Condition	34
4.6.7	Test Results	35
5 F	ctures of Test Arrangements	36
Append	lix – Information on the Testing Laboratories	37



# **Release Control Record**

Issue No.	Description	Date Issued
RF160713C04	Original release.	Aug. 09, 2016



### 1 Certificate of Conformity

**Product:** High Definition IP TV receiver

Brand: entone, amino (Refer to item 3.1 for more details)

**Test Model:** Kamai 650m, Amulet 655m (Refer to item 3.1 for more details)

Series Model: Kamai 6XYzzzzzz, Amulet 6XYzzzzzz (where "X" can be 0-9, "Y" can be 0-9,

"zzzzzz" can be any combination of "0-9", "a-z", "-", or "/" or blank for marketing

purpose) (Refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: Amino Communications Ltd

Test Date: Jul. 15 ~ Aug. 08, 2016

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by: My Special Aug. 09, 2016

4√y Lin / Specialist

Approved by : Aug. 09, 2016

Ken Liu / Senior Manager



# 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)						
FCC Clause	Test Item	Result	Remarks			
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -9.78dB at 0.36505MHz.			
15.205 / 15.209 / 15.247(d)	15.209 / Radiated Emissions and Band Edge   Measurement		Meet the requirement of limit. Minimum passing margin is -3.9dB at 901.06MHz.			
15.247(d) Antenna Port Emission		Pass	Meet the requirement of limit.			
15.247(a)(2) 6dB bandwidth		Pass	Meet the requirement of limit.			
15.247(b)	Conducted power	Pass	Meet the requirement of limit.			
15.247(e)	15.247(e) Power Spectral Density		Meet the requirement of limit.			
15.203	Antenna Requirement	Pass	Antenna connector is IPEX not a standard connector.			

# 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.63 dB
Radiated Emissions up to 1 GHz	200MHz ~1000MHz	3.64 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
Radiated Emissions above 1 GHZ	18GHz ~ 40GHz	2.29 dB

### 2.2 Modification Record

There were no modifications required for compliance.



# 3 General Information

# 3.1 General Description of EUT

Product	High Definition IP TV receiver
Brand	entone, amino (Refer to Note for more details)
Test Model	Kamai 650m, Amulet 655m
Series Model	Kamai 6XYzzzzzz, Amulet 6XYzzzzzzz (where "X" can be 0-9, "Y" can be 0-9, "zzzzzz" can be any combination of "0-9", "a-z", "-", or "/" or blank for marketing purpose)
Model Difference	Refer to Note for more details
Status of EUT	Engineering sample
Power Supply Rating	12Vdc (adapter)
Modulation Type	GFSK
Transfer Rate	1Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	40
Channel Spacing	2MHz
Output Power	2.344mW
Antenna Type	PIFA (Printed) antenna with 1.8dBi gain
Antenna Connector	IPEX
Accessory Device	Adapter, Remote controller (Brand: entone)
Data Cable Supplied	1.5m non-shielded Mini-din out-YPbPr & Mini-din out- AV cable without core 2m shielded HDMI cable without core 2m non-shielded RJ45 cable without core



### Note:

1. All models are listed as below. Model: Kamai 650m and Amulet 655m are representatives for final test.

Brand	Product Name	Model	Difference
entone, amino	High Definition IP TV receiver	Amulet 6XYZZZZZZ (wnere "X"	With BT, without HDD  With BT, with HDD 500GB, power key, 7-segment display and touch Panel
		"zzzzzz" can be any combination of "0-9", "a-z", "-", or "/" or blank for marketing purpose)	With BT, with HDD 1TB, powe key, 7-segment display and touch Panel

<sup>\*</sup> After pre-testing HDD 500GB and 1TB, the EUT with 1TB HDD is the worst case for final test.

2. The EUT uses following adapters.

The EOT does following adapters.						
Adapter 1	Adapter 1					
Brand Asian Power Devices Inc.						
Model WA-24Q12R						
Input Power	100-240Vac, 50-60Hz, 0.7A Max					
Output Power 12Vdc/ 2A						
Power Line	1.8m non-shielded DC cable without core attached on adapter					

Adapter 2	Adapter 2					
Brand Asian Power Devices Inc.						
Model WA-24Q12FU						
Input Power	100-240Vac, 50-60Hz, 0.7A Max					
Output Power	12Vdc/ 2A					
Power Line	1.45m non-shielded DC cable without core attached on adapter					

<sup>\*</sup> After pre-testing, adapter 1 is the worst case for final test.

<sup>\*\*</sup> After pre-testing, model: Amulet 655m is the worst case for radiated emission above 1GHz test.

<sup>3.</sup> The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



# 3.2 Description of Test Modes

40 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE		APPLICA	ABLE TO		DESCRIPTION
MODE	RE≥1G	RE<1G	PLC	APCM	DESCRIPTION
А	-	V	V	-	Model: Kamai 650m
В	V	V	V	√	Model: Amulet 655m

Where RE≥1G: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: "-" means no effect.

### Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
В	0 to 39	0, 19, 39	GFSK	1

### **Radiated Emission Test (Below 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)	
A, B	0 to 39	39	GFSK	1	

### **Power Line Conducted Emission:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)	
A, B	0 to 39	39	GFSK	1	

Report No.: RF160713C04 Page No. 10 / 37 Report Format Version: 6.1.1



# **Antenna Port Conducted Measurement:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)	
В	0 to 39	0, 19, 39	GFSK	1	

# **Test Condition:**

APPLICABLE TO ENVIRONMENTAL CONDITIONS		INPUT POWER	TESTED BY	
<b>RE≥1G</b> 20deg. C, 69%RH		120Vac, 60Hz	Tank Wu	
<b>RE&lt;1G</b> 20deg. C, 69%RH		120Vac, 60Hz	Tank Wu	
PLC	25deg. C, 60%RH	120Vac, 60Hz	Tank Wu	
APCM	25deg. C, 60%RH	120Vac, 60Hz	Frank Liu	

Report No.: RF160713C04 Page No. 11 / 37 Report Format Version: 6.1.1




# 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	TV Monitor	sony	KDL-32EX650	4365185	FCC DoC Approved	-
B.	USB 3.0 FLASH	HP	v250W	01	FCC DoC Approved	-
C.	Load	N/A	N/A	N/A	N/A	-

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	HDMI cable	1	2	Υ	0	Accessory of EUT
2.			2	N	0	Accessory of EUT

# 3.3.1 Configuration of System under Test



Report No.: RF160713C04 Page No. 12 / 37 Report Format Version: 6.1.1



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) KDB 558074 D01 DTS Meas Guidance v03r05

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

Report No.: RF160713C04 Page No. 13 / 37 Report Format Version: 6.1.1



### 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

## 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### Note:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: RF160713C04 Page No. 14 / 37 Report Format Version: 6.1.1



#### 4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Dec. 23, 2015	Dec. 22, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Apr. 19, 2016	Apr. 18, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-148	Jan. 18, 2016	Jan. 17, 2017
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Jan. 08, 2016	Jan. 07, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Jan. 18, 2016	Jan. 17, 2017
Preamplifier Agilent	8447D	2944A10738	Oct.18, 2015	Oct. 17, 2016
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-02(309222 +248780)	Aug. 09, 2015	Aug. 08, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-03(274092)	Aug. 09, 2015	Aug. 08, 2016
RF signal cable Woken	8D-FB	Cable-CH9-01	Aug. 09, 2015	Aug. 08, 2016
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower &Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
High Speed Peak Power Meter	ML2495A	1232003	Oct. 07, 2015	Oct. 06, 2016
Power Sensor	MA2411B	1207333	Oct. 07, 2015	Oct. 06, 2016

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 9.
- 3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 215374.
- 5. The IC Site Registration No. is IC 7450F-9.



#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
- 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 5. All modes of operation were investigated and the worst-case emissions are reported.


4.1.4	Deviation	from	Test	Standar	d

No	dΔ	いハコ	tı∩	n
IVU	uc	via	LIU	11.




### 4.1.5 Test Setup

# <Frequency Range below 1GHz>



## <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.



### 4.1.7 Test Results

### Above 1GHz Worst-Case Data

CHANNEL	TX Channel 0	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	2390.00	59.9 PK	74.0	-14.1	1.48 H	342	25.10	34.80	
2	2390.00	47.8 AV	54.0	-6.2	1.48 H	342	13.00	34.80	
3	*2402.00	94.4 PK			1.48 H	342	59.60	34.80	
4	*2402.00	93.3 AV			1.48 H	342	58.50	34.80	
5	4804.00	52.3 PK	74.0	-21.7	1.21 H	272	47.70	4.60	
6	4804.00	45.5 AV	54.0	-8.5	1.21 H	272	40.90	4.60	
		ANTENN	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL AT	Г 3 M		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	2390.00	59.6 PK	74.0	-14.4	1.51 V	161	24.80	34.80	
2	2390.00	48.0 AV	54.0	-6.0	1.51 V	161	13.20	34.80	
3	*2402.00	85.2 PK			1.51 V	161	50.40	34.80	
4	*2402.00	83.6 AV			1.51 V	161	48.80	34.80	
5	4804.00	52.7 PK	74.0	-21.3	1.25 V	191	48.10	4.60	
6	4804.00	46.6 AV	54.0	-7.4	1.25 V	191	42.00	4.60	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
  - Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	*2440.00	95.5 PK			1.47 H	336	60.50	35.00		
2	*2440.00	94.0 AV			1.47 H	336	59.00	35.00		
3	4880.00	50.0 PK	74.0	-24.0	1.55 H	302	45.50	4.50		
4	4880.00	37.6 AV	54.0	-16.4	1.55 H	302	33.10	4.50		
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: VI	ERTICAL AT	Г 3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	*2440.00	84.8 PK			2.12 V	156	49.80	35.00		
2	*2440.00	83.2 AV			2.12 V	156	48.20	35.00		
3	4880.00	49.8 PK	74.0	-24.2	1.24 V	198	45.30	4.50		
4	4880.00	37.0 AV	54.0	-17.0	1.24 V	198	32.50	4.50		

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
  - Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	*2480.00	96.3 PK			1.51 H	344	61.10	35.20		
2	*2480.00	95.0 AV			1.51 H	344	59.80	35.20		
3	2483.50	60.3 PK	74.0	-13.7	1.51 H	344	25.10	35.20		
4	2483.50	48.4 AV	54.0	-5.6	1.51 H	344	13.20	35.20		
5	4960.00	50.4 PK	74.0	-23.6	1.42 H	296	45.60	4.80		
6	4960.00	38.0 AV	54.0	-16.0	1.42 H	296	33.20	4.80		
		ANTENN	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL AT	Г 3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	*2480.00	87.1 PK			1.88 V	161	51.90	35.20		
2	*2480.00	85.8 AV			1.88 V	161	50.60	35.20		
3	2483.50	60.0 PK	74.0	-14.0	1.88 V	161	24.80	35.20		
4	2483.50	48.3 AV	54.0	-5.7	1.88 V	161	13.10	35.20		
5	4960.00	50.0 PK	74.0	-24.0	1.26 V	201	45.20	4.80		
6	4960.00	37.2 AV	54.0	-16.8	1.26 V	201	32.40	4.80		

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
  - Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.



### Below 1GHz worst-case data

CHANNEL	TX Channel 39	DETECTOR FUNCTION	IDETECTOR I	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)	
TEST MODE	А			

		ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	30.00	18.0 QP	40.0	-22.0	2.00 H	220	33.60	-15.60			
2	49.40	18.3 QP	40.0	-21.7	1.00 H	357	32.10	-13.80			
3	127.00	19.2 QP	43.5	-24.3	1.49 H	246	35.10	-15.90			
4	538.28	25.8 QP	46.0	-20.2	1.49 H	240	33.70	-7.90			
5	829.28	34.8 QP	46.0	-11.2	1.49 H	159	37.00	-2.20			
6	972.84	31.9 QP	54.0	-22.1	1.49 H	77	31.40	0.50			
		ANTENN	A POLARITY	/ & TEST DI	STANCE: VI	ERTICAL AT	Г 3 M				
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	36.38	32.7 QP	40.0	-7.3	1.00 V	324	48.00	-15.30			
2	49.40	33.8 QP	40.0	-6.2	1.00 V	295	47.60	-13.80			
3	49.40 99.84	33.8 QP 27.4 QP	40.0 43.5	-6.2 -16.1	1.00 V 1.25 V	295 15	47.60 46.30	-13.80 -18.90			
_				-							
3	99.84	27.4 QP	43.5	-16.1	1.25 V	15	46.30	-18.90			

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
  - Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



CHANNEL	TX Channel 39	DETECTOR	Ougoi Dook (OD)	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)	
TEST MODE	В			

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	49.40	17.3 QP	40.0	-22.7	2.00 H	332	31.10	-13.80		
2	101.78	20.6 QP	43.5	-22.9	2.00 H	337	39.30	-18.70		
3	447.10	32.3 QP	46.0	-13.7	2.00 H	347	41.50	-9.20		
4	522.76	28.5 QP	46.0	-17.5	1.49 H	337	36.70	-8.20		
5	901.06	42.1 QP	46.0	-3.9	1.49 H	289	43.00	-0.90		
6	976.72	36.6 QP	54.0	-17.4	1.49 H	251	35.90	0.70		
		ANTENN	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL AT	3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	37.53	31.4 QP	40.0	-8.6	1.00 V	334	46.40	-15.00		
2	103.72	26.1 QP	43.5	-17.4	1.25 V	225	44.40	-18.30		
3	136.70	21.8 QP	43.5	-21.7	1.01 V	175	36.60	-14.80		
4	447.10	27.6 QP	46.0	-18.4	1.01 V	280	36.80	-9.20		
5	825.40	36.9 QP	46.0	-9.1	1.01 V	133	39.10	-2.20		
6	897.18	36.9 QP	46.0	-9.1	1.51 V	314	37.90	-1.00		

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
  - Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



### 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Fraguency (MHz)	Conducted Limit (dBuV)				
Frequency (MHz)	Quasi-peak	Average			
0.15 - 0.5	66 - 56	56 - 46			
0.50 - 5.0	56	46			
5.0 - 30.0	60	50			

Note: 1. The lower limit shall apply at the transition frequencies.

### 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 16, 2015	Nov. 15, 2016
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Dec. 26, 2015	Dec. 25, 2016
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2016	Feb. 25, 2017
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100220	Nov. 13, 2015	Nov. 12, 2016
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.

<sup>2.</sup> The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.



#### 4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) were not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

### 4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.2.6 EUT Operating Conditions

Same as 4.1.6.




### 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
TEST MODE	A		

	From	Corr.	Readin	g Value	Emissio	n Level	Lir	nit	Ма	rgin
No	Freq.	Factor	[dB (	(uV)]	[dB (	(uV)]	[dB (	(uV)]	(d	B)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.02	41.02	30.41	51.04	40.43	65.79	55.79	-14.75	-15.36
2	0.16922	10.02	38.39	28.44	48.41	38.46	65.00	55.00	-16.59	-16.54
3	0.36334	10.10	34.47	28.44	44.57	38.54	58.65	48.65	-14.08	-10.11
4	4.49924	10.44	18.89	11.03	29.33	21.47	56.00	46.00	-26.67	-24.53
5	11.43426	10.81	18.00	9.88	28.81	20.69	60.00	50.00	-31.19	-29.31
6	17.19369	11.17	20.53	12.86	31.70	24.03	60.00	50.00	-28.30	-25.97

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
TEST MODE	A		

	Erog C		Reading Value		Emission Level		Limit		Margin	
No	Freq.	Factor	[dB (	(uV)]	[dB (	(uV)]	[dB (	(uV)]	(d	B)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15782	10.03	39.12	28.56	49.15	38.59	65.58	55.58	-16.43	-16.99
2	0.17147	10.03	38.08	27.48	48.11	37.51	64.89	54.89	-16.78	-17.38
3	0.36505	10.11	31.83	28.72	41.94	38.83	58.61	48.61	-16.67	-9.78
4	4.53311	10.46	17.17	9.16	27.63	19.62	56.00	46.00	-28.37	-26.38
5	11.79007	10.91	18.37	9.85	29.28	20.76	60.00	50.00	-30.72	-29.24
6	17.61597	11.30	19.79	12.39	31.09	23.69	60.00	50.00	-28.91	-26.31

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






Phase	Line (L)	LI Jefector Flinction	Quasi-Peak (QP) / Average (AV)
TEST MODE	В		

From		Corr.	Reading Value		Emission Level		Limit		Margin	
No	Freq.	Factor	[dB	(uV)]	[dB	(uV)]	[dB	(uV)]	(d	B)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16569	10.02	36.58	26.88	46.60	36.90	65.17	55.17	-18.57	-18.27
2	0.22820	10.04	34.08	26.03	44.12	36.07	62.51	52.51	-18.39	-16.44
3	0.36816	10.11	32.45	27.16	42.56	37.27	58.54	48.54	-15.98	-11.27
4	11.52810	10.82	20.13	12.37	30.95	23.19	60.00	50.00	-29.05	-26.81
5	16.99037	11.15	19.59	11.74	30.74	22.89	60.00	50.00	-29.26	-27.11
6	28.53660	11.90	16.07	9.65	27.97	21.55	60.00	50.00	-32.03	-28.45

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
TEST MODE	В		

Frog		Erog Corr.		Reading Value		Emission Level		Limit		Margin	
No	Freq.	Factor	[dB (	(uV)]	[dB	(uV)]	[dB (	(uV)]	(d	B)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.17346	10.03	36.30	26.46	46.33	36.49	64.79	54.79	-18.46	-18.30	
2	0.36896	10.12	30.66	25.51	40.78	35.63	58.52	48.52	-17.74	-12.89	
3	4.40408	10.45	18.56	9.87	29.01	20.32	56.00	46.00	-26.99	-25.68	
4	11.73924	10.91	20.28	12.60	31.19	23.51	60.00	50.00	-28.81	-26.49	
5	17.03338	11.26	20.28	11.61	31.54	22.87	60.00	50.00	-28.46	-27.13	
6	28.27854	12.06	17.56	10.25	29.62	22.31	60.00	50.00	-30.38	-27.69	

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.





#### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 30kHz
- b. Set the video bandwidth (VBW)  $\geq$  3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.3.5 Deviation from Test Standard

No deviation.


### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 4.3.7 Test Result

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.57	0.5	Pass
19	2440	0.58	0.5	Pass
39	2480	0.58	0.5	Pass






### 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

# 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

#### 4.4.5 Deviation from Test Standard

No deviation.

# 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

### 4.4.7 Test Results

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	1.778	2.50	30	Pass
19	2440	2.089	3.20	30	Pass
39	2480	2.344	3.70	30	Pass

Report No.: RF160713C04 Page No. 31 / 37 Report Format Version: 6.1.1




### 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



#### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW ≥ 3 × RBW.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

#### 4.5.5 Deviation from Test Standard

No deviation.


### 4.5.6 EUT Operating Condition

Same as Item 4.3.6



### 4.5.7 Test Results

Channel	Freq. (MHz)	PSD (dBm)	Limit (dBm)	Pass /Fail
0	2402	-12.25	8	Pass
19	2440	-11.74	8	Pass
39	2480	-11.73	8	Pass






#### 4.6 Conducted Out of Band Emission Measurement

#### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



#### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- a. Set the RBW = 100 kHz.
- b. Set the VBW ≥ 300 kHz.
- c. Detector = peak.
- d. Sweep time = auto couple.
- e. Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

### **MEASUREMENT PROCEDURE OOBE**

- a. Set RBW = 100 kHz.
- b. Set VBW ≥ 300 kHz.
- c. Detector = peak.
- d. Sweep = auto couple.
- e. Trace Mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum amplitude level.


#### 4.6.5 Deviation from Test Standard

No deviation.

# 4.6.6 EUT Operating Condition

Same as Item 4.3.6







5 Pictures of Test Arrangements	
Please refer to the attached file (Test Setup Photo).	



### Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>
Web Site: <a href="mailto:www.bureauveritas-adt.com">www.bureauveritas-adt.com</a>

The address and road map of all our labs can be found in our web site also.

--- END ---