

TEST REPORT

of

FCC Part 15 Subpart C

Limited Modular Approval

New Application; Class I PC; Class II PC

Product :

Aria

Brand:

amino, entone

Model:

XYZazzzzzz where "X" can be 6, 7, 8 for marketing purpose. "Y" can be 0~9 for marketing purpose. "Z" - can be 0~9. Among 0~9, number 1 & 3 are fixed for WiFi model, others are for marketing purpose. "a" - can be 0~9, A~Z, a~z, "-", "/", "~". Capital letter "I" is fixed for Bluetooth model; lowercase letter "r" is fixed for RF4CE model; others are for marketing purpose. "zzzzzzzz" - can be any combination of "0-9", "A-Z", "a-z", "-", "/", "~" or blank for marketing purpose.

Model Difference:

For market segmentation

FCC ID:

XVG50-0102-RT-22

FCC Rule Part:

§15.247, Cat: DTS

Applicant:

Amino Communications Ltd

Address:

Buckingway Business Park, Anderson Road, Swavesey, Cambridge CB24 4UQ, United Kingdom

Test Performed by:

International Standards Laboratory

<Lung-Tan LAB>

*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997; IC: IC4067B-3;

*Address:

No. 120, Lane 180, Hsin Ho Rd.,

Lung-Tan Dist., Tao Yuan City 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-17LR134FCTDS

Issue Date : 2017/11/24

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.



VERIFICATION OF COMPLIANCE

Applicant: Amino Communications Ltd

Product Description: Aria

Brand Name: amino, entone

XYZazzzzzz where “X” can be 6, 7, 8 for marketing purpose.“Y” can be 0~9 for marketing purpose.“Z” - can be 0~9. Among 0~9, number 1 & 3 are fixed for WiFi model, others are for marketing purpose.

Model No.: “a” - can be 0~9, A~Z, a~z, “-“, “/”, “~”. Capital letter “I” is fixed for Bluetooth model; lowercase letter “r” is fixed for RF4CE model; others are for marketing purpose.
“zzzzzzzz” – can be any combination of “0-9”, “A-Z”, “a-z”, “-“, “/”, “~” or blank for marketing purpose.

Model Difference: For market segmentation

FCC ID: XVG50-0102-RT-22

Date of test: 2017/06/03 ~ 2017/07/23

Date of EUT Received: 2017/06/03

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:


Lake Cheng

Date:

2017/11/24


Lake Cheng / Engineer

Prepared By:


Gigi Yeh

Date:

2017/11/24


Gigi Yeh / Engineer

Approved By:


Dino Chen

Date:

2017/11/24


Dino Chen / Sr. Engineer

Version

Version No.	Date	Description
00	2017/11/24	Initial creation of document

Uncertainty of Measurement

Description Of Test	Uncertainty
Conducted Emission (AC power line)	2.586 dB
Field Strength of Spurious Radiation	<=30MHz: 2.96dB 30-1GHz: 4.22 dB 1-40 GHz: 4.08 dB
Conducted Power	2.412 GHz: 1.30 dB 5.805 GHz: 1.55 dB
Power Density	2.412 GHz: 1.30 dB 5.805 GHz: 1.67 dB
Frequency	0.0032%
Time	0.01%
DC Voltage	1%

Table of Contents

1	GENERAL INFORMATION	7
1.1	Related Submittal(s) / Grant (s)	11
1.2	Test Methodology	11
1.3	Test Facility.....	11
1.4	Special Accessories.....	11
1.5	Equipment Modifications.....	11
2	SYSTEM TEST CONFIGURATION	12
2.1	EUT Configuration	12
2.2	EUT Exercise	12
2.3	Test Procedure.....	12
2.4	Configuration of Tested System.....	13
3	SUMMARY OF TEST RESULTS	14
4	DESCRIPTION OF TEST MODES	14
5	AC POWER LINE CONDUCTED EMISSION TEST	15
5.1	Standard Applicable:	15
5.2	Measurement Equipment Used:	15
5.3	EUT Setup:.....	15
5.4	Measurement Procedure:	16
5.5	Measurement Result:	16
6	PEAK OUTPUT POWER MEASUREMENT	19
6.1	Standard Applicable:	19
6.2	Measurement Equipment Used:	20
6.3	Test Set-up:	20
6.4	Measurement Procedure:	20
6.5	Measurement Result:	21
7	6dB Bandwidth.....	22
7.1	Standard Applicable:	22
7.2	Measurement Equipment Used:	22
7.3	Test Set-up:	22
7.4	Measurement Procedure:	22
7.5	Measurement Result:	23
8	100KHz BANDWIDTH OF BAND EDGES MEASUREMENT.....	30
8.1	Standard Applicable:	30
8.2	Measurement Equipment Used:	30
8.3	Test SET-UP:.....	32
8.4	Measurement Procedure:	33
8.5	Field Strength Calculation:	33
8.6	Measurement Result:	33
9	SPURIOUS RADIATED EMISSION TEST.....	59
9.1	Standard Applicable	59
9.2	Measurement Equipment Used:	59
9.3	Test SET-UP:.....	59
9.4	Measurement Procedure:	60
9.5	Field Strength Calculation	60
9.6	Measurement Result:	60

10	Peak Power Spectral Density	67
10.1	Standard Applicable:	67
10.2	Measurement Equipment Used:	67
10.3	Test Set-up:	67
10.4	Measurement Procedure:	67
10.5	Measurement Result:	68
11	ANTENNA REQUIREMENT	78
11.1	Standard Applicable:	78
11.2	Antenna Connected Construction:	78

1 GENERAL INFORMATION

General:

Product Name:	Aria
Brand:	amino, entone
Model:	XYZazzzzzz where "X" can be 6, 7, 8 for marketing purpose. "Y" can be 0~9 for marketing purpose. "Z" - can be 0~9. Among 0~9, number 1 & 3 are fixed for WiFi model, others are for marketing purpose. "a" - can be 0~9, A~Z, a~z, "-", "/", "~". Capital letter "I" is fixed for Bluetooth model; lowercase letter "r" is fixed for RF4CE model; others are for marketing purpose. "zzzzzzzz" – can be any combination of "0-9", "A-Z", "a-z", "-", "/", "~" or blank for marketing purpose.
Model different:	For market segmentation
Power Supply:	3.3Vdc

Host product details:

Product Name:	Aria	
Brand:	amino, entone	
Model:	XYZazzzzzz where "X" can be 6, 7, 8 for marketing purpose. "Y" can be 0~9 for marketing purpose. "Z" - can be 0~9. Among 0~9, number 1 & 3 are fixed for WiFi model, others are for marketing purpose. "a" - can be 0~9, A~Z, a~z, "-", "/", "~". Capital letter "I" is fixed for Bluetooth model; lowercase letter "r" is fixed for RF4CE model; others are for marketing purpose. "zzzzzzzz" – can be any combination of "0-9", "A-Z", "a-z", "-", "/", "~" or blank for marketing purpose.	
Model different:	For market segmentation	
Power Supply:	12Vdc from AC/DC adapter Adapter: Model: MSA-C1000IC12.0-12W-DE	

RF power setting in TEST Software	2.4G :			
	b mode :	Low (30)	Mid (30)	High (31)
	g mode:	Low (25)	Mid (25)	High (26)
	n-HT20 mode: chain 0	Low (25)	Mid (25)	High (25)
	n-HT20 mode: chain 1	Low (25)	Mid (25)	High (26)
	n-HT40 mode : chain 0	Low (25)	Mid (25)	High (25)
	n-HT40 mode : Ant b chain 1	Low (25)	Mid (25)	High (26)
	5G : B1+B2			
	a mode :	Low (48)	Mid (47)	High (45)
	n-VHT20 mode chain 0	Low (45)	Mid (45)	High (44)
	n-VHT20 mode chain 1	Low (45)	Mid (45)	High (44)
	n-VHT40 mode chain 0	Low (48)	Mid (48)	High (46)
	n-VHT40 mode chain 1	Low (48)	Mid (48)	High (46)
	n-VHT80 mode chain 0	Low (46)	High (46)	
	n-VHT80 mode chain 1	Low (45)	High (45)	
	5G : B3			
	a mode :	Low (52)	Mid (50)	High (48)
	n-VHT20 mode chain 0	Low (47)	Mid (47)	High (44)
	n-VHT20 mode chain 1	Low (47)	Mid (47)	High (44)
	n-VHT40 mode chain 0	Low (52)	Mid (52)	High (47)
	n-VHT40 mode chain 1	Low (52)	Mid (52)	High (47)
	n-VHT80 mode chain 0	Low (48)		
	n-VHT80 mode chain 1	Low (48)		

RF power setting in TEST Software	5G : B4			
	a mode :	Low (46)	Mid (46)	High (47)
	n-VHT20 mode chain 0	Low (47)	Mid (47)	High (44)
	n-VHT20 mode chain 1	Low (47)	Mid (47)	High (44)
	n-VHT40 mode chain 0	Low (52)	Mid (52)	High (47)
	n-VHT40 mode chain 1	Low (52)	Mid (52)	High (47)
	n-VHT80 mode chain 0	Low (48)		
	n-VHT80 mode chain 1	Low (48)		

2.4GHz WLAN: 2TX/2RX SM-MIMO, 5GHz WLAN: 2TX/2RX SM-MIMO

Wi-Fi	Frequency Range (MHz)	Channels	Peak / Average Rated Power	Modulation Technology	
802.11b	2412 – 2462(DTS)	11	16.57dBm (PK)	DSSS	
802.11g	2412 – 2462(DTS)	11	15.50dBm (PK)		
802.11n (2.4G)	HT20 2412 – 2462(DTS)	11	15.98dBm (PK)		
	HT40 2422 – 2452(DTS)	7	15.48dBm (PK)		
802.11a (5G)	5180 – 5320(NII)	8	15.76dBm (AV)	OFDM	
	5500 – 5700(NII)	8	15.65dBm (AV)		
	5745 – 5825(NII)	5	15.53dBm (AV)		
802.11n (5G)	VHT20, 5180 – 5320(NII)	8	15.39dBm (AV)		
	VHT20, 5500 – 5700(NII)	8	15.44dBm (AV)		
	VHT20, 5745 – 5825(NII)	5	15.57 dBm (AV)		
	VHT40, 5190 – 5310(NII)	7	15.44dBm (AV)		
	VHT40, 5510 – 5690(NII)	6	15.44dBm (AV)		
	VHT40, 5755 – 5815(NII)	4	15.30dBm (AV)		
802.11ac (5G)	VHT80, 5210 – 5290(NII)	2	14.19dBm (AV)		
	VHT80, 5530(NII)	1	14.17dBm (AV)		
	VHT80, 5775(NII)	1	14.30dBm (AV)		
Power Tolerance:	+/- 1.0 dBm				
Modulation type	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM				
Antenna Designation	PIFA Antenna WiFi 2.4G Antenna 1 : 2.91 dBi (Max) WiFi 2.4G Antenna 2 : 2.60 dBi (Max) WiFi 5G Antenna 1: 3.22 dBi (Max) WiFi 5G Antenna 2: 3.07 dBi (Max) According to KDB662911 D01 SM-MIMO signals could be considered uncorrelated for purposes of directional gain computation. Directional gain = $GANT$				

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.1 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: XVG50-0102-RT-22** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

KDB Document: 558074 D01 DTS Meas Guidance v03r05

1.3 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory** <Lung-Tan LAB> No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.10: 2013. FCC Registration Number is: TW1036, Canada Registration Number: 4067B-3.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

2 SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of C63.10: 2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8/1.5 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” Is still within the 3dB illumination BW of the measurement antenna. According to the requirements in Section 8 and 13 and Subclause 8.3.1.2 of ANSI C63.10: 2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System (Fixed channel)



Table 2-1 Equipment Used in Tested System

Item	Equipment	Mrf /Brand	Model name	Series No	Data Cable	Power Cable
1	NB	HP	440G1	2CE40911GZ	Non-shield	Non-shield

3 SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207(a)	AC Power Line Conducted Emission	Compliant
§15.247(b) (3),(4))	Peak Output Power	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(d)	100 KHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(d)	Spurious Emission	Compliant
§15.247(e)	Peak Power Density	Compliant
§15.203/	Antenna Requirement	Compliant

4 DESCRIPTION OF TEST MODES

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

802.11 b mode: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 1Mbps lowest data rate are chosen for full testing.

802.11 g mode: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6Mbps lowest data rate are chosen for full testing.

802.11 n _20MHz: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

802.11 n _40MHz: Channel low (2422MHz), mid (2437MHz), high (2462MHz) with 13.5Mbps lowest data rate are chosen for full testing.

The worst case 802.11b mode was reported for Radiated Emission.

5 AC POWER LINE CONDUCTED EMISSION TEST

5.1 Standard Applicable:

According to §15.207 and RSS-Gen §8.8, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note

- 1.The lower limit shall apply at the transition frequencies
- 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.2 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Conduction 04-3 Cable	WOKEN	CFD 300-NL	Conduction 04 -3	09/11/2017	09/10/2018
EMI Receiver 16	Rohde & Schwarz	ESCI	101221	10/23/2017	10/22/2018
LISN 18	ROHDE & SCHWARZ	ENV216	101424	02/05/2017	02/04/2018
LISN 19	ROHDE & SCHWARZ	ENV216	101425	03/07/2017	03/06/2018
Test Software	Farad	EZEMC Ver:ISL-03A2	N/A	N/A	N/A

5.3 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10-2013.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.5 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Normal Operation	Test Date:	2017/06/22
-----------------	------------------	------------	------------



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan.
 Tel:03-4071718


Conducted Emission Measurement

Date: 2017/6/22

operator: SAWYER

Temperature: 26 °C

Humidity: 54 %




Site: Conduction 04

Phase: L1

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.254	31.10	19.84	9.69	40.79	61.63	-20.84	29.53	51.63	-22.10
2	0.290	27.57	16.70	9.70	37.27	60.52	-23.25	26.40	50.52	-24.12
3	0.302	26.33	12.91	9.69	36.02	60.19	-24.17	22.60	50.19	-27.59
4	0.382	22.70	9.37	9.69	32.39	58.24	-25.85	19.06	48.24	-29.18
5	1.630	16.99	7.90	9.74	26.73	56.00	-29.27	17.64	46.00	-28.36
6	23.130	35.78	31.87	10.09	45.87	60.00	-14.13	41.96	50.00	-8.04



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan.
 Tel: 03-4071718



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.150	37.96	19.69	9.68	47.64	66.00	-18.36	29.37	56.00	-26.63
2	0.194	35.14	20.16	9.68	44.82	63.86	-19.04	29.84	53.86	-24.02
3	0.218	33.40	20.50	9.68	43.08	62.89	-19.81	30.18	52.89	-22.71
4	0.266	26.62	13.51	9.68	36.30	61.24	-24.94	23.19	51.24	-28.05
5	0.310	26.40	11.56	9.68	36.08	59.97	-23.89	21.24	49.97	-28.73
6	0.454	22.36	10.77	9.69	32.05	56.80	-24.75	20.46	46.80	-26.34

6 PEAK OUTPUT POWER MEASUREMENT

6.1 Standard Applicable:

According to §15.247(b)(3),(4)(b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:


(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

6.2 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power Meter 05	Anritsu	ML2495A	1116010	09/07/2017	09/06/2018
Power Sensor 05	Anritsu	MA2411B	34NKF50	09/07/2017	09/06/2018
Power Sensor 06	DARE	RPR3006W	13I00030SN O33	11/03/2017	11/02/2018
Power Sensor 07	DARE	RPR3006W	13I00030SN O34	11/03/2017	11/02/2018
Temperature Chamber	KSON	THS-B4H100	2287	06/27/2017	06/26/2018
DC Power supply	ABM	8185D	N/A	10/05/2017	10/04/2018
AC Power supply	EXTECH	CFC105W	NA	12/25/2016	12/24/2017
Attenuator	Woken	Watt-65m3502	11051601	NA	NA
Splitter	MCLI	PS4-199	12465	12/26/2015	12/25/2017
Spectrum analyzer	keysight	N9010A	MY56070257	05/31/2017	05/30/2018
Spectrum analyzer	R&S	FSP40	100143	08/07/2017	08/06/2018
Test Software	DARE	Radimation Ver:2013.1.23	NA	NA	NA

6.3 Test Set-up:



6.4 Measurement Procedure:

Refer to section 9.1.3 and 9.2.3 Peak and Average Conducted Output Power Measurement Procedure of KDB Document: 558074 D01 DTS Meas Guidance v03r05

6.5 Measurement Result:

802.11b

Cable loss = 0		Output Power		Limit (dBm)	
CH		Detector			
		PK (dBm)	AV (dBm)		
Low		16.57	14.05	30.00	
Mid		16.26	13.74		
High		16.23	13.71		

802.11g

Cable loss = 0		Output Power		Limit (dBm)	
CH		Detector			
		PK (dBm)	AV (dBm)		
Low		15.50	5.38	30.00	
Mid		15.23	5.17		
High		15.42	5.21		

Peak 2TX/2RX

Channel		Output Chain (dBm)		Combined Output Power (dBm)	Limit(dBm)	Result
		Chain 1	chain 2			
AN HT20	Low	13.21	12.54	15.90	30.00	Pass
	Mid	13.46	12.42	15.98	30.00	Pass
	High	12.60	12.11	15.37	30.00	Pass
AN HT40	Low	12.86	11.71	15.33	30.00	Pass
	Mid	12.77	12.14	15.48	30.00	Pass
	High	12.63	12.25	15.45	30.00	Pass

Average 2TX/2RX

Channel		Output Chain (dBm)		Combined Output Power (dBm)	Limit(dBm)	Result
		Chain 1	chain 2			
AN HT20	Low	3.87	3.12	6.52	30.00	Pass
	Mid	4.16	3.06	6.66	30.00	Pass
	High	3.17	2.85	6.02	30.00	Pass
AN HT40	Low	3.19	2.09	5.69	30.00	Pass
	Mid	3.12	2.05	5.63	30.00	Pass
	High	3.06	2.77	5.93	30.00	Pass

Offset: 1dB

7 6dB Bandwidth


7.1 Standard Applicable:

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

7.2 Measurement Equipment Used:

Refer to section 6.2 for details.

7.3 Test Set-up:



7.4 Measurement Procedure:

- 1 Place the EUT on the table and set it in transmitting mode.
- 2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3 Set the spectrum analyzer as RBW=100KHz, VBW = 3*RBW, Span= cover the complete power envelope of the signal of the UUT Sweep=auto
- 4 Mark the peak frequency and -6dB (upper and lower) frequency.

Repeat above procedures until all frequency measured were complete.

7.5 Measurement Result:

802.11b

CH	6dB Bandwidth (MHz)	Limit (KHz)	Result
Low	10.14	> 500	PASS
Mid	10.13	> 500	PASS
High	10.14	> 500	PASS

802.11g

CH	6dB Bandwidth (MHz)	Limit (KHz)	Result
Low	16.57	> 500	PASS
Mid	16.57	> 500	PASS
High	16.57	> 500	PASS

802.11n HT20

CH	6dB Bandwidth (MHz)	Limit (KHz)	Result
Low	17.71	> 500	PASS
Mid	17.75	> 500	PASS
High	17.71	> 500	PASS


802.11n HT40

CH	6dB Bandwidth (MHz)	Limit (KHz)	Result
Low	36.52	> 500	PASS
Mid	36.54	> 500	PASS
High	36.56	> 500	PASS


Note: Refer to next page for plots.

802.11b


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid




6dB Band Width Test Data CH-High




802.11g


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid




6dB Band Width Test Data CH-High




802.11n_20M


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid




6dB Band Width Test Data CH-High




802.11n_40M


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid



6dB Band Width Test Data CH-High



8 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

8.1 Standard Applicable:

According to §15.247(c), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2 Measurement Equipment Used:

8.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.


8.2.2 Radiated emission:

Chamber 19(966 Chamber)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
966 Chamber	Chance Most	Chamber 19	N/A	08/14/2017	08/13/2018
Spectrum Analyzer 21(3Hz-44GHz)	Agilent	N9030A	MY51360021	11/14/2017	11/13/2018
EMI Receiver	SCHWARZBECK	FCVU1534	1534149	11/30/2016	11/29/2017
Loop Antenna(9K-30M)	EM	EM-6879	271	11/01/2016	10/31/2018
Bilog Antenna (30M-1G)	SCHWARZBECK	VULB9168 w 5dB Att	736	07/21/2017	07/20/2018
Horn antenna (1G-18G)	SCHWARZBECK	9120D	9120D-1627	07/21/2016	07/20/2018
Horn antenna (18G-26G)	Com-power	AH-826	081001	07/23/2017	07/22/2019
Horn antenna (26G-40G)	Com-power	AH-640	100A	02/22/2017	02/21/2019
Preamplifier (9k-1000M)	HP	8447F	3113A06362	11/13/2017	11/12/2018
Preamplifier(1G-26G)	Agilent	8449B	3008A02471	08/24/2017	08/23/2018
Preamplifier (26G-40G)	MITEQ	JS4-26004000-27-5A	818471	07/22/2017	07/21/2019
RF Cable (9k-18G)	HUBER SUHNER	SUCOFLEX 104A	MY1397/4A	08/24/2017	08/23/2018
RF cable (18G~40G)	HUBER SUHNER	Sucoflex 102	27963/2&37421/2	11/03/2017	11/02/2019
Turn Table	MF	Turn Table-19	Turn Table-19	N/A	N/A
Mast Tower	MF	JSDES-15A	1308283	N/A	N/A
Controller	MF	MF-7802BS	MF780208460	N/A	N/A
AC power source	T-Power	TFC-1005	40006471	N/A	N/A
Signal Generator	R&S	SMU200A	102330	03/15/2017	03/14/2018
Signal Generator	Anritsu	MG3692A	20311	11/04/2017	11/03/2018
2.4G Filter	Micro-Tronics	Brm50702	76	12/25/2016	12/24/2017
5G Filter	Micro-Tronics	Brm50716	005	12/25/2016	12/24/2017
Test Software	Audix	E3 Ver:6.12023	N/A	N/A	N/A


8.3 Test SET-UP:

The test item only performed radiated mode

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-Up Frequency Over 1 GHz



8.4 Measurement Procedure:

- 1 Place the EUT on the table and set it in transmitting mode.
- 2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3 Set center frequency of spectrum analyzer = operating frequency.
- 4 Set the spectrum analyzer as RBW, VBW=100KHz, Span=25MHz, Sweep = auto
- 5 Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
- 6 Repeat above procedures until all frequency measured were complete.

8.5 Field Strength Calculation:

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and EUTy Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$


Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Radiated Emission: 802.11b mode

 Operation Mode TX CH Low
 Fundamental Frequency 2412 MHz
 Temperature 25


 Test Date 2017/06/13
 Test By Lake
 Humidity 60 %


No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol V/H
1	2390.00	52.22	-3.15	49.07	74.00	-24.93	Peak	VERTICAL
2	2400.00	62.77	-3.16	59.61	80.31	-20.70	Peak	VERTICAL
3	2410.69	103.46	-3.15	100.31	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2390.00	50.02	-3.15	46.87	74.00	-27.13	Peak	HORIZONTAL
2	2400.00	59.04	-3.16	55.88	78.50	-22.62	Peak	HORIZONTAL
3	2411.14	101.65	-3.15	98.50	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2462 MHz
 Temperature 25

Test Date 2017/06/13
 Test By Lake
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol
1	2463.52	103.73	-3.13	100.60	F	--	Peak	VERTICAL
2	2483.50	50.12	-3.11	47.01	74.00	-26.99	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2462.03	100.83	-3.12	97.71	F	--	Peak	HORIZONTAL
2	2483.50	47.02	-3.11	43.91	74.00	-30.09	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Radiated Emission: 802.11g mode

 Operation Mode TX CH Low
 Fundamental Frequency 2412 MHz
 Temperature 25


 Test Date 2017/06/13
 Test By Lake
 Humidity 60 %


No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol V/H
1	2390.00	52.16	-3.15	49.01	74.00	-24.99	Peak	VERTICAL
2	2400.00	71.54	-3.16	68.38	76.10	-7.72	Peak	VERTICAL
3	2405.76	99.25	-3.15	96.10	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2390.00	50.41	-3.15	47.26	74.00	-26.74	Peak	HORIZONTAL
2	2400.00	65.99	-3.16	62.83	71.59	-8.76	Peak	HORIZONTAL
3	2405.87	94.74	-3.15	91.59	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2462 MHz
 Temperature 25

Test Date 2017/06/13
 Test By Lake
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol
1	2456.90	98.42	-3.12	95.30	F	--	Peak	VERTICAL
2	2483.50	48.61	-3.11	45.50	74.00	-28.50	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2455.60	93.87	-3.12	90.75	F	--	Peak	HORIZONTAL
2	2483.50	46.52	-3.11	43.41	74.00	-30.59	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Radiated Emission: 802.11n_20HT mode

Operation Mode	TX CH Low	Test Date	2017/06/13
Fundamental Frequency	2412 MHz	Test By	Lake
Temperature	25	Humidity	60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol V/H
1	2390.00	51.14	-3.15	47.99	74.00	-26.01	Peak	VERTICAL
2	2400.00	67.77	-3.16	64.61	73.88	-9.27	Peak	VERTICAL
3	2406.54	97.03	-3.15	93.88	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2390.00	49.55	-3.15	46.40	74.00	-27.60	Peak	HORIZONTAL
2	2400.00	70.25	-3.16	67.09	75.01	-7.92	Peak	HORIZONTAL
3	2408.90	98.16	-3.15	95.01	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2462 MHz
 Temperature 25

Test Date 2017/06/13
 Test By Lake
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol
1	2454.93	95.98	-3.12	92.86	F	--	Peak	VERTICAL
2	2483.50	49.56	-3.11	46.45	74.00	-27.55	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2467.74	97.83	-3.12	94.71	F	--	Peak	HORIZONTAL
2	2483.50	48.36	-3.11	45.25	74.00	-28.75	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Radiated Emission: 802.11n_40HT mode

 Operation Mode TX CH Low
 Fundamental Frequency 2412 MHz
 Temperature 25


 Test Date 2017/06/13
 Test By Lake
 Humidity 60 %


No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol V/H
1	2390.00	52.63	-3.15	49.48	74.00	-24.52	Peak	VERTICAL
2	2400.00	65.85	-3.16	62.69	69.18	-6.49	Peak	VERTICAL
3	2420.09	92.33	-3.15	89.18	F	--	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2390.00	49.53	-3.15	46.38	74.00	-27.62	Peak	HORIZONTAL
2	2400.00	66.14	-3.16	62.98	67.46	-4.48	Peak	HORIZONTAL
3	2406.36	90.61	-3.15	87.46	F	--	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency

Operation Mode TX CH High
 Fundamental Frequency 2462 MHz
 Temperature 25

Test Date 2017/06/13
 Test By Lake
 Humidity 60 %




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over Li mit dB	Remark	Pol V/H
1	2453.62	92.34	-3.13	89.21	F	--	Peak	VERTICAL
2	2483.50	48.12	-3.11	45.01	74.00	-28.99	Peak	VERTICAL
3	2484.63	51.13	-3.11	48.02	74.00	-25.98	Peak	VERTICAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Over L imit dB	Remark	Pol V/H
1	2453.62	91.10	-3.13	87.97	F	--	Peak	HORIZONTAL
2	2483.50	48.69	-3.11	45.58	74.00	-28.42	Peak	HORIZONTAL


Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: “F” denotes fundamental frequency


802.11b
WiFi out of Band Test Plot (CH-Low)


Date: 22.FEB.2018 14:43:45

WiFi out of Band Test Plot (CH-Mid)



Date: 22.FEB.2018 14:45:48

WiFi out of Band Test Plot (CH-High)




Date: 22.FEB.2018 14:47:04

802.11g WiFi out of Band Test Plot (CH-Low)




Date: 22.FEB.2018 14:49:04

WiFi out of Band Test Plot (CH-Mid)



Date: 22.FEB.2018 14:50:24


WiFi out of Band Test Plot (CH-High)



Date: 22.FEB.2018 14:51:40


802.11n 20HT (Chain 1)

WiFi out of Band Test Plot (CH-Low)




Date: 22.FEB.2018 14:01:55

WiFi out of Band Test Plot (CH-Mid)




Date: 22.FEB.2018 14:06:15

WiFi out of Band Test Plot (CH-High)




Date: 22.FEB.2018 13:59:14

802.11n 20HT (Chain 2) WiFi out of Band Test Plot (CH-Low)




Date: 22.FEB.2018 14:04:53

WiFi out of Band Test Plot (CH-Mid)




Date: 22.FEB.2018 14:07:14

WiFi out of Band Test Plot (CH-High)




Date: 22.FEB.2018 14:00:38

802.11n 40HT (Chain 1) WiFi out of Band Test Plot (CH-Low)




Date: 22.FEB.2018 14:14:44

WiFi out of Band Test Plot (CH-Mid)




Date: 22.FEB.2018 14:36:17

WiFi out of Band Test Plot (CH-High)




Date: 22.FEB.2018 14:39:49

802.11n 40HT (Chain 2) WiFi out of Band Test Plot (CH-Low)




Date: 22.FEB.2018 14:34:07

WiFi out of Band Test Plot (CH-Mid)



Date: 22.FEB.2018 14:38:02

WiFi out of Band Test Plot (CH-High)



Date: 22.FEB.2018 14:40:59

7 SPURIOUS RADIATED EMISSION TEST

7.1 Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

7.2 Measurement Equipment Used:

7.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

7.2.2 Radiated emission:

Refer to section 7.2 for details.

7.3 Test SET-UP:

The test item only performed radiated mode

Refer to section 8.3 for details.

7.4 Measurement Procedure:

- 1 According 414788 section 2, Either OATS or chamber for radiated emission below 30MHz, the test was done at 966 chamber, the test site was evaluated with OATS and the Chamber has test signals level greater than OATS's .
- 2 The EUT was placed on a turn table which is 0.8m/1.5m above ground plane in 966 chamber.
- 3 The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 4 EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 5 When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
- 6 Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 7 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 8 Repeat above procedures until all frequency measured were complete.

7.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and EUTy Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

7.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Radiated Spurious Emission Measurement Result: (below 1GHz) (worst case: 802.11b mode)

Operation Mode	TX mode	Test Date	2017/06/13
Channel Number	CH Low	Test By	Lake
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	49.40	40.44	-5.18	35.26	40.00	-4.74	Peak	VERTICAL
2	106.63	42.26	-8.78	33.48	43.50	-10.02	Peak	VERTICAL
3	328.76	33.15	-3.29	29.86	46.00	-16.14	Peak	VERTICAL
4	515.97	34.08	-0.25	33.83	46.00	-12.17	Peak	VERTICAL
5	591.63	33.64	1.06	34.70	46.00	-11.30	Peak	VERTICAL
6	896.21	34.77	5.86	40.63	46.00	-5.37	Peak	VERTICAL
1	74.62	39.39	-8.97	30.42	40.00	-9.58	Peak	HORIZONTAL
2	106.63	42.73	-8.78	33.95	43.50	-9.55	Peak	HORIZONTAL
3	322.94	36.70	-3.48	33.22	46.00	-12.78	Peak	HORIZONTAL
4	359.80	41.83	-3.02	38.81	46.00	-7.19	Peak	HORIZONTAL
5	784.66	33.55	4.11	37.66	46.00	-8.34	Peak	HORIZONTAL
6	897.18	36.21	5.88	42.09	46.00	-3.91	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	TX mode	Test Date	2017/06/13
Channel Number	CH Mid	Test By	Lake
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	47.46	42.18	-5.17	37.01	40.00	-2.99	Peak	VERTICAL
2	106.63	41.79	-8.78	33.01	43.50	-10.49	Peak	VERTICAL
3	593.57	36.32	1.17	37.49	46.00	-8.51	Peak	VERTICAL
4	784.66	31.86	4.11	35.97	46.00	-10.03	Peak	VERTICAL
5	864.20	31.66	5.34	37.00	46.00	-9.00	Peak	VERTICAL
6	898.15	38.72	5.89	44.61	46.00	-1.39	Peak	VERTICAL
1	73.65	37.85	-8.72	29.13	40.00	-10.87	Peak	HORIZONTAL
2	104.69	43.45	-9.16	34.29	43.50	-9.21	Peak	HORIZONTAL
3	322.94	35.69	-3.48	32.21	46.00	-13.79	Peak	HORIZONTAL
4	359.80	41.03	-3.02	38.01	46.00	-7.99	Peak	HORIZONTAL
5	864.20	35.17	5.34	40.51	46.00	-5.49	Peak	HORIZONTAL
6	892.33	35.42	5.81	41.23	46.00	-4.77	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	TX mode	Test Date	2017/06/13
Channel Number	CH High	Test By	Lake
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	47.46	41.52	-5.17	36.35	40.00	-3.65	Peak	VERTICAL
2	106.63	42.22	-8.78	33.44	43.50	-10.06	Peak	VERTICAL
3	513.06	36.57	-0.36	36.21	46.00	-9.79	Peak	VERTICAL
4	593.57	37.04	1.17	38.21	46.00	-7.79	Peak	VERTICAL
5	784.66	32.04	4.11	36.15	46.00	-9.85	Peak	VERTICAL
6	897.18	35.58	5.88	41.46	46.00	-4.54	Peak	VERTICAL
1	74.62	39.19	-8.97	30.22	40.00	-9.78	Peak	HORIZONTAL
2	104.69	43.43	-9.16	34.27	43.50	-9.23	Peak	HORIZONTAL
3	359.80	41.51	-3.02	38.49	46.00	-7.51	Peak	HORIZONTAL
4	784.66	33.83	4.11	37.94	46.00	-8.06	Peak	HORIZONTAL
5	864.20	35.87	5.34	41.21	46.00	-4.79	Peak	HORIZONTAL
6	898.15	36.19	5.89	42.08	46.00	-3.92	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (above 1GHz) (worst case: 802.11b mode)

Operation Mode	TX mode	Test Date	2017/06/13
Channel Number	CH Low	Test By	Lake
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	4824.00	41.68	3.27	44.95	74.00	-29.05	Peak	VERTICAL
1	4824.00	42.23	3.27	45.50	74.00	-28.50	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	TX mode	Test Date	2017/06/13
Channel Number	CH Mid	Test By	Lake
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	4874.00	40.72	3.39	44.11	74.00	-29.89	Peak	VERTICAL
1	4874.00	40.54	3.39	43.93	74.00	-30.07	Peak	HORIZONTAL

Remark:

- 1 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 2 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 4 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	TX mode	Test Date	2017/06/13
Channel Number	CH High	Test By	Lake
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	4924.00	40.97	3.51	44.48	74.00	-29.52	Peak	VERTICAL
1	4924.00	40.74	3.51	44.25	74.00	-29.75	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

9 Peak Power Spectral Density

9.1 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.2 Measurement Equipment Used:

Refer to section 6.2 for details.

9.3 Test Set-up:

Refer to section 7.3 for details.

9.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW =3KHz, VBW = 10KHz, Set the span to 1.5 DTS bandwidth., Sweep=Auto
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.

9.5 Measurement Result:

802.11b Mode

CH	Power Density Level dBm/3KHz	Maximum Limit (dBm)
Low	-16.17	8
Mid	-16.65	8
High	-16.68	8

802.11g Mode

CH	Power Density Level dBm/3KHz	Maximum Limit (dBm)
Low	-23.41	8
Mid	-23.54	8
High	-23.25	8

2TX / 2RX

	CH	Output Chain dbm		Combine Power Density (dBm/3KHz)	Limit(dBm)	Result
		Chain 1	chain 2			
AN HT20	Low	-22.66	-24.13	-20.32	8	Pass
	Mid	-24.01	-23.95	-20.97	8	Pass
	High	-23.76	-24.74	-21.21	8	Pass
AN HT40	Low	-27.04	-26.29	-23.64	8	Pass
	Mid	-25.47	-26.55	-22.97	8	Pass
	High	-24.92	-25.41	-22.15	8	Pass

offset : 1dB

802.11b

Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11g


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11n_20M, Chain 0


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11n_20M, Chain 1

Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Power Spectral Density Test Plot (CH-High)



802.11n_40M, Chain 0

Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11n_40M, Chain 1

Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Power Spectral Density Test Plot (CH-High)



10 ANTENNA REQUIREMENT

10.1 Standard Applicable:

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

10.2 Antenna Connected Construction:

The directional gins of antenna used for transmitting is 2.91dBi for WLAN, and the antenna is designed with fixed type and no consideration of replacement. Please see EUT photo and antenna spec. for details.