



dresden elektronik ingenieurtechnik gmbh = Enno-Heidebroek-Str. 12 = D-01237 Dresden

Federal Communications Commission Equipment Authorization Branch 7435 Oakland Mills Rd Columbia MD 21046-1609

Dresden, 30th May 2011

RF Exposure Calculation

dresden elektronik ingenieurtechnik gmbh FCC ID: XVV-ARM323E00 FCC Part 15 Certification

Dear Sir or Madam,

End-users may not be provided with the usb radio stick installation instructions. OEM integrators and end-users must be provided with transmitter operating conditions for satisfying RF exposure compliance.

For portable applications OEM integrators need no SAR evaluation. The max source-based time-averaged output of 2.75 mW is below the low threshold of 24 mW for distance < 2.5 cm.

Section 15.203: Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.



The following calculation is the reference data for distance < 2.5 cm.

| name | | value | log value | |
|--|------------|----------|-----------|--------|
| maximum conducted power | | 2.04 mW | 3.10 dBm | |
| maximum antenna gain | | 1.35 | 1.3 dBi | |
| calculated radiated power | | 2.75 mW | 4.40 dBm | |
| duty cycle factor | | | | |
| frequency | | 2400 MHz | | |
| dwell time | | 100 ms | | |
| time of occupacy / pulse-train time | | 100 ms | | |
| duty cycle factor | | 100 % | 0.00 dB | |
| maxium source-based time-averaged | power | | | 6174.S |
| conducted power | | 2.04 mW | 3.10 dBm | |
| calculated radiated power | | 2.75 mW | 4.40 dBm | |
| Specific power | | | | 100 |
| measured condacted power $S = \frac{P \cdot G}{4 \cdot \pi \cdot r^2} \left[\frac{mW}{cm^2} \right]$ | | | | |
| r [cm] | 20.00 | 2.50 | 1.50 | 0.47 |
| S [mW/cm ²] | 0.0005 | 0.0351 | 0.0974 | 1.0 |
| limit general population [mW/cm²] | 1.0 | | | |
| limit occupational population [mW/cm²] | 5.0 | | | |
| calculated with max source-based time-ameasured radiated power $S = \frac{EIRP}{4 \cdot \pi \cdot r^2} \left[\frac{mW}{cm^2} \right]$ | averaged p | ower | | |
| r [cm] | 20.00 | 2.50 | 1.50 | n.a. |
| S [mW/cm ²] | n.a. | n.a. | n.a. | 1.0 |

Sincerely,

Signature Name

Title

Andreas Palm

Development Engineer dresden elektronik ingenieurtechnik gmbh Company