



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822  
 Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>



Dates of Tests: Oct 28 – Nov 04, 2009  
 Test Report S/N: LR500190911D  
 Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.

**XVY-IDRO900F**

APPLICANT

**IDRO Co., Ltd.**

<b>FCC Classification</b>	:	<b>FHSS Sequence Spread Spectrum (FHSS)</b>
<b>Manufacturing Description</b>	:	<b>UHF RFID Reader</b>
<b>Manufacturer</b>	:	<b>IDRO Co., Ltd.</b>
<b>Model name</b>	:	<b>IDRO900F</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	:	<b>902.75 ~ 927.25MHz</b>
<b>RF power</b>	:	<b>0.85W - Conducted</b>
<b>Data of issue</b>	:	<b>November 5, 2009</b>

This test report is issued under the authority of:

Dong-Min JUNG, Technical Manager

The test was supervised by:

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S -----	3
2. INFORMATION'S ABOUT TEST ITEM -----	4
3. TEST REPORT -----	5
3.1 SUMMARY OF TESTS -----	5
3.2 TECHNICAL CHARACTERISTICS TEST -----	6
3.2.1 CARRIER FREQUENCY SEPARATION -----	6
3.2.2 NUMBER OF HOPPING FREQUENCIES -----	8
3.2.3 20 dB BANDWIDTH -----	10
3.2.4 TIME OF OCCUPANCY (Dwell Time) -----	12
3.2.5 TRANSMITTER OUTPUT POWER -----	14
3.2.6 BAND – EDGE (Conducted) -----	16
3.2.7 FIELD STRENGTH OF HARMONICS -----	21
3.2.8 AC CONDUCTED EMISSIONS -----	24
 <b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS -----	27

## 1. General information's

### **1-1 Test Performed**

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### **1-2 Accredited agencies**

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2010-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2010-05-03	IC filing

## 2. Information's about test item

### 2-1 Client

Company name : IDRO Co., Ltd.  
 Address : 5th Fl. #A8, GSBC Bldg., 906-5, Iui-dong, yeongtong-gu Suwon-si,  
 Gyeonggi-do, Korea  
 Tel / Fax : +82-31-259-7887 / +82-31-259-7886

### 2-2 Equipment Under Test (EUT)

Trade name : UHF RFID Reader  
 FCC ID : XVY-IDRO900F  
 Model name : IDRO900F  
 Serial number : Identical prototype  
 Date of receipt : October 27, 2009  
 EUT condition : Pre-production, not damaged  
 Antenna type : Patch Antenna Gain 5.45 dBi  
 Antenna Connector Type : Reverse Polarity SMA Type  
 Frequency Range : 902.75 ~ 927.25MHz  
 RF output power : 0.85 W- Conducted  
 Number of channels : 50  
 Channel spacing : 500KHz  
 Channel Access Protocol : Frequency Hopping  
 Power Source : 5VDC by Adaptor

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	902.75	915.25	927.25

### 2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
NoteBook	PP17L	FJ681A03	DELL

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	$\geq$ 50 hops		C
15.247(a)	20 dB Bandwidth	-		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1 Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207 / 15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

#### → Antenna Requirement

The IDRO Co., Ltd. IDRO900F unit complies with the requirement of §15.203.

The Antenna type is Reverse Polarity SMA Type ; Refer to the External photo

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

#### The spectrum analyzer is set to:

Span = 1 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more)      Sweep = auto

VBW = 10 kHz      Detector function = peak

Trace = max hold

#### Measurement Data:

Test Results	
Carrier Frequency Separation (KHz)	Result
500.7	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

#### Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

## Carrier Frequency Separation



### 3.2.2 Number of Hopping Frequencies

#### Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 902 ~ 928 MHz FH band were examined.

#### The spectrum analyzer is set to:

Frequency range 1: Start = 900 MHz, Stop = 930 MHz

RBW = 100 kHz (1% of the span or more) Sweep = auto

VBW = 100 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold Span = 30MHz

#### Measurement Data: Complies

<b>Total number of Hopping Channels</b>	50
---	----

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

At least 50 hopes

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## Number of Hopping Frequencies



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 1 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 3 kHz Sweep = auto

VBW = 10 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Channel No.	Test Results	
		Measured Bandwidth (kHz)	Result
902.75	0	53.84	Complies
915.25	25	53.55	Complies
927.25	49	51.81	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

-

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## 20 dB Bandwidth



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 914.9 MHz

Span = zero

RBW = 100 KHz

VBW = 300 KHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Channel Number	Channel Frequency (MHz)	Test Results			
		Length (ms)	number	Dwell Time (ms)	Result
25	915.25	99.71	2	199.42	Complies



- See next pages for actual measured spectrum plots.

#### Minimum Standard:

0.4 seconds within a 20 second period per any frequency

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)



### 3.2.5 Transmitter Output Power

## Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

Sweep = auto

## Measurement Data:

Frequency (MHz)	Ch.	Test Results		
		dBm	W	Result
902.75	0	29.00	0.79	Complies
915.25	25	29.30	0.85	Complies
927.25	49	29.00	0.79	Complies




- See next pages for actual measured spectrum plots.

**Minimum Standard:** < 1W

## Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

## Peak Output Power



### 3.2.6 Band Edge

### **Procedure:**

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

VBW = 300 kHz

Span = 10 MHz

Detector function = peak

#### Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

---


<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

---

## Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


## Band - edge




**Band - edge (at 20 dB blow) – Low channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



**Band - edge (at 20 dB blow) – Mid channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



**Band - edge (at 20 dB blow) – High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



### 3.2.7 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

= 1 MHz ( 1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Trace = max hold

Peak mode: VBW = 1 MHz

Average mode: VBW = 10Hz

Detector function = Peak & average

Sweep = auto

#### Measurement Data:

→ Refer to the Next page

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

#### Minimum Standard: FCC Part 15.109

Frequency (MHz)	Limit (uV/m) @ 10m
30 ~ 88	90
88 ~ 216	150
216 ~ 960	210
Above 960	300

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Antenna	Amp. Gain	Cable			AV / Peak	AV / Peak		
1804.70	52.5	54.3	V	26.0	38.2	3.5	54.0	74.0	43.8	45.6	10.2	28.4
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Antenna	Amp. Gain	Cable			AV / Peak	AV / Peak		
1830.30	54.2	56.3	V	26.0	38.2	3.5	54.0	74.0	45.5	47.6	8.5	26.4
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Antenna	Amp. Gain	Cable			AV / Peak	AV / Peak		
1853.50	54.2	56.2	V	26.0	38.2	3.5	54.0	74.0	45.5	47.5	8.5	26.5
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-

## Measurement Data:




243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax :+82-31-3236010

EUT/Model No.: IDR0900F

TEST MODE: RFID mode

Temp Humi : 18 / 59

Tested by: B.S.KIM



### 3.2.8 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

##### Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

##### Class A


Frequency Range	quasi-peak	Average
0.15 ~ 0.5 MHz	79 dBuV	66 dBuV
0.5 ~ 30 MHz	73 dBuV	60 dBuV

## AC Conducted Emissions –Line



243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : IDR0900F Phase : LINE  
 Test Mode : RFID mode Test Power : 120 / 60  
 Temp./Humi. : 21 / 50 Test Engineer : B.S.KIM



Freq MHz	RD QP		RD AV		C. F dB	Result QP		Result AV		Limit QP		Limit AV		Margin dB	Margin dB
	dBuV	dBuV	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
0.150	42.10	30.90	9.75	51.85	40.65	79.00	66.00	27.15	25.35						
0.197	35.69	23.99	9.61	45.30	33.60	79.00	66.00	33.70	32.40						
0.440	27.25	22.55	9.67	36.92	32.22	79.00	66.00	42.08	33.78						
1.905	24.75	17.35	9.81	34.56	27.16	73.00	60.00	38.44	32.84						
2.199	27.06	21.16	9.82	36.88	30.98	73.00	60.00	36.12	29.02						
2.641	27.45	18.35	9.86	37.31	28.21	73.00	60.00	35.69	31.79						


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## AC Conducted Emissions -Neutral



243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel. +82-31-3236008,9  
Fax. +82-31-3236010

EUT / Model No. : IDR0900F Phase : NEUTRAL  
 Test Mode : RFID mode Test Power : 120 / 60  
 Temp./Humi. : 21 / 50 Test Engineer : B.S.KIM



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result		Limit		Margin	
				QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.150	41.20	28.60	9.72	50.92	38.32	79.00	66.00	28.08	27.68
0.194	34.99	24.39	9.67	44.66	34.06	79.00	66.00	34.34	31.94
0.439	29.15	25.05	9.71	38.86	34.76	79.00	66.00	40.14	31.24
1.173	24.95	20.55	9.81	34.76	30.36	73.00	60.00	38.24	29.64
2.345	28.66	22.36	9.84	38.50	32.20	73.00	60.00	34.50	27.80
2.638	27.85	17.45	9.89	37.74	27.34	73.00	60.00	35.26	32.66

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	Feb-10
2	Spectrum Analyzer	8563E	3425A02505	HP	Apr-10
3	Spectrum Analyzer	8594E	3710A04074	HP	Oct-10
4	Signal Generator	8648C	3623A02597	HP	Apr-10
5	Signal Generator	83711B	US34490456	HP	Apr-10
6	Attenuator (3dB)	8491A	37822	HP	Oct-10
7	Attenuator (10dB)	8491A	63196	HP	Oct-10
8	Attenuator (30dB)	8498A	1801A06689	HP	Oct-10
9	EMI Test Receiver	ESVD	843748/001	R&S	Apr-10
10	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	Nov-10
11	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	Nov-10
12	RF Amplifier	8447D	2949A02670	HP	Oct-10
13	RF Amplifier	8449B	3008A02126	HP	Apr-10
14	Test Receiver	ESHS10	828404/009	R&S	Apr-10
15	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Apr-11
16	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-11
17	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-11
18	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-11
19	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	Dec-11
20	Dipole Antenna	VHA9103	2116	SCHWARZBECK	Nov-09
21	Dipole Antenna	VHA9103	2117	SCHWARZBECK	Nov-09
22	Dipole Antenna	VHA9105	2261	SCHWARZBECK	Nov-09
23	Dipole Antenna	VHA9105	2262	SCHWARZBECK	Nov-09
24	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Apr-10
25	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
26	RF Switch	MP59B	6200414971	ANRITSU	-
27	Power Divider	11636A	6243	HP	Oct-10
28	DC Power Supply	6622A	3448A03079	HP	Oct-10
29	Frequency Counter	5342A	2826A12411	HP	Apr-10
30	Power Meter	EPM-441A	GB32481702	HP	Apr-10
31	Power Sensor	8481A	2702A64048	HP	Apr-10
32	Audio Analyzer	8903B	3729A18901	HP	Oct-10
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-10
34	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	Oct-10
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-11
36	Stop Watch	HS-3	601Q09R	CASIO	Apr-10
37	LISN	ENV216	100408	R&S	Oct-10